

Portfolio Optimisation with Threshold Accepting

Enrico Schumann
enricoschumann@yahoo.de

This vignette provides the code for some of the examples from Gilli et al. [2011]. For more details, please see Chapter 13 of the book; the code in this vignette uses the scripts `exampleSquaredRets.R`, `exampleSquaredRets2.R` and `exampleRatio.R`.

We start by attaching the package. We will later on need the function `resample` (see `?sample`).

```
> require("NMOF")
> resample <- function(x, ...) x[sample.int(length(x), ...)]
> set.seed(112233)
```

1 Minimising squares

1.1 A first implementation

This problem serves as a benchmark: we wish to find a long-only portfolio w (weights) that minimises squared returns across all return scenarios. These scenarios are stored in a matrix R of size number of scenarios ns times number of assets na . More formally, we want to solve the following problem:

$$\begin{aligned} \min_w \quad & \Phi \\ & w'1 = 1, \\ & 0 \leq w_j \leq w_j^{\sup} \quad \text{for } j = 1, 2, \dots, n_A. \end{aligned} \tag{1}$$

We set w_j^{\sup} to 5% for all assets. Φ is the squared return of the portfolio, $w'R'RW$, which is similar to the portfolio return's variance. We have

$$\frac{1}{n_S} R'R = \text{Cov}(R) + mm'$$

in which Cov is the variance–covariance matrix operator, which maps the columns of R into their variance–covariance matrix; m is a column vector that holds the column means of R , ie, $m' = \frac{1}{n_S} 1'R$. For short time horizons, the mean of a column is small compared with the average squared return of the column. Hence, we ignore the matrix mm' , and variance and squared returns become equivalent.

For testing purposes we use the matrix `fundData` for R .

```
> na <- dim(fundData)[2L]
> ns <- dim(fundData)[1L]
> winf <- 0.0; wsup <- 0.05
> data <- list(R = t(fundData),
+             RR = crossprod(fundData),
+             na = na,
+             ns = ns,
+             eps = 0.5/100,
+             winf = winf,
+             wsup = wsup,
+             resample = resample)
```

The neighbourhood function automatically enforces the budget constraint.

```
> neighbour <- function(w, data){
+   eps <- runif(1L) * data$eps
+   toSell <- w > data$winf
+   toBuy <- w < data$wsup
+   i <- data$resample(which(toSell), size = 1L)
```

```

+   j <- data$resample(which(toBuy), size = 1L)
+   eps <- min(w[i] - data$winf, data$wsup - w[j], eps)
+   w[i] <- w[i] - eps
+   w[j] <- w[j] + eps
+   w
+ }

```

The objective function.

```

> OF1 <- function(w, data) {
+   Rw <- crossprod(data$R, w)
+   crossprod(Rw)
+ }
> OF2 <- function(w, data) {
+   aux <- crossprod(data$RR, w)
+   crossprod(w, aux)
+ }

```

OF2 uses $R'R$; thus, it does not depend on the number of scenarios. But this is only possible for this very specific problem.

We specify a random initial solution w_0 and define all settings in a list `algo`.

```

> w0 <- runif(na); w0 <- w0/sum(w0)
> algo <- list(x0 = w0,
+   neighbour = neighbour,
+   nS = 2000L,
+   nT = 10L,
+   nD = 5000L,
+   q = 0.20,
+   printBar = FALSE,
+   printDetail = FALSE)

```

We can now run `TAopt`, first with `OF1` ...

```

> system.time(res <- TAopt(OF1,algo,data))

   user  system elapsed 
13.869   0.008  13.882 

> 100 * sqrt(crossprod(fundData %*% res$xbest)/ns)

      [,1]
[1,] 0.3363246

```

...and then with `OF2`.

```

> system.time(res <- TAopt(OF2,algo,data))

   user  system elapsed 
 4.965   0.000   4.964 

> 100*sqrt(crossprod(fundData %*% res$xbest)/ns)

      [,1]
[1,] 0.3367206

```

Note that we have rescaled the results (see the book for details). Both results are similar, but `OF2` typically requires less time. We check the constraints.

```

> min(res$xbest) ## should not be smaller than data$winf

[1] 0

> max(res$xbest) ## should not be greater than data$wsup

```

```
[1] 0.05
```

```
> sum(res$xbest) ## should be one
```

```
[1] 1
```

The problem can actually be solved quadratic programming; we use the quadprog package [Turlach and Weingessel, 2011].

```
> if (require(quadprog, quietly = TRUE)) {
+   covMatrix <- crossprod(fundData)
+   A <- rep(1, na); a <- 1
+   B <- rbind(-diag(na), diag(na))
+   b <- rbind(array(-data$wsup, dim = c(na, 1L)),
+               array( data$winf, dim = c(na, 1L)))
+   system.time({
+     result <- solve.QP(Dmat = covMatrix,
+                        dvec = rep(0,na),
+                        Amat = t(rbind(A,B)),
+                        bvec = rbind(a,b),
+                        meq = 1L)
+   })
+   wqp <- result$solution
+
+   cat("Compare results...\n")
+   cat("QP:", 100 * sqrt( crossprod(fundData %*% wqp)/ns ), "\n")
+   cat("TA:", 100 * sqrt( crossprod(fundData %*% res$xbest)/ns ) , "\n")
+
+   cat("Check constraints ... \n")
+   cat("min weight:", min(wqp), "\n")
+   cat("max weight:", max(wqp), "\n")
+   cat("sum of weights:", sum(wqp), "\n")
+ }
```

```
Compare results...
```

```
QP: 0.3361227
```

```
TA: 0.3367206
```

```
Check constraints ...
```

```
min weight: -1.142463e-16
```

```
max weight: 0.05
```

```
sum of weights: 1
```

1.2 Updating

Here we implement the updating of the objective function as described in Gilli et al. [2011].

```
> neighbourU <- function(sol, data){
+   wn <- sol$w
+   toSell <- wn > data$winf
+   toBuy <- wn < data$wsup
+   i <- data$resample(which(toSell), size = 1L)
+   j <- data$resample(which(toBuy), size = 1L)
+   eps <- runif(1) * data$eps
+   eps <- min(wn[i] - data$winf, data$wsup - wn[j], eps)
+   wn[i] <- wn[i] - eps
+   wn[j] <- wn[j] + eps
+   Rw <- sol$Rw + data$R[,c(i,j)] %*% c(-eps,eps)
+   list(w = wn, Rw = Rw)
+ }
> OF <- function(sol, data) crossprod(sol$Rw)
```

Prepare the data list (we reuse several items used before).

```
> data <- list(R = fundData, na = na, ns = ns,
+             eps = 0.5/100, winf = winf, wsup = wsup,
+             resample = resample)
```

We start, again, with a random solution, and also use the same number of iterations as before.

```
> w0 <- runif(data$na); w0 <- w0/sum(w0)
> x0 <- list(w = w0, Rw = fundData %*% w0)
> algo <- list(x0 = x0,
+             neighbour = neighbourU,
+             nS = 2000L,
+             nT = 10L,
+             nD = 5000L,
+             q = 0.20,
+             printBar = FALSE,
+             printDetail = FALSE)
> system.time(res2 <- TAOpt(OF, algo, data))

   user  system elapsed
 3.940   0.000   3.938

> 100*sqrt(crossprod(fundData %*% res2$xbest$w)/ns)

      [,1]
[1,] 0.3367288
```

This should be faster, and we arrive at the same solution as before.

1.3 Redundant assets

We duplicate the last column of fundData.

```
> fundData <- cbind(fundData, fundData[, 200L])
```

Thus, while the dimension increases, the column rank stays unchanged.

```
> dim(fundData)

[1] 500 201

> qr(fundData)$rank

[1] 200

> qr(cov(fundData))$rank

[1] 200
```

Checking the weight of the last asset (which was zero), we know that the solution to our model must be unchanged, too.

```
> if (require(quadprog, quietly = TRUE))
+     wqp[200L]

[1] 1.104024e-16
```

We redo our example.

```
> na <- dim(fundData)[2L]
> ns <- dim(fundData)[1L]
> winf <- 0.0; wsup <- 0.05
> data <- list(R = fundData, na = na, ns = ns,
+             eps = 0.5/100, winf = winf, wsup = wsup,
+             resample = resample)
>
```

But a number of QP solvers have problems with such cases.

```
> if (require(quadprog, quietly = TRUE)) {
+   covMatrix <- crossprod(fundData)
+   A <- rep(1, na); a <- 1
+   B <- rbind(-diag(na), diag(na))
+   b <- rbind(array(-data$wsup, dim = c(na, 1L)),
+               array( data$winf, dim = c(na, 1L)))
+   cat(try(result <- solve.QP(Dmat = covMatrix,
+                               dvec = rep(0,na),
+                               Amat = t(rbind(A,B)),
+                               bvec = rbind(a,b),
+                               meq = 1L)
+       ))
+ }
```

```
Error in solve.QP(Dmat = covMatrix, dvec = rep(0, na), Amat = t(rbind(A, :
matrix D in quadratic function is not positive definite!
```

But TA can handle this case.

```
> w0 <- runif(data$na); w0 <- w0/sum(w0)
> x0 <- list(w = w0, Rw = fundData %*% w0)
> algo <- list(x0 = x0,
+             neighbour = neighbourU,
+             nS = 2000L,
+             nT = 10L,
+             nD = 5000L,
+             q = 0.20,
+             printBar = FALSE,
+             printDetail = FALSE)
> system.time(res3 <- TAopt(OF, algo, data))

   user  system elapsed 
 3.892   0.000   3.893 

> 100*sqrt(crossprod(fundData %*% res3$xbest$w)/ns)

      [,1]
[1,] 0.3371547
```

Final check: weights for asset 200 and its twin, asset 201.

```
> res3$xbest$w[200:201]

[1] 0 0
```

See Gilli et al. [2011, Section 13.2.5] for a discussion of rank-deficiency and its (computational and empirical) consequences for such problems.

References

- Manfred Gilli, Dietmar Maringer, and Enrico Schumann. *Numerical Methods and Optimization in Finance*. Elsevier, 2011.
- Berwin A. Turlach and Andreas Weingessel. *quadprog: Functions to solve Quadratic Programming Problems*, 2011. R package version 1.5-4 (S original by Berwin A. Turlach; R port by Andreas Weingessel.).