

# 5: Generalized Linear Models – Logistic and Poisson Regression

John H Maindonald

November 25, 2013

## Ideas and issues illustrated by the graphs in this vignette

Generalized linear models (GLMs) are an extension of linear models. An important special case is models with a binary outcome. Poission regression models are another special case. Graphs shown here illustrate important aspects of the use of these models.

## 1 Code for the Figures

```
fig5.1 <-
function (){
  opar <- par(mar=c(4,4,2.6,.1))
  ylim <- range(bronchit$poll)+c(0,2.5)
  par(fig=c(0,.525, 0,1))
  plot(xlab="# cigarettes per day", ylab="Pollution", poll ~ cig,
    col=c(2,4)[r+1], pch=(3:2)[r+1], data=bronchit, ylim=ylim)
  legend(x="topleft", legend=c("Non-sufferer","Sufferer"), ncol=2,
    pch=c(3,2), col=c(2,4))
  mtext(side=3, line=1.0,
    expression("A: Untransformed *italic(x)*-scale"),
    cex=0.95, adj=0)
  par(fig=c(.475,1, 0,1), new=TRUE)
  plot(poll ~ log(cig+1), col=c(2,4)[r+1], pch=(3:2)[r+1],
    xlab="log(# cigarettes per day + 1)", ylab="",
    data=bronchit, ylim=ylim)
  xy1 <- with(subset(bronchit, r==0), cbind(x=log(cig+1), y=poll))
  xy2 <- with(subset(bronchit, r==1), cbind(x=log(cig+1), y=poll))
  est1 <- bkde2D(xy1, bandwidth=c(0.7, 3))
  est2 <- bkde2D(xy2, bandwidth=c(0.7, 3))
  lev <- pretty(c(est1$fhat, est2$fhat),4)
  contour(est1$x1, est1$x2, est1$fhat, levels=lev, add=TRUE, col=2)
  contour(est2$x1, est2$x2, est2$fhat, levels=lev, add=TRUE, col=4,
```

```

        lty=2)
legend(x="topleft", legend=c("Non-sufferer", "Sufferer"), ncol=2,
       lty=1:2, col=c(2,4), x.intersp=0.5)
mtext(side=3, line=1.0,
      expression("B: Log-transformed *italic(x)*-scale"),
      cex=0.95, adj=0)
par(fig=c(0,1,0,1))
par(opar)
}

```

```

fig5.2 <-
function (plotit=TRUE)
{
  par(mfrow=c(1,2))
  cig2.glm <- glm(r ~ log(cig+1) + poll, family=binomial,
                    data=bronchit)
  termplot(cig2.glm, se=TRUE, ylim=c(-2,4))
  par(mfrow=c(1,1))
}

```

```

fig5.3 <-
function ()
{
  nassnew <- subset(nassCDS,
                     !is.na(yearVeh) & yearVeh>=1986 & weight>0)
  nassnew.glm <- glm(dead ~ seatbelt + airbag + dvcat + yearVeh +
                       age0Focc, weights=weight, family = quasibinomial,
                       data=nassnew)
  par(mfrow=c(1,2))
  termplot(nassnew.glm, terms=c("yearVeh", "age0Focc"),
            smooth=panel.smooth, se=TRUE)
  par(mfrow=c(1,1))
  par(fig=c(0,0.5,0,1), new=TRUE)
  mtext(side=3, line=1.0, "A", adj=0)
  par(fig=c(0.5,1,0,1), new=TRUE)
  mtext(side=3, line=1.0, "B", adj=0)
  par(fig=c(0,1,0,1))
}

```

```

fig5.4 <-
function (){
  opar <- par(mfrow=c(1,2), mar=c(3.6,3.6,1.6,0.6), mgp=c(2.25,.5,0))

```

```

qqnorm(rpois(30, 5), ylab="", main="")
qqnorm(rpois(30, 5), ylab="", main="")
par(opar)
}

```

```

fig5.5 <-
function (){
  if(!require(car))
    stop("Package 'car' must be installed")
  spm(~ . | habitat, data=moths, cex.labels=1.2,
       smooth=FALSE, reg.line=NA)
}

```

```

fig5.6 <-
function (){
{
  P.glm <- glm(P ~ habitat + log(meters), data=moths,
                 family=quasipoisson)
  par(mfrow=c(2,2))
  plot(P.glm, which=1:4)
  par(mfrow=c(1,1))
}

```

## 2 Show the Figures

Unless `doFigs` is found in the workspace and is `FALSE`, then subject to checks that all necessary datasets and packages are available, the figures are now shown.

```


if(!exists("doFigs")) doFigs <- TRUE

if(!exists("bronchit")){
  cat("Will try to load 'bronchit' from the SMIR package")
  if(!require(SMIR)) stop("Package SMIR is not installed")
  library(SMIR)
  data(bronchit)
}
library(DAAG)
library(KernSmooth)


```

```
cig2.glm <- glm(r ~ log(cig+1) + poll, family=binomial,
                  data=bronchit)
```

`fig5.1()`



`fig5.2()`



`fig5.3()`




fig5.4()





fig5.5()



`fig5.6()`

Warning: not plotting observations with leverage one:  
40

