

Arbitrarily Accurate Computation with R: The 'Rmpfr' Package

Martin Mächler

maechler@R-project.org (R-Core)
maechler@stat.math.ethz.ch (ETH)

Seminar für Statistik
ETH Zurich Switzerland

ZurichR @ ETH, Jan.19, 2012

Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of Rmpfr
- 5 Package and Session Information
- 6 Conclusions

Navigation icons

Martin Mächler (R Core/ ETH Zurich) Arbitrarily Accurate R: Package 'Rmpfr' ZurichR @ ETH, Jan.2012 1 / 31

Outline


- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of Rmpfr
- 5 Package and Session Information
- 6 Conclusions

Logistic regression: Computing “logit()”s, $\log \frac{p}{1-p}$ accurately for very small p , i.e., $p = \exp(-L)$, or

$$\log \frac{p}{1-p} = \log p - \log(1-p) = -L - \log(1 - \exp(-L)),$$

and hence $-\log(1 - \exp(-L))$ is needed, e.g., when p is really really close to 0, say $p = 10^{-1000}$, as then we can only compute $\logit(p)$, if we specify $L := -\log(p) \leftrightarrow p = \exp(-L)$.

`> curve(-log(1 - exp(-x)), 0, 10)`



seems fine. — — However, ...


Navigation icons

Martin Mächler (R Core/ ETH Zurich) Arbitrarily Accurate R: Package 'Rmpfr' ZurichR @ ETH, Jan.2012 3 / 31

Navigation icons

Martin Mächler (R Core/ ETH Zurich) Arbitrarily Accurate R: Package 'Rmpfr' ZurichR @ ETH, Jan.2012 4 / 31

```
> curve(-log(1 - exp(-x)), 0, 50, log="y")
```



◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ↺ 🔍 ↻

A set of navigation icons typically found in Beamer presentations, including symbols for back, forward, search, and other slide controls.

$$> -\log(1 - \exp(x))$$

```
> log(-log(1 - exp(x)))# --> -Inf values
```

```
> ## ok, how about more accuracy
```

```
> x. <- mpfr(x, 120)
```

```
> log(-log(1 - exp(x.)))# aha... looks perfect now
```

6 'mpfr' numbers of precision 120 bits

[1] -39.9999999999999999997932904877538241734

[2] -38.9999999999999999423372196756935807

```
[3] -37.9999999999999998430451715981029611
```

[4] -36.9999999999999957331848579613165434

[5] -35.99999999999999884024061830552087239

[6] -34.999999999999999684744214015307532692

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡

Navigation icons: back, forward, search, and other controls.

```
> x <- seq(-40, -20, by = .5)
```


```
> plot(x,x, type="n", ylab="", ann=FALSE)
```

```
> lines(x, log(-log(1 - exp(x))), type = "o", col = "purple", lwd=3
```



Now repeat this with “with accuracy”:

```
> x <- seq(-40, -20, by = .5)
> plot(x,x, type="n", ylab="", ann=FALSE)
> lines(x, log(-log(1 - exp(x))), type = "o", col = "purple", lwd=3)
> x. <- mpfr(x, 120)
> lines(x, log(-log(1 - exp(x.))), col=2, lwd=1.5)
```



Navigation icons: back, forward, search, etc.

Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of Rmpfr
- 5 Package and Session Information
- 6 Conclusions

Exact Factorials and Binomial Coefficients

In combinatorics or when computing series, work with *exact* factorials or binomial coefficients. E.g., need all factorials $k!$, for $k = 1, 2, \dots, 24$ or a full row of Pascal's triangle, i.e., want all $\binom{n}{k}$ for $n = 50$.

With R's double precision, and if you display its full internal precision,

```
> noquote(sprintf("%-30.0f", factorial(24)))
```

```
[1] 620448401733239409999872
```

then it is obviously wrong for $24!$, as its last digits are known to be 0.

Easily get full precision results, by replacing “simple” numbers by “mpfr”s:

```
> ns <- mpfr(5:24, 120) ; factorial(ns)
```

```
20 'mpfr' numbers of precision 120 bits
[1] 120 720
[3] 5040 40320
[5] 362880 3628800
[7] 39916800 479001600
```

```
.....
.....
[13] 355687428096000 6402373705728000
[15] 121645100408832000 2432902008176640000
[17] 51090942171709440000 112400072777607680000
[19] 25852016738884976640000 6204484017332394099998720000
```

Navigation icons: back, forward, search, etc.

Or for the 70-th Pascal triangle row, $\binom{n}{k}$ for $n = 70$ and $k = 0, \dots, n$,

```
> chooseMpfr.all(n = 70)
```

```
70 'mpfr' numbers of precision 67 bits
[1] 70 2415 54740
[4] 916895 12103014 131115985
[7] 1198774720 9440350920 65033528560
[10] 396704524216 2163842859360 10638894058520
.....
.....
[25] 6455761770304780752 11173433833219812840 18208558839321176480
[28] 27963143931814663880 40498346384007444240 55347740058143507128
[31] 71416438784701299520 87038784768854708790 100226479430802391940
[34] 109069992321755544170 112186277816662845432 109069992321755544170
.....
.....
[67] 54740 2415 70
[70] 1
```

Navigation icons: back, forward, search, etc.

Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of Rmpfr
- 5 Package and Session Information
- 6 Conclusions

Alternating Binomial Sums

Alternating binomial sums appear in different contexts and are typically challenging, i.e., currently impossible, to evaluate reliably as soon as n is larger than around 50 – 70.

The alternating binomial sum $sB(f, n) := \text{sumBinom}(n, f, n0=0)$ is (up to sign) equal to the n -th forward difference operator $\Delta^n f$,

$$sB(f, n) := \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot f(k) = (-1)^n \Delta^n f, \quad (1)$$

where

$$\Delta^n f = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot f(k) \quad (2)$$

is the n -fold iterated forward difference $\Delta f(x) = f(x+1) - f(x)$ (for $x = 0$).

Navigation icons

Navigation icons

computing alternating binomial sums in R

An obvious R implementation of $sB(f, n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot f(k)$,

```
> sumBinom <- function(n, f, n0=0, ...) {  
+   k <- n0:n  
+   sum( choose(n, k) * (-1)^k * f(k, ...))  
+ }  
> ## and the same for a whole *SET* of n values:  
> sumBin.all.R <- function(n, f, n0=0, ...)  
+   sapply(n, sumBinom, f=f, n0=n0, ...)
```

Will see: gets numerical problems, for relatively small n even for well behaved functions $f(\cdot)$.

The Rmpfr version is pretty simple, as well:

```
> sumBinomMpfr  
  
function (n, f, n0 = 0, alternating = TRUE, precBits = 256)  
{  
  stopifnot(0 <= n0, n0 <= n, is.function(f))  
  sum(chooseMpfr.all(n, k0 = n0, alternating = alternating) *  
      f(mpfr(n0:n, precBits = precBits)))  
}  
<environment: namespace:Rmpfr>
```

and has a corresponding version for a full set of n :

Navigation icons

Navigation icons

Comparison “double” vs “mpfr”:

Compute `sumBinomMpfr(n)` for a whole set of 'n' values:

```
> sumBin.all <- function(n, f, n0=0, precBits = 256, ...)
+ {
+   N <- length(n)
+   precBits <- rep(precBits, length = N)
+   ll <- lapply(seq_len(N), function(i)
+     sumBinomMpfr(n[i], f, n0=n0, precBits=precBits[i], ...)
+   )
+   sapply(ll, as, "double")
+ }
```

((Note that `sapply(.)` is not directly applicable, because its “simplify” part behaves wrongly with vectors of “mpfr” numbers.))

For comparison, computing the alternating binomial sum,

$$sB(f, n) := \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot f(k),$$

now try the simple $f(x) = \sqrt{x}$, i.e., in R, `sqrt(x)`:

```
> nn <- 5:80
> system.time(res.R <- sumBin.all.R(nn, f = sqrt)) ## instant!


  user  system elapsed 
0.002   0.000   0.002 

> system.time(resMpfr <- sumBin.all (nn, f = sqrt)) ## ~2 seconds

  user  system elapsed 
1.525   0.007   1.573
```

```
> matplot(nn, cbind(res.R, resMpfr), type = "l", lty=1,
+   ylim = extendrange(resMpfr, f = 0.25), xlab = "n",
+   main = "sumBinomMpfr(n, f = sqrt) vs. R double precision",
+   legend("topleft", leg=c("double prec.", "mpfr"), lty=1, col=1:2, 1
```

sumBinomMpfr(n, f = sqrt) vs. R double precision



Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of Rmpfr
- 5 Package and Session Information
- 6 Conclusions

“All” R arithmetic and math functions just work with “mpfr” numbers:

Via “Group” S4 methods

```
> getGroupMembers("Arith")
```

```
[1] "+" "-" "*" "^" "%%" "%/%" "/"
```

```
> getGroupMembers("Compare")
```

```
[1] "==" ">" "<" "!=" "<=" ">="
```

```
> getGroupMembers("Math")
```

```
[1] "abs"      "sign"      "sqrt"      "ceiling"   "floor"     "trunc"
[7] "cummax"   "cummin"    "cumprod"   "cumsum"    "exp"        "expm1"
[13] "log"      "log10"     "log2"      "log1p"     "cos"        "cosh"
[19] "sin"      "sinh"      "tan"        "tanh"      "acos"       "acosh"
[25] "asin"     "asinh"     "atan"       "atanh"     "gamma"      "lgamma"
[31] "digamma"  "trigamma"
```

Navigation icons

- Arbitrarily precise numerical integration (via Romberg), via our `integrateR()`
- Arbitrarily root finding (and hence numerical *inverse* function), via `unirootR()`.

Navigation icons

In addition to the basic arithmetic (including all “Math” functions!), based on the MPFR C library, Rmpfr provides arbitrarily precise versions of

- Bessel functions $j_n(x)$, $y_n(x)$, and $Ai(x)$
- Error functions `erf(x)`, and `erfc(x)`, or equivalently, `pnorm(x)` and `pnorm(x, lower.tail=FALSE)`.
- Riemann’s $\zeta(x) = \text{zeta}(x)$,
- Exponential integral $Ei(x)$
- Dilogarithm $Li_2(x) = \text{Li2}(x)$

Can also do simple arithmetic with “mpfrMatrix” and “mpfrArray” objects, e.g.

```
> head(x <- mpfr(0:7, 64)/7)
```

```
6 'mpfr' numbers of precision 64 bits
```

```
[1] 0 0.142857142857142857141 0.285714285714285714282
[4] 0.428571428571428571436 0.571428571428571428564 0.714285714285714285691
```

```
> mx <- x ; dim(mx) <- c(4,2)
```

```
> mx[ 1:3, ] + c(1,10,100)
```

```
'mpfrMatrix' of dim(.) = (3, 2) of precision 64 bits
```

```
      [,1]      [,2]
[1,] 1.000000000000000000000 1.57142857142857142851
[2,] 10.1428571428571428570 10.7142857142857142860
[3,] 100.285714285714285712 100.857142857142857144
```

Navigation icons

We can transpose or multiply such matrices, e.g.,

```
> t(mx) %*% 10^(1:4)
```

```
'mpfrMatrix' of dim(.) = (2, 1) of precision 64 bits
      [,1]
```

```
[1,] 4585.71428571428571441
```

```
[2,] 10934.2857142857142856
```

or

```
> crossprod(mx)
```

```
'mpfrMatrix' of dim(.) = (2, 2) of precision 64 bits
      [,1] [,2]
```

```
[1,] 0.285714285714285714282 0.775510204081632653086
```

```
[2,] 0.775510204081632653086 2.57142857142857142851
```

and apply works too :

```
> (s7 <- apply(7 * mx, 2, sum))
```

```
2 'mpfr' numbers of precision 64 bits
```

```
[1] 6 22
```

and, note that `all.equal()` methods are provided, as well:

```
> all.equal(s7, c(6,22), tol = 1e-40) # note the tolerance!
```

```
[1] TRUE
```

Navigation icons

Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of `Rmpfr`
- 5 Package and Session Information
- 6 Conclusions

Navigation icons

We can transpose or multiply such matrices, e.g.,

```
> t(mx) %*% 10^(1:4)
```

```
'mpfrMatrix' of dim(.) = (2, 1) of precision 64 bits
      [,1]
```

```
[1,] 4585.71428571428571441
```

```
[2,] 10934.2857142857142856
```

or

```
> crossprod(mx)
```

```
'mpfrMatrix' of dim(.) = (2, 2) of precision 64 bits
      [,1] [,2]
```

```
[1,] 0.285714285714285714282 0.775510204081632653086
```

```
[2,] 0.775510204081632653086 2.57142857142857142851
```

and apply works too :

```
> (s7 <- apply(7 * mx, 2, sum))
```

```
2 'mpfr' numbers of precision 64 bits
```

```
[1] 6 22
```

and, note that `all.equal()` methods are provided, as well:

```
> all.equal(s7, c(6,22), tol = 1e-40) # note the tolerance!
```

```
[1] TRUE
```

Navigation icons

```
> toLatex(sessionInfo())
```

- R version 2.14.1 Patched (2012-01-17 r58138),
x86_64-unknown-linux-gnu
- Locale: LC_CTYPE=de_CH.UTF-8, LC_NUMERIC=C,
LC_TIME=en_US.UTF-8, LC_COLLATE=de_CH.UTF-8,
LC_MONETARY=en_US.UTF-8, LC_MESSAGES=de_CH.UTF-8,
LC_PAPER=C, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C,
LC_MEASUREMENT=de_CH.UTF-8, LC_IDENTIFICATION=C
- Base packages: base, datasets, graphics, grDevices, methods, stats,
utils
- Other packages: Rmpfr 0.4-5, sfsmisc 1.0-19
- Loaded via a namespace (and not attached): gmp 0.5-0, tools 2.14.1

Navigation icons

```
> packageDescription("Rmpfr")
```

```
Package: Rmpfr
Type: Package
Title: R MPFR - Multiple Precision Floating-Point Reliable
Version: 0.4-5
Date: 2012-01-12
Author: Martin Maechler
Maintainer: Martin Maechler <maechler@stat.math.ethz.ch>
Depends: methods, R (>= 2.11.0)
SystemRequirements: gmp (>= 4.2.3), mpfr (>= 3.0.0)
SystemReqNotes: MPFR (MP Floating-Point Reliable Library,
  http://mpfr.org/) and GMP (GNU Multiple Precision library,
  http://gmplib.org/), see README
Imports: gmp
Suggests: gmp, polynom
SuggestNotes: 'polynom' is only needed for vignette
URL: http://rmpfr.r-forge.r-project.org/
Description: Rmpfr provides S4 classes and methods for arithmetic
  including transcendental ("special") functions for
  arbitrary precision floating point numbers. To this end, it
  interfaces to the LGPL'ed MPFR (Multiple Precision
  Floating-Point Reliable) Library which itself is based on
  the GMP (GNU Multiple Precision) Library.
```

```
License: GPL (>= 2)
```

Martin Mächler (R Core/ ETH Zurich)

Arbitrarily Accurate R: Package 'Rmpfr'

ZurichR @ ETH, Jan.2012

28 / 31

Martin Mächler (R Core/ ETH Zurich)

Arbitrarily Accurate R: Package 'Rmpfr'

ZurichR @ ETH, Jan.2012

29 / 31

Conclusion

- The package `Rmpfr` allows to use arbitrarily high precision numbers instead of R's double precision numbers in many R computations and functions.
- This is achieved by defining S4 classes of such numbers and vectors, matrices, and arrays thereof, where all arithmetic and mathematical functions work via the (GNU) MPFR C library, where MPFR is acronym for "**M**ultiple **P**recision **F**loating-**P**oint **R**eliably". MPFR is Free Software, available under the LGPL license, and itself is built on the free GNU Multiple Precision arithmetic library (GMP).
- Consequently, by using `Rmpfr`, you can often call your R function or numerical code with `mpfr`-numbers instead of simple numbers, and all results will automatically be much more accurate.

Outline

- 1 Example: 16 digits are not always enough!
- 2 Example 2: Exact Factorials and Binomial Coefficients
- 3 Alternating Binomial Sums
- 4 Capabilities of `Rmpfr`
- 5 Package and Session Information
- 6 Conclusions

Executive Summary

- Double precision accuracy (almost 16 digits) is not always sufficient
- `Rmpfr` is here for arbitrarily precision computations in R.
- Many R functions — **when** `source()` **d** — will work with "mpfr"-numbers automagically

That's all folks — with thanks for your attention!

Martin Mächler – maechler@R-project.org

Executive Summary

- Double precision accuracy (almost 16 digits) is not always sufficient
- `Rmpfr` is here for arbitrarily precision computations in R .
- Many R functions — **when** `source()` **d** — will work with “mpfr”-numbers automagically

That's all folks — with thanks for your attention!

Martin Mächler – maechler@R-project.org