

# Package 'RTL'

April 12, 2023

**Type** Package

**Title** Risk Tool Library - Trading, Risk, 'Analytics' for Commodities

**Version** 1.3.3

**Date** 2023-04-11

**Description** A toolkit for Commodities 'analytics', risk management and trading professionals. Includes functions for API calls to [<https://commodities.morningstar.com/#/>](https://commodities.morningstar.com/#/), [<https://developer.genscape.com/>](https://developer.genscape.com/), and [and <https://www.bankofcanada.ca/valet/docs>](https://www.bankofcanada.ca/valet/docs).

**License** MIT + file LICENSE

**URL** <https://github.com/risktoollib/RTL>

**Depends** R (>= 4.0)

**Imports** dplyr, ggplot2, htr, jsonlite, lubridate, magrittr, plotly, purrr, RCurl, readr, rlang, stringr, tibble, tidyr, timetk, tsibble, xts, zoo, glue, Rcpp, lifecycle, TTR, tidyselect, PerformanceAnalytics

**Suggests** testthat (>= 3.0.0), covr, lpSolve, rgdal, rugarch, tidyquant, feasts, fabletools, MASS

**Encoding** UTF-8

**LazyData** true

**LazyDataCompression** xz

**RoxygenNote** 7.2.3

**Config/testthat/edition** 3

**LinkingTo** Rcpp

**BugReports** <https://github.com/risktoollib/RTL/issues>

**NeedsCompilation** yes

**Author** Philippe Cote [aut, cre],  
Nima Safaian [aut]

**Maintainer** Philippe Cote <pcote@ualberta.ca>

**Repository** CRAN

**Date/Publication** 2023-04-12 10:00:09 UTC

**R topics documented:**

bond . . . . .	3
chart_eia_sd . . . . .	4
chart_eia_steo . . . . .	5
chart_fwd_curves . . . . .	6
chart_pairs . . . . .	7
chart_PerfSummary . . . . .	7
chart_spreads . . . . .	8
chart_zscore . . . . .	10
cma . . . . .	11
CRReuro . . . . .	11
crudeOil . . . . .	12
cushing . . . . .	13
dflong . . . . .	13
dfwide . . . . .	14
efficientFrontier . . . . .	14
eia2tidy . . . . .	15
eia2tidy_all . . . . .	16
eiaStocks . . . . .	17
eiaStorageCap . . . . .	17
eurodollar . . . . .	18
expiry_table . . . . .	18
fitOU . . . . .	19
fizdiffs . . . . .	19
futuresRef . . . . .	20
fx fwd . . . . .	20
garch . . . . .	21
getBoC . . . . .	21
getCurve . . . . .	22
getGenscapePipeOil . . . . .	23
getGenscapeStorageOil . . . . .	25
getGIS . . . . .	26
getPrice . . . . .	27
getPrices . . . . .	29
holidaysOil . . . . .	30
npv . . . . .	31
ohlc . . . . .	32
planets . . . . .	32
promptBeta . . . . .	33
refineryLP . . . . .	34
refineryLPdata . . . . .	34
returns . . . . .	35
rolladjust . . . . .	36
simGBM . . . . .	36
simMultivariates . . . . .	37
simOU . . . . .	38
simOUJ . . . . .	39

simOUt . . . . .	40
spot2futConvergence . . . . .	41
spot2futCurve . . . . .	42
steo . . . . .	42
stocks . . . . .	43
swapCOM . . . . .	43
swapFutWeight . . . . .	44
swapInfo . . . . .	45
swapIRS . . . . .	46
tickers_eia . . . . .	48
tradeCycle . . . . .	48
tradeHubs . . . . .	49
tradeprocess . . . . .	49
tradeStats . . . . .	50
tradeStrategyDY . . . . .	50
tradeStrategySMA . . . . .	51
tsQuotes . . . . .	52
usSwapCurves . . . . .	52
usSwapCurvesPar . . . . .	53
wtiSwap . . . . .	53
<b>Index</b>	<b>54</b>

---

bond	<i>Bond pricing</i>
------	---------------------

---

### Description

Compute bond price, cash flow table or duration

### Usage

```
bond(ytm = 0.05, C = 0.05, T2M = 1, m = 2, output = "price")
```

### Arguments

ytm	Yield to Maturity. numeric
C	Coupon rate per annum. numeric
T2M	Time to maturity in years. numeric
m	Periods per year for coupon payments e.g semi-annual = 2. numeric
output	"price", "df" or "duration". character

### Value

Returns price numeric, cash flows tibble, or duration numeric

**Author(s)**

Philippe Cote

**Examples**

```
bond(ytm = 0.05, C = 0.05, T2M = 1, m = 2, output = "price")
bond(ytm = 0.05, C = 0.05, T2M = 1, m = 2, output = "df")
bond(ytm = 0.05, C = 0.05, T2M = 1, m = 2, output = "duration")
```

---

chart\_eia\_sd

*EIA weekly supply-demand information by product group*


---

**Description**

Given a product group extracts all information to create SD Balances.

**Usage**

```
chart_eia_sd(
  market = "mogas",
  key = "your EIA.gov API key",
  from = "2011-01-01",
  legend.pos = list(x = 0.4, y = 0.53),
  output = "chart"
)
```

**Arguments**

market	"mogas", "dist", "jet" or "resid". character
key	Your private EIA API token. character
from	Date as character "2020-07-01". Default to all dates available. character
legend.pos	Defaults to list(x = 0.4, y = 0.53). list
output	"chart" for plotly object or "data" for dataframe.

**Value**

A plotly chart htmlwidget or a tibble.

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
chart_eia_sd(key = key, market = "mogas")

## End(Not run)
```

---

chart_eia_steo	<i>EIA Short Term Energy Outlook</i>
----------------	--------------------------------------

---

## Description

Extract data and either plots or renders dataframe.

## Usage

```
chart_eia_steo(  
  market = "globalOil",  
  key = "your EIA.gov API key",  
  from = "2018-07-01",  
  fig.title = "EIA STEO Global Liquids SD Balance",  
  fig.units = "million barrels per day",  
  legend.pos = list(x = 0.4, y = 0.53),  
  output = "chart"  
)
```

## Arguments

market	"globalOil" only currently implemented. character
key	Your private EIA API token. character
from	Date as character "2020-07-01". Default to all dates available. character
fig.title	Defaults to "EIA STEO Global Liquids SD Balance". character
fig.units	Defaults to "million barrels per day" character
legend.pos	Defaults to list(x = 0.4, y = 0.53) list
output	"chart" for plotly object or "data" for dataframe.

## Value

A plotly chart htmlwidget or a tibble.

## Author(s)

Philippe Cote

## Examples

```
## Not run:  
chart_eia_steo(key = EIAkey, market = "globalOil")  
  
## End(Not run)
```

---

chart_fwd_curves	<i>Plots historical forward curves</i>
------------------	--

---

## Description

Returns a plot of forward curves through time

## Usage

```
chart_fwd_curves(df = dfwide, cmdty = "cmewti", weekly = TRUE, ...)
```

## Arguments

df	Wide dataframe with date column and multiple series columns (multivariate). tibble
cmdty	Futures contract code in expiry_table object: unique(expiry_table\$cmdty). character
weekly	Defaults to TRUE for weekly forward curves. logical
...	other graphical parameters

## Value

plot of forward curves through time. NULL

## Author(s)

Philippe Cote

## Examples

```
df <- dfwide %>%  
  dplyr::select(date, dplyr::starts_with("CL")) %>%  
  tidyr::drop_na()  
chart_fwd_curves(  
  df = df, cmdty = "cmewti", weekly = TRUE,  
  main = "WTI Forward Curves", ylab = "$ per bbl", xlab = "", cex = 2  
)
```

---

chart_pairs	<i>Pairwise scatter plots for timeseries</i>
-------------	--

---

**Description**

Plots pairwise scatter plots with the time dimension. Useful when exploring structural changes in timeseries properties for modeling.

**Usage**

```
chart_pairs(df = df, title = "Time Series Pairs Plot")
```

**Arguments**

df	Wide data frame. tibble
title	Chart title. character

**Value**

A plotly object. htmlwidget

**Author(s)**

Philippe Cote

**Examples**

```
df <- dfwide %>%  
  dplyr::select(date, CL01, NG01, HO01, RB01) %>%  
  tidyr::drop_na()  
chart_pairs(df = df, title = "example")
```

---

chart_PerfSummary	<i>Cumulative performance and drawdown summary.</i>
-------------------	---

---

**Description**

Multi Asset Display of Cumulative Performance and Drawdowns

**Usage**

```
chart_PerfSummary(  
  ret = ret,  
  geometric = TRUE,  
  main = "Cumulative Returns and Drawdowns",  
  linesize = 1.25  
)
```

**Arguments**

ret	Wide dataframe univariate or multivariate of percentage returns. tibble
geometric	Use geometric returns TRUE or FALSE. logical
main	Chart title. character
linesize	Size of lines in chart and legend. numeric

**Value**

Cumulative performance and drawdown charts. ggplot

**Author(s)**

Philippe Cote

**Examples**

```
ret <- data.frame(
  date = seq.Date(Sys.Date() - 60, Sys.Date(), 1),
  CL01 = rnorm(61, 0, .01), RB01 = rnorm(61, 0, 0.02)
)
chart_PerfSummary(ret = ret,
  geometric = TRUE,
  main = "Cumulative Returns and Drawdowns",
  linesize = 1.25)
```

---

chart\_spreads

*Futures contract spreads comparison across years*

---

**Description**

Plots specific contract pairs across years with time being days from expiry.

**Usage**

```
chart_spreads(
  cpairs = cpairs,
  daysFromExpiry = 200,
  from = "2012-01-01",
  conversion = c(1, 1),
  feed = "CME_NymexFutures_EOD",
  iuser = "x@xyz.com",
  ipassword = "pass",
  title = "March/April ULSD Nymex Spreads",
  yaxis = "$ per bbl",
  output = "chart"
)
```



**Arguments**

cpairs	Tibble of contract pairs - see example for expiry when not expired yet. tibble
daysFromExpiry	Number of days from expiry to compute spreads. numeric
from	From date character
conversion	Defaults to c(1,1) first and second contracts. 42 from \$ per gallons to bbls. numeric
feed	Morningstar Feed Table. character
iuser	Morningstar user name as character - sourced locally in examples. character
ipassword	Morningstar user password as character - sourced locally in examples. character
title	Title for chart. character
yaxis	y-axis label. character
output	"chart" for htmlwidget or "data" for tibble.

**Value**

A plotly object or a dataframe

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
cpairs <- dplyr::tibble(
  year = c("2018", "2019", "2020", "2021", "2022", "2023"),
  first = c("@H08H", "@H09H", "@H00H", "@H021H", "@H022H", "@H023H"),
  second = c("@CL8H", "@CL9H", "@CL0H", "@CL21H", "@CL22H", "@CL23H"),
  expiry = c(NA, NA, NA, NA, NA, "2023-02-23")
)
chart_spreads(
  cpairs = cpairs, daysFromExpiry = 200, from = "2012-01-01",
  conversion = c(42, 1), feed = "CME_NymexFutures_EOD",
  iuser = "x@xyz.com", ipassword = "pass",
  title = "March/April ULSD Nymex Spreads",
  yaxis = "$ per bbl",
  output = "data"
)

## End(Not run)
```

---

chart_zscore	<i>Z-Score applied to seasonal data divergence</i>
--------------	--

---

### Description

Supports analytics and display of seasonal data. Z-Score is computed on residuals conditional on their seasonal period. Beware that most seasonal charts in industry e.g. (NG Storage) is not de-trended so results once you apply an STL decomposition will vary from the unadjusted seasonal plot.

### Usage

```
chart_zscore(
  df = df,
  title = "NG Storage Z Score",
  per = "yearweek",
  output = "zscore",
  chart = "seasons"
)
```

### Arguments

df	Long data frame with columns series, date and value. tibble
title	Default is a blank space returning the unique value in df\$series. character
per	Frequency of seasonality "yearweek" (DEFAULT). "yearmonth", "yearquarter" character
output	"stl" for STL decomposition chart, "stats" for STL fitted statistics. "res" for STL fitted data. "zscore" for residuals Z-score, "seasonal" for standard seasonal chart.
chart	"seasons" for feasts::gg_season() (DEFAULT) "series" for feasts::gg_subseries()

### Value

Time series of STL decomposition residuals Z-Scores, or standard seasonal chart with feasts package.

### Author(s)

Philippe Cote

### Examples

```
## Not run:
df <- eiaStocks %>% dplyr::filter(series == "NGLower48")
title <- "NGLower48"
chart_zscore(df = df, title = " ", per = "yearweek", output = "stl", chart = "seasons")
chart_zscore(df = df, title = " ", per = "yearweek", output = "stats", chart = "seasons")
```

```

chart_zscore(df = df, title = " ", per = "yearweek", output = "res", chart = "seasons")
chart_zscore(df = df, title = " ", per = "yearweek", output = "zscore", chart = "seasons")
chart_zscore(df = df, title = " ", per = "yearweek", output = "seasonal", chart = "seasons")

## End(Not run)

```

cma

*metadata for WTI CMA***Description**

CME WTI Calendar Month Average swap information

**Usage**

```
cma
```

**Format**

data frame

**Value**

tibble

**Source**

cme

CRReuro

*Cox-Ross-Rubinstein binomial option model***Description**

European option binomial model on a stock without dividends. For academic purpose only. Use `fOptions::CRRBinomialTreeOptions` for real-life usage.

**Usage**

```
CRReuro(S, X, sigma, r, T2M, N, type)
```

**Arguments**

S	Stock price. numeric
X	Strike price. numeric
sigma	Implied volatility e.g. 0.20 numeric
r	Risk-free rate. numeric
T2M	Time to maturity in years numeric
N	Number of time steps. Internally $dt = T2M/N$ . numeric
type	"call" or "put" character

**Value**

List of asset price tree, option value tree and option price. list

**Author(s)**

Philippe Cote

**Examples**

```
CRReuro(S = 100, X = 100, sigma = 0.2, r = 0.1, T2M = 1, N = 5, type = "call")
```

---

crudeOil	<i>dataset: crude assays</i>
----------	------------------------------

---

**Description**

crude assays

**Usage**

```
crudeOil
```

**Format**

list

**Value**

list

---

cushing	<i>dataset: WTI Cushing Futures and storage utilization</i>
---------	---

---

**Description**

c1, c2, c1c2 and Cushing storage utilization

**Usage**

cushing

**Format**

list

**Value**

list

**Source**

CME and EIA

---

dflong	<i>dataset: commodity prices in a long dataframe format</i>
--------	---

---

**Description**

Futures settlement data set.

**Usage**

dflong

**Format**

data frame

**Value**

tibble

**Source**

Morningstar Commodities

---

dfwide	<i>dataset: commodity prices in a wide dataframe format</i>
--------	---

---

**Description**

Futures settlement data set.

**Usage**

```
dfwide
```

**Format**

data frame

**Value**

tibble

**Source**

Morningstar Commodities

---

efficientFrontier	<i>Markowitz Efficient Frontier</i>
-------------------	-------------------------------------

---

**Description**

Generates random portfolio weights statistics based on absolute returns.

**Usage**

```
efficientFrontier(
  nsims = 5000,
  x = RTL::fizdiffs %>% dplyr::select(date, dplyr::contains("WCS")),
  expectedReturns = NULL
)
```

**Arguments**

nsims	Number of portfolio simulations. Defaults to 5000 numeric
x	List as provided by output of RTL::simMultivariates(). list
expectedReturns	Defaults to NULL using periodic returns means. numeric

**Details****Commodities:**

Unlike traditional portfolio management, in commodities many transactions are with derivatives (futures and swaps) and have zero or low initial investments.

**Return types:**

This function is used for commodities where returns are dollars per units for real assets e.g. storage tanks, pipelines...Here we measure directly the periodic return in dollars per contract unit.

**Empirical Finance:**

I would encourage you to pick a commodity futures contract of your choice and draw a scatter plot of price level versus the daily dollar per unit change as measure of risk. As a trading analyst or risk manager, then ask yourself about the implications of using log returns that you then re-apply to current forward curve level to arrive at a dollar risk measure per units instead of measuring directly risk in dollars per unit.

**Value**

List of portfolios and chart of efficient frontier list

**Author(s)**

Philippe Cote

**Examples**

```
x = RTL::fizdiffs %>% dplyr::select(date, dplyr::contains("WCS"))
efficientFrontier(nsims = 10, x = x, expectedReturns = NULL)
efficientFrontier(nsims = 10, x = x, expectedReturns = c(0.5,0.8,0.9))
```

---

eia2tidy

*EIA API call with tidy output*

---

**Description**

Extracts data from the Energy Information Administration (EIA) API to tibble format with optional custom series name. Makes a clean wrapper for use with purrr for multiple series extraction. Query Browser at <https://www.eia.gov/opendata/qb.php>.

**Usage**

```
eia2tidy(ticker, key, name = " ")
```

**Arguments**

ticker	EIA series name. character
key	Your private EIA API token as character "yourapikey". character
name	Name you want to give the series. Defaults to ticker if set to " " character

**Value**

A tibble object with class date for weekly, monthly, quarterly or annual data and class POSIXct for hourly. tibble

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
# Single Series
RTL::eia2tidy(ticker = "PET.MCRFPTX2.M", key = "yourapikey", name = "TexasProd")
# Multiple Series
# Use eia2tidy_all() or pivot_longer, drop_na and then pivot_wider to wrangled results.

## End(Not run)
```

---

eia2tidy\_all

*EIA API multiple calls with tidy output*

---

**Description**

Extracts data from the Energy Information Administration (EIA) API to tibble format with optional custom series name. Makes a clean wrapper for use with purrr for multiple series extraction. Query Browser at <https://www.eia.gov/opa/opa/qb.php>.

**Usage**

```
eia2tidy_all(
  tickers = tibble::tribble(~ticker, ~name, "PET.W_EPC0_SAX_YCUOK_MBBL.W",
    "CrudeCushing", "NG.NW2_EPG0_SWO_R48_BCF.W", "NGLower48"),
  key,
  long = TRUE
)
```

**Arguments**

tickers	tibble of EIA series and names you want to assign. character
key	Your private EIA API token as character "yourapikey". character
long	TRUE (default) to return a long data frame or FASLE for wide. logical

**Value**

A tibble object with class date for weekly, monthly, quarterly or annual data and class POSIXct for hourly. tibble



**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
eia2tidy_all(tickers = tibble::tribble(~ticker, ~name,
                                     "PET.W_EPC0_SAX_YCUOK_MBBL.W", "CrudeCushing",
                                     "NG.NW2_EPG0_SWO_R48_BCF.W", "NGLower48"),
            key = "your API key", long = TRUE)

## End(Not run)
```

---

eiaStocks	<i>dataset: EIA weekly stocks</i>
-----------	-----------------------------------

---

**Description**

EIA weekly crude, NG, ULSD and RBOB stocks.

**Usage**

eiaStocks

**Format**

data frame

**Value**

tibble

---

eiaStorageCap	<i>dataset: EIA working storage capacity</i>
---------------	--

---

**Description**

EIA working storage capacity in kbs except NG in bcf.

**Usage**

eiaStorageCap

**Format**

data frame

**Value**

tibble

---

`eurodollar`*dataset: Eurodollar futures contracts*

---

**Description**

ED futures contract for December 2024

**Usage**`eurodollar`**Format**

data frame

**Value**

tibble

**Source**

Morningstar

---

`expiry_table`*dataset: expiry of common commodity futures contract.*

---

**Description**

This dataframe provides detailed information on major futures contracts specifications pertaining to last settlement, notices and delivery dates. It also provides tickers in some data service.

**Usage**`expiry_table`**Format**

data frame

**Value**

tibble

---

fitOU	<i>Fits a Ornstein–Uhlenbeck process to a dataset</i>
-------	---

---

**Description**

Parameter estimation for Ornstein–Uhlenbeck process

**Usage**

```
fitOU(spread)
```

**Arguments**

spread            Spread time series. tibble

**Value**

List of alpha, mu and sigma estimates. list

**Author(s)**

Philippe Cote

**Examples**

```
spread <- simOU(mu = 5, theta = .5, sigma = 0.2, T = 5, dt = 1 / 250)
fitOU(spread)
```

---

fizdiffs	<i>dataset: randomised physical crude differentials</i>
----------	---

---

**Description**

Randomized data set for education purpose of selected physical crude differentials to WTI.

**Usage**

```
fizdiffs
```

**Format**

data frame

**Value**

tibble

---

futuresRef	<i>dataset: futures contracts metadata</i>
------------	--

---

**Description**

Exchange-traded contract month codes and specifications.

**Usage**

futuresRef

**Format**

data frame

**Value**

tibble

---

fxfwd	<i>dataset: USDCAD FX forward rates</i>
-------	---

---

**Description**

USDCAD historicals and forward curve

**Usage**

fxfwd

**Format**

list

**Value**

list

**Source**

Morningstar and <https://ca.investing.com/rates-bonds/forward-rates>

---

garch	<i>Wrapper for a Garch(1,1) returning either a plot or data.</i>
-------	--

---

**Description**

Computes annualised Garch(1,1) volatilities using fGarch package.

**Usage**

```
garch(x = x, out = TRUE)
```

**Arguments**

x	Wide dataframe with date column and single series (univariate). tibble
out	"chart" to return replot_xts chart, "data" to return xts data or "fit" for uGARCHfit fit output

**Value**

replot\_xts chart, xts data, or uGARCHfit fit

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
x <- dflong %>% dplyr::filter(series == "CL01")
x <- returns(df = x, retType = "rel", period.return = 1, spread = TRUE)
x <- rolladjust(x = x, commodityname = c("cmewti"), rolltype = c("Last.Trade"))
summary(garch(x = x, out = "fit"))
garch(x = x, out = "chart")
garch(x = x, out = "data")

## End(Not run)
```

---

getBoC	<i>Bank of Canada Valet API</i>
--------	---------------------------------

---

**Description**

Extracts series from the Bank of Canada's Valet API. API documentation at <https://www.bankofcanada.ca/valet/docs>.

**Usage**

```
getBoC(series)
```

**Arguments**

series            Array of series name: c("FXCADUSD", "BD.CDN.2YR.DQ.YLD"). character

**Value**

A long data frame. tibble

**Author(s)**

Philippe Cote

**Examples**

```
RTL::getBoC(series = c("FXCADUSD", "BD.CDN.2YR.DQ.YLD"))
```

---

getCurve

*Morningstar Commodities API forward curves*

---

**Description**

Returns forward curves from Morningstar API. See below for current feeds supported. You need your own credentials with Morningstar.

**Usage**

```
getCurve(
  feed = "Crb_Futures_Price_Volume_And_Open_Interest",
  contract = "CL",
  date = "2020-08-10",
  fields = c("Open, High, Low, Close"),
  iuser = "x@xyz.com",
  ipassword = "pass"
)
```

**Arguments**

feed	Morningstar Feed Table e.g "Crb_Futures_Price_Volume_And_Open_Interest". character
contract	Morningstar contract root e.g. "CL" for CME WTI and "BG" for ICE Brent. character
date	From date yyyy-mm-dd. character
fields	Defaults to c("Open, High, Low, Close"). character
iuser	Morningstar user name as character - sourced locally in examples. character
ipassword	Morningstar user password as character - sourced locally in examples. character

**Value**

wide data frame. tibble

**Current Feeds Supported**

- Crb\_Futures\_Price\_Volume\_And\_Open\_Interest
- CME\_NymexFuturesIntraday\_EOD
- ICE\_EuroFutures and ICE\_EuroFutures\_continuous

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
# CME WTI Futures
getCurve(
  feed = "Crb_Futures_Price_Volume_And_Open_Interest", contract = "CL",
  date = "2020-07-13", fields = c("Open, High, Low, Close"),
  iuser = "x@xyz.com", ipassword = "pass"
)

getCurve(
  feed = "Crb_Futures_Price_Volume_And_Open_Interest", contract = "BG",
  date = "2020-07-13", fields = c("Open, High, Low, Close"),
  iuser = "x@xyz.com", ipassword = "pass"
)

getCurve(
  feed = "LME_ClosingPriceDelayed", contract = "AHD",
  date = "2021-06-25", fields = c("Last_Price"),
  iuser = "x@xyz.com", ipassword = "pass"
)

## End(Not run)
```

---

getGenscapePipeOil      *Genscape API call for oil pipelines*

---

**Description**

Returns oil pipeline flows in barrels per day data from Genscape API. You need your own credentials. Refer to API documentation for argument values. It is assumed if you use this function that you know the pipelines you need to extract to build supply demand balances. Use the online API to identify the pipeline IDs. <https://developer.genscape.com/docs/services/oil-transportation/operations/GetPipelineFlowValues>

**Usage**

```
getGenscapePipeOil(  
  frequency = "daily",  
  regions = "Canada",  
  pipelineIDs = c(97),  
  revision = "revised",  
  limit = 5000,  
  offset = 0,  
  startDate = "2015-01-01",  
  endDate = as.character(Sys.Date()),  
  apikey = "yourapikey"  
)
```

**Arguments**

frequency	"daily" DEFAULT. character
regions	See API webpage. Multiple values separated by commas e.g. "Canada", "Gulf-Coast"). character
pipelineIDs	See API webpage. c(98,54...) for specific pipes. numeric
revision	See API webpage. character
limit	See API webpage. Max 5000. numeric
offset	See API webpage. numeric
startDate	"yyyy-mm-dd". character
endDate	"yyyy-mm-dd". character
apikey	Your API key. character

**Value**

wide data frame. tibble

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:  
getGenscapePipeOil(  
  frequency = "daily", regions = "Canada", pipelineIDs = c(97),  
  revision = "revised", limit = 5000, offset = 0,  
  startDate = "2015-01-01", endDate = as.character(Sys.Date()),  
  apikey = "yourapikey"  
)  
  
## End(Not run)
```



---

getGenscapeStorageOil *Genscape API call for oil storage*

---

### Description

Returns oil storage data from Genscape API. You need your own credentials. Refer to API documentation for argument values. <https://developer.genscape.com/docs/services/oil-storage/operations/StorageVolumeByOwnerGet>

### Usage

```
getGenscapeStorageOil(
  feed = "owner-volumes",
  regions = "Canada",
  products = "Crude",
  revision = "revised",
  limit = 5000,
  offset = 0,
  startDate = "2011-01-01",
  endDate = as.character(Sys.Date()),
  apikey = "yourapikey"
)
```

### Arguments

feed	"owner-volumes" DEFAULT or "tank-volumes". character
regions	See API webpage. Multiple values separated by commas e.g. "Canada, Cushing"). character
products	See API webpage. Multiple values separated by commas e.g. "Crude, JetFuel"). character
revision	See API webpage. character
limit	See API webpage. Max 5000. numeric
offset	See API webpage. numeric
startDate	"yyyy-mm-dd". character
endDate	"yyyy-mm-dd". character
apikey	Your API key as a character string. character

### Value

wide data frame tibble

### Author(s)

Philippe Cote

**Examples**

```
## Not run:
# where yourapikey = "yourapikey".
getGenscapeStorageOil(
  feed = "owner-volumes", regions = "Canada", products = "Crude",
  revision = "revised", limit = 5000, offset = 0,
  startDate = "2011-01-01", endDate = "2020-11-01", apikey = yourapikey
)

## End(Not run)
```

---

getGIS

---

*Extract and convert GIS data from a URL*


---

**Description**

Returns a `SpatialPointsDataFrame` from a shapefile URL. @section Examples with EIA and Government of Alberta

- from [https://www.eia.gov/maps/layer\\_info-m.php](https://www.eia.gov/maps/layer_info-m.php) :
- `crudepipelines <- getGIS(url = "https://www.eia.gov/maps/map_data/CrudeOil_Pipelines_US_EIA.zip")`
- `refineries <- getGIS(url = "https://www.eia.gov/maps/map_data/Petroleum_Refineries_US_EIA.zip")`
- from <https://gis.energy.gov.ab.ca/Geoview/OSPNG>
- `AB <- getGIS(url = "https://gis.energy.gov.ab.ca/GeoviewData/OS_Agreements_Shape.zip")`

**Usage**

```
getGIS(
  url = "https://gis.energy.gov.ab.ca/GeoviewData/OS_Agreements_Shape.zip"
)
```

**Arguments**

`url` URL of the zipped shapefile. character

**Value**

`SpatialPointsDataFrame`. `SpatialPolygonsDataFrame`

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
getGIS(url = "https://gis.energy.gov.ab.ca/GeoviewData/OS_Agreements_Shape.zip")

## End(Not run)
```

---

getPrice	<i>Morningstar Commodities API single call</i>
----------	--

---

**Description**

Returns data from Morningstar API. See below for current feeds supported. You need your own credentials with Morningstar. In examples sourced locally.

**Usage**

```
getPrice(
  feed = "CME_NymexFutures_EOD",
  contract = "@CL21Z",
  from = "2020-09-01",
  iuser = "x@xyz.com",
  ipassword = "pass"
)
```

**Arguments**

feed	Morningstar Feed Table. character
contract	Morningstar key. character
from	From date yyyy-mm-dd. character
iuser	Morningstar user name as character - sourced locally in examples. character
ipassword	Morningstar user password as character - sourced locally in examples. character

**Value**

wide data frame. tibble

**Current Feeds Supported**

- CME\_CbotFuturesEOD and CME\_CbotFuturesEOD\_continuous
- CME\_NymexFutures\_EOD and CME\_NymexFutures\_EOD\_continuous
- CME\_NymexOptions\_EOD
- CME\_CmeFutures\_EOD and CME\_CmeFutures\_EOD\_continuous
- CME\_Comex\_FuturesSettlement\_EOD and CME\_Comex\_FuturesSettlement\_EOD\_continuous
- LME\_AskBidPrices\_Delayed

- SHFE\_FuturesSettlement\_RT
- ICE\_EuroFutures and ICE\_EuroFutures\_continuous
- ICE\_NybotCoffeeSugarCocoaFutures and ICE\_NybotCoffeeSugarCocoaFutures\_continuous
- CME\_STLCPC\_Futures
- CFTC\_CommitmentsOfTradersCombined. Requires multiple keys. Separate them by a space e.g. "N10 06765A NYME 01".
- Morningstar\_FX\_Forwards. Requires multiple keys. Separate them by a space e.g. "USD-CAD 2M".
- ERCOT\_LmpsByResourceNodeAndElectricalBus.
- PJM\_Rt\_Hourly\_Lmp.
- AESO\_ForecastAndActualPoolPrice.

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
getPrice(
  feed = "CME_NymexFutures_EOD", contract = "@CL21Z",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_NymexFutures_EOD_continuous", contract = "CL_006_Month",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_NymexOptions_EOD", contract = "@LQ21ZP4000",
  from = "2020-03-15", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_CbotFuturesEOD", contract = "C0Z",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_CbotFuturesEOD_continuous", contract = "ZB_001_Month",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_CmeFutures_EOD_continuous", contract = "HE_006_Month",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "Morningstar_FX_Forwards", contract = "USDCAD 2M",
  from = "2019-08-26", iuser = username, ipassword = password
)
getPrice(
  feed = "CME_CmeFutures_EOD", contract = "LH0N",
```

```

    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "CME_CmeFutures_EOD_continuous", contract = "HE_006_Month",
    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "ICE_EuroFutures", contract = "BRN0Z",
    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "ICE_EuroFutures_continuous", contract = "BRN_001_Month",
    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "ICE_NybotCoffeeSugarCocoaFutures", contract = "SB21H",
    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "ICE_NybotCoffeeSugarCocoaFutures_continuous", contract = "SF_001_Month",
    from = "2019-08-26", iuser = username, ipassword = password
  )
  getPrice(
    feed = "AESO_ForecastAndActualPoolPrice", contract = "Forecast_Pool_Price",
    from = "2021-04-01", iuser = username, ipassword = password
  )
  getPrice(
    feed = "LME_MonthlyDelayed_Derived", contract = "AHD 2021-12-01 2021-12-31",
    from = "2021-04-01", iuser = username, ipassword = password
  )

## End(Not run)

```

---

getPrices

*Morningstar Commodities API multiple calls*


---

### Description

Multiple Morningstar API calls using getPrice functions. Refer to getPrices() for list of currently supported data feeds.

### Usage

```

getPrices(
  feed = "CME_NymexFutures_EOD",
  contracts = c("CL9Z", "CL0F", "CL0M"),
  from = "2019-01-01",
  iuser = "x@xyz.com",
  ipassword = "pass"
)

```

**Arguments**

feed	Morningstar Feed Table. character
contracts	Symbols vector. character
from	From date yyyy-mm-dd. character
iuser	Morningstar user name as character - sourced locally in examples. character
ipassword	Morningstar user password as character - sourced locally in examples. character

**Value**

wide data frame. tibble

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
getPrices(
  feed = "CME_NymexFutures_EOD", contracts = c("@CL0Z", "@CL1F", "@CL21H", "@CL21Z"),
  from = "2020-01-01", iuser = username, ipassword = password
)

## End(Not run)
```

---

holidaysOil

*dataset: NYMEX and ICE holiday calendars*

---

**Description**

Holiday calendars for NYMEX and ICE Brent

**Usage**

```
holidaysOil
```

**Format**

data frame

**Value**

tibble

---

 npv

 NPV
 

---

### Description

Computes NPV with discount factor interpolation. This function is used for teaching NPV and NPV at Risk and needs to be customized.

### Usage

```
npv(
  init.cost = -375,
  C = 50,
  cf.freq = 0.25,
  TV = 250,
  T2M = 2,
  disc.factors = us.df,
  BreakEven = FALSE,
  BE.yield = 0.01
)
```

### Arguments

<code>init.cost</code>	Initial investment cost. numeric
<code>C</code>	Periodic cash flow. numeric
<code>cf.freq</code>	Cash flow frequency in year fraction e.g. quarterly = 0.25. numeric
<code>TV</code>	Terminal Value. numeric
<code>T2M</code>	Time to Maturity in years. numeric
<code>disc.factors</code>	Data frame of discount factors using <code>ir.df.us()</code> function. numeric
<code>BreakEven</code>	TRUE when using a flat discount rate assumption. logical
<code>BE.yield</code>	Set the flat IR rate when <code>BreakEven = TRUE</code> . logical

### Value

List of NPV and NPV Data frame. list

### Author(s)

Philippe Cote

**Examples**

```

npv(
  init.cost = -375, C = 50, cf.freq = .5, TV = 250, T2M = 2,
  disc.factors = RTL::usSwapCurves, BreakEven = FALSE, BE.yield = .0399
)$npv
npv(
  init.cost = -375, C = 50, cf.freq = .5, TV = 250, T2M = 2,
  disc.factors = RTL::usSwapCurves, BreakEven = FALSE, BE.yield = .0399
)$df

```

---

ohlc

*dataset: randomiser to convert settlement into OHLC*


---

**Description**

OHLC profile using historical CL 1st Contract OHLC

**Usage**

```
ohlc
```

**Format**

data frame

**Value**

tibble

**Source**

CME

---

planets

*dataset: IR compounding*


---

**Description**

Planet metrics from NASA

**Usage**

```
planets
```

**Format**

data frame



**Value**

tibble

**Source**

<https://nssdc.gsfc.nasa.gov/planetary/factsheet/index.html>

---

promptBeta	<i>Computes betas of futures contracts with respect to the 1st line contract</i>
------------	--

---

**Description**

Returns betas of futures contracts versus front futures contract.

**Usage**

```
promptBeta(x = x, period = "all", betatype = "all", output = "chart")
```

**Arguments**

x	Wide dataframe with date column and multiple series columns (multivariate). tibble
period	"all" or numeric period of time in last n periods as character eg "100". character
betatype	"all" "bull" "bear". character
output	"betas" or "chart". character

**Value**

betas data frame tibble or plotly chart of betas htmlwidgets

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
x <- dflong %>%
  dplyr::filter(grepl("CL",series)) %>%
  dplyr::mutate(series = readr::parse_number(series)) %>% dplyr::group_by(series) %>%
  RTL::returns(df = ., retType = "abs",period.return = 1,spread = TRUE) %>%
  RTL::rolladjust(x = .,commodityname = c("cmewti"),rolltype = c("Last.Trade")) %>%
  # removing the day it prices went negative...
  dplyr::filter(!date %in% c(as.Date("2020-04-20"),as.Date("2020-04-21")))
promptBeta(x = x, period = "all", betatype = "all", output = "chart")
promptBeta(x = x, period = "all", betatype = "bull", output = "betas")
promptBeta(x = x, period = "100", betatype = "bear", output = "betas")
```

```
## End(Not run)
```

---

refineryLP	<i>LP model for refinery optimization</i>
------------	---

---

### Description

Plain vanilla refinery optimization LP model.

### Usage

```
refineryLP(
  crudes = RTL::refineryLPdata$inputs,
  products = RTL::refineryLPdata$outputs
)
```

### Arguments

crudes	Data frame of crude inputs. tibble
products	Data frame of product outputs and max outputs. tibble

### Value

Optimal crude slate and profits. tibble

### Author(s)

Philippe Cote

### Examples

```
refineryLP(crudes = RTL::refineryLPdata$inputs, products = RTL::refineryLPdata$outputs)
```

---

refineryLPdata	<i>dataset: refinery LP model sample inputs and outputs</i>
----------------	---

---

### Description

Simple refinery to be used in running LP modeling for education purposes.

### Usage

```
refineryLPdata
```

**Format**

list

**Value**

list

---

returns	<i>Compute absolute, relative or log returns.</i>
---------	---

---

**Description**

Computes periodic returns from a dataframe ordered by date

**Usage**

```
returns(df = dflong, retType = "abs", period.return = 1, spread = FALSE)
```

**Arguments**

df	Long dataframe with colnames = c("date","value","series"). character
retType	"abs" for absolute, "rel" for relative, or "log" for log returns. character
period.return	Number of rows over which to compute returns. numeric
spread	TRUE if you want to spread into a long dataframe. logical

**Value**

A dataframe object of returns. tibble

**Author(s)**

Philippe Cote

**Examples**

```
x <- dflong %>% dplyr::filter(grepl("CL01", series))
returns(df = x, retType = "abs", period.return = 1, spread = TRUE)
```

---

rolladjust	<i>Adjusts daily returns for futures contracts roll</i>
------------	---

---

### Description

Returns a xts price or return object adjusted for contract roll. The methodology used to adjust returns is to remove the daily returns on the day after expiry and for prices to adjust historical rolling front month contracts by the size of the roll at each expiry. This is conducive to quantitative trading strategies as it reflects the PL of a financial trader.

### Usage

```
rolladjust(x, commodityname = c("cmewti"), rolltype = c("Last.Trade"), ...)
```

### Arguments

x	A df of returns.
commodityname	Name of commodity in expiry_table: unique(expiry_table\$cmdty) or "cmecan" for WCW
rolltype	Type of contract roll: "Last.Trade" or "First.Notice".
...	Other parms

### Value

Roll-adjusted xts object of returns

### Author(s)

Philippe Cote

### Examples

```
ret <- dplyr::tibble(date = seq.Date(Sys.Date() - 60, Sys.Date(), 1), CL01 = rnorm(61, 0, 1))
rolladjust(x = ret, commodityname = c("cmewti"), rolltype = c("Last.Trade"))
```

---

simGBM	<i>GBM process simulation</i>
--------	-------------------------------

---

### Description

Simulates a Geometric Brownian Motion process

**Usage**

```
simGBM(  
  nsims = 1,  
  S0 = 10,  
  drift = 0,  
  sigma = 0.2,  
  T2M = 1,  
  dt = 1/12,  
  vec = TRUE  
)
```

**Arguments**

nsims	number of simulations. Defaults to 1. numeric
S0	Spot price at t=0. numeric
drift	Drift term in percentage. numeric
sigma	Standard deviation. numeric
T2M	Maturity in years. numeric
dt	Time step in period e.g. 1/250 = 1 business day. numeric
vec	Vectorized implementation. Defaults to TRUE. logical

**Value**

A tibble of simulated values. tibble

**Author(s)**

Philippe Cote

**Examples**

```
simGBM(nsims = 2, S0 = 10, drift = 0, sigma = 0.2, T2M = 1, dt = 1 / 12, vec = TRUE)
```

---

simMultivariates	<i>Multivariate normal from historical dataset</i>
------------------	--

---

**Description**

Generates multivariate random epsilons using absolute returns.

**Usage**

```
simMultivariates(nsims = 10, x, s0 = NULL)
```

**Arguments**

nsims	Number of simulations. Defaults to 10. numeric
x	Wide data frame of prices with date as first column. tibble
s0	Vector of starting value for each variables. Defaults to NULL with zero. numeric

**Value**

List of means, sds, covariance matrix, correlation matrix and simulated values. list

**Author(s)**

Philippe Cote

**Examples**

```
simMultivariates(nsims = 10, x = RTL::fizdiffs, s0 = NULL)
```

---

simOU	<i>OU process simulation</i>
-------	------------------------------

---

**Description**

Simulates a Ornstein–Uhlenbeck process

**Usage**

```
simOU(
  nsims = 2,
  S0 = 5,
  mu = 5,
  theta = 0.5,
  sigma = 0.2,
  T2M = 1,
  dt = 1/12,
  epsilon = NULL
)
```

**Arguments**

nsims	number of simulations. Defaults to 2. numeric
S0	S at t=0. numeric
mu	Mean reversion level. numeric
theta	Mean reversion speed. numeric
sigma	Standard deviation. numeric
T2M	Maturity in years. numeric

dt Time step size e.g.  $1/250 = 1$  business day. numeric

epsilon Defaults to NULL function generates its own. numeric OPTIONAL: Array of epsilons for nsims = 1, if you want to feed your own e.g. in a multivariate context.

**Value**

Simulated values. tibble

**Author(s)**

Philippe Cote

**Examples**

```
simOU(nsims = 5, S0 = 5, mu = 5, theta = .5, sigma = 0.2, T2M = 1, dt = 1 / 12, epsilon = NULL)
simOU(nsims = 1, S0 = 5, mu = 5, theta = .5, sigma = 0.2, T2M = 1, dt = 1 / 12,
epsilon = matrix(rnorm(12,0,sqrt(1/12))))
simOU(nsims = 2, S0 = 5, mu = 5, theta = .5, sigma = 0.2, T2M = 1, dt = 1 / 12,
epsilon = replicate(2,rnorm(12,0,sqrt(1/12))))
```

---

simOUJ

*OUJ process simulation*

---

**Description**

Simulates a Ornstein–Uhlenbeck process with Jumps

**Usage**

```
simOUJ(
  nsims = 2,
  S0 = 5,
  mu = 5,
  theta = 10,
  sigma = 0.2,
  jump_prob = 0.05,
  jump_avesize = 2,
  jump_stdv = 0.05,
  T2M = 1,
  dt = 1/250
)
```

**Arguments**

nsims	number of simulations. Defaults to 2. numeric
S0	S at t=0. numeric
mu	Mean reversion level. numeric
theta	Mean reversion speed. numeric
sigma	Standard deviation. numeric
jump_prob	Probability of jumps. numeric
jump_avesize	Average size of jumps. numeric
jump_stdv	Standard deviation of jump average size. numeric
T2M	Maturity in years. numeric
dt	Time step size e.g. 1/250 = 1 business day. numeric

**Value**

Simulated values. tibble

**Author(s)**

Philippe Cote

**Examples**

```
simOUJ(nsims = 2, S0 = 5, mu = 5, theta = .5, sigma = 0.2,
jump_prob = 0.05, jump_avesize = 3, jump_stdv = 0.05,
T2M = 1, dt = 1 / 12)
```

---

simOUt

*OU process simulation*

---

**Description**

Simulates a Ornstein–Uhlenbeck process with mu as a function of time

**Usage**

```
simOUt(
  nsims = 2,
  S0 = 0,
  mu = dplyr::tibble(t = 0:20, mr = c(rep(2, 7), rep(4, 14))),
  theta = 12,
  sigma = 0.2,
  T2M = 1,
  dt = 1/12
)
```



**Arguments**

nsims	number of simulations. Defaults to 2. numeric
S0	S at t=0. numeric
mu	data frame of mean reversion level as a function of time. tibble
theta	Mean reversion speed. numeric
sigma	Standard deviation. numeric
T2M	Maturity in years. numeric
dt	Time step size e.g. 1/250 = 1 business day. numeric

**Value**

Simulated values. tibble

**Author(s)**

Philippe Cote

**Examples**

```
mu = dplyr::tibble(t = 0:20, mr = c(rep(2,7), rep(4,14)))  
simOut(nsims = 2, S0 = 5, mu = mu, theta = .5, sigma = 0.2, T2M = 1, dt = 1 / 12)
```

---

spot2futConvergence     *dataset: spot to futures convergence*

---

**Description**

Cash and futures

**Usage**

```
spot2futConvergence
```

**Format**

data frame

**Value**

tibble

**Source**

Morningstar, EIA

---

spot2futCurve      *dataset: spot to futures convergence curve*

---

**Description**

Forward Curve

**Usage**

spot2futCurve

**Format**

data frame

**Value**

tibble

**Source**

Morningstar, EIA

---

steo      *dataset: EIA Short Term Energy Outlook*

---

**Description**

Short Term Energy Outlook from the EIA.

**Usage**

steo

**Format**

plotly object

**Value**

htmlwidget

**Source**

eia

---

stocks	<i>dataset: Yahoo Finance data sets</i>
--------	---

---

**Description**

Traded equity prices and returns

**Usage**

```
stocks
```

**Format**

```
list
```

**Value**

```
list
```

**Source**

Yahoo Finance

---

swapCOM	<i>Commodity Calendar Month Average Swaps</i>
---------	---

---

**Description**

Commodity swap pricing from exchange settlement

**Usage**

```
swapCOM(  
  futures = futs,  
  futuresNames = c("CL0M", "CL0N"),  
  pricingDates = c("2020-05-01", "2020-05-30"),  
  contract = "cmewti",  
  exchange = "nymex"  
)
```

**Arguments**

futures	Wide data frame of futures prices for the given swap pricing dates. tibble
futuresNames	Tickers of relevant futures contracts. character
pricingDates	Vector of start and end pricing dates. See example. character
contract	Contract code in data(expiry_table). sort(unique(expiry_table\$comdty)) for options. character
exchange	Exchange code in data(holidaysOil). Currently only "nymex" and "ice" supported. character

**Value**

Data frame of historical swap prices. tibble

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
c <- paste0("CL0", c("M", "N", "Q"))
futs <- getPrices(
  feed = "CME_NymexFutures_EOD", contracts = c, from = "2019-08-26",
  iuser = username, ipassword = password
)
swapCOM(
  futures = futs, futuresNames = c("CL0M", "CL0N"),
  pricingDates = c("2020-05-01", "2020-05-30"), contract = "cmewti", exchange = "nymex"
)

## End(Not run)
```

---

swapFutWeight

*Commodity Calendar Month Average Swap futures weights*

---

**Description**

Returns the percentage weight of the future in Calendar Month Average swaps

**Usage**

```
swapFutWeight(
  Month = "2020-09-01",
  contract = "cmewti",
  exchange = "nymex",
  output = "first.fut.weight"
)
```

**Arguments**

Month	First calendar day of the month. character
contract	Contract code in data(expiry_table). sort(unique(expiry_table\$cmdty)) for options. character
exchange	Exchange code in data(holidaysOil). Currently only "nymex" and "ice" supported. character
output	Either "numDaysFut1", "numDaysFut2" or "first.fut.weight". character

**Value**

Depending on output setting. numeric If first.fut.weight, to compute swap 1 - first.fut.weight = % applied to 2nd line contract.

**Author(s)**

Philippe Cote

**Examples**

```
swapFutWeight(
  Month = "2020-09-01",
  contract = "cmewti", exchange = "nymex", output = "first.fut.weight"
)
```

---

swapInfo

*Commodity Swap details to learn their pricing*

---

**Description**

Returns dataframe required to price a WTI averaging instrument based on first line settlements.

**Usage**

```
swapInfo(
  date = "2020-05-06",
  feeds = dplyr::tibble(feed = c("Crb_Futures_Price_Volume_And_Open_Interest",
    "CME_NymexFutures_EOD_continuous"), ticker = c("CL", "CL_001_Month")),
  contract = "cmewti",
  exchange = "nymex",
  iuser = "x@xyz.com",
  ipassword = "pass",
  output = "all"
)
```

**Arguments**

date	Character date as of which you want to extract daily settlement and forward values. character
feeds	Feeds for Morningstar getCurve() and getPrice(). character
contract	Contract code in data(expiry_table). sort(unique(expiry_table\$cmdty)) for options. character
exchange	Exchange code in data(holidaysOil). Defaults to "nymex". character
iuser	Morningstar user name as character - sourced locally in examples. character
ipassword	Morningstar user password as character - sourced locally in examples. character
output	"chart" or "all". character

**Value**

Plot or a list of data frame and plot if output = "all". htmlwidget or list

**Author(s)**

Philippe Cote

**Examples**

```
## Not run:
feeds <- dplyr::tibble(
  feed = c(
    "Crb_Futures_Price_Volume_And_Open_Interest",
    "CME_NymexFutures_EOD_continuous"
  ),
  ticker = c("CL", "CL_001_Month")
)
swapInfo(
  date = "2020-05-06", feeds = feeds, contract = "cmewti", exchange = "nymex",
  iuser = "x@xyz.com", ipassword = "pass", output = "all"
)

## End(Not run)
```

---

swapIRS

*Interest Rate Swap*

---

**Description**

Computes the mark to market of an IRS

**Usage**

```

swapIRS(
  trade.date = lubridate::today(),
  eff.date = lubridate::today() + 2,
  mat.date = lubridate::today() + 2 + lubridate::years(2),
  notional = 1e+06,
  PayRec = "Rec",
  fixed.rate = 0.05,
  float.curve = usSwapCurves,
  reset.freq = 3,
  disc.curve = usSwapCurves,
  convention = c("act", 360),
  bus.calendar = "NY",
  output = "price"
)

```

**Arguments**

trade.date	Date object. Defaults to today(). Date
eff.date	Date object. Defaults to today() + 2 days. Date
mat.date	Date object. Defaults to today() + 2 years. Date
notional	Numeric value of notional. Defaults to 1,000,000. numeric
PayRec	"Pay" or "Rec" fixed. character
fixed.rate	Numeric fixed interest rate. Defaults to 0.05. Date
float.curve	List of interest rate curves. Defaults to data("usSwapCurves"). list
reset.freq	Numeric where 1 = "monthly", 3 = quarterly, 6 = Semi annual 12 = yearly. character
disc.curve	List of interest rate curves. Defaults to data("usSwapCurves"). list
convention	Vector of convention e.g. c("act",360) c(30,360),... character
bus.calendar	Banking day calendar. Not implemented.
output	"price" for swap price or "all" for price, cash flow data frame, duration. character

**Value**

List of swap price, cash flow data frame, duration. list

**Author(s)**

Philippe Cote

**Examples**

```

data("usSwapCurves")
swapIRS(
  trade.date = as.Date("2020-01-04"), eff.date = as.Date("2020-01-06"),
  mat.date = as.Date("2022-01-06"), notional = 1000000,

```

```

PayRec = "Rec", fixed.rate = 0.05, float.curve = usSwapCurves, reset.freq = 3,
disc.curve = usSwapCurves, convention = c("act", 360),
bus.calendar = "NY", output = "all"
)

```

---

tickers_eia	<i>dataset: metadata of key EIA tickers grouped by products.</i>
-------------	--

---

### Description

Supports automated upload of EIA data through its API by categories. Data frame organized by Supply Demand categories and products.

### Usage

```
tickers_eia
```

### Format

data frame

### Value

tibble

---

tradeCycle	<i>dataset: Canadian and US physical crude trading calendars</i>
------------	--

---

### Description

Crude Trading Trade Cycles. Note that is uses NYMEX calendar (WIP)

### Usage

```
tradeCycle
```

### Format

data frame

### Value

tibble



---

tradeHubs	<i>dataset: GIS locations for crude oil trading hubs</i>
-----------	--

---

**Description**

Trading Hubs

**Usage**

tradeHubs

**Format**

data frame

**Value**

tibble

---

tradeprocess	<i>dataset: data for teaching the various ways to monetize a market call.</i>
--------------	---

---

**Description**

Data set for explaining the various ways to monetize a market view.

**Usage**

tradeprocess

**Format**

data frame

**Value**

tibble

---

tradeStats	<i>Risk-reward statistics for quant trading</i>
------------	---

---

**Description**

Compute list of risk reward metrics

**Usage**

```
tradeStats(x, Rf = 0)
```

**Arguments**

x	Univariate xts object of returns OR dataframe with date and return variables. xts
Rf	Risk-free rate. numeric

**Value**

List of risk/reward metrics. list

**Author(s)**

Philippe Cote

**Examples**

```
library(PerformanceAnalytics)
tradeStats(x = stocks$spy, Rf = 0)
```

---

tradeStrategyDY	<i>Sample quantitative trading strategy</i>
-----------------	---

---

**Description**

Based on dividend yield.

**Usage**

```
tradeStrategyDY(data, par1value = 50, par2value = 200)
```

**Arguments**

data	Dataframe of OHLC data e.g. RTL::uso. tibble
par1value	Value of first parameter e.g. short MA. numeric
par2value	Value of second parameter e.g. long MA. numeric

**Value**

Dataframe with indicators, signals, trades and profit and loss. tibble

**Author(s)**

Philippe Cote

**Examples**

```
tradeStrategyDY(data = RTL::stocks$ry, par1value = 50, par2value = 200)
```

---

tradeStrategySMA	<i>Sample quantitative trading strategy</i>
------------------	---

---

**Description**

Moving average crossover strategy

**Usage**

```
tradeStrategySMA(data = RTL::stocks$uso, par1value = 50, par2value = 200)
```

**Arguments**

data	Dataframe of OHLC data e.g. RTL::uso. tibble
par1value	Value of first parameter e.g. short MA. numeric
par2value	Value of second parameter e.g. long MA. numeric

**Value**

Dataframe with indicators, signals, trades and profit and loss. tibble

**Author(s)**

Philippe Cote

**Examples**

```
tradeStrategySMA(data = RTL::stocks$uso, par1value = 50, par2value = 200)
```

---

tsQuotes	<i>dataset: interest rate curve data for RQuantlib .</i>
----------	--

---

**Description**

USD IR curve input for RQuantlib::DiscountCurve

**Usage**

tsQuotes

**Format**

data frame

**Value**

tibble

---

usSwapCurves	<i>dataset: US bootstrapped interest rate curve.</i>
--------------	--

---

**Description**

USD IR Discount, Forward and Zero curves from RQuantlib::DiscountCurve

**Usage**

usSwapCurves

**Format**

List

**Value**

list

**Source**

Morningstar and FRED

---

usSwapCurvesPar	<i>dataset: US bootstrapped interest rate curve parallel sample.</i>
-----------------	--

---

**Description**

USD IR Discount, Forward and Zero curves from RQuantlib::DiscountCurve - Parallel toy data set

**Usage**

```
usSwapCurvesPar
```

**Format**

data frame

**Value**

tibble

---

wtiSwap	<i>dataset: WTI Calendar Month Average Swap pricing data</i>
---------	--

---

**Description**

WTI Crude futures

**Usage**

```
wtiSwap
```

**Format**

data frame

**Value**

tibble

**Source**

Morningstar

# Index

## \* datasets

- cma, 11
- crudeOil, 12
- cushing, 13
- dflong, 13
- dfwide, 14
- eiaStocks, 17
- eiaStorageCap, 17
- eurodollar, 18
- expiry\_table, 18
- fizdiffs, 19
- futuresRef, 20
- fx fwd, 20
- holidaysOil, 30
- ohlc, 32
- planets, 32
- refineryLPdata, 34
- spot2futConvergence, 41
- spot2futCurve, 42
- steo, 42
- stocks, 43
- tickers\_eia, 48
- tradeCycle, 48
- tradeHubs, 49
- tradeprocess, 49
- tsQuotes, 52
- usSwapCurves, 52
- usSwapCurvesPar, 53
- wtiSwap, 53

bond, 3

chart\_eia\_sd, 4

chart\_eia\_steo, 5

chart\_fwd\_curves, 6

chart\_pairs, 7

chart\_PerfSummary, 7

chart\_spreads, 8

chart\_zscore, 10

cma, 11

CRReuro, 11

crudeOil, 12

cushing, 13

dflong, 13

dfwide, 14

efficientFrontier, 14

eia2tidy, 15

eia2tidy\_all, 16

eiaStocks, 17

eiaStorageCap, 17

eurodollar, 18

expiry\_table, 18

fitOU, 19

fizdiffs, 19

futuresRef, 20

fx fwd, 20

garch, 21

getBoC, 21

getCurve, 22

getGenscapePipeOil, 23

getGenscapeStorageOil, 25

getGIS, 26

getPrice, 27

getPrices, 29

holidaysOil, 30

npv, 31

ohlc, 32

planets, 32

promptBeta, 33

refineryLP, 34

refineryLPdata, 34

returns, 35

rolladjust, [36](#)

simGBM, [36](#)  
simMultivariates, [37](#)  
simOU, [38](#)  
simOUJ, [39](#)  
simOUt, [40](#)  
spot2futConvergence, [41](#)  
spot2futCurve, [42](#)  
steo, [42](#)  
stocks, [43](#)  
swapCOM, [43](#)  
swapFutWeight, [44](#)  
swapInfo, [45](#)  
swapIRS, [46](#)

tickers\_eia, [48](#)  
tradeCycle, [48](#)  
tradeHubs, [49](#)  
tradeprocess, [49](#)  
tradeStats, [50](#)  
tradeStrategyDY, [50](#)  
tradeStrategySMA, [51](#)  
tsQuotes, [52](#)

usSwapCurves, [52](#)  
usSwapCurvesPar, [53](#)

wtiSwap, [53](#)