

Package ‘htsr’

December 23, 2022

Type Package

Title Hydro-Meteorology Time-Series

Version 1.2.0

Date 2022-12-23

Author Pierre Chevallier [aut, cre]

Maintainer Pierre Chevallier <pierre.chevallier@ird.fr>

Description Functions for the management and treatment of hydrology and meteorology time-series stored in a 'Sqlite' data base.

License GPL-2

Depends R (>= 3.5.0)

Imports dplyr, tibble, ggplot2, readr, stringr, purrr, lubridate, RSQLite, DBI, RODBC, zoo, utils, stats, WriteXLS, readxl, RColorBrewer, grDevices, directlabels, openair, raster, editData, shiny

Suggests knitr, rmarkdown

Encoding UTF-8

RoxygenNote 7.2.3

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2022-12-23 08:40:02 UTC

R topics documented:

| | |
|--------------|---|
| ds_dismeas | 3 |
| ds_exp_hts | 4 |
| ds_inventory | 4 |
| ds_sensor | 5 |
| ds_station | 6 |
| d_backup | 6 |

| | |
|--------------------------------|----|
| d_compact | 7 |
| d_convert_hydraccess | 7 |
| d_convert_weewx | 8 |
| d_create | 9 |
| d_exp_hts | 10 |
| d_imp_hts | 11 |
| d_inventory | 12 |
| d_rem_hts | 13 |
| d_sensor | 13 |
| d_station | 15 |
| d_table | 18 |
| d_wind | 19 |
| fc | 20 |
| f_change_id | 20 |
| f_convert | 21 |
| f_csv_multivar | 22 |
| f_month2day | 22 |
| f_properties | 23 |
| hs_tstep | 24 |
| htsr | 24 |
| h_addna | 25 |
| h_avday | 25 |
| h_common | 26 |
| h_condition | 27 |
| h_cumul | 28 |
| h_gaperr | 29 |
| h_gapfill | 29 |
| h_gaprem_itv | 30 |
| h_month | 31 |
| h_nodata | 32 |
| h_rainsnow | 33 |
| h_rbind | 34 |
| h_replace | 35 |
| h_restrict | 36 |
| h_rollav | 36 |
| h_season | 37 |
| h_stat_basic | 38 |
| h_substitute | 38 |
| h_timestep | 39 |
| h_weightedsum | 40 |
| h_wl_di | 41 |
| h_year | 42 |
| ps_plohts | 43 |
| p_bar | 43 |
| p_bar_app | 45 |
| p_box_month | 46 |
| p_clim | 47 |
| p_discalib | 48 |

| | |
|-----------------------------------------|-----------|
| <code>ds_dismeas</code> | 3 |
| <code>p_gaps</code> | 49 |
| <code>p_hypso</code> | 50 |
| <code>p_line</code> | 51 |
| <code>p_line_app</code> | 53 |
| <code>p_scatter</code> | 54 |
| <code>p_wind</code> | 55 |
| <code>w_atmp_alt</code> | 56 |
| <code>w_etp</code> | 57 |
| <code>w_spechum2relhum</code> | 59 |
| <code>w_temp_alt</code> | 60 |
| <code>z_coord</code> | 60 |
| <code>z_set</code> | 61 |
| Index | 63 |

| | |
|-------------------------|-----------------------------------------------------------------|
| <code>ds_dismeas</code> | <i>Add, Modify or Remove discharge measurements (Shiny app)</i> |
|-------------------------|-----------------------------------------------------------------|

Description

Add, Modify or Remove discharge measurements for a station/sensor

Usage

```
ds_dismeas(fsq, sta, sen)
```

Arguments

| | |
|------------------|----------------|
| <code>fsq</code> | htsr data base |
| <code>sta</code> | Station Id. |
| <code>sen</code> | Sensor Id. |

Value

an actualized data base

Author(s)

P. Chevallier - Dec 2020

ds_exp_hts

Shiny app: export hts files from a sqlite data base

Description

Shiny application of the [d_exp_hts](#) function

Usage

```
ds_exp_hts(fsq)
```

Arguments

fsq File name of the Sqlite data base

Details

Complete the requested information in the left panel, then press the submit button in order to extract the file. If you want to display the plot of the extracted file, choose "line" or "bar" and press the plot button. When finished press "done".

If the data do not exist, the app crashes and error messages are displayed in the console window.

Value

a shiny session

Author(s)

P. Chevallier - Apr 2020 - Oct 2021

ds_inventory

Shiny app: inventory of htsr sqlite data base

Description

Shiny application of the [d_inventory](#) function

Usage

```
ds_inventory(fsq)
```

Arguments

fsq File name of the Sqlite data base

Details

Complete the requested information in the left panel, then press the submit button. If the station field is empty, the function will return the list of the stations in the data base. If the station field is filled, the function will return the list of the station sensors in the data base. When finished press "done".

If the data do not exist, the app crashes and error messages are displayed in the console window.

Value

a shiny session

Author(s)

P. Chevallier - Sep-Nov 2020

ds_sensor

Shiny app: create, modify or remove a sensor from a data base

Description

Shiny application of the [d_sensor](#) function

Usage

```
ds_sensor(fsq)
```

Arguments

fsq File name of the Sqlite data base

Value

a shiny session

Author(s)

P. Chevallier - Nov 2020

ds_station

Shiny app: create, modify or remove a station from a data base

Description

Shiny application of the [d_station](#) function

Usage

```
ds_station(fsq)
```

Arguments

fsq File name of the Sqlite data base

Value

a shiny session

Author(s)

P. Chevallier - Apr-Nov 2020

d_backup

Backup a data base

Description

Back a htsr sqlite data base

Usage

```
d_backup(fsq)
```

Arguments

fsq Full name of the data base

Value

A saved data base with extension .bak

Author(s)

P. Chevallier - Jan 2019 / Nov 2020

| | |
|-----------|----------------------------|
| d_compact | <i>Compact a data base</i> |
|-----------|----------------------------|

Description

Compact htsr sqlite data base

Usage

```
d_compact(fsq)
```

Arguments

| | |
|-----|----------------------------|
| fsq | Full name of the data base |
|-----|----------------------------|

Value

New data base or overwritten data base. Note that the created data base is empty.

Author(s)

P. Chevallier - Jan 2019

| | |
|----------------------|------------------------------------------------------------------------------------------|
| d_convert_hydraccess | <i>Convert a full Hydraccess database into a new htsr sqlite database (Windows only)</i> |
|----------------------|------------------------------------------------------------------------------------------|

Description

Because the Hydraccess application only works into a Windows environment, this function cannot be applied on other platforms (Mas OS or Linux). Additionally, the R session must be configured in 32b (see the htsr-package vignette).

Usage

```
d_convert_hydraccess(fsq, db.hydraccess)
```

Arguments

| | |
|---------------|---------------------------------------|
| fsq | Full name of the sqlite data base |
| db.hydraccess | Full name of the hydraccess data base |

Details

If the specified sqlite data base already exists, a confirmation is requested to overwrite it.

An 32b ODBC Microsoft driver must be configured in the "administrative tools" and installed for the hydraccess data base. The correct functioning can be verified using the sub-function `u_test_rodbc(db.hydraccess)`, which must be successful.

Value

A new or a replaced sqlite htsr data base.

Author(s)

P. Chevallier - Nov 2018-Nov 2020

See Also

[d_inventory](#) or [ds_inventory](#) for displaying the content of the sqlite data base; [ds_exp_hts](#) for extracting a time-series.

Examples

```
## Not run:

d_import_hydraccess("foo.sqlite", "foo.mdb")

## End(Not run)
```

d_convert_weewx

Convert a weewx data base into a htsr sqlite base

Description

Convert a weewx data base into a tshm sqlite base

Usage

```
d_convert_weewx(fsq, db.weewx, sta, name_st, tzo = "CET", bku = TRUE)
```

Arguments

| | |
|----------|-----------------------------------------------|
| fsq | Full name of the htsr data base |
| db.weewx | Full name of the weewx data base |
| sta | Station id |
| name_st | Station name |
| tzo | Time zone of the weewx data (default = "CET") |
| bku | Backup the data base (default = TRUE) |

Author(s)

P. Chevallier - Feb 2018 - Jan 2022

See Also

[d_inventory](#) or [ds_inventory](#) list the content of the data base ; [d_exp_hts](#) to extract time-series.

Examples

```
## Not run:

d_imp_weewx("foo.sqlite", "weewx.sql")

## End(Not run)
```

| | |
|----------|---------------------------|
| d_create | <i>Create a data base</i> |
|----------|---------------------------|

Description

Create htsr sqlite data base

Usage

```
d_create(fsq, cr_table = TRUE, bku = TRUE)
```

Arguments

| | |
|----------|---------------------------------------------------------|
| fsq | Full name of the data base |
| cr_table | Create the basis tables : TRUE (default), FALSE |
| bku | Operate a backup if fsq exists : TRUE (default) / FALSE |

Details

If the data base already exists and bku is TRUE, a backup is automatically generated.

If cr_table is TRUE, The following tables are also created: ST (stations), SS (sensors), WL (water levels), DI (discharges), PR (Precipitations), WE (weather) and QU (quality)

Value

a new data base

Author(s)

P. Chevallier - Jan 2019

`d_exp_hts`*Extraction of a time-series from htsr data base*

Description

The function extracts a time-series in the "hts" format. It products a "tibble" table with four columns : Date, Value, Station, Sensor. It is the default format of the package. The function [f_convert](#) converts it in Excel or csv format.

Usage

```
d_exp_hts(fsq, sta, sen, rtime = FALSE, dstart, dend, rplot = FALSE)
```

Arguments

| | |
|---------------------|-------------------------------------------------------|
| <code>fsq</code> | Full name of the data base |
| <code>sta</code> | Station id. |
| <code>sen</code> | Sensor id. |
| <code>rtime</code> | Reduce time interval TRUE / FALSE (default) |
| <code>dstart</code> | Start date YYYY-MM-DD (default: start date of the ts) |
| <code>dend</code> | End date YYYY-MM-DD (default: end date of the ts) |
| <code>rplot</code> | Plot the extracted file TRUE / FALSE (default) |

Details

For a step by step operation the function [ds_exp_hts](#) is more convenient.

Value

The function returns:

- a tibble tstab with 4 columns Date, Value, Station, Sensor
- a file (nomfic) with the following name: <sensor.id>_<station.id>.hts

Author(s)

P. Chevallier - oct 2017 - dec 2019

See Also

[ds_exp_hts](#) manual settings of the parameters

Examples

```
## Not run:  
  
f <- d_exp_hts("foo.sqlite", "M", "station", "sensor")  
  
## End(Not run)
```

| | |
|-----------|-------------------------------------------|
| d_imp_hts | <i>Import a hts file into a data base</i> |
|-----------|-------------------------------------------|

Description

Import a hts file into a tshm sqlite base

Usage

```
d_imp_hts(fsq, file, table, bku = TRUE)
```

Arguments

| | |
|-------|-----------------------------------------|
| fsq | Full name of the data base |
| file | Full name of hts file to import |
| table | Table |
| bku | Automatic Backup TRUE (default) / FALSE |

Details

The main table where the data have to be removed must be selected with one the following abbreviation: WL (water level), DI (discharge), WE (weather), PR (precipitation) or QU (quality) If records already exist during the same interval, they are removed and replaced.

Value

Actualized data base

Author(s)

P. Chevallier - jan 2019

| | |
|-------------|---------------------------------------|
| d_inventory | <i>Inventory of an htsr data base</i> |
|-------------|---------------------------------------|

Description

The function produces an inventory of the stations and of sensors of an htsr data base. If only a display is needed, the function [ds_inventory](#) is more convenient.

Usage

```
d_inventory(fsq, sta_sen = NA, form.out = NA)
```

Arguments

| | |
|----------|------------------------------------------------------------------------------|
| fsq | Data base file |
| sta_sen | Station_id, with its list of sensors |
| form.out | Display option: NA (console, default) or excel (xlsx) or text (csv; ou csv,) |

Details

If sta_sen is NA (default), all stations and sensors are processed. If sta_sen is a Station_id, only the sensors of this station are processed.

- form.out can take the following values : NA, "csv," text file with ',' as decimal separator and ';' as field separator / "csv;" text file with ',' as decimal separator and ';' as field separator / "xlsx" Excel file.

Value

Two tables with the inventory of stations and sensors of a data base. If the output format is an excel file, they are displayed in two sheets of the same excel file.

Author(s)

P. Chevallier - Jan 2019 - Nov 2020

See Also

[ds_inventory](#)

| | |
|-----------|--------------------------------------------|
| d_rem_hts | <i>Remove hts records from a data base</i> |
|-----------|--------------------------------------------|

Description

Remove hts records from a Sqlite base

Usage

```
d_rem_hts(fsq, table, sta, sen, start, end)
```

Arguments

| | |
|-------|-------------------------------|
| fsq | Full name of the data base |
| table | Table |
| sta | Station id |
| sen | Sensor id |
| start | Start time of removed records |
| end | End time of removed records |

Details

The main table where the data have to be removed must be selected with one the following abbreviation: WL (water level), DI (discharge), WE (weather), PR (precipitation) or QU (quality)

Value

Actualized data base

Author(s)

P. Chevallier - jan 2019 - dec 2022

| | |
|----------|------------------------------------------|
| d_sensor | <i>Create, Modify or Remove a sensor</i> |
|----------|------------------------------------------|

Description

Create, Modify or Remove a sensor. A shiny version of this function is available: [link{ds_sensor}](#)

Usage

```
d_sensor(
  fsq,
  op = "C",
  sta,
  sen,
  table,
  name_fld = NA,
  value_fld = NA,
  bku = TRUE
)
```

Arguments

| | |
|-----------|------------------------------------------|
| fsq | Full name of the data base |
| op | Create (default), modify or remove C/M/R |
| sta | Station id |
| sen | Sensor id |
| table | Table of the sensor |
| name_fld | List of field names |
| value_fld | List of field values |
| bku | Automatic Backup TRUE (default) / FALSE |

Details

If op is C, the fields sta, table and sen are compulsory and cannot be modified afterwards.

Allowed entries for table are: WL (water levels), DI (discharges), QU (Quality), PR (precipitations), WE (weather).

The field names are expressed in French for compatibility reason with Hydraccess. A translation is given in [].

If op is C or M, the following fields can be completed :

- [Nature] Nature= as.character(NA),
- [Description] Description = as.character(NA),
- [Comment] Commentaire= as.character(NA),
- [Limni id] Code_Limni= as.character(NA),
- [Principal] Principal = as.logical(NA),
- [Fictive] Fictif = as.logical(NA),
- [Daily update] Maj_Journaliers = as.logical(NA),
- [Translation update] Maj_Traduction = as.logical(NA),
- [Automatic acquisition] Acquisition_Auto = as.logical(NA),
- [Operationnal] Operationnel = as.logical(NA),

- [Instantaneous list] Liste_Inst = as.character(NA),
- [Daily list] Liste_Jour = as.character(NA),
- [Monthly list] Liste_Mois = as.character(NA),
- [Aggregation] Agregation = as.character(NA),
- [Time shift] Decalage_Temps = as.numeric(NA),
- [Min] Mini = as.numeric(NA),
- [Max] Maxi = as.numeric(NA),
- [Gradient] Gradient_Maxi = as.numeric(NA),
- [Accuracy] Precision = as.numeric(NA),
- [Decimals] Decimales = as.numeric(NA),
- [Slope] Pente = as.numeric(NA))

If op is R, all data corresponding to the sensor of the selected station are removed.

Value

Sensor created, modified or removed from the data base

Author(s)

P. Chevallier - Feb 2018-Dec 2022

See Also

- [d_inventory](#) or [ds_inventory](#) to explore the data base content;
- [ds_exp_hts](#) to extract a time-series;
- [d_create](#), [d_table](#) to create a data base and/or create/remove a table ;
- [d_station](#) or [ds_station](#) for create/remove a station.

d_station

Create, Modify or Remove a station

Description

Create, Modify or Remove a station in a tshm data base. A shiny version of this function is available: [ds_station](#).

Usage

```
d_station(
  fsq,
  op = "C",
  sta,
  ty_st = NA,
  name_st = NA,
  name_fld = NA,
  value_fld = NA,
  bku = TRUE
)
```

Arguments

| | |
|-----------|------------------------------------------|
| fsq | Full name of the data base |
| op | Create (default), Modify or Remove C/M/R |
| sta | Station id |
| ty_st | Station type: "H" hydro or "M" meteo |
| name_st | Station name |
| name_fld | List of field names |
| value_fld | list of field values |
| bku | Automatic Backup TRUE (default) / FALSE |

Details

The field names are expressed in French for compatibility reason with Hydraccess. A translation is given in [].

If op is C, the fields Id_Station (sta), Type_Station and Nom (name_st) are compulsory. The field Nom (name_st) can be modified afterwards.

If op is C or M, the following fields can be completed :

- [Order] Ordre = as.character(NA),
- [Station type] Type_Station = as.character(type_st),
- [Station id] Id_Station = as.character(sta),
- [Second station Id] Id_Secondaire = as.character(NA),
- [Third station id] Id_Tertiaire = as.character(NA),
- [Meteo type] Type_Meteo = as.character(NA),
- [Name] Nom = as.character(name_st),
- [Country] Pays = as.character(NA),
- [Zone] Zone = as.character(NA),
- [Sub-zone] SousZone = as.character(NA),
- [Large basin] GrandBassin = as.character(NA),

- [Basin] Bassin = as.character(NA),
- [Small basin] PetitBassin = as.character(NA),
- [River] Riviere = as.character(NA),
- [Manager] Gestionnaire = as.character(NA),
- [Latitude] Latitude = as.numeric(NA),
- [Longitude] Longitude = as.numeric(NA),
- [Altitude] Altitude = as.integer(NA),
- [Basin area] Superficie_bv = as.numeric(NA),
- [Starting month of hydro year] Mois_Debut_Hydro = as.numeric(NA),
- [Starting activity date] Debut_Activite = as.numeric(NA),
- [Activity] Activite = as.logical(NA),
- [Yes/No criterion] Critere_OuiNon = as.logical(NA),
- [Yes/No second criterion] Critere_OuiNon2 = as.logical(NA),
- [Numeric criterion] Critere_Numerique = as.numeric(NA),
- [Text criterion] Critere_Texte = as.character(NA),
- [Observer name] Nom_Observateur = as.character(NA),
- [Address] Adresse = as.character(NA),
- [Teletransmission] Teletransmission = as.logical(NA),
- [Recorder] Enregistreur = as.logical(NA),
- [Fictive] Fictive = as.logical(NA),
- [Comment] Commentaire = as.character(NA),
- [Flag] Flag = as.logical(NA),
- [District] District = as.character(NA),
- [Place] Localite = as.character(NA)

If op is M, station type and station id cannot be modified. The sensor data corresponding to the station are conserved.

If op is R, all data and sensors of the station are removed.

Value

Station created, modified ou removed from the data base

Author(s)

P. Chevallier - Jan 2018-Dec 2022

See Also

- [d_inventory](#) or [ds_inventory](#) for exploring the data base content;
- [ds_exp_hrs](#) for extracting a time-series;
- [d_table](#) for creating a data base and/or creating/removing a table ;
- [d_sensor](#) for creating, modifying or removing a sensor.

| | |
|---------|-------------------------------------------------------|
| d_table | <i>Create or remove a table of a htsr sqlite base</i> |
|---------|-------------------------------------------------------|

Description

The function allows to create or remove of a tshm sqlite base. If the base doesn't exist, it is created.

Usage

```
d_table(fsq, table, op = "C", bku = TRUE)
```

Arguments

| | |
|-------|-----------------------------------------|
| fsq | Full name of the data base |
| table | Table name |
| op | Create (default) or Remove C/R |
| bku | Automatic Backup TRUE (default) / FALSE |

Details

Possible table names : ST (Stations), SS (Sensors), WL (Water levels), DI (Discharges), WE, (Weather), PR (Precipitations), QU (Quality)

Value

Table created or removed

Author(s)

P. Chevallier - Jan-Feb 2018

See Also

- [d_inventory](#) or [ds_inventory](#) to list the content of the base ;
- [ds_exp_hts](#) to extract a time-series

| | |
|--------|----------------------------|
| d_wind | <i>Create a wind table</i> |
|--------|----------------------------|

Description

Create a tibble with wind direction and speed

Usage

```
d_wind(fsq, sta = NA, swd = NA, swv = NA)
```

Arguments

| | |
|-----|---------------------------------|
| fsq | Full name of the tshm data base |
| sta | Station id |
| swd | Id of wind direction sensor |
| swv | Id of wind speed sensor |

Value

A tibble named "data_wind" with 5 columns date, month, year, wind_dir, wind_spd

Author(s)

P. Chevallier - Dec 2019

See Also

[p_wind](#) plot wind roses

Examples

```
## Not run:  
  
h_wind (fsq, sta="VB", swd="WD", swv="WV")  
  
## End(Not run)
```

| | |
|----|----------------------------------|
| fc | <i>Short-cut for file.choose</i> |
|----|----------------------------------|

Description

Short-cut for file.choose

Usage

fc()

Value

A filename

Author(s)

P. Chevallier

| | |
|-------------|-----------------------------------------------------|
| f_change_id | <i>Change Station id or Sensor id in a hts file</i> |
|-------------|-----------------------------------------------------|

Description

The function changes the station and/or the sensor id of a hts file. The new file is renamed with the new ids and a prefix n_: nw_<sensor.id>_<station.id>.hts, BUT the eventual prefixes or suffixes of the original name are not conserved. The original file is not removed.

Usage

f_change_id(file, sta = NA, sen = NA, overwrite = FALSE)

Arguments

| | |
|-----------|--------------------------------------------------|
| file | file to proceed |
| sta | new station id (default: NA) |
| sen | new sensor id (default: NA) |
| overwrite | TRUE / FALSE (default) if the output file exists |

Author(s)

P. Chevallier - Nov 2017-Jan 2019

| | |
|-----------|--------------------------------------------------------------------------------|
| f_convert | <i>Convert an hts file in another format (xls, xlsx or csv) and vice-versa</i> |
|-----------|--------------------------------------------------------------------------------|

Description

Converter in formats hts, xls, xlsx and text (csv et csv2)

Usage

```
f_convert(file, form_start = "hts", form_end = "xlsx")
```

Arguments

| | |
|------------|---------------------------------------------------------------------------------------------------------------------------|
| file | Hts file |
| form_start | Initial format ("hts" (default) or "xls" or "xlsx") |
| form_end | Final format ("hts" or "xls" or "xlsx" (default) or "csv" (separator , & decimal .) or "csv2" (separator ; and decimal ,) |

Details

'form_start' = csv or csv2 is for instance not accepted. It could be converted previously in xls or xlsx format.

Value

A file in the requested format with 4 columns: Date, Value, Station, Sensor

Author(s)

P. Chevallier - October 2017 - May 2022

Examples

```
## Not run:  
f_convert(file, "xlsx", "hts")  
  
## End(Not run)
```

f_csv_multivar *Build a multivariable table file in csv format*

Description

Build a multivariable table file in csv format

Usage

```
f_csv_multivar(files, daily = TRUE, fileo = "fileo")
```

Arguments

| | |
|-------|---------------------------------------------|
| files | list of hts files |
| daily | default = TRUE |
| fileo | name of the output file (without extension) |

Details

The function build a cvs file with values extracted from several hts files at the same date. So, it's better to run 'h_common' before to apply 'f_csv_multivar'

If daily is TRUE, only the date is taking into account, not the time.

Value

A csv table, where the first field is a date and the next fields values

Author(s)

P. Chevallier - Jan-Feb 2022

f_month2day *Interpolation of daily records from a monthly time series*

Description

Interpolation of daily records from a monthly time-series

Usage

```
f_month2day(file)
```

Arguments

| | |
|------|--------------------------------|
| file | monthly time series to process |
|------|--------------------------------|

Details

The function build and interpolated daily time-series from a monthly one. The daily values are linearly computed between two consecutive monthly values.

Value

a daily time series

Author(s)

P. Chevallier - dec 2022

| | |
|--------------|-----------------------------------|
| f_properties | <i>Properties of a hts series</i> |
|--------------|-----------------------------------|

Description

The function provides the properties of a time-series, its duration and the inventory of its gaps

Usage

```
f_properties(file, gaps = FALSE)
```

Arguments

file : file to be analyzed
gaps : produce a file with a table of the gaps: TRUE / FALSE (default)

Details

If gaps = TRUE, a file is produced, with the same name of file and the extension .gap. It contents a table with the gaps of the series and allows to build a plot with the function [p_gaps](#).

Value

Basic infos on a hts time-series

Author(s)

P. Chevallier - Jan 2019 - Oct 2021

See Also

[p_gaps](#).

| | |
|----------|-------------------------------------------------------|
| hs_tstep | <i>Shiny app: convert f file with fixed time-step</i> |
|----------|-------------------------------------------------------|

Description

Shiny application of the functions [h_timestep](#) and [h_month](#)

Usage

```
hs_tstep(file)
```

Arguments

| | |
|------|-----------------|
| file | File to process |
|------|-----------------|

Value

a shiny session

Author(s)

P. Chevallier - Dec 2020 - Oct 2021

| | |
|------|---------------------|
| htsr | <i>htsr package</i> |
|------|---------------------|

Description

htsr: A package for managing sqlite data bases, which contain hydro-meteorology time-series.

The htsr package contains 6 types of functions: data base (d_<NAME>), file f_<NAME>, hydromet (h_<NAME>), plotting (p_<NAME>), shiny (s_<NAME>) and miscellaneous (z_<NAME>).

| | |
|---------|-------------------------------------------|
| h_addna | <i>Add NA values within a time series</i> |
|---------|-------------------------------------------|

Description

Add NA values within a time series

Usage

```
h_addna(file, add)
```

Arguments

| | |
|------|------------------------------------------|
| file | File name to proceed |
| add | List of dates with NA values to be added |

Details

The function adds records with NA in a time series at given dates. If the date already exists, the value is replaced by NA

The output file is named with a nap_ prefix.

Author(s)

P. Chevallier - November 2022

Examples

```
## Not run:  
f <- h_addna (f, add = c("2021-01-01 12:00:00 UTC", "2031-01-01 12:00:00 UTC"))  
## End(Not run)
```

| | |
|---------|-------------------------------------------------------|
| h_avday | <i>Daily average over a sequence of several years</i> |
|---------|-------------------------------------------------------|

Description

Daily average over a sequence of several years

Usage

```
h_avday(file, start = NA, end = NA, mhy = 1, precip = FALSE, dig = 1)
```

Arguments

| | |
|--------|-------------------------------------------------------|
| file | File name to proceed |
| start | Starting date (default = NA) |
| end | Ending date (default = NA) |
| mhy | Starting month of the hydrological year (default = 1) |
| precip | Precipitation time series (default = FALSE) |
| dig | Number of significant digits for Value (default = 1) |

Details

The function means the values of each calendar day over a period larger than 4 years (i.e. it includes at least one Feb 29 day). The result is transferred to the last possible hydrological year of the interval.

In the special case of precipitation, where the distribution is discontinuous over time, the original values of the last hydrological year are replaced by values corrected proportionately.

Author(s)

P. Chevallier - Nov 2022

Examples

```
## Not run:

f <- h_avday(f, start=NA, end=NA, mhy=10, precip=TRUE, dig=1)

## End(Not run)
```

h_common

Extract 2 (or more) time-series on their common period

Description

The fonction extract the data of 2 (or more) hts time-series for the common date/time records (precision of the second).

Usage

```
h_common(files)
```

Arguments

| | |
|-------|--------------------------------|
| files | List of file names to process. |
|-------|--------------------------------|

Value

hts files resulting of the operation; their names are composed as: co_<original filename>

Author(s)

P. Chevallier - Oct 2017-Dec 2019

Examples

```
## Not run:  
  
f <- h_common(files = c("foo1.hts", "foo2.hts"))  
  
## End(Not run)
```

h_condition

Conditional extraction of a time-series regarding another one

Description

The series to proceed is the first of the list, the conditional series the second. Only the common record dates are kept.

Usage

```
h_condition(files, condition)
```

Arguments

| | |
|-----------|--------------------------------------------------------------------------------------------------|
| files | Liste de 2 file names |
| condition | Liste 3 objects : oper ("sup" or "inf" or "between"), thrhd1 < thrhd2 ; default is c("inf",0,NA) |

Details

If the condition on the file 2 value is not respected, the value of file 1 is changed as NA.

The condition has 3 options : $x <$ ("inf"), $x \geq$ ("sup"), $< x \leq$ ("between"). In case of error or by default, "inf" is considered. In the cases "inf" and "sup", only one threshold is used (thrhd1) ; in the case "between", two thresholds are needed (thrhd1 < thrhd2).

The output file is the name of the fist file with a cd_ prefix.

Author(s)

P. Chevallier - Oct 2017-Jan 2019

Examples

```
## Not run:  
  
f <- h_condition(c(f1,f2), c("between", 0, 2))  
  
## End(Not run)
```

| | |
|---------|-----------------------------|
| h_cumul | <i>Cumul of time-series</i> |
|---------|-----------------------------|

Description

The function returns a time-series of cumulated values. If the value is negative, the absolute value is taken. It is possible to limit the computation time interval. NA values are ignored.

Usage

```
h_cumul(file, start = NA, end = NA)
```

Arguments

| | |
|-------|--------------------------|
| file | File name to proceed |
| start | Start date, default = NA |
| end | End date, default NA |

Details

The output file is named with a cu_ prefix.

Author(s)

P. Chevallier - Oct 2017-Jan 2019

Examples

```
## Not run:  
  
f <- h_cumul(f, start="2012-1-1", end = "2013-1-1")  
  
## End(Not run)
```

h_gaperr *Replace errors with gaps in a time-series based on neighboring values*

Description

Replace errors with gaps in a time-series based on neighboring values

Usage

```
h_gaperr(file, nv = 1, itv0 = 43201, df)
```

Arguments

| | |
|-------|--------------------------------------------------------------------------------|
| file, | File name to proceed |
| nv | Number of below and above neighboring values to take into account, default = 1 |
| itv0 | Threshold of minimum time gap (see function h_gaprem_itv) |
| df | Deviation value factor for testing if a value is correct or not |

Details

Replace errors with gaps in a time-series based on neighboring values

Value

a time-series file with the prefix eg_

Author(s)

P. Chevallier - Nov 2019

h_gapfill *Simple gapfilling in a time-series*

Description

Simple gapfilling in a time-series

Usage

```
h_gapfill(file, npdt)
```

Arguments

| | |
|------|----------------------|
| file | File name to proceed |
| npdt | Number of time-steps |

Details

Replace the missing values with the linear interpolated value within the gap interval, when the time interval is less than a number of fixed time steps.

CAUTION! this operation is only possible when the time-series has a fixed time-step.

Value

a time-series file with the prefix gf_

Author(s)

P. Chevallier - Nov 2017 - Nov 2021

h_gaprem_itv

Remove gaps in a time-series with a time interval threshold

Description

Remove gaps in a time-series with a time interval threshold

Usage

```
h_gaprem_itv(file, itv0 = 43201)
```

Arguments

| | |
|------|-----------------------------------------------------------|
| file | File name to proceed |
| itv0 | Time threshold in seconds, default = 43201 (i.e 12 hours) |

Details

Remove the missing values when the time interval between the previous and the next record is less than a fixed threshold

Value

a time-series file with the prefix gr_

Author(s)

P. Chevallier - Nov 2019

| | |
|---------|---------------------------------------------------------|
| h_month | <i>Monthly operations, based on a daily time-series</i> |
|---------|---------------------------------------------------------|

Description

Monthly operations, based on a daily time-series

Usage

```
h_month(
  file,
  op = "M",
  ba = NA,
  rmna = FALSE,
  climatedit = FALSE,
  caledit_j = FALSE,
  caledit_m = FALSE,
  gapfill = FALSE,
  hts_year = FALSE
)
```

Arguments

| | |
|------------|-------------------------------------------------------------------------------|
| file | Full file name of the daily time-series. |
| op | Operation: mean ("M") or sum ("S") |
| ba | Basin area in km2 or NA (default) |
| rmna | Remove NA values TRUE / FALSE (default) |
| climatedit | Write a climatology file TRUE / FALSE (default) |
| caledit_j | Write an Excel file with daily calendar TRUE / FALSE (default) |
| caledit_m | Write an Excel file with monthly calendar TRUE / FALSE (default) |
| gapfill | Replace the missing months by the "climatology" value TRUE / FALSE (default) |
| hts_year | Extract the mean, max & min yearly values in hts files TRUE / FALSE (default) |

Details

Based on a daily time-series, the function returns a monthly time-series, and computes a mean monthly climatology. It allows to consider or not the missing daily values: option `rmna`.

The function can also produce Excel files: with a calendar presentation (days in rows, months in columns, years in sheets): option `caledit_j` ; with the monthly means (or sums): option `caledit_m`. In addition, the missing values can be replaced by the mean of the existing values for other years : option `gapfill`.

Climatology files are by convention awarded to year 2000.

Generally, the values of the monthly climatologies are mean values (op="M"), except if they are volumes (e.g.: precipitation, evaporation, etc.). In these cases, the parameter op="S" must be pre-cised.

If rmna = TRUE , the NA values are not taken into consideration for computing the sum or the mean.

In the case of discharge values, it is possible to compute monthly volumes expressed in mm. For that purpose, the basin area ba must be given in km2.

By default, the reference name of the time-series is <sensor.id>_<station.id>. It is possible to change it giving a value to the parameter ref.

Value

A list of timeSeries class objects including: [1] raw monthly data; [2] 12 climatology means (January to December); [3] gapfilled monthly data, if the option gapfill is TRUE.

Three hts time series files: a monthly data file with the suffix _M, a climatology data file with the suffix _C and, optionally, a gapfilled monthly data file with the suffix _G.

Optionally, two Excel files with calendar presented values:, one with daily data and one with monthly data, the fist one with a ad_ prefix and the second one with the am_ prefix.

Author(s)

P. Chevallier - Oct 2017- Apr 2020

Examples

```
## Not run:
res <- h_month("foo.ts",op="S", ba=135, caledit_m = TRUE)
## End(Not run)
```

h_nodata

Replace values with NA conditionally or in a time interval

Description

Replace values with NA conditionally or in a time interval

Usage

```
h_nodata(file, threshold = NA, test = "=", start = NA, end = NA)
```


Arguments

| | |
|-----------|------------------------------------------------------------|
| file | File name to proceed |
| threshold | Threshold value (default = NA) |
| test | Test "=" (default); "<"; "<="; ">"; ">=" |
| start | Start date/time (included) of POSIXct class (default = NA) |
| end | End date/time (excluded) of POSIXct class (default = NA) |

Details

The function replace values with NA conditionally or introduce a gap for a given interval.

For the conditional option, the start parameter must be NA. A conditional test is applied on the values (= ; > ; >= ; < ; <=) with a fixed threshold returning NA if the test is verified.

For the gap option, the threshold parameter must be NA. All the values of the records within the interval start end are replaces by NA.

CAUTION ! At least one of both parameters threshold or start must not be NA. NA.

The output file is named with a na_ prefix.

Author(s)

P. Chevallier - Oct 2017-Jan 2019

Examples

```
## Not run:  
  
f <- h_nodata(f, threshold=10., test= "<=", start=NA)  
  
## End(Not run)
```

h_rainsnow

Share the solid and liquid precipitations with a temperature criteria

Description

The precipitations are shared with a linear bevel between two temperature values

Usage

```
h_rainsnow(fpr, fta, ta0, ta1, sta = NA)
```

Arguments

| | |
|-----|----------------------------|
| fpr | Precipitation file name |
| fta | Temperature file name |
| ta0 | Low temperature threshold |
| ta1 | High temperature threshold |
| sta | Station id. (default = NA) |

Details

The two time-series must be previously restricted to the same interval of time.

The two temperature thresholds can be equal.

The temperature time-series must be complete with no gap. Gaps are allowed in the precipitation time-series.

Is the station id is NA, the station id of the file fta is used.

Value

2 hts files, one with the liquid precipitation (prefix rn_) and one with the solid precipitation (prefix sn_).

Author(s)

P. Chevallier - Oct 2017- Feb 2019

h_rbind

Bind 2 time-series on consecutive periods

Description

The fonction binds the data of 2 hts time-series for consecutive date/time records (precision of the second) of the same station.

Usage

```
h_rbind(files, sensor = "NewS", gap = TRUE)
```

Arguments

| | |
|--------|-------------------------------------------------------------|
| files | List of char, File names to process. |
| sensor | New sensor name of the resulting hts file (default ="NewS") |
| gap | Introduce or not a gap between both series (default = TRUE) |

Details

In the list, the files must be ordered from the oldest to the newest. If gap is TRUE, a gap is introduced between both series.

Value

hts file resulting of the operation; its names are composed as: <sensor>_<station>.hts, with the prefix na, if a gap has been introduced.

Author(s)

P. Chevallier - Mar-Nov 2020

Examples

```
## Not run:  
  
f <- h_bind(files = c("foo1.hts", "foo2.hts"), sensor = "NewOne")  
  
## End(Not run)
```

h_replace

Replace a value by another

Description

Replace a value by another

Usage

```
h_replace(file, old.val, new.val)
```

Arguments

| | |
|---------|----------------------|
| file | File name to proceed |
| old.val | Value to be replaced |
| new.val | New value |

Details

The output file is named with a re_ prefix.

Author(s)

P. Chevallier - Oct 2017- Nov 2020

Examples

```
## Not run:  
  
f <- ts_replace_ts(f, NA, 0)  
  
## End(Not run)
```

| | |
|------------|------------------------------------------|
| h_restrict | <i>Restrict a series between 2 dates</i> |
|------------|------------------------------------------|

Description

Restrict a series between 2 dates

Usage

```
h_restrict(file, start = NA, end = NA)
```

Arguments

| | |
|-------|------------------------------------------------------------|
| file | File name to proceed |
| start | Start date/time (included) of POSIXct class (default = NA) |
| end | End date/time (excluded) of POSIXct class (default = NA) |

Details

The output file is named with a rs_ prefix.

Author(s)

P. Chevallier - Nov 2017-Jan 2019

| | |
|----------|-----------------------------------------------|
| h_rollav | <i>Rolling average of a daily time-series</i> |
|----------|-----------------------------------------------|

Description

The function compute a rollong average of daily time-series values. NA values are removed.

Usage

```
h_rollav(file, ti = 7, position = "central")
```

Arguments

| | |
|----------|----------------------------------------------------|
| file | File name to proceed |
| ti | Time interval of computation in days (default = 7) |
| position | Position "central" or "right" |

Details

The output file is named with a ro_ prefix. The computation can considers the values before and after the current time step (position = "central") or the values before the current time step. If the position is "central", the position must be an odd integer.

Author(s)

P. Chevallier - Apr 2020

| | |
|----------|---------------------------|
| h_season | <i>Seasonal selection</i> |
|----------|---------------------------|

Description

The function provides seasonal time-series.

Usage

```
h_season(file, monthstart)
```

Arguments

| | |
|------------|--------------------------------------------------------------------------------------|
| file | Full file name to proceed |
| monthstart | List of 2 to 4 integers (between 1 and 12) giving the starting month of each season. |

Details

2 to 4 seasons can be selected. For each season, the prefix sx_ where x is the season is added to the file name.

Value

list of file names for each seasonal time-series.

Author(s)

P. Chevallier - Oct 2017 - Mar 2020

Examples

```
## Not run:

files <- h_season("foo.hts", monthstart=c(3,6,9,12))

## End(Not run)
```

| | |
|--------------|------------------------------------------|
| h_stat_basic | <i>Basic statistics of a time-series</i> |
|--------------|------------------------------------------|

Description

Compute the main statistic parameters of a time-series

Usage

```
h_stat_basic(files)
```

Arguments

files vector of file names to process

Value

a tibble with the basic stats of the files.

Author(s)

P. Chevallier - Oct 2017 - Feb 2022

Examples

```
## Not run:  
simplestat <- h_stat_basic(c("foo1.hts", "foo2.hts")  
  
## End(Not run)
```

| | |
|--------------|---------------------------------------------------------------------------------------|
| h_substitute | <i>Substitute the missing values in a series by existing values of another series</i> |
|--------------|---------------------------------------------------------------------------------------|

Description

The series to proceed (first in file list) contents missing values or gaps to be replaced by those of the second series (second in file list).

The function only works on the common dates of both series.

Usage

```
h_substitute(files)
```

Arguments

files List of two file names

Details

The output file is named with a sb_ prefix.

Author(s)

P. Chevallier - Feb 2017 - Mar 2020

Examples

```
## Not run:
f <- h_substitute(c(f1, f2))
## End(Not run)
```

| | |
|------------|-----------------------------------|
| h_timestep | <i>Infra-daily fixed timestep</i> |
|------------|-----------------------------------|

Description

Computes a time-series with a fixed infra-daily timestep starting from an instantaneous time-series
- possible option: sum, mean, max or min

Usage

```
h_timestep(file, tst, op = "M", shift = 0)
```

Arguments

file Instantaneous time-series
tst Timestep in minutes - must be a divisor of 1440 between 10 and 1440
op "S", "M" (default), "Mn" ou "Mx"
shift time shift for computing daily data in hours (default = 0)

Details

The op parameter give precise the chosen computation method within the interval: sum ("S"), la mean ("M"), minimum ("Mn") or maximum ("Mx").

In the case of a daily timestep (tst = 1440), the parameter shift allows to shift the time interval. For example if shift = 6, the date is computed from 6am until 6am the following day. The result is dated in the middle of the interval, i.e. if shift = 6; the datetime is 18.

Value

A hts time-series file with a fixed timestep. The duration of the time-step in minutes is added to the file name.

Author(s)

P. Chevallier - Oct 2017 - Jan 2022

Examples

```
## Not run:  
  
f <- t_timestep(f, tst, op="S", shift = 6)  
  
## End(Not run)
```

| | |
|---------------|------------------------------------|
| h_weightedsum | <i>Weighted sum of time-series</i> |
|---------------|------------------------------------|

Description

The function only works on the common period of the files without NA values. It operates weighted sums on one or several time-series. It is also possible to add a constant.

Usage

```
h_weightedsum(files, weights, constant = 0)
```

Arguments

| | |
|----------|------------------------------------------------------|
| files | List of file names to proceed |
| weights | List of weights (must have the same length as files) |
| constant | Constant to add (default = 0) |

Details

For averaging n time-series one can use n weights wit a value of 1/n and constant = 0.

Value

The function returns + n hts files with the extracted common period + 1 hts file named as the first file of the list with the prefix w_. The sensor id is automatically set to "weighted".

Author(s)

P. Chevallier - Oct 2017-Oct 2021

Examples

```
## Not run:

# choose time-series f1, f2, f3
f1 <- "foo1.hts" ; f2 <- "foo2.hts" ; f3 <- "foo3.hts"
# the new f time-series contains records f[i] = f1[i] - (0.5 * f2[i]) + (0.5 * f3[i]) + 5
f <- h_weightedsum(c(f1,f2,f3), c(1,-0.5,0.5)), 5)
# the new f time-series contains records f[i] = (1.12 * f1[i]) + 3
f <- h_weightedsum(f1, 1.12, 3)

## End(Not run)
```

h_wl_di

*Computation of the discharges from water-levels***Description**

Computes a discharge time-series from water levels data and calibration curves

Usage

```
h_wl_di(fsq, sta, seni, seno, dstart = NA, dend = NA, dbo = TRUE)
```

Arguments

| | |
|--------|--------------------------------------------------------|
| fsq | htsr data base |
| sta | Station Id. |
| seni | Input sensor Id (water levels) |
| seno | Output sensor Id (discharges) |
| dstart | Start date (NA by default) |
| dend | End date (NA by default) |
| dbo | Includes the result in the data base (TRUE by default) |

Details

Calibration curves must exist in the data base.

If 'dbo' is TRUE, a discharge table "DI" and the sensor 'seno' must exist in the data base. The new discharge time-series overwrites the already existing data ; however, it is asked to confirm the operation. In any case the data base is previously backed up.

Value

Writes an hts file with the resulting discharges and optionally includes it in the data base.

Author(s)

P. Chevallier - Dec 2020

See Also

The functions [d_exp_hts](#) and [d_imp_hts](#) are used for export the water levels, respectively import the discharges within the data base. The function [u_exp_discalib](#) included in [p_discalib](#) is used for loading the calibration curves.

| | |
|--------|---------------------------|
| h_year | <i>Annual time series</i> |
|--------|---------------------------|

Description

Annual time series

Usage

```
h_year(file, mhy = 1, op = "M", dig = 1)
```

Arguments

| | |
|------|-------------------------------------------------------|
| file | File name to proceed |
| mhy | Starting month of the hydrological year (default = 1) |
| op | Sum (S) or Mean (M) (default = "M") |
| dig | Number of significant digits for Value (default = 1) |

Details

The function computes an annual time-series using the annual mean or the annual sum of daily values. It allows the use of hydrological years. The date corresponds to the middle of the year, i.e. the 182th day.

Value

The function returns a time-series of annual values.

Author(s)

P. Chevallier - Nov 2022

ps_plothts

Shiny app: plot hts files

Description

Shiny application of the [p_line_app](#) and [p_bar_app](#) functions

Usage

```
ps_plothts(files)
```

Arguments

files List of the time-series files to be plotted.

Details

When launched, a shiny window is open. The setting tab must be first completed and saved. Then go to the plot tab, complete the plotting settings and press Plot. If you want to modify the initial settings, return to the setting tab. After setting changes press Save one more time, go to the plot tab and press Plot!

When finished, press Done to exit from the shiny windows

Author(s)

P. Chevallier - May 2020

p_bar

Bar plot

Description

Bar plot based on htsr time-series. The parameters can be set by [p_bar_app](#). For a step by step operation the function [ps_plothts](#) is more convenient.

Usage

```
p_bar(  
  nbst,  
  filei,  
  serlab,  
  title,  
  type,  
  rnorm,  
  rtime,
```

```

    start,
    end,
    rfixy,
    y.down = NA,
    y.up = NA,
    pal,
    fct
  )

```

Arguments

| | |
|--------|----------------------------------------------------|
| nbst | Number of files to process |
| filei | List of the file names to process |
| serlab | List of the series labels to process |
| title | Title of the plot - default : "Title" |
| type | Title of the y axis - default : "Y axis" |
| rnorm | Normalized values - TRUE/FALSE(default) |
| rtime | Reduce the plotting interval - TRUE/FALSE(default) |
| start | Start date - "YYYY-MM-DD" or NA (default) |
| end | End date - "YYYY-MM-DD" or NA(default) |
| rfixy | Fix the y scale - TRUE/FALSE(default) |
| y.down | Min y - value or NA(default) |
| y.up | Max y - value or NA(default) |
| pal | List of colors |
| fct | Plot facets (TRUE / FALSE) |

Details

For a full description of the settings, see [p_bar_app](#)

If the number of files existing in the setting file is higher than the number of processed series nbst, only the nbst first files are processed.

Value

a ggplot2 object

Author(s)

P. Chevallier - Apr 2015 - Mar 2020

See Also

[p_line](#) for plotting lines and/or points and [p_line](#) for setting the plot parameters

Examples

```
## Not run:

filei <- c("foo1.xlsx", "foo2.xlsx")
serlab <- c("station1", "station2")
p_bar(filei, serlab)

## End(Not run)
```

p_bar_app

Plot bars or points

Description

Application of the function `p_bar` for plotting points or bars. The resulting plot can be saved as .png, .jpg or .pdf files.

Usage

```
p_bar_app(
  nbst,
  rpal = 0,
  savefig = FALSE,
  width = 8,
  height = 6,
  fileo = "plot.png"
)
```

Arguments

| | |
|---------|----------------------------------------------------------------------------------|
| nbst | Number of time-series to be plotted (default 1) |
| rpal | Color palette settings 0 (default); 1 (mapalette) or 2 (manual) |
| savefig | Save plot as png (default FALSE) |
| width | Plot width (x100 pixels) (default = 8) |
| height | Plot height (x100 pixels) (default = 6) |
| fileo | Name of the plot file including extension (png, jpg or pdf) default = "plot.png" |

Details

The number of time-series to be plotted is limited to 8, with option `rpal = 0`, 12 otherwise.

If `savefig=TRUE`, the plot is saved in the working directory. Following the chosen extension, the file is formatted as .png, .jpg or .pdf. The default is "plot.png".

Value

A ggplot2 object.

Author(s)

P. Chevallier - Oct 2017 - Mar 2020

See Also

[p_line](#), [p_bar](#)

Examples

```
## Not run:  
  
p <- p_line_app(filelist = c(foo1, foo2), pset=TRUE, pfil=TRUE, rpal=1, fileo="plot23.pdf")  
  
## End(Not run)
```

p_box_month

Boxplot of the 12 months of a time-series.

Description

Boxplot of the 12 months of a time-series.

Usage

```
p_box_month(  
  file,  
  title = "Title",  
  axeY = "Y-axis",  
  savefig = FALSE,  
  fileo = "plot.png",  
  width = 8,  
  height = 6  
)
```

Arguments

| | |
|---------|------------------------------------------------------|
| file | File name of the time-series |
| title | Title plot (default = Title) |
| axeY | Title of y-axis (default Y-axis) |
| savefig | Save plot file TRUE / FALSE (default) |
| fileo | Name of the plot file with extension png, jpg or pdf |

width Plot width (x 100 pixels), default = 8
 height Plot heights (x 100 pixels), default = 6

Value

A ggplot2 object

Author(s)

P. Chevallier - Nov 2017 -Feb 2019

p_clim *Plot climatologies in hydrological year*

Description

This function processes climatology hts files created with [h_month](#).

Usage

```
p_clim(
  files,
  type = "line",
  hydro.month = 1,
  title = "Title",
  yaxis = "Value",
  y.down = NA,
  y.up = NA,
  rpal = FALSE,
  pal = mapalette,
  legend.l = NA
)
```

Arguments

files List of climatology file names
 type Type: "line" (default) or bar"
 hydro.month Starting month or the hydrological year (default = 1)
 title Title of the plot (default = "Title")
 yaxis Title of y-axis (default = "Value")
 y.down Down limit of y-axis (default = NA)
 y.up Up limit of y-axis (default = NA)
 rpal Choice of a color palette TRUE/FALSE(default)
 pal Color choice or mapalette (default)
 legend.l List of text to be displayed in the plot legend (default = NA)

Details

The parameter tyoe allows to display a line graph or a bar graph.

The parameter hydro.mont fixes the starting month of the hydrological year.

The y-axis scale can be fixed with y.down and y.up.

By default, the color palette is the R one. It can be change with a color list in the pal parameter or choosing mapalette (default in pal)

Par default station_sensor ids are displayed in the legend.l list. But it can be changed entering a list of texts in legend.l,, which must have the same length as the file number.

Value

A ggplot2 object.

Author(s)

P. Chevallier - Feb 2017-Feb 2019

p_discalib

Plot calibration curves water levels vs discharges

Description

Experimental function, which is for instance limited to only two calibration curves on the same plot.

The function plot the discharges measurements and the corresponding calibration curves starting.

Only the "active" discharge measurements are plotted. The parameter plotdism displays them or not.

One can zoom on a subpart of the plot using the limit values on the x and y axis.

The savefig (default = FALSE by default) parameter allows to save the result i a png, jpg or pdf file, according to the extension of fout.

Usage

```
p_discalib(  
  fsq,  
  sta,  
  sen = "IH",  
  plotcalib = TRUE,  
  plotdism = TRUE,  
  title = "Title",  
  savefig = FALSE,  
  width = 8,  
  height = 6,  
  fout = "plot.png",  
  limx = FALSE,
```



```

    limy = FALSE,
    xinf = NA,
    xsup = NA,
    yinf = NA,
    ysup = NA
  )

```

Arguments

| | |
|-----------|----------------------------------------------------|
| fsq | Data base file name |
| sta | Station Id. |
| sen | Sensor Id. (default = "IH") |
| plotcalib | Plot calibrations TRUE (default) / FALSE |
| plotdism | Plot discharge measurements TRUE (default) / FALSE |
| title | Plot title (default: Title) |
| savefig | Save plot in a png file TRUE (default) / FALSE |
| width | Plot width (x 100 pixels) (default = 8) |
| height | Plot height (x 100 pixels) (default = 6) |
| fout | Plot file name (default = "plot.png") |
| limx | Limit x axis TRUE / FALSE (default) |
| limy | Limit y axis TRUE / FALSE (default) |
| xinf | Low value for x (default = NA) |
| xsup | High value for x (default = NA) |
| yinf | Low value for y (default = NA) |
| ysup | High value for y (default = NA) |

Author(s)

P. Chevallier - Sep 2017 - Dec 2020

p_gaps *Plot of data inventory*

Description

This function plot an inventory of the data from one or several station(s)-sensor(s). It is based on the .gap files provided by the function [f_properties](#). It allows to highlight the gaps in time-series.

Usage

```
p_gaps(files, title = "Inventory", BW = FALSE, margin = 0.1)
```

Arguments

| | |
|--------|---------------------------------------------------|
| files | List of series to plot |
| title | Plot title, default is "Inventory" |
| BW | Black & white plot TRUE / FALSE (default) |
| margin | Reserved space for label writing - default is 0.1 |

Details

The inventories are represented with lines displayed bottom-up in the order of the files list. They are labeled with the station_sensor ids.

Colors are the default colors of ggplot2. For a black & white plot, precise BW = TRUE

The margin value is a reserved space for writing the label at the end of each line. Default value is 0.1 of the difference between the minimum and the maximum date. It shall be adjusted following the length of the labels.

Value

A ggplot2 object

Author(s)

P. Chevallier - Nov 2017 - Jan 2019

See Also

[f_properties.](#)

p_hypso

Plot the hypsometry curve of one or more basins

Description

Plot the hypsometry curve of one or more basins

Usage

```
p_hypso(  
  file,  
  abbrev,  
  prop = FALSE,  
  range = 50,  
  fact = 5,  
  title = "Title",  
  savefig = FALSE,  
  width = 8,  
  height = 6,  
  fileo = "plot.png"  
)
```

Arguments

| | |
|---------|-------------------------------------------------------------------|
| file | Raster file list of elevation model of basin(s) |
| abbrev | List of abbreviated basin name(s) |
| prop | TRUE / FALSE (default) plot a proportion curve of altitude ranges |
| range | Width of altitude range (default = 50m) |
| fact | Exagerating factor of the areas (default=5) |
| title | Title of the plot (default = Title) |
| savefig | Save the plot in png (default FALSE) |
| width | Plot width (x 100 pixels) (default = 8) |
| height | Plot height (x 100 pixels) (default = 6) |
| fileo | Name of plot file with extension (default = "plot.png") |

Details

This function uses the "raster" library and the dependencies "sp" and "rgdal", which must be installed.

Value

An object of ggplot2 class

Author(s)

P. Chevallier - Sep 2017- Nov 2021

p_line *Line plot*

Description

Line plot based on htsr time-series. The parameters can be setted by [p_line_app](#). For a step by step operation the function [ps_plothts](#) is more convenient.

Usage

```
p_line(
  nbst,
  filei,
  serlab,
  title,
  type,
  rnorm,
  rtime,
  start,
```

```

end,
rfixy,
y.down,
y.up,
pal,
linet,
linew,
rppt = FALSE,
pointt = NA,
points = NA,
smooth,
fct
)

```

Arguments

| | |
|--------|---------------------------------------------|
| nbst | Number of files to process |
| filei | List of the file names to process |
| serlab | List of the time-series labels to process |
| title | Title of the plot |
| type | Title of the y axis |
| rnorm | Normalized values (TRUE / FALSE) |
| rtime | Reduce the plotting interval (TRUE / FALSE) |
| start | Start date - "YYYY-MM-DD" |
| end | End date - "YYYY-MM-DD" |
| rfixy | Fix the y scale (TRUE / FALSE) |
| y.down | Min y - value |
| y.up | Max y - value |
| pal | List of colors |
| linet | List of line type |
| linew | Line size |
| rppt | Plot the points (TRUE / FALSE) |
| pointt | List of point type |
| points | Point size |
| smooth | Trend fitting (TRUE / FALSE) |
| fct | Plot facets (TRUE / FALSE) |

Details

For a full description of the settings, see [p_line_app](#)

If the number of files existing in the setting file is higher than the number of processed time-series nbst, only the nbst first files are processed.

If fct is TRUE, the plot is presented in facet shape, each facet corresponding to a file.

Value

a ggplot2 object

Author(s)

P. Chevallier - Apr 2015 - Mar 2020

See Also

[p_bar](#) for plotting bars and [p_line_app](#) for setting the plot parameters

Examples

```
## Not run:  
  
filei <- c("foo1.xlsx", "foo2.xlsx")  
serlab <- c("station1", "station2")  
p_line(filei, serlab)  
  
## End(Not run)
```

p_line_app

Plot lines

Description

Application of the functions `p_line` [p_line](#) for plotting lines. The resulting plot can be saved as .png, .jpg or .pdf files.

Usage

```
p_line_app(  
  nbst,  
  rpal = 0,  
  savefig = FALSE,  
  width = 8,  
  height = 6,  
  fileo = "plot.png"  
)
```

Arguments

| | |
|---------|-----------------------------------------------------------------|
| nbst | Number of time-series to be plotted (default 1) |
| rpal | Color palette settings 0 (default); 1 (mapalette) or 2 (manual) |
| savefig | Save plot as png (default FALSE) |

| | |
|--------|-----------------------------------------------------------------------------------|
| width | Plot width (x100 pixels) (default = 8) |
| height | Plot height (x100 pixels) (default = 6) |
| fileo | Name of the plot file including extension (png, jpg or pdf) default = "plot.png") |

Details

The number of time-series to be plotted is limited to 8, with option rpal = 0, 12 otherwise.

If savefig=TRUE, the plot is saved in the working directory. Following the chosen extension, the file is formatted as .png, .jpg or .pdf. The default is "plot.png".

Value

A ggplot2 object.

Author(s)

P. Chevallier - Oct 2017 - Mar 2020

See Also

[p_line](#), [p_bar](#)

Examples

```
## Not run:
p <- p_line_app(filelist = c(foo1, foo2), pset=TRUE, pfil=TRUE, rpal=1, fileo="plot23.pdf")
## End(Not run)
```

p_scatter

Scatter plot of 2 or more time-series

Description

The reference time-series is the first of the list. The scatter plot regards only the common dates of the series. In addition to the plot, a linear function is adjusted forcing or not the interception by the origin.

Usage

```
p_scatter(
  files,
  intercept.zero = FALSE,
  remove.zero = FALSE,
  lg.axis = c(NA, NA),
  title = "Title"
)
```

Arguments

| | |
|----------------|--------------------------------------------------------------------------------|
| files | List of file names to proceed |
| intercept.zero | TRUE/FALSE (default) force the interception by origin |
| remove.zero | TRUE / FALSE (default) remove the records with Value = 0 (e.g. precipitations) |
| lg.axis | Legend list for axis x & y (default = NA) |
| title | Title of the plot (default: Title) |

Value

a table named "result" with 5 columns : variable name, size of the sample, correlation coefficient, regression line slope, interception

Author(s)

P. Chevallier - Oct 2017-Jan 2019

Examples

```
## Not run:  
  
result <- p_scatter(files = c("foo1.RData", "foo2.RData"),  
  intercept.zero = TRUE)  
  
## End(Not run)
```

p_wind

Plot wind roses

Description

Plot wind roses using the "data_wind" tibble created with the function [d_wind](#).

Usage

```
p_wind(  
  data_wind,  
  ws.int = 0.5,  
  angle = 45,  
  grid.line = 10,  
  type = "default",  
  breaks = 5,  
  offset = 5,  
  paddle = FALSE,  
  key.position = "right"  
)
```

Arguments

| | |
|--------------|--------------------------------------------------------------------|
| data_wind | Name of the tibble containing the wind data |
| ws.int | Size of speed intervals |
| angle | Value in percent of the range unit |
| grid.line | Value in percent of the grid line frequency |
| type | Type of plot: "default", "year" or "month" |
| breaks | Number of speed intervals |
| offset | Size in percent of the central hole |
| paddle | Shape of the basic elements: if FALSE, polar, if TRUE, rectangular |
| key.position | Position of the legend |

Details

For a detailed description of all parameters see [windRose](#)

Value

A wind rose plot

Author(s)

P. Chevallier - Dec 2019

See Also

[d_wind](#), [windRose](#)

Examples

```
## Not run:  
p_wind (data_wind = data_wind)  
  
## End(Not run)
```

w_atmp_alt

Compute atmospheric pressure, function of altitude

Description

Compute atmospheric pressure, function of altitude

Usage

```
w_atmp_alt(f_atmp, f_temp, alt)
```


Arguments

| | |
|--------|-------------------------------------------------------------|
| f_atmp | File name of the known atmospheric pressure ts (mb) |
| f_temp | File name of the air temperature at the known altitude (°C) |
| alt | Altitude of the computed air- temperature ts (m) |

Details

The function computes an atmospheric pressure time-series at a given altitude, based on a known atmospheric pressure time-series at the sea level. It also needs the air temperature time-series at the sea level for the same times.

In order to verify that both time-series correspond, it is strongly recommended to run previously the function [h_common](#).

Value

An hts file with the suffixe `_alt`

Author(s)

P. Chevallier - Nov 2021 / Nov 2022

w_etp

Compute the potential evapotranspiration with several methods

Description

ETP calculation

Usage

```
w_etp(  
  method = c("Turc", "Penman-Monteith", "Priestley-Taylor", "Makkink",  
            "Heargraves-Samani"),  
  freq = c("day", "month"),  
  f_temp,  
  f_relh = NA,  
  f_radg = NA,  
  f_radn = NA,  
  f_atmp = NA,  
  f_wvel = NA,  
  f_tmin = NA,  
  f_tmax = NA,  
  lat = NA,  
  alt = NA,  
  albedo = NA,  
  z = NA  
)
```

Arguments

| | |
|--------|--------------------------------------------------------------------------------------|
| method | Method "Turc", "Penman-Monteith", "Priestley-Taylor", "Makkink", "Heargraves-Samani" |
| freq | Frequency "day", "month" |
| f_temp | File of air temperature in degC, mandatory |
| f_relh | File of relative humidity in percent, mandatory |
| f_radg | File of global radiation in W/m2 |
| f_radn | File of net radiation in W/m2 |
| f_atmp | File of atmospheric pressure in hPa |
| f_wvel | File of wind velocities in m/s |
| f_tmin | File of air min temperature in degC |
| f_tmax | File of air max temperature in degC |
| lat | Latitude in deg |
| alt | Altitude in m |
| albedo | Albedo |
| z | Anemometer high in m |

Details

f_temp and f_relh are mandatory in all cases.

For the Turc method, f_radg is needed.

For the Penman-Monteith method, f_atmp, f_wvel, h and z are needed. If f_radn is not available, lat, f_tmin and f_tmax are also needed.

The Turc method only works with a monthly frequency.

Value

An hts files resulting of the operation with a name composed as:

<J or M><EtpTu>_<Station_id>.hts for the Turc method,

<J or M><EtpPM>_<Station_id>.hts for the Penman-Monteith method,

<J or M><EtpPT>_<Station_id>.hts for the Priestley-Taylor method

<J or M><EtpMa>_<Station_id>.hts for the Makkink method

<J or M><EtpHS>_<Station_id>.hts for the Heargraves-Samani method

Author(s)

P. Chevallier - April 2020-Nov2022

Source

- Hingray, B., Picouet, C., Musy A., Hydrologie, une science pour l'ingénieur, Presses Polytechniques et Universitaires Romandes, 2008,
- Allen, R.G., L.S. Pereira, D. Raes, and M. Smith. 1998. Crop Evapotranspiration. Guidelines for Computing Crop Water Requirements. FAO Irrigation and Drainage Paper 56. 300p
- Er-Raki, S., A. Chehbouni, S. Khabba, V. Simonneaux, L. Jarlan, A. Ouldbba, J. C. Rodriguez, and R. Allen. 2010. "Assessment of Reference Evapotranspiration Methods in Semi-Arid Regions: Can Weather Forecast Data Be Used as Alternate of Ground Meteorological Parameters?" Journal of Arid Environments 74 (12): 1587–96. <https://doi.org/10.1016/j.jaridenv.2010.07.002>.

w_spechum2relhum *Convert specific humidity to relative humidity*

Description

Convert specific humidity to relative humidity

Usage

w_spechum2relhum(f_spechum, f_temp, f_atm)

Arguments

| | |
|-----------|--------------------------------------------------------------------------------------------|
| f_spechum | file of specific humidity, dimensionless (e.g. kg/kg) ratio of water mass / total air mass |
| f_temp | file of temperature degrees C |
| f_atm | file of atmospheric pressure in mb |

Details

Converting specific humidity into relative humidity. from Bolton 1980 The computation of Equivalent Potential Temperature

Value

a file of relative humidity, ratio of actual water mixing ratio to saturation mixing ratio

Author(s)

P. Chevallier - Nov 2022

Source

David LeBauer - 2014

from Bolton 1980 The computation of Equivalent Potential Temperature

<https://earthscience.stackexchange.com/questions/2360/how-do-i-convert-specific-humidity-to-relativ>

`w_temp_alt`*Compute temperature, function of altitude*

Description

Compute temperature, function of altitude

Usage

```
w_temp_alt(file, alt0 = 0, alt, grad = -0.0065)
```

Arguments

| | |
|-------------------|--------------------------------------------------------------|
| <code>file</code> | File name of the known air temperature ts (°C) |
| <code>alt0</code> | Altitude of the known air temperature ts - default = 0 (m) |
| <code>alt</code> | Altitude of the computed air- temperature ts (m) |
| <code>grad</code> | Temperature gradient vs elevation - default = -0.0065 (°C/m) |

Details

The function computes an air temperature time-series at a given altitude, based on a known air temperature time-series at a known altitude.

Value

An hts file with the suffix `_<alt>`

Author(s)

P. Chevallier - Nov 2021

`z_coord`*Coordinate utility*

Description

Convert numeric coordinates in character coordinates

Usage

```
z_coord(ncoord = NA, ccoord = NA, type)
```

Arguments

| | |
|--------|----------------------|
| ncoord | Numeric coordinate |
| ccoord | Character coordinate |
| type | Lat / Lon |

Details

Only one of both parameters ncoord (numeric) and ccoord (character) must be filled, the other one remaining NA. The type of coordinate (Lat or Lon) is compulsory.

The character coordinate must be organized in one string with 4 fields (degrees, minutes, seconds, direction) separated with blanks (space or tab). Within each field, no blanks are allowed to share the numeric value and the unit character. For the unit character, the only following letters are allowed: letter d/m/s. For direction, the only the following letters are allowed: N/n/W/w/S/s/E/e.

Example: "25d 18m 56.2s S"

Value

Coordinates in characters

Author(s)

P. Chevallier - Jan 2019 / Nov 2020

z_set

Edit settings

Description

Utility for editing the settings of the htsr package.

Usage

```
z_set(tz = FALSE, mapal = FALSE)
```

Arguments

| | |
|-------|---------------------------------------------|
| tz | Logical, setting time zone (default=FALSE) |
| mapal | Logical, setting my palette (default=FALSE) |

Details

The function allows to edit user settings for time zone and color palette.

The settings are stored in an external data file of the htsr package, named "settings.RData".

tz is the time zone coded following the Olson standard list.

my palette is a list of 12 colors from the R color name list.

Author(s)

P. Chevallier - nov 2018 - nov 2020

Index

d_backup, 6
d_compact, 7
d_convert_hydraccess, 7
d_convert_weewx, 8
d_create, 9, 15
d_exp_hts, 4, 9, 10, 42
d_imp_hts, 11, 42
d_inventory, 4, 8, 9, 12, 15, 17, 18
d_rem_hts, 13
d_sensor, 5, 13, 17
d_station, 6, 15, 15
d_table, 15, 17, 18
d_wind, 19, 55, 56
ds_dismeas, 3
ds_exp_hts, 4, 8, 10, 15, 17, 18
ds_inventory, 4, 8, 9, 12, 15, 17, 18
ds_sensor, 5
ds_station, 6, 15

f_change_id, 20
f_convert, 10, 21
f_csv_multivar, 22
f_month2day, 22
f_properties, 23, 49, 50
fc, 20

h_addna, 25
h_avday, 25
h_common, 26, 57
h_condition, 27
h_cumul, 28
h_gaperr, 29
h_gapfill, 29
h_gaprem_itv, 30
h_month, 24, 31, 47
h_nodata, 32
h_rainsnow, 33
h_rbind, 34
h_replace, 35
h_restrict, 36

h_rollav, 36
h_season, 37
h_stat_basic, 38
h_substitute, 38
h_timestep, 24, 39
h_weightedsum, 40
h_wl_di, 41
h_year, 42
hs_tstep, 24
htsr, 24

p_bar, 43, 45, 46, 53, 54
p_bar_app, 43, 44, 45
p_box_month, 46
p_clim, 47
p_discalib, 42, 48
p_gaps, 23, 49
p_hypso, 50
p_line, 44, 46, 51, 53, 54
p_line_app, 43, 51–53, 53
p_scatter, 54
p_wind, 19, 55
ps_plothts, 43, 43, 51

w_atmp_alt, 56
w_etp, 57
w_spechum2relhum, 59
w_temp_alt, 60
windRose, 56

z_coord, 60
z_set, 61