

## Package ‘makeit’

October 27, 2023

Version 1.0.1

Date 2023-10-27

## Title Run R Scripts if Needed

**Suggests** dplyr, ggplot2, knitr, readr, rmarkdown

**Description** Automation tool to run R scripts if needed, based on last modified time. Implemented in base R with no additional software requirements, organizational overhead, or structural requirements. In short: run an R script if underlying files have changed, otherwise do nothing.

License GPL-3

URL <https://github.com/arni-magnusson/makeit>

VignetteBuilder knitr

## Encoding UTF-8

**RoxxygenNote** 7.2.3

## NeedsCompilation no

**Author** Arni Magnusson [aut, cre]

Maintainer Arni Magnusson <thisisarni@gmail.com>

Repository CRAN

Date/Publication 2023-10-27 08:00:09 UTC

## R topics documented:

make . . . . .	2
<b>Index</b>	<b>4</b>

<code>make</code>	<i>Run R Script if Needed</i>
-------------------	-------------------------------

## Description

Run an R script if underlying files have changed, otherwise do nothing.

## Usage

```
make(recipe, prereq, target, include = TRUE, details = FALSE,
    force = FALSE, recon = FALSE, quiet = FALSE, ...)
```

## Arguments

<code>recipe</code>	script filename.
<code>prereq</code>	one or more files required by the script. For example, data files, scripts, or NULL.
<code>target</code>	one or more output files produced by the script. Directory names can also be used.
<code>include</code>	whether to automatically include the script itself as a prerequisite file. This means that if the script file has been modified, it should be run.
<code>details</code>	whether to show a diagnostic table of files and time last modified.
<code>force</code>	whether to run the R script unconditionally.
<code>recon</code>	whether to return TRUE or FALSE, without actually running the R script.
<code>quiet</code>	whether to suppress messages.
...	passed to <code>source</code> .

## Value

TRUE or FALSE, indicating whether the script was run.

## Note

This function provides functionality similar to makefile rules, to determine whether a script should be (re)run or not.

If any `target` is either missing or is older than any `prereq`, then the script is run.

## References

Stallman, R. M. *et al.* An introduction to makefiles. Chapter 2 in the *GNU Make manual*.

## See Also

See `vignette("makeit")` for annotated examples and discussion.

`file.exists` and `file.mtime` are the underlying functions used to check if files are missing or have changed.

`source` is the underlying function to run a script.

## Examples

```
# Copy examples 'analysis' and 'sequential' to temporary directory
exdir <- tempdir()
file.copy(system.file("examples/analysis", package="makeit"),
          exdir, recursive=TRUE)
file.copy(system.file("examples/sequential", package="makeit"),
          exdir, recursive=TRUE)
owd <- getwd()

# This analysis uses input.dat to produce output.dat
setwd(file.path(exdir, "analysis"))
dir()
make("analysis.R", "input.dat", "output.dat") # Running analysis.R
dir()
make("analysis.R", "input.dat", "output.dat") # Nothing to be done

# Suppress message, show last modified
make("analysis.R", "input.dat", "output.dat", quiet=TRUE)
make("analysis.R", "input.dat", "output.dat", details=TRUE)

# Sequential scripts
setwd(file.path(exdir, "sequential"))
print.simple.list(dir(recursive=TRUE))
make("01_model.R", "data.dat", "results.dat")
make("02_plots.R", "results.dat", c("plots/A.png", "plots/B.png"))
make("03_tables.R", "results.dat", c("tables/A.csv", "tables/B.csv"))
print.simple.list(dir(recursive=TRUE))

# Clean up
unlink(file.path(exdir, c("analysis", "sequential")), recursive=TRUE)
setwd(owd)

# See vignette("makeit") for more examples and discussion
```

# Index

`file.exists`, [2](#)  
`file.mtime`, [2](#)

`make`, [2](#)  
`makeit (make)`, [2](#)  
`source`, [2](#)