

Package ‘mcmsupply’

August 14, 2023

Type Package

Title Estimating Public and Private Sector Contraceptive Market Supply Shares

Version 0.2.2

Description

Family Planning programs and initiatives typically use nationally representative surveys to estimate key indicators of a country’s family planning progress. However, in recent years, routinely collected family planning services data (Service Statistics) have been used as a supplementary data source to bridge gaps in the surveys. The use of service statistics comes with the caveat that adjustments need to be made for missing private sector contributions to the contraceptive method supply chain. Evaluating the supply source of modern contraceptives often relies on Demographic Health Surveys (DHS), where many countries do not have recent data beyond 2015/16. Fortunately, in the absence of recent surveys we can rely on statistical model-based estimates and projections to fill the knowledge gap. We present a Bayesian, hierarchical, penalized-spline model with multivariate-normal spline coefficients, to account for across method correlations, to produce country-specific, annual estimates for the proportion of modern contraceptive methods coming from the public and private sectors. This package provides a quick and convenient way for users to access the DHS modern contraceptive supply share data at national and subnational administration levels, estimate, evaluate and plot annual estimates with uncertainty for a sample of low- and middle-income countries. Methods for the estimation of method supply shares at the national level are described in Comiskey, Alkema, Cahill (2022) <[arXiv:2212.03844](https://arxiv.org/abs/2212.03844)>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0)

RoxygenNote 7.2.3

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Imports R2jags, magrittr, foreach, tidyverse, tidybayes, runjags, stats, rlang, abind, dplyr, ggplot2, plyr, readxl, stringr, tibble, tidyr

URL <https://hannahcomiskey.github.io/mcmsupply/>,
<https://hannahcomiskey.github.io/mcmsupply/>

NeedsCompilation no

Author Hannah Comiskey [aut, cre],
 Niamh Cahill [aut],
 Leontine Alkema [aut]

Maintainer Hannah Comiskey <hannah.comiskey.2015@mumail.ie>

Repository CRAN

Date/Publication 2023-08-14 17:40:02 UTC

R topics documented:

Country_and_area_classification	2
country_names	3
DEFT_DHS_database	4
get_data	4
get_subnational_modelinputs	5
national_estimated_correlations_logitnormal	6
national_FPsource_data	7
national_FPsource_format	8
national_sigma_delta_hat_logitnormal	8
national_tau_alpha_cms_hat_logitnormal	9
national_theta_rms_hat_logitnormal	9
plot_estimates	10
run_jags_model	10
subnational_alpha_cms_hat	11
subnational_estimated_correlations	12
subnational_inv.sigma_delta_hat	13
subnational_tau_alpha_pms_hat	13
subnat_FPsource_data	14
subnat_FPsource_format	14
Index	16

Country_and_area_classification

*The Country and area classification according to the United Nations
 Standard Statistical Division, Standard country or area codes for statistical
 use (M49). Adapted for use in FP2030 by the Track20 project. A
 subset of data from the United Nations country classifications*

Description

The Country and area classification according to the United Nations Standard Statistical Division, Standard country or area codes for statistical use (M49). Adapted for use in FP2030 by the Track20 project. A subset of data from the United Nations country classifications

Usage

Country_and_area_classification

Format

A data frame with 231 rows and 8 columns:

Country or area Country name

ISO Code 1, 2 & 3 number ISO country codes

Major area Continent

Region Sub-continent

Developed region Binary indicator for development status

Least developed country Binary indicator for least developed status

Sub-Saharan Africa Binary indicator for whether country is in Sub-Saharan Africa

FP2020 Binary indicator for FP2020 participation status

Source

<https://unstats.un.org/unsd/methodology/m49/>

country_names	<i>The names of the countries with national and subnational administration level data stored</i>
---------------	--

Description

The names of the countries with national and subnational administration level data stored

Usage

country_names

Format

A data frame with 30 rows and 3 columns:

Country names Country name

National level data available Indicator for whether data at the national administration level is available in the package

Subnational level data available Indicator for whether data at the subnational administration level is available in the package

DEFT_DHS_database	<i>DEFT_DHS_database A database of the design effects for some of the DHS surveys in the national and subnational datasets. Due to due to multistage and clustering of the DHS sample, the average standard error is increased by a design effect (DEFT) factor over that in an equivalent simple random sample.</i>
-------------------	--

Description

DEFT_DHS_database A database of the design effects for some of the DHS surveys in the national and subnational datasets. Due to due to multistage and clustering of the DHS sample, the average standard error is increased by a design effect (DEFT) factor over that in an equivalent simple random sample.

Usage

```
DEFT_DHS_database
```

Format

A dataframe of Country names, survey year and design effects for DHS surveys

Source

DHS final reports Appendix B, 'ESTIMATES OF SAMPLING ERRORS'.

get_data	<i>Wrapper function that retrieves the DHS data used for modelling the proportion of modern contraceptives supplied by the public and private sectors at the national and subnational administration levels.</i>
----------	--

Description

Wrapper function that retrieves the DHS data used for modelling the proportion of modern contraceptives supplied by the public and private sectors at the national and subnational administration levels.

Usage

```
get_data(
  national = TRUE,
  local = FALSE,
  mycountry = NULL,
  fp2030 = TRUE,
  surveydata_filepath = NULL
)
```

Arguments

national	TRUE/FALSE. Default is TRUE for national administration level data. FALSE retrieves subnational level data.
local	TRUE/FALSE. Default is FALSE for global runs. Decides if this is a single-country or global run.
mycountry	The name of country of interest. Default is NULL. For the names of potential countries, review vigentte .
fp2030	Default is TRUE. Filter raw data to only include the Family Planning 2030 focus countries discussed in the Comiskey et al. paper .
surveydata_filepath	Path to survey data. Default is NULL. Survey data should be a .xlsx with the following format national_FPsource_data .

Value

returns a list containing the DHS data set used for inputs into the model and the arguments that specify the data set up.

Examples

```
raw_data <- get_data(national=FALSE, local=TRUE, mycountry="Nepal")
```

```
get_subnational_modelinputs
  Get JAGS model inputs
```

Description

Get JAGS model inputs

Usage

```
get_modelinputs(startyear = 1990, endyear = 2030.5, nsegments = 12, raw_data)
```

Arguments

startyear	The year you wish to begin your predictions from. Default is 1990.
endyear	The year you wish to finish your predictions. Default is 2030.5.
nsegments	The number of knots you wish to use in your basis functions. Default is 12.
raw_data	The list of arguments and family planning source data from the 'get_data' function.

Value

A list of modelling inputs for the JAGS model.

1. Tstar is the year index for the most recent survey in each province.
2. Kstar is the knot index that aligns with Tstar.
3. B.ik are the basis functions.
4. n_years are total number of years
5. n_obs are the total number of observations
6. K are the number of knots.
7. H is K-1. Used in the calculation of first order differences of spline coefficients.
8. P_count is the number of subnational provinces/regions.
9. M_count is the number of modern contraceptive methods.
10. matchsubnat is the subnational province indexing to match the observed data to the predictions.
11. matchcountry is the country indexing to match the observed data to the predictions.
12. matchmethod is the method indexing to match the observed data to the predictions.
13. matchyears is the year indexing to match the observed data to the predictions.

Examples

```
raw_data <- get_data(national=FALSE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2030.5, nsegments=12, raw_data)
```

national_estimated_correlations_logitnormal

The estimated national-level correlations between the rates of change in methods

Description

The estimated national-level correlations between the rates of change in methods

Usage

```
national_estimated_correlations_logitnormal
```

Format

A array of 2 matrices with 5 rows and 5 columns:

row Contraceptive method the correlation estimate refers to

column Contraceptive method the correlation estimate refers to

public_cor The estimated correlation between the rates of change in methods supplied by the public sector

private_cor The estimated correlation between the rates of change in methods supplied by the private sector

national_FPsource_data

DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Description

DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Usage

national_FPsource_data

Format

national_FPsource_data:

A data frame with 2448 rows and 9 columns:

year Year of survey

Country Country names

Super_region Sub-continent names

Method Contraceptive method name

average_year Average year of the survey

sector_category Name of sector

proportion Proportion supplied by the sector

SE.proportion Standard error associated with the proportion

n Sample size associated with the observation

Source

On request from DHS microdata - using the womens individuals recode file. Contact details found at https://dhsprogram.com/data/dataset_admin/login_main.cfm

national_FPsource_format

A checklist for ensuring national-level custom data is appropriate to be used for estimation

Description

A checklist for ensuring national-level custom data is appropriate to be used for estimation

Usage

national_FPsource_format

Format

A list of requirements for custom data to meet before being accepted into the model

Country Country name variable classification

Method Method name variable classification

average_year average_year variable classification

sector_category sector_category name variable classification

proportion proportion variable classification

SE.proportion SE.proportion variable classification

n n variable classification

national_sigma_delta_hat_logitnormal

The median estimate for the national-level variance-covariance matrix of the delta.k terms in the multi-country national model.

Description

The median estimate for the national-level variance-covariance matrix of the delta.k terms in the multi-country national model.

Usage

national_sigma_delta_hat_logitnormal

Format

A array of 2 matrices with 5 rows and 5 columns:

Array 1 Estimated public sector variance-covariance matrix

Array 2 Estimated private sector variance-covariance matrix

national_tau_alpha_cms_hat_logitnormal

The median estimates of the precision for the national-level country, sector-, method-specific intercepts in the multi-country national model. This vector is used to inform the precision in the Normal prior of the national-level intercept in single-country national models.

Description

The median estimates of the precision for the national-level country, sector-, method-specific intercepts in the multi-country national model. This vector is used to inform the precision in the Normal prior of the national-level intercept in single-country national models.

Usage

national_tau_alpha_cms_hat_logitnormal

Format

A vector of two precision estimates

national_theta_rms_hat_logitnormal

The median estimates of the national-level sub-continental, sector-, method-specific intercepts in the multi-country national model. This array is used to inform the Normal prior of the country-level intercept in the single-country national model.

Description

The median estimates of the national-level sub-continental, sector-, method-specific intercepts in the multi-country national model. This array is used to inform the Normal prior of the country-level intercept in the single-country national model.

Usage

national_theta_rms_hat_logitnormal

Format

A array of 5 matrices with 2 rows and 5 columns

plot_estimates	<i>Wrapper function to plot the JAGS estimates</i>
----------------	--

Description

Wrapper function to plot the JAGS estimates

Usage

```
plot_estimates(jagsdata, model_output)
```

Arguments

jagsdata	Output of the mcmsupply::get_modelinputs() function.
model_output	The output of the mcmsupply::run_jags_model() function.

Value

A list of ggplot objects.

Examples

```
## Not run:
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2030.5, nsegments=12, raw_data)
mod <- run_jags_model(jagsdata, n_iter=5, n_burnin=1, n_thin=1)
plots <- plot_estimates(jagsdata = jagsdata, model_output = mod)

## End(Not run)
```

run_jags_model	<i>Wrapper function to run the jags model for estimating the proportion of modern contraceptive methods supplied by the public & private Sectors using a Bayesian hierarchical penalized spline model for the national and subnational administration levels</i>
----------------	--

Description

Wrapper function to run the jags model for estimating the proportion of modern contraceptive methods supplied by the public & private Sectors using a Bayesian hierarchical penalized spline model for the national and subnational administration levels

Usage

```
run_jags_model(
  jagsdata,
  jagsparams = NULL,
  n_iter = 80000,
  n_burnin = 10000,
  n_thin = 35,
  n_chain = 2,
  n_cores = NULL,
  ...
)
```

Arguments

jagsdata	The object from the <code>mcmsupply::get_modelinputs()</code> function.
jagsparams	The parameters of the JAGS model you wish to review
n_iter	Default is 80000. Number of iterations to do in JAGS model.
n_burnin	Default is 10000. Number of samples to burn-in in JAGS model.
n_thin	Default is 35. Number of samples to thin by in JAGS model.
n_chain	Default is 2. Number of chains to run in your MCMC sample.
n_cores	The number of cores to use for parallel execution in subnational estimation. If not specified, the number of cores is set to the value of <code>options("cores")</code> , if specified, or to approximately half the number of cores detected by the parallel package.
...	Arguments from the <code>mcmsupply::get_modelinputs()</code> function.

Value

returns the jags model object

Examples

```
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2025.5, nsegments=12, raw_data)
run_jags_model(jagsdata, n_iter=5, n_burnin=1, n_thin=1)
```

subnational_alpha_cms_hat

The median estimates of the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This array is used to inform the Normal prior of the subnational-level intercept in the single-country subnational model.

Description

The median estimates of the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This array is used to inform the Normal prior of the subnational-level intercept in the single-country subnational model.

Usage

subnational_alpha_cms_hat

Format

A array of 23 matrices with 2 rows and 5 columns

subnational_estimated_correlations

The estimated subnational-level correlations between the rates of change in methods

Description

The estimated subnational-level correlations between the rates of change in methods

Usage

subnational_estimated_correlations

Format

A array of 2 matrices with 5 rows and 5 columns:

row Contraceptive method the correlation estimate refers to

column Contraceptive method the correlation estimate refers to

public_cor The estimated correlation between the rates of change in methods supplied by the public sector

private_cor The estimated correlation between the rates of change in methods supplied by the private sector

subnational_inv.sigma_delta_hat

The median estimate for the subnational-level precision matrix of the delta.k terms in the multi-country subnational model. This array is used to inform the multi-variate normal prior in the single-country subnational model.

Description

The median estimate for the subnational-level precision matrix of the delta.k terms in the multi-country subnational model. This array is used to inform the multi-variate normal prior in the single-country subnational model.

Usage

subnational_inv.sigma_delta_hat

Format

A array of 2 matrices with 5 rows and 5 columns:

Array 1 Estimated public sector precision matrix

Array 2 Estimated private sector precision matrix

subnational_tau_alpha_pms_hat

subnational_tau_alpha_pms_hat The median estimates of the precision for the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This vector is used to inform the precision in the Normal prior of the subnational-level intercept in single-country subnational models.

Description

subnational_tau_alpha_pms_hat The median estimates of the precision for the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This vector is used to inform the precision in the Normal prior of the subnational-level intercept in single-country subnational models.

Usage

subnational_tau_alpha_pms_hat

Format

A vector of two precision estimates

subnat_FPsource_data *DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the subnational administration level.*

Description

Elizabeth Heger Boyle, Miriam King and Matthew Sobek. IPUMS-Demographic and Health Surveys: Version 9 (dataset). IPUMS and ICF, 2022. <https://doi.org/10.18128/D080.V9>

Usage

subnat_FPsource_data

Format

subnat_FPsource_data:

A data frame with 6940 rows and 8 columns:

Country Country names

Region Subnational region names

Method Contraceptive method name

average_year Average year of the survey

sector_categories Name of sector

proportion Proportion supplied by the sector

SE.proportion Standard error associated with the proportion

n Sample size associated with the observation

Source

On request from IPUMS - <https://www.idhsdata.org/idhs/index.shtml>

subnat_FPsource_format

A checklist for ensuring subnational-level custom data is appropriate to be used for estimation

Description

A checklist for ensuring subnational-level custom data is appropriate to be used for estimation

Usage

subnat_FPsource_format

Format

A list of requirements for custom data to meet before being accepted into the model

Country Country name variable classification

Region Subnational region name variable classification

Method Method name variable classification

average_year average_year variable classification

sector_categories sector_categories name variable classification

proportion proportion variable classification

SE.proportion SE.proportion variable classification

n n variable classification

Index

- * **Country_and_area_classification**
 - Country_and_area_classification, 2
 - * **DEFT_DHS_database**
 - DEFT_DHS_database, 4
 - * **country_names**
 - country_names, 3
 - * **datasets**
 - national_FPsource_data, 7
 - subnat_FPsource_data, 14
 - * **national_FPsource_format**
 - national_FPsource_format, 8
 - * **national_estimated_correlations_logitnormal**
 - national_estimated_correlations_logitnormal, 6
 - * **national_sigma_delta_hat_logitnormal**
 - national_sigma_delta_hat_logitnormal, 8
 - * **national_tau_alpha_cms_hat_logitnormal**
 - national_tau_alpha_cms_hat_logitnormal, 9
 - * **national_theta_rms_hat_logitnormal**
 - national_theta_rms_hat_logitnormal, 9
 - * **subnat_FPsource_format**
 - subnat_FPsource_format, 14
 - * **subnational_alpha_cms_hat**
 - subnational_alpha_cms_hat, 11
 - * **subnational_estimated_correlations**
 - subnational_estimated_correlations, 12
 - * **subnational_inv.sigma_delta_hat**
 - subnational_inv.sigma_delta_hat, 13
 - * **subnational_tau_alpha_pms_hat**
 - subnational_tau_alpha_pms_hat, 13
- Country_and_area_classification, 2
country_names, 3
- DEFT_DHS_database, 4
- get_data, 4
get_modelinputs
 (get_subnational_modelinputs),
 5
get_subnational_modelinputs, 5
- national_estimated_correlations_logitnormal,
 6
national_FPsource_data, 5, 7
national_FPsource_format, 8
national_sigma_delta_hat_logitnormal,
 8
national_tau_alpha_cms_hat_logitnormal,
 9
national_theta_rms_hat_logitnormal, 9
- plot_estimates, 10
- run_jags_model, 10
- subnat_FPsource_data, 14
subnat_FPsource_format, 14
subnational_alpha_cms_hat, 11
subnational_estimated_correlations, 12
subnational_inv.sigma_delta_hat, 13
subnational_tau_alpha_pms_hat, 13