

Package ‘paws.database’

January 9, 2024

Title 'Amazon Web Services' Database Services

Version 0.5.0

Description Interface to 'Amazon Web Services' database services, including 'Relational Database Service' ('RDS'), 'DynamoDB' 'NoSQL' database, and more <<https://aws.amazon.com/>>.

License Apache License (>= 2.0)

URL <https://github.com/paws-r/paws>

BugReports <https://github.com/paws-r/paws/issues>

Imports paws.common (>= 0.6.0)

Suggests testthat

Encoding UTF-8

RoxygenNote 7.2.3

Collate 'dax_service.R' 'dax_interfaces.R' 'dax_operations.R'
'docdb_service.R' 'docdb_interfaces.R' 'docdb_operations.R'
'docdbelastic_service.R' 'docdbelastic_interfaces.R'
'docdbelastic_operations.R' 'dynamodb_service.R'
'dynamodb_interfaces.R' 'dynamodb_operations.R'
'dynamodbstreams_service.R' 'dynamodbstreams_interfaces.R'
'dynamodbstreams_operations.R' 'elasticsearch_service.R'
'elasticsearch_interfaces.R' 'elasticsearch_operations.R'
'keyspaces_service.R' 'keyspaces_interfaces.R'
'keyspaces_operations.R' 'lakeformation_service.R'
'lakeformation_interfaces.R' 'lakeformation_operations.R'
'memorydb_service.R' 'memorydb_interfaces.R'
'memorydb_operations.R' 'neptune_service.R'
'neptune_interfaces.R' 'neptune_operations.R'
'neptunedata_service.R' 'neptunedata_interfaces.R'
'neptunedata_operations.R' 'qlldb_service.R' 'qlldb_interfaces.R'
'qlldb_operations.R' 'qlldbsession_service.R'
'qlldbsession_interfaces.R' 'qlldbsession_operations.R'
'rds_service.R' 'rds_operations.R' 'rds_custom.R'
'rds_interfaces.R' 'rdsdataservice_service.R'

'rdsdataservice_interfaces.R' 'rdsdataservice_operations.R'
 'redshift_service.R' 'redshift_interfaces.R'
 'redshift_operations.R' 'redshiftdataapiservice_service.R'
 'redshiftdataapiservice_interfaces.R'
 'redshiftdataapiservice_operations.R'
 'redshiftserverless_service.R'
 'redshiftserverless_interfaces.R'
 'redshiftserverless_operations.R' 'reexports_paws.common.R'
 'simpledb_service.R' 'simpledb_interfaces.R'
 'simpledb_operations.R' 'timestreamquery_service.R'
 'timestreamquery_interfaces.R' 'timestreamquery_operations.R'
 'timestreamwrite_service.R' 'timestreamwrite_interfaces.R'
 'timestreamwrite_operations.R'

NeedsCompilation no

Author David Kretch [aut],
 Adam Banker [aut],
 Dyfan Jones [cre],
 Amazon.com, Inc. [cph]

Maintainer Dyfan Jones <dyfan.r.jones@gmail.com>

Repository CRAN

Date/Publication 2024-01-09 22:00:02 UTC

R topics documented:

dax	3
docdb	5
docdbelastic	9
dynamodb	11
dynamodbstreams	15
elasticache	18
keyspaces	22
lakeformation	24
memorydb	28
neptune	31
neptunedata	35
qldb	38
qldbsession	40
rds	43
rdsdataservice	49
redshift	51
redshiftdataapiservice	56
redshiftserverless	59
simpledb	62
timestreamquery	65
timestreamwrite	68

Index

71

dax

Amazon DynamoDB Accelerator (DAX)

Description

DAX is a managed caching service engineered for Amazon DynamoDB. DAX dramatically speeds up database reads by caching frequently-accessed data from DynamoDB, so applications can access that data with sub-millisecond latency. You can create a DAX cluster easily, using the AWS Management Console. With a few simple modifications to your code, your application can begin taking advantage of the DAX cluster and realize significant improvements in read performance.

Usage

```
dax(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config

Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials

Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- dax(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

- | | |
|--|-------------------------------|
| create_cluster | Creates a DAX cluster |
| create_parameter_group | Creates a new parameter group |
| create_subnet_group | Creates a new subnet group |

<code>decrease_replication_factor</code>	Removes one or more nodes from a DAX cluster
<code>delete_cluster</code>	Deletes a previously provisioned DAX cluster
<code>delete_parameter_group</code>	Deletes the specified parameter group
<code>delete_subnet_group</code>	Deletes a subnet group
<code>describe_clusters</code>	Returns information about all provisioned DAX clusters if no cluster identifier is specified, or a
<code>describe_default_parameters</code>	Returns the default system parameter information for the DAX caching software
<code>describe_events</code>	Returns events related to DAX clusters and parameter groups
<code>describe_parameter_groups</code>	Returns a list of parameter group descriptions
<code>describe_parameters</code>	Returns the detailed parameter list for a particular parameter group
<code>describe_subnet_groups</code>	Returns a list of subnet group descriptions
<code>increase_replication_factor</code>	Adds one or more nodes to a DAX cluster
<code>list_tags</code>	List all of the tags for a DAX cluster
<code>reboot_node</code>	Reboots a single node of a DAX cluster
<code>tag_resource</code>	Associates a set of tags with a DAX resource
<code>untag_resource</code>	Removes the association of tags from a DAX resource
<code>update_cluster</code>	Modifies the settings for a DAX cluster
<code>update_parameter_group</code>	Modifies the parameters of a parameter group
<code>update_subnet_group</code>	Modifies an existing subnet group

Examples

```
## Not run:
svc <- dax()
svc$create_cluster(
  Foo = 123
)

## End(Not run)
```

docdb

Amazon DocumentDB with MongoDB compatibility

Description

Amazon DocumentDB is a fast, reliable, and fully managed database service. Amazon DocumentDB makes it easy to set up, operate, and scale MongoDB-compatible databases in the cloud. With Amazon DocumentDB, you can run the same application code and use the same drivers and tools that you use with MongoDB.

Usage

```
docdb(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- docdb(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
    creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

add_source_identifier_to_subscription	Adds a source identifier to an existing event notification subscription
add_tags_to_resource	Adds metadata tags to an Amazon DocumentDB resource
apply_pending_maintenance_action	Applies a pending maintenance action to a resource (for example, to an Amazon DocumentDB instance)
copy_db_cluster_parameter_group	Copies the specified cluster parameter group
copy_db_cluster_snapshot	Copies a snapshot of a cluster
create_db_cluster	Creates a new Amazon DocumentDB cluster
create_db_cluster_parameter_group	Creates a new cluster parameter group
create_db_cluster_snapshot	Creates a snapshot of a cluster
create_db_instance	Creates a new instance
create_db_subnet_group	Creates a new subnet group
create_event_subscription	Creates an Amazon DocumentDB event notification subscription
create_global_cluster	Creates an Amazon DocumentDB global cluster that can span multiple multiple Availability Zones
delete_db_cluster	Deletes a previously provisioned cluster
delete_db_cluster_parameter_group	Deletes a specified cluster parameter group
delete_db_cluster_snapshot	Deletes a cluster snapshot
delete_db_instance	Deletes a previously provisioned instance
delete_db_subnet_group	Deletes a subnet group
delete_event_subscription	Deletes an Amazon DocumentDB event notification subscription
delete_global_cluster	Deletes a global cluster
describe_certificates	Returns a list of certificate authority (CA) certificates provided by Amazon DocumentDB

<code>describe_db_cluster_parameter_groups</code>	Returns a list of DBClusterParameterGroup descriptions
<code>describe_db_cluster_parameters</code>	Returns the detailed parameter list for a particular cluster parameter group
<code>describe_db_clusters</code>	Returns information about provisioned Amazon DocumentDB clusters
<code>describe_db_cluster_snapshot_attributes</code>	Returns a list of cluster snapshot attribute names and values for a manual DB cluster snapshot
<code>describe_db_cluster_snapshots</code>	Returns information about cluster snapshots
<code>describe_db_engine_versions</code>	Returns a list of the available engines
<code>describe_db_instances</code>	Returns information about provisioned Amazon DocumentDB instances
<code>describe_db_subnet_groups</code>	Returns a list of DBSubnetGroup descriptions
<code>describe_engine_default_cluster_parameters</code>	Returns the default engine and system parameter information for the cluster default parameter group
<code>describe_event_categories</code>	Displays a list of categories for all event source types, or, if specified, for a specific event source type
<code>describe_events</code>	Returns events related to instances, security groups, snapshots, and DB parameter groups
<code>describe_event_subscriptions</code>	Lists all the subscription descriptions for a customer account
<code>describe_global_clusters</code>	Returns information about Amazon DocumentDB global clusters
<code>describe_orderable_db_instance_options</code>	Returns a list of orderable instance options for the specified engine
<code>describe_pending_maintenance_actions</code>	Returns a list of resources (for example, instances) that have at least one pending maintenance action
<code>failover_db_cluster</code>	Forces a failover for a cluster
<code>list_tags_for_resource</code>	Lists all tags on an Amazon DocumentDB resource
<code>modify_db_cluster</code>	Modifies a setting for an Amazon DocumentDB cluster
<code>modify_db_cluster_parameter_group</code>	Modifies the parameters of a cluster parameter group
<code>modify_db_cluster_snapshot_attribute</code>	Adds an attribute and values to, or removes an attribute and values from, a manual DB cluster snapshot
<code>modify_db_instance</code>	Modifies settings for an instance
<code>modify_db_subnet_group</code>	Modifies an existing subnet group
<code>modify_event_subscription</code>	Modifies an existing Amazon DocumentDB event notification subscription
<code>modify_global_cluster</code>	Modify a setting for an Amazon DocumentDB global cluster
<code>reboot_db_instance</code>	You might need to reboot your instance, usually for maintenance reasons
<code>remove_from_global_cluster</code>	Detaches an Amazon DocumentDB secondary cluster from a global cluster
<code>remove_source_identifier_from_subscription</code>	Removes a source identifier from an existing Amazon DocumentDB event notification subscription
<code>remove_tags_from_resource</code>	Removes metadata tags from an Amazon DocumentDB resource
<code>reset_db_cluster_parameter_group</code>	Modifies the parameters of a cluster parameter group to the default value
<code>restore_db_cluster_from_snapshot</code>	Creates a new cluster from a snapshot or cluster snapshot
<code>restore_db_cluster_to_point_in_time</code>	Restores a cluster to an arbitrary point in time
<code>start_db_cluster</code>	Restarts the stopped cluster that is specified by DBClusterIdentifier
<code>stop_db_cluster</code>	Stops the running cluster that is specified by DBClusterIdentifier

Examples

```
## Not run:
svc <- docdb()
svc$add_source_identifier_to_subscription(
  Foo = 123
)

## End(Not run)
```

docdbelastic

Amazon DocumentDB Elastic Clusters

Description

The new Amazon Elastic DocumentDB service endpoint.

Usage

```
docdbelastic(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|-------------|---|
| config | <p>Optional configuration of credentials, endpoint, and/or region.</p> <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html |
| credentials | <p>Optional credentials shorthand for the config parameter</p> <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. |

- **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- docdbelastic(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

create_cluster	Creates a new Elastic DocumentDB cluster and returns its Cluster structure
create_cluster_snapshot	Creates a snapshot of a cluster
delete_cluster	Delete a Elastic DocumentDB cluster

<code>delete_cluster_snapshot</code>	Delete a Elastic DocumentDB snapshot
<code>get_cluster</code>	Returns information about a specific Elastic DocumentDB cluster
<code>get_cluster_snapshot</code>	Returns information about a specific Elastic DocumentDB snapshot
<code>list_clusters</code>	Returns information about provisioned Elastic DocumentDB clusters
<code>list_cluster_snapshots</code>	Returns information about Elastic DocumentDB snapshots for a specified cluster
<code>list_tags_for_resource</code>	Lists all tags on a Elastic DocumentDB resource
<code>restore_cluster_from_snapshot</code>	Restores a Elastic DocumentDB cluster from a snapshot
<code>tag_resource</code>	Adds metadata tags to a Elastic DocumentDB resource
<code>untag_resource</code>	Removes metadata tags to a Elastic DocumentDB resource
<code>update_cluster</code>	Modifies a Elastic DocumentDB cluster

Examples

```
## Not run:
svc <- docdbelastic()
svc$create_cluster(
  Foo = 123
)

## End(Not run)
```

dynamodb

Amazon DynamoDB

Description

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and predictable performance with seamless scalability. DynamoDB lets you offload the administrative burdens of operating and scaling a distributed database, so that you don't have to worry about hardware provisioning, setup and configuration, replication, software patching, or cluster scaling.

With DynamoDB, you can create database tables that can store and retrieve any amount of data, and serve any level of request traffic. You can scale up or scale down your tables' throughput capacity without downtime or performance degradation, and use the Amazon Web Services Management Console to monitor resource utilization and performance metrics.

DynamoDB automatically spreads the data and traffic for your tables over a sufficient number of servers to handle your throughput and storage requirements, while maintaining consistent and fast performance. All of your data is stored on solid state disks (SSDs) and automatically replicated across multiple Availability Zones in an Amazon Web Services Region, providing built-in high availability and data durability.

Usage

```
dynamodb(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- dynamodb(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
    creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

[batch_execute_statement](#)

[batch_get_item](#)

[batch_write_item](#)

[create_backup](#)

[create_global_table](#)

[create_table](#)

[delete_backup](#)

[delete_item](#)

[delete_table](#)

[describe_backup](#)

[describe_continuous_backups](#)

[describe_contributor_insights](#)

[describe_endpoints](#)

[describe_export](#)

[describe_global_table](#)

[describe_global_table_settings](#)

[describe_import](#)

[describe_kinesis_streaming_destination](#)

[describe_limits](#)

[describe_table](#)

This operation allows you to perform batch reads or writes on data stored in Dynam

The BatchGetItem operation returns the attributes of one or more items from one or

The BatchWriteItem operation puts or deletes multiple items in one or more tables

Creates a backup for an existing table

Creates a global table from an existing table

The CreateTable operation adds a new table to your account

Deletes an existing backup of a table

Deletes a single item in a table by primary key

The DeleteTable operation deletes a table and all of its items

Describes an existing backup of a table

Checks the status of continuous backups and point in time recovery on the specified

Returns information about contributor insights for a given table or global secondary

Returns the regional endpoint information

Describes an existing table export

Returns information about the specified global table

Describes Region-specific settings for a global table

Represents the properties of the import

Returns information about the status of Kinesis streaming

Returns the current provisioned-capacity quotas for your Amazon Web Services acc

Returns information about the table, including the current status of the table, when i

describe_table_replica_auto_scaling	Describes auto scaling settings across replicas of the global table at once
describe_time_to_live	Gives a description of the Time to Live (TTL) status on the specified table
disable_kinesis_streaming_destination	Stops replication from the DynamoDB table to the Kinesis data stream
enable_kinesis_streaming_destination	Starts table data replication to the specified Kinesis data stream at a timestamp chosen by you
execute_statement	This operation allows you to perform reads and singleton writes on data stored in DynamoDB
execute_transaction	This operation allows you to perform transactional reads or writes on data stored in DynamoDB
export_table_to_point_in_time	Exports table data to an S3 bucket
get_item	The GetItem operation returns a set of attributes for the item with the given primary key
import_table	Imports table data from an S3 bucket
list_backups	List DynamoDB backups that are associated with an Amazon Web Services account
list_contributor_insights	Returns a list of ContributorInsightsSummary for a table and all its global secondary indexes
list_exports	Lists completed exports within the past 90 days
list_global_tables	Lists all global tables that have a replica in the specified Region
list_imports	Lists completed imports within the past 90 days
list_tables	Returns an array of table names associated with the current account and endpoint
list_tags_of_resource	List all tags on an Amazon DynamoDB resource
put_item	Creates a new item, or replaces an old item with a new item
query	You must provide the name of the partition key attribute and a single value for that attribute
restore_table_from_backup	Creates a new table from an existing backup
restore_table_to_point_in_time	Restores the specified table to the specified point in time within EarliestRestorableTime
scan	The Scan operation returns one or more items and item attributes by accessing every item in the table
tag_resource	Associate a set of tags with an Amazon DynamoDB resource
transact_get_items	TransactGetItems is a synchronous operation that atomically retrieves multiple items from a table
transact_write_items	TransactWriteItems is a synchronous write operation that groups up to 100 action requests
untag_resource	Removes the association of tags from an Amazon DynamoDB resource
update_continuous_backups	UpdateContinuousBackups enables or disables point in time recovery for the specified table
update_contributor_insights	Updates the status for contributor insights for a specific table or index
update_global_table	Adds or removes replicas in the specified global table
update_global_table_settings	Updates settings for a global table
update_item	Edits an existing item's attributes, or adds a new item to the table if it does not already exist
update_table	Modifies the provisioned throughput settings, global secondary indexes, or DynamoDB Streams
update_table_replica_auto_scaling	Updates auto scaling settings on your global tables at once
update_time_to_live	The UpdateTimeToLive method enables or disables Time to Live (TTL) for the specified table

Examples

```
## Not run:
svc <- dynamodb()
# This example reads multiple items from the Music table using a batch of
# three GetItem requests. Only the AlbumTitle attribute is returned.
svc$batch_get_item(
  RequestItems = list(
    Music = list(
      Keys = list(
        list(
          Artist = list(
            S = "No One You Know"
```

```

    ),
    SongTitle = list(
      S = "Call Me Today"
    )
  ),
  list(
    Artist = list(
      S = "Acme Band"
    ),
    SongTitle = list(
      S = "Happy Day"
    )
  ),
  list(
    Artist = list(
      S = "No One You Know"
    ),
    SongTitle = list(
      S = "Scared of My Shadow"
    )
  )
),
ProjectionExpression = "AlbumTitle"
)
)
)

## End(Not run)

```

dynamodbstreams

Amazon DynamoDB Streams

Description

Amazon DynamoDB

Amazon DynamoDB Streams provides API actions for accessing streams and processing stream records. To learn more about application development with Streams, see [Capturing Table Activity with DynamoDB Streams](#) in the Amazon DynamoDB Developer Guide.

Usage

```

dynamodbstreams(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)

```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- dynamodbstreams(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```



```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

describe_stream	Returns information about a stream, including the current status of the stream, its Amazon Resource Name
get_records	Retrieves the stream records from a given shard
get_shard_iterator	Returns a shard iterator
list_streams	Returns an array of stream ARNs associated with the current account and endpoint

Examples

```

## Not run:
svc <- dynamodbstreams()
# The following example describes a stream with a given stream ARN.
svc$describe_stream(
  StreamArn = "arn:aws:dynamodb:us-west-2:111122223333:table/Forum/stream/2..."
)

## End(Not run)

```

 elasticache

 Amazon ElastiCache

Description

Amazon ElastiCache is a web service that makes it easier to set up, operate, and scale a distributed cache in the cloud.

With ElastiCache, customers get all of the benefits of a high-performance, in-memory cache with less of the administrative burden involved in launching and managing a distributed cache. The service makes setup, scaling, and cluster failure handling much simpler than in a self-managed cache deployment.

In addition, through integration with Amazon CloudWatch, customers get enhanced visibility into the key performance statistics associated with their cache and can receive alarms if a part of their cache runs hot.

Usage

```
elasticache(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- elasticache(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
```

```

    region = "string"
)

```

Operations

add_tags_to_resource	A tag is a key-value pair where the key and value are case-sensitive
authorize_cache_security_group_ingress	Allows network ingress to a cache security group
batch_apply_update_action	Apply the service update
batch_stop_update_action	Stop the service update
complete_migration	Complete the migration of data
copy_serverless_cache_snapshot	Creates a copy of an existing serverless cache's snapshot
copy_snapshot	Makes a copy of an existing snapshot
create_cache_cluster	Creates a cluster
create_cache_parameter_group	Creates a new Amazon ElastiCache cache parameter group
create_cache_security_group	Creates a new cache security group
create_cache_subnet_group	Creates a new cache subnet group
create_global_replication_group	Global Datastore for Redis offers fully managed, fast, reliable and secure
create_replication_group	Creates a Redis (cluster mode disabled) or a Redis (cluster mode enabled)
create_serverless_cache	Creates a serverless cache
create_serverless_cache_snapshot	This API creates a copy of an entire ServerlessCache at a specific moment
create_snapshot	Creates a copy of an entire cluster or replication group at a specific moment
create_user	For Redis engine version 6
create_user_group	For Redis engine version 6
decrease_node_groups_in_global_replication_group	Decreases the number of node groups in a Global datastore
decrease_replica_count	Dynamically decreases the number of replicas in a Redis (cluster mode)
delete_cache_cluster	Deletes a previously provisioned cluster
delete_cache_parameter_group	Deletes the specified cache parameter group
delete_cache_security_group	Deletes a cache security group
delete_cache_subnet_group	Deletes a cache subnet group
delete_global_replication_group	Deleting a Global datastore is a two-step process:
delete_replication_group	Deletes an existing replication group
delete_serverless_cache	Deletes a specified existing serverless cache
delete_serverless_cache_snapshot	Deletes an existing serverless cache snapshot
delete_snapshot	Deletes an existing snapshot
delete_user	For Redis engine version 6
delete_user_group	For Redis engine version 6
describe_cache_clusters	Returns information about all provisioned clusters if no cluster identifier
describe_cache_engine_versions	Returns a list of the available cache engines and their versions
describe_cache_parameter_groups	Returns a list of cache parameter group descriptions
describe_cache_parameters	Returns the detailed parameter list for a particular cache parameter group
describe_cache_security_groups	Returns a list of cache security group descriptions
describe_cache_subnet_groups	Returns a list of cache subnet group descriptions
describe_engine_default_parameters	Returns the default engine and system parameter information for the specified
describe_events	Returns events related to clusters, cache security groups, and cache parameter
describe_global_replication_groups	Returns information about a particular global replication group
describe_replication_groups	Returns information about a particular replication group
describe_reserved_cache_nodes	Returns information about reserved cache nodes for this account, or about
describe_reserved_cache_nodes_offerings	Lists available reserved cache node offerings

describe_serverless_caches	Returns information about a specific serverless cache
describe_serverless_cache_snapshots	Returns information about serverless cache snapshots
describe_service_updates	Returns details of the service updates
describe_snapshots	Returns information about cluster or replication group snapshots
describe_update_actions	Returns details of the update actions
describe_user_groups	Returns a list of user groups
describe_users	Returns a list of users
disassociate_global_replication_group	Remove a secondary cluster from the Global datastore using the Global
export_serverless_cache_snapshot	Provides the functionality to export the serverless cache snapshot data
failover_global_replication_group	Used to failover the primary region to a secondary region
increase_node_groups_in_global_replication_group	Increase the number of node groups in the Global datastore
increase_replica_count	Dynamically increases the number of replicas in a Redis (cluster mode)
list_allowed_node_type_modifications	Lists all available node types that you can scale your Redis cluster's or
list_tags_for_resource	Lists all tags currently on a named resource
modify_cache_cluster	Modifies the settings for a cluster
modify_cache_parameter_group	Modifies the parameters of a cache parameter group
modify_cache_subnet_group	Modifies an existing cache subnet group
modify_global_replication_group	Modifies the settings for a Global datastore
modify_replication_group	Modifies the settings for a replication group
modify_replication_group_shard_configuration	Modifies a replication group's shards (node groups) by allowing you to
modify_serverless_cache	This API modifies the attributes of a serverless cache
modify_user	Changes user password(s) and/or access string
modify_user_group	Changes the list of users that belong to the user group
purchase_reserved_cache_nodes_offering	Allows you to purchase a reserved cache node offering
rebalance_slots_in_global_replication_group	Redistribute slots to ensure uniform distribution across existing shards
reboot_cache_cluster	Reboots some, or all, of the cache nodes within a provisioned cluster
remove_tags_from_resource	Removes the tags identified by the TagKeys list from the named resource
reset_cache_parameter_group	Modifies the parameters of a cache parameter group to the engine or sy
revoke_cache_security_group_ingress	Revokes ingress from a cache security group
start_migration	Start the migration of data
test_failover	Represents the input of a TestFailover operation which test automatic f
test_migration	Async API to test connection between source and target replication gro

Examples

```
## Not run:
svc <- elasticache()
svc$add_tags_to_resource(
  Foo = 123
)

## End(Not run)
```

keyspaces

*Amazon Keyspaces***Description**

Amazon Keyspaces (for Apache Cassandra) is a scalable, highly available, and managed Apache Cassandra-compatible database service. Amazon Keyspaces makes it easy to migrate, run, and scale Cassandra workloads in the Amazon Web Services Cloud. With just a few clicks on the Amazon Web Services Management Console or a few lines of code, you can create keyspaces and tables in Amazon Keyspaces, without deploying any infrastructure or installing software.

In addition to supporting Cassandra Query Language (CQL) requests via open-source Cassandra drivers, Amazon Keyspaces supports data definition language (DDL) operations to manage keyspaces and tables using the Amazon Web Services SDK and CLI, as well as infrastructure as code (IaC) services and tools such as CloudFormation and Terraform. This API reference describes the supported DDL operations in detail.

For the list of all supported CQL APIs, see [Supported Cassandra APIs, operations, and data types in Amazon Keyspaces](#) in the *Amazon Keyspaces Developer Guide*.

To learn how Amazon Keyspaces API actions are recorded with CloudTrail, see [Amazon Keyspaces information in CloudTrail](#) in the *Amazon Keyspaces Developer Guide*.

For more information about Amazon Web Services APIs, for example how to implement retry logic or how to sign Amazon Web Services API requests, see [Amazon Web Services APIs](#) in the *General Reference*.

Usage

```
keyspaces(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- `config` Optional configuration of credentials, endpoint, and/or region.
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.

	<ul style="list-style-type: none"> • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- keyspaces(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
```

```

credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_keyspace	The CreateKeyspace operation adds a new keyspace to your account
create_table	The CreateTable operation adds a new table to the specified keyspace
delete_keyspace	The DeleteKeyspace operation deletes a keyspace and all of its tables
delete_table	The DeleteTable operation deletes a table and all of its data
get_keyspace	Returns the name and the Amazon Resource Name (ARN) of the specified table
get_table	Returns information about the table, including the table's name and current status, the keyspace name
list_keyspaces	Returns a list of keyspaces
list_tables	Returns a list of tables for a specified keyspace
list_tags_for_resource	Returns a list of all tags associated with the specified Amazon Keyspaces resource
restore_table	Restores the specified table to the specified point in time within the earliest_restorable_timestamp and
tag_resource	Associates a set of tags with a Amazon Keyspaces resource
untag_resource	Removes the association of tags from a Amazon Keyspaces resource
update_table	Adds new columns to the table or updates one of the table's settings, for example capacity mode, enc

Examples

```

## Not run:
svc <- keyspaces()
svc$create_keyspace(
  Foo = 123
)

## End(Not run)

```


Description

Lake Formation

Defines the public endpoint for the Lake Formation service.

Usage

```
lakeformation(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lakeformation(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[add_lf_tags_to_resource](#)

[assume_decorated_role_with_saml](#)

[batch_grant_permissions](#)

[batch_revoke_permissions](#)

[cancel_transaction](#)

[commit_transaction](#)

[create_data_cells_filter](#)

[create_lake_formation_identity_center_configuration](#)

Attaches one or more LF-tags to an existing resource

Allows a caller to assume an IAM role decorated as the SAML user

Batch operation to grant permissions to the principal

Batch operation to revoke permissions from the principal

Attempts to cancel the specified transaction

Attempts to commit the specified transaction

Creates a data cell filter to allow one to grant access to certain columns

Creates an IAM Identity Center connection with Lake Formation to

<code>create_lake_formation_opt_in</code>	Enforce Lake Formation permissions for the given databases, tables
<code>create_lf_tag</code>	Creates an LF-tag with the specified name and values
<code>delete_data_cells_filter</code>	Deletes a data cell filter
<code>delete_lake_formation_identity_center_configuration</code>	Deletes an IAM Identity Center connection with Lake Formation
<code>delete_lake_formation_opt_in</code>	Remove the Lake Formation permissions enforcement of the given
<code>delete_lf_tag</code>	Deletes the specified LF-tag given a key name
<code>delete_objects_on_cancel</code>	For a specific governed table, provides a list of Amazon S3 objects
<code>deregister_resource</code>	Deregisters the resource as managed by the Data Catalog
<code>describe_lake_formation_identity_center_configuration</code>	Retrieves the instance ARN and application ARN for the connection
<code>describe_resource</code>	Retrieves the current data access role for the given resource register
<code>describe_transaction</code>	Returns the details of a single transaction
<code>extend_transaction</code>	Indicates to the service that the specified transaction is still active and
<code>get_data_cells_filter</code>	Returns a data cells filter
<code>get_data_lake_settings</code>	Retrieves the list of the data lake administrators of a Lake Formation
<code>get_effective_permissions_for_path</code>	Returns the Lake Formation permissions for a specified table or data
<code>get_lf_tag</code>	Returns an LF-tag definition
<code>get_query_state</code>	Returns the state of a query previously submitted
<code>get_query_statistics</code>	Retrieves statistics on the planning and execution of a query
<code>get_resource_lf_tags</code>	Returns the LF-tags applied to a resource
<code>get_table_objects</code>	Returns the set of Amazon S3 objects that make up the specified go
<code>get_temporary_glue_partition_credentials</code>	This API is identical to GetTemporaryTableCredentials except that
<code>get_temporary_glue_table_credentials</code>	Allows a caller in a secure environment to assume a role with perm
<code>get_work_unit_results</code>	Returns the work units resulting from the query
<code>get_work_units</code>	Retrieves the work units generated by the StartQueryPlanning opera
<code>grant_permissions</code>	Grants permissions to the principal to access metadata in the Data C
<code>list_data_cells_filter</code>	Lists all the data cell filters on a table
<code>list_lake_formation_opt_ins</code>	Retrieve the current list of resources and principals that are opt in to
<code>list_lf_tags</code>	Lists LF-tags that the requester has permission to view
<code>list_permissions</code>	Returns a list of the principal permissions on the resource, filtered b
<code>list_resources</code>	Lists the resources registered to be managed by the Data Catalog
<code>list_table_storage_optimizers</code>	Returns the configuration of all storage optimizers associated with a
<code>list_transactions</code>	Returns metadata about transactions and their status
<code>put_data_lake_settings</code>	Sets the list of data lake administrators who have admin privileges o
<code>register_resource</code>	Registers the resource as managed by the Data Catalog
<code>remove_lf_tags_from_resource</code>	Removes an LF-tag from the resource
<code>revoke_permissions</code>	Revokes permissions to the principal to access metadata in the Data
<code>search_databases_by_lf_tags</code>	This operation allows a search on DATABASE resources by TagCor
<code>search_tables_by_lf_tags</code>	This operation allows a search on TABLE resources by LFTags
<code>start_query_planning</code>	Submits a request to process a query statement
<code>start_transaction</code>	Starts a new transaction and returns its transaction ID
<code>update_data_cells_filter</code>	Updates a data cell filter
<code>update_lake_formation_identity_center_configuration</code>	Updates the IAM Identity Center connection parameters
<code>update_lf_tag</code>	Updates the list of possible values for the specified LF-tag key
<code>update_resource</code>	Updates the data access role used for vending access to the given (re
<code>update_table_objects</code>	Updates the manifest of Amazon S3 objects that make up the specif
<code>update_table_storage_optimizer</code>	Updates the configuration of the storage optimizers for a table

Examples

```
## Not run:
svc <- lakeformation()
svc$add_lf_tags_to_resource(
  Foo = 123
)

## End(Not run)
```

memorydb

Amazon MemoryDB

Description

MemoryDB for Redis is a fully managed, Redis-compatible, in-memory database that delivers ultra-fast performance and Multi-AZ durability for modern applications built using microservices architectures. MemoryDB stores the entire database in-memory, enabling low latency and high throughput data access. It is compatible with Redis, a popular open source data store, enabling you to leverage Redis' flexible and friendly data structures, APIs, and commands.

Usage

```
memorydb(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config

Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- memorydb(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
```

```

    region = "string"
)

```

Operations

batch_update_cluster	Apply the service update to a list of clusters supplied
copy_snapshot	Makes a copy of an existing snapshot
create_acl	Creates an Access Control List
create_cluster	Creates a cluster
create_parameter_group	Creates a new MemoryDB parameter group
create_snapshot	Creates a copy of an entire cluster at a specific moment in time
create_subnet_group	Creates a subnet group
create_user	Creates a MemoryDB user
delete_acl	Deletes an Access Control List
delete_cluster	Deletes a cluster
delete_parameter_group	Deletes the specified parameter group
delete_snapshot	Deletes an existing snapshot
delete_subnet_group	Deletes a subnet group
delete_user	Deletes a user
describe_ac_ls	Returns a list of ACLs
describe_clusters	Returns information about all provisioned clusters if no cluster identifier is specified, or
describe_engine_versions	Returns a list of the available Redis engine versions
describe_events	Returns events related to clusters, security groups, and parameter groups
describe_parameter_groups	Returns a list of parameter group descriptions
describe_parameters	Returns the detailed parameter list for a particular parameter group
describe_reserved_nodes	Returns information about reserved nodes for this account, or about a specified reserved
describe_reserved_nodes_offerings	Lists available reserved node offerings
describe_service_updates	Returns details of the service updates
describe_snapshots	Returns information about cluster snapshots
describe_subnet_groups	Returns a list of subnet group descriptions
describe_users	Returns a list of users
failover_shard	Used to failover a shard
list_allowed_node_type_updates	Lists all available node types that you can scale to from your cluster's current node type
list_tags	Lists all tags currently on a named resource
purchase_reserved_nodes_offering	Allows you to purchase a reserved node offering
reset_parameter_group	Modifies the parameters of a parameter group to the engine or system default value
tag_resource	A tag is a key-value pair where the key and value are case-sensitive
untag_resource	Use this operation to remove tags on a resource
update_acl	Changes the list of users that belong to the Access Control List
update_cluster	Modifies the settings for a cluster
update_parameter_group	Updates the parameters of a parameter group
update_subnet_group	Updates a subnet group
update_user	Changes user password(s) and/or access string

Examples

```
## Not run:
svc <- memorydb()
svc$batch_update_cluster(
  Foo = 123
)

## End(Not run)
```

neptune

Amazon Neptune

Description

Amazon Neptune is a fast, reliable, fully-managed graph database service that makes it easy to build and run applications that work with highly connected datasets. The core of Amazon Neptune is a purpose-built, high-performance graph database engine optimized for storing billions of relationships and querying the graph with milliseconds latency. Amazon Neptune supports popular graph models Property Graph and W3C's RDF, and their respective query languages Apache TinkerPop Gremlin and SPARQL, allowing you to easily build queries that efficiently navigate highly connected datasets. Neptune powers graph use cases such as recommendation engines, fraud detection, knowledge graphs, drug discovery, and network security.

This interface reference for Amazon Neptune contains documentation for a programming or command line interface you can use to manage Amazon Neptune. Note that Amazon Neptune is asynchronous, which means that some interfaces might require techniques such as polling or callback functions to determine when a command has been applied. In this reference, the parameter descriptions indicate whether a command is applied immediately, on the next instance reboot, or during the maintenance window. The reference structure is as follows, and we list following some related topics from the user guide.

Usage

```
neptune(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.

	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	<p>Optional credentials shorthand for the config parameter</p> <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- neptune(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
```



```

    ),
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
  )

```

Operations

add_role_to_db_cluster	Associates an Identity and Access Management (IAM) role with an Neptune DB cluster
add_source_identifier_to_subscription	Adds a source identifier to an existing event notification subscription
add_tags_to_resource	Adds metadata tags to an Amazon Neptune resource
apply_pending_maintenance_action	Applies a pending maintenance action to a resource (for example, to a DB instance)
copy_db_cluster_parameter_group	Copies the specified DB cluster parameter group
copy_db_cluster_snapshot	Copies a snapshot of a DB cluster
copy_db_parameter_group	Copies the specified DB parameter group
create_db_cluster	Creates a new Amazon Neptune DB cluster
create_db_cluster_endpoint	Creates a new custom endpoint and associates it with an Amazon Neptune DB cluster
create_db_cluster_parameter_group	Creates a new DB cluster parameter group
create_db_cluster_snapshot	Creates a snapshot of a DB cluster
create_db_instance	Creates a new DB instance
create_db_parameter_group	Creates a new DB parameter group
create_db_subnet_group	Creates a new DB subnet group
create_event_subscription	Creates an event notification subscription
create_global_cluster	Creates a Neptune global database spread across multiple Amazon Regions
delete_db_cluster	The DeleteDBCluster action deletes a previously provisioned DB cluster
delete_db_cluster_endpoint	Deletes a custom endpoint and removes it from an Amazon Neptune DB cluster
delete_db_cluster_parameter_group	Deletes a specified DB cluster parameter group
delete_db_cluster_snapshot	Deletes a DB cluster snapshot
delete_db_instance	The DeleteDBInstance action deletes a previously provisioned DB instance
delete_db_parameter_group	Deletes a specified DBParameterGroup
delete_db_subnet_group	Deletes a DB subnet group
delete_event_subscription	Deletes an event notification subscription
delete_global_cluster	Deletes a global database
describe_db_cluster_endpoints	Returns information about endpoints for an Amazon Neptune DB cluster
describe_db_cluster_parameter_groups	Returns a list of DBClusterParameterGroup descriptions
describe_db_cluster_parameters	Returns the detailed parameter list for a particular DB cluster parameter group
describe_db_clusters	Returns information about provisioned DB clusters, and supports pagination
describe_db_cluster_snapshot_attributes	Returns a list of DB cluster snapshot attribute names and values for a manual snapshot
describe_db_cluster_snapshots	Returns information about DB cluster snapshots
describe_db_engine_versions	Returns a list of the available DB engines

<code>describe_db_instances</code>	Returns information about provisioned instances, and supports pagination
<code>describe_db_parameter_groups</code>	Returns a list of DBParameterGroup descriptions
<code>describe_db_parameters</code>	Returns the detailed parameter list for a particular DB parameter group
<code>describe_db_subnet_groups</code>	Returns a list of DBSubnetGroup descriptions
<code>describe_engine_default_cluster_parameters</code>	Returns the default engine and system parameter information for the cluster da
<code>describe_engine_default_parameters</code>	Returns the default engine and system parameter information for the specified
<code>describe_event_categories</code>	Displays a list of categories for all event source types, or, if specified, for a spe
<code>describe_events</code>	Returns events related to DB instances, DB security groups, DB snapshots, and
<code>describe_event_subscriptions</code>	Lists all the subscription descriptions for a customer account
<code>describe_global_clusters</code>	Returns information about Neptune global database clusters
<code>describe_orderable_db_instance_options</code>	Returns a list of orderable DB instance options for the specified engine
<code>describe_pending_maintenance_actions</code>	Returns a list of resources (for example, DB instances) that have at least one p
<code>describe_valid_db_instance_modifications</code>	You can call DescribeValidDBInstanceModifications to learn what modificatio
<code>failover_db_cluster</code>	Forces a failover for a DB cluster
<code>failover_global_cluster</code>	Initiates the failover process for a Neptune global database
<code>list_tags_for_resource</code>	Lists all tags on an Amazon Neptune resource
<code>modify_db_cluster</code>	Modify a setting for a DB cluster
<code>modify_db_cluster_endpoint</code>	Modifies the properties of an endpoint in an Amazon Neptune DB cluster
<code>modify_db_cluster_parameter_group</code>	Modifies the parameters of a DB cluster parameter group
<code>modify_db_cluster_snapshot_attribute</code>	Adds an attribute and values to, or removes an attribute and values from, a mar
<code>modify_db_instance</code>	Modifies settings for a DB instance
<code>modify_db_parameter_group</code>	Modifies the parameters of a DB parameter group
<code>modify_db_subnet_group</code>	Modifies an existing DB subnet group
<code>modify_event_subscription</code>	Modifies an existing event notification subscription
<code>modify_global_cluster</code>	Modify a setting for an Amazon Neptune global cluster
<code>promote_read_replica_db_cluster</code>	Not supported
<code>reboot_db_instance</code>	You might need to reboot your DB instance, usually for maintenance reasons
<code>remove_from_global_cluster</code>	Detaches a Neptune DB cluster from a Neptune global database
<code>remove_role_from_db_cluster</code>	Disassociates an Identity and Access Management (IAM) role from a DB clus
<code>remove_source_identifier_from_subscription</code>	Removes a source identifier from an existing event notification subscription
<code>remove_tags_from_resource</code>	Removes metadata tags from an Amazon Neptune resource
<code>reset_db_cluster_parameter_group</code>	Modifies the parameters of a DB cluster parameter group to the default value
<code>reset_db_parameter_group</code>	Modifies the parameters of a DB parameter group to the engine/system default
<code>restore_db_cluster_from_snapshot</code>	Creates a new DB cluster from a DB snapshot or DB cluster snapshot
<code>restore_db_cluster_to_point_in_time</code>	Restores a DB cluster to an arbitrary point in time
<code>start_db_cluster</code>	Starts an Amazon Neptune DB cluster that was stopped using the Amazon con
<code>stop_db_cluster</code>	Stops an Amazon Neptune DB cluster

Examples

```
## Not run:
svc <- neptune()
svc$add_role_to_db_cluster(
  Foo = 123
)

## End(Not run)
```

neptunedata

*Amazon NeptuneData***Description**

Neptune Data API

The Amazon Neptune data API provides SDK support for more than 40 of Neptune's data operations, including data loading, query execution, data inquiry, and machine learning. It supports the Gremlin and openCypher query languages, and is available in all SDK languages. It automatically signs API requests and greatly simplifies integrating Neptune into your applications.

Usage

```
neptunedata(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**
 - **access_key_id:** AWS access key ID
 - **secret_access_key:** AWS secret access key
 - **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- neptunedata(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

cancel_gremlin_query	Cancels a Gremlin query
cancel_loader_job	Cancels a specified load job
cancel_ml_data_processing_job	Cancels a Neptune ML data processing job
cancel_ml_model_training_job	Cancels a Neptune ML model training job
cancel_ml_model_transform_job	Cancels a specified model transform job
cancel_open_cypher_query	Cancels a specified openCypher query
create_ml_endpoint	Creates a new Neptune ML inference endpoint that lets you query one specific model
delete_ml_endpoint	Cancels the creation of a Neptune ML inference endpoint
delete_propertygraph_statistics	Deletes statistics for Gremlin and openCypher (property graph) data
delete_sparql_statistics	Deletes SPARQL statistics
execute_fast_reset	The fast reset REST API lets you reset a Neptune graph quickly and easily, removing a
execute_gremlin_explain_query	Executes a Gremlin Explain query
execute_gremlin_profile_query	Executes a Gremlin Profile query, which runs a specified traversal, collects various me
execute_gremlin_query	This commands executes a Gremlin query
execute_open_cypher_explain_query	Executes an openCypher explain request
execute_open_cypher_query	Executes an openCypher query
get_engine_status	Retrieves the status of the graph database on the host
get_gremlin_query_status	Gets the status of a specified Gremlin query
get_loader_job_status	Gets status information about a specified load job
get_ml_data_processing_job	Retrieves information about a specified data processing job
get_ml_endpoint	Retrieves details about an inference endpoint
get_ml_model_training_job	Retrieves information about a Neptune ML model training job
get_ml_model_transform_job	Gets information about a specified model transform job
get_open_cypher_query_status	Retrieves the status of a specified openCypher query
get_propertygraph_statistics	Gets property graph statistics (Gremlin and openCypher)
get_propertygraph_stream	Gets a stream for a property graph
get_propertygraph_summary	Gets a graph summary for a property graph
get_rdf_graph_summary	Gets a graph summary for an RDF graph
get_sparql_statistics	Gets RDF statistics (SPARQL)
get_sparql_stream	Gets a stream for an RDF graph
list_gremlin_queries	Lists active Gremlin queries
list_loader_jobs	Retrieves a list of the loadIds for all active loader jobs
list_ml_data_processing_jobs	Returns a list of Neptune ML data processing jobs
list_ml_endpoints	Lists existing inference endpoints
list_ml_model_training_jobs	Lists Neptune ML model-training jobs
list_ml_model_transform_jobs	Returns a list of model transform job IDs
list_open_cypher_queries	Lists active openCypher queries
manage_propertygraph_statistics	Manages the generation and use of property graph statistics
manage_sparql_statistics	Manages the generation and use of RDF graph statistics
start_loader_job	Starts a Neptune bulk loader job to load data from an Amazon S3 bucket into a Neptun
start_ml_data_processing_job	Creates a new Neptune ML data processing job for processing the graph data exported
start_ml_model_training_job	Creates a new Neptune ML model training job
start_ml_model_transform_job	Creates a new model transform job

Examples

```
## Not run:
svc <- neptunedata()
svc$cancel_gremlin_query(
  Foo = 123
)

## End(Not run)
```

qldb

Amazon QLDB

Description

The resource management API for Amazon QLDB

Usage

```
qldb(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	<p>Optional configuration of credentials, endpoint, and/or region.</p> <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	<p>Optional credentials shorthand for the config parameter</p> <ul style="list-style-type: none"> • creds:

	<ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- qldb(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

<code>cancel_journal_kinesis_stream</code>	Ends a given Amazon QLDB journal stream
<code>create_ledger</code>	Creates a new ledger in your Amazon Web Services account in the current Region
<code>delete_ledger</code>	Deletes a ledger and all of its contents
<code>describe_journal_kinesis_stream</code>	Returns detailed information about a given Amazon QLDB journal stream
<code>describe_journal_s3_export</code>	Returns information about a journal export job, including the ledger name, export ID, and time range
<code>describe_ledger</code>	Returns information about a ledger, including its state, permissions mode, encryption, and time range
<code>export_journal_to_s3</code>	Exports journal contents within a date and time range from a ledger into a specified S3 bucket
<code>get_block</code>	Returns a block object at a specified address in a journal
<code>get_digest</code>	Returns the digest of a ledger at the latest committed block in the journal
<code>get_revision</code>	Returns a revision data object for a specified document ID and block address
<code>list_journal_kinesis_streams_for_ledger</code>	Returns all Amazon QLDB journal streams for a given ledger
<code>list_journal_s3_exports</code>	Returns all journal export jobs for all ledgers that are associated with the current Amazon Web Services account
<code>list_journal_s3_exports_for_ledger</code>	Returns all journal export jobs for a specified ledger
<code>list_ledgers</code>	Returns all ledgers that are associated with the current Amazon Web Services account
<code>list_tags_for_resource</code>	Returns all tags for a specified Amazon QLDB resource
<code>stream_journal_to_kinesis</code>	Creates a journal stream for a given Amazon QLDB ledger
<code>tag_resource</code>	Adds one or more tags to a specified Amazon QLDB resource
<code>untag_resource</code>	Removes one or more tags from a specified Amazon QLDB resource
<code>update_ledger</code>	Updates properties on a ledger
<code>update_ledger_permissions_mode</code>	Updates the permissions mode of a ledger

Examples

```
## Not run:
svc <- qldb()
svc$cancel_journal_kinesis_stream(
  Foo = 123
)

## End(Not run)
```

 qldbsession

Amazon QLDB Session

Description

The transactional data APIs for Amazon QLDB

Instead of interacting directly with this API, we recommend using the QLDB driver or the QLDB shell to execute data transactions on a ledger.

- If you are working with an AWS SDK, use the QLDB driver. The driver provides a high-level abstraction layer above this *QLDB Session* data plane and manages `send_command` API calls for you. For information and a list of supported programming languages, see [Getting started with the driver](#) in the *Amazon QLDB Developer Guide*.

- If you are working with the AWS Command Line Interface (AWS CLI), use the QLDB shell. The shell is a command line interface that uses the QLDB driver to interact with a ledger. For information, see [Accessing Amazon QLDB using the QLDB shell](#).

Usage

```
qldb-session(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- qldbession(  
  config = list(  
    credentials = list(  
      creds = list(  
        access_key_id = "string",  
        secret_access_key = "string",  
        session_token = "string"  
      ),  
      profile = "string",  
      anonymous = "logical"  
    ),  
    endpoint = "string",  
    region = "string",  
    close_connection = "logical",  
    timeout = "numeric",  
    s3_force_path_style = "logical",  
    sts_regional_endpoint = "string"  
  ),  
  credentials = list(  
    creds = list(  
      access_key_id = "string",  
      secret_access_key = "string",  
      session_token = "string"  
    ),  
    profile = "string",  
    anonymous = "logical"  
  ),  
  endpoint = "string",  
  region = "string"  
)
```

Operations

[send_command](#) Sends a command to an Amazon QLDB ledger

Examples

```
## Not run:  
svc <- qldbession()
```

```
svc$send_command(  
  Foo = 123  
)  
  
## End(Not run)
```

Description

Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. It provides cost-efficient, resizeable capacity for an industry-standard relational database and manages common database administration tasks, freeing up developers to focus on what makes their applications and businesses unique.

Amazon RDS gives you access to the capabilities of a MySQL, MariaDB, PostgreSQL, Microsoft SQL Server, Oracle, Db2, or Amazon Aurora database server. These capabilities mean that the code, applications, and tools you already use today with your existing databases work with Amazon RDS without modification. Amazon RDS automatically backs up your database and maintains the database software that powers your DB instance. Amazon RDS is flexible: you can scale your DB instance's compute resources and storage capacity to meet your application's demand. As with all Amazon Web Services, there are no up-front investments, and you pay only for the resources you use.

This interface reference for Amazon RDS contains documentation for a programming or command line interface you can use to manage Amazon RDS. Amazon RDS is asynchronous, which means that some interfaces might require techniques such as polling or callback functions to determine when a command has been applied. In this reference, the parameter descriptions indicate whether a command is applied immediately, on the next instance reboot, or during the maintenance window. The reference structure is as follows, and we list following some related topics from the user guide.

Amazon RDS API Reference

- For the alphabetical list of API actions, see [API Actions](#).
- For the alphabetical list of data types, see [Data Types](#).
- For a list of common query parameters, see [Common Parameters](#).
- For descriptions of the error codes, see [Common Errors](#).

Amazon RDS User Guide

- For a summary of the Amazon RDS interfaces, see [Available RDS Interfaces](#).
- For more information about how to use the Query API, see [Using the Query API](#).

Usage

```
rds(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- rds(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
    creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

[add_role_to_db_cluster](#)
[add_role_to_db_instance](#)
[add_source_identifier_to_subscription](#)
[add_tags_to_resource](#)
[apply_pending_maintenance_action](#)
[authorize_db_security_group_ingress](#)
[backtrack_db_cluster](#)
[build_auth_token](#)
[cancel_export_task](#)
[copy_db_cluster_parameter_group](#)
[copy_db_cluster_snapshot](#)
[copy_db_parameter_group](#)
[copy_db_snapshot](#)
[copy_option_group](#)
[create_blue_green_deployment](#)
[create_custom_db_engine_version](#)
[create_db_cluster](#)
[create_db_cluster_endpoint](#)
[create_db_cluster_parameter_group](#)
[create_db_cluster_snapshot](#)

Associates an Identity and Access Management (IAM) role with a DB cl
 Associates an Amazon Web Services Identity and Access Management (A
 Adds a source identifier to an existing RDS event notification subscrip
 Adds metadata tags to an Amazon RDS resource
 Applies a pending maintenance action to a resource (for example, to a DB
 Enables ingress to a DBSecurityGroup using one of two forms of authori
 Backtracks a DB cluster to a specific time, without creating a new DB cl
 Return an authentication token for a database connection
 Cancels an export task in progress that is exporting a snapshot or cluster
 Copies the specified DB cluster parameter group
 Copies a snapshot of a DB cluster
 Copies the specified DB parameter group
 Copies the specified DB snapshot
 Copies the specified option group
 Creates a blue/green deployment
 Creates a custom DB engine version (CEV)
 Creates a new Amazon Aurora DB cluster or Multi-AZ DB cluster
 Creates a new custom endpoint and associates it with an Amazon Aurora
 Creates a new DB cluster parameter group
 Creates a snapshot of a DB cluster

<code>create_db_instance</code>	Creates a new DB instance
<code>create_db_instance_read_replica</code>	Creates a new DB instance that acts as a read replica for an existing source instance
<code>create_db_parameter_group</code>	Creates a new DB parameter group
<code>create_db_proxy</code>	Creates a new DB proxy
<code>create_db_proxy_endpoint</code>	Creates a DBProxyEndpoint
<code>create_db_security_group</code>	Creates a new DB security group
<code>create_db_snapshot</code>	Creates a snapshot of a DB instance
<code>create_db_subnet_group</code>	Creates a new DB subnet group
<code>create_event_subscription</code>	Creates an RDS event notification subscription
<code>create_global_cluster</code>	Creates an Aurora global database spread across multiple Amazon Web Services Regions
<code>create_integration</code>	Creates a zero-ETL integration with Amazon Redshift
<code>create_option_group</code>	Creates a new option group
<code>create_tenant_database</code>	Creates a tenant database in a DB instance that uses the multi-tenant configuration
<code>delete_blue_green_deployment</code>	Deletes a blue/green deployment
<code>delete_custom_db_engine_version</code>	Deletes a custom engine version
<code>delete_db_cluster</code>	The DeleteDBCluster action deletes a previously provisioned DB cluster
<code>delete_db_cluster_automated_backup</code>	Deletes automated backups using the DbClusterResourceId value of the source DB cluster
<code>delete_db_cluster_endpoint</code>	Deletes a custom endpoint and removes it from an Amazon Aurora DB cluster
<code>delete_db_cluster_parameter_group</code>	Deletes a specified DB cluster parameter group
<code>delete_db_cluster_snapshot</code>	Deletes a DB cluster snapshot
<code>delete_db_instance</code>	Deletes a previously provisioned DB instance
<code>delete_db_instance_automated_backup</code>	Deletes automated backups using the DbiResourceId value of the source DB instance
<code>delete_db_parameter_group</code>	Deletes a specified DB parameter group
<code>delete_db_proxy</code>	Deletes an existing DB proxy
<code>delete_db_proxy_endpoint</code>	Deletes a DBProxyEndpoint
<code>delete_db_security_group</code>	Deletes a DB security group
<code>delete_db_snapshot</code>	Deletes a DB snapshot
<code>delete_db_subnet_group</code>	Deletes a DB subnet group
<code>delete_event_subscription</code>	Deletes an RDS event notification subscription
<code>delete_global_cluster</code>	Deletes a global database cluster
<code>delete_integration</code>	Deletes a zero-ETL integration with Amazon Redshift
<code>delete_option_group</code>	Deletes an existing option group
<code>delete_tenant_database</code>	Deletes a tenant database from your DB instance
<code>deregister_db_proxy_targets</code>	Remove the association between one or more DBProxyTarget data structures and a DB proxy
<code>describe_account_attributes</code>	Lists all of the attributes for a customer account
<code>describe_blue_green_deployments</code>	Describes one or more blue/green deployments
<code>describe_certificates</code>	Lists the set of certificate authority (CA) certificates provided by Amazon RDS
<code>describe_db_cluster_automated_backups</code>	Displays backups for both current and deleted DB clusters
<code>describe_db_cluster_backtracks</code>	Returns information about backtracks for a DB cluster
<code>describe_db_cluster_endpoints</code>	Returns information about endpoints for an Amazon Aurora DB cluster
<code>describe_db_cluster_parameter_groups</code>	Returns a list of DBClusterParameterGroup descriptions
<code>describe_db_cluster_parameters</code>	Returns the detailed parameter list for a particular DB cluster parameter group
<code>describe_db_clusters</code>	Describes existing Amazon Aurora DB clusters and Multi-AZ DB clusters
<code>describe_db_cluster_snapshot_attributes</code>	Returns a list of DB cluster snapshot attribute names and values for a particular DB cluster snapshot
<code>describe_db_cluster_snapshots</code>	Returns information about DB cluster snapshots
<code>describe_db_engine_versions</code>	Describes the properties of specific versions of DB engines
<code>describe_db_instance_automated_backups</code>	Displays backups for both current and deleted instances
<code>describe_db_instances</code>	Describes provisioned RDS instances

describe_db_log_files	Returns a list of DB log files for the DB instance
describe_db_parameter_groups	Returns a list of DBParameterGroup descriptions
describe_db_parameters	Returns the detailed parameter list for a particular DB parameter group
describe_db_proxies	Returns information about DB proxies
describe_db_proxy_endpoints	Returns information about DB proxy endpoints
describe_db_proxy_target_groups	Returns information about DB proxy target groups, represented by DBProxyTargetGroup objects
describe_db_proxy_targets	Returns information about DBProxyTarget objects
describe_db_recommendations	Describes the recommendations to resolve the issues for your DB instance
describe_db_security_groups	Returns a list of DBSecurityGroup descriptions
describe_db_snapshot_attributes	Returns a list of DB snapshot attribute names and values for a manual DB snapshot
describe_db_snapshots	Returns information about DB snapshots
describe_db_snapshot_tenant_databases	Describes the tenant databases that exist in a DB snapshot
describe_db_subnet_groups	Returns a list of DBSubnetGroup descriptions
describe_engine_default_cluster_parameters	Returns the default engine and system parameter information for the cluster
describe_engine_default_parameters	Returns the default engine and system parameter information for the specified DB instance
describe_event_categories	Displays a list of categories for all event source types, or, if specified, for a specific event source type
describe_events	Returns events related to DB instances, DB clusters, DB parameter groups, and DB snapshots
describe_event_subscriptions	Lists all the subscription descriptions for a customer account
describe_export_tasks	Returns information about a snapshot or cluster export to Amazon S3
describe_global_clusters	Returns information about Aurora global database clusters
describe_integrations	Describe one or more zero-ETL integrations with Amazon Redshift
describe_option_group_options	Describes all available options for the specified engine
describe_option_groups	Describes the available option groups
describe_orderable_db_instance_options	Describes the orderable DB instance options for a specified DB engine
describe_pending_maintenance_actions	Returns a list of resources (for example, DB instances) that have at least one pending maintenance action
describe_reserved_db_instances	Returns information about reserved DB instances for this account, or about all reserved DB instances
describe_reserved_db_instances_offerings	Lists available reserved DB instance offerings
describe_source_regions	Returns a list of the source Amazon Web Services Regions where the current DB instance is replicated
describe_tenant_databases	Describes the tenant databases in a DB instance that uses the multi-tenant architecture
describe_valid_db_instance_modifications	You can call DescribeValidDBInstanceModifications to learn what modifications are valid for a DB instance
disable_http_endpoint	Disables the HTTP endpoint for the specified DB cluster
download_db_log_file_portion	Downloads all or a portion of the specified log file, up to 1 MB in size
enable_http_endpoint	Enables the HTTP endpoint for the DB cluster
failover_db_cluster	Forces a failover for a DB cluster
failover_global_cluster	Promotes the specified secondary DB cluster to be the primary DB cluster
list_tags_for_resource	Lists all tags on an Amazon RDS resource
modify_activity_stream	Changes the audit policy state of a database activity stream to either locked or unlocked
modify_certificates	Override the system-default Secure Sockets Layer/Transport Layer Security (SSL/TLS) certificates
modify_current_db_cluster_capacity	Set the capacity of an Aurora Serverless v1 DB cluster to a specific value
modify_custom_db_engine_version	Modifies the status of a custom engine version (CEV)
modify_db_cluster	Modifies the settings of an Amazon Aurora DB cluster or a Multi-AZ DB instance
modify_db_cluster_endpoint	Modifies the properties of an endpoint in an Amazon Aurora DB cluster
modify_db_cluster_parameter_group	Modifies the parameters of a DB cluster parameter group
modify_db_cluster_snapshot_attribute	Adds an attribute and values to, or removes an attribute and values from, a DB cluster snapshot
modify_db_instance	Modifies settings for a DB instance
modify_db_parameter_group	Modifies the parameters of a DB parameter group
modify_db_proxy	Changes the settings for an existing DB proxy
modify_db_proxy_endpoint	Changes the settings for an existing DB proxy endpoint

<code>modify_db_proxy_target_group</code>	Modifies the properties of a DBProxyTargetGroup
<code>modify_db_recommendation</code>	Updates the recommendation status and recommended action status for t
<code>modify_db_snapshot</code>	Updates a manual DB snapshot with a new engine version
<code>modify_db_snapshot_attribute</code>	Adds an attribute and values to, or removes an attribute and values from,
<code>modify_db_subnet_group</code>	Modifies an existing DB subnet group
<code>modify_event_subscription</code>	Modifies an existing RDS event notification subscription
<code>modify_global_cluster</code>	Modifies a setting for an Amazon Aurora global database cluster
<code>modify_option_group</code>	Modifies an existing option group
<code>modify_tenant_database</code>	Modifies an existing tenant database in a DB instance
<code>promote_read_replica</code>	Promotes a read replica DB instance to a standalone DB instance
<code>promote_read_replica_db_cluster</code>	Promotes a read replica DB cluster to a standalone DB cluster
<code>purchase_reserved_db_instances_offering</code>	Purchases a reserved DB instance offering
<code>reboot_db_cluster</code>	You might need to reboot your DB cluster, usually for maintenance reaso
<code>reboot_db_instance</code>	You might need to reboot your DB instance, usually for maintenance reas
<code>register_db_proxy_targets</code>	Associate one or more DBProxyTarget data structures with a DBProxyTa
<code>remove_from_global_cluster</code>	Detaches an Aurora secondary cluster from an Aurora global database cl
<code>remove_role_from_db_cluster</code>	Removes the association of an Amazon Web Services Identity and Acce
<code>remove_role_from_db_instance</code>	Disassociates an Amazon Web Services Identity and Access Managemen
<code>remove_source_identifier_from_subscription</code>	Removes a source identifier from an existing RDS event notification sub
<code>remove_tags_from_resource</code>	Removes metadata tags from an Amazon RDS resource
<code>reset_db_cluster_parameter_group</code>	Modifies the parameters of a DB cluster parameter group to the default v
<code>reset_db_parameter_group</code>	Modifies the parameters of a DB parameter group to the engine/system d
<code>restore_db_cluster_from_s3</code>	Creates an Amazon Aurora DB cluster from MySQL data stored in an A
<code>restore_db_cluster_from_snapshot</code>	Creates a new DB cluster from a DB snapshot or DB cluster snapshot
<code>restore_db_cluster_to_point_in_time</code>	Restores a DB cluster to an arbitrary point in time
<code>restore_db_instance_from_db_snapshot</code>	Creates a new DB instance from a DB snapshot
<code>restore_db_instance_from_s3</code>	Amazon Relational Database Service (Amazon RDS) supports importing
<code>restore_db_instance_to_point_in_time</code>	Restores a DB instance to an arbitrary point in time
<code>revoke_db_security_group_ingress</code>	Revokes ingress from a DBSecurityGroup for previously authorized IP ra
<code>start_activity_stream</code>	Starts a database activity stream to monitor activity on the database
<code>start_db_cluster</code>	Starts an Amazon Aurora DB cluster that was stopped using the Amazon
<code>start_db_instance</code>	Starts an Amazon RDS DB instance that was stopped using the Amazon
<code>start_db_instance_automated_backups_replication</code>	Enables replication of automated backups to a different Amazon Web Se
<code>start_export_task</code>	Starts an export of DB snapshot or DB cluster data to Amazon S3
<code>stop_activity_stream</code>	Stops a database activity stream that was started using the Amazon Web
<code>stop_db_cluster</code>	Stops an Amazon Aurora DB cluster
<code>stop_db_instance</code>	Stops an Amazon RDS DB instance
<code>stop_db_instance_automated_backups_replication</code>	Stops automated backup replication for a DB instance
<code>switchover_blue_green_deployment</code>	Switches over a blue/green deployment
<code>switchover_global_cluster</code>	Switches over the specified secondary DB cluster to be the new primary
<code>switchover_read_replica</code>	Switches over an Oracle standby database in an Oracle Data Guard enviro

Examples

```
## Not run:
svc <- rds()
svc$add_role_to_db_cluster(
```



```

    Foo = 123
)

## End(Not run)

```

rdsdataservice	<i>AWS RDS DataService</i>
----------------	----------------------------

Description

RDS Data API

Amazon RDS provides an HTTP endpoint to run SQL statements on an Amazon Aurora DB cluster. To run these statements, you use the RDS Data API (Data API).

Data API is available with the following types of Aurora databases:

- Aurora PostgreSQL - Serverless v2, Serverless v1, and provisioned
- Aurora MySQL - Serverless v1 only

For more information about the Data API, see [Using RDS Data API](#) in the *Amazon Aurora User Guide*.

Usage

```

rdsdataservice(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)

```

Arguments

- | | |
|--------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
|--------|---|
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.
 - **region:** The AWS Region used in instantiating the client.
 - **close_connection:** Immediately close all HTTP connections.

	<ul style="list-style-type: none"> • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- rdsdataservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>batch_execute_statement</code>	Runs a batch SQL statement over an array of data
<code>begin_transaction</code>	Starts a SQL transaction
<code>commit_transaction</code>	Ends a SQL transaction started with the BeginTransaction operation and commits the changes
<code>execute_sql</code>	Runs one or more SQL statements
<code>execute_statement</code>	Runs a SQL statement against a database
<code>rollback_transaction</code>	Performs a rollback of a transaction

Examples

```

## Not run:
svc <- rdsdataservice()
svc$batch_execute_statement(
  Foo = 123
)

## End(Not run)

```

redshift

Amazon Redshift

Description

Overview

This is an interface reference for Amazon Redshift. It contains documentation for one of the programming or command line interfaces you can use to manage Amazon Redshift clusters. Note that Amazon Redshift is asynchronous, which means that some interfaces may require techniques, such as polling or asynchronous callback handlers, to determine when a command has been applied. In this reference, the parameter descriptions indicate whether a change is applied immediately, on the next instance reboot, or during the next maintenance window. For a summary of the Amazon Redshift cluster management interfaces, go to [Using the Amazon Redshift Management Interfaces](#).

Amazon Redshift manages all the work of setting up, operating, and scaling a data warehouse: provisioning capacity, monitoring and backing up the cluster, and applying patches and upgrades

to the Amazon Redshift engine. You can focus on using your data to acquire new insights for your business and customers.

If you are a first-time user of Amazon Redshift, we recommend that you begin by reading the [Amazon Redshift Getting Started Guide](#).

If you are a database developer, the [Amazon Redshift Database Developer Guide](#) explains how to design, build, query, and maintain the databases that make up your data warehouse.

Usage

```
redshift(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- redshift(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[accept_reserved_node_exchange](#)

[add_partner](#)

[associate_data_share_consumer](#)

[authorize_cluster_security_group_ingress](#)

[authorize_data_share](#)

[authorize_endpoint_access](#)

[authorize_snapshot_access](#)

[batch_delete_cluster_snapshots](#)

Exchanges a DC1 Reserved Node for a DC2 Reserved Node with no cl

Adds a partner integration to a cluster

From a datashare consumer account, associates a datashare with the ac

Adds an inbound (ingress) rule to an Amazon Redshift security group

From a data producer account, authorizes the sharing of a datashare wi

Grants access to a cluster

Authorizes the specified Amazon Web Services account to restore the s

Deletes a set of cluster snapshots

batch_modify_cluster_snapshots	Modifies the settings for a set of cluster snapshots
cancel_resize	Cancels a resize operation for a cluster
copy_cluster_snapshot	Copies the specified automated cluster snapshot to a new manual cluster snapshot
create_authentication_profile	Creates an authentication profile with the specified parameters
create_cluster	Creates a new cluster with the specified parameters
create_cluster_parameter_group	Creates an Amazon Redshift parameter group
create_cluster_security_group	Creates a new Amazon Redshift security group
create_cluster_snapshot	Creates a manual snapshot of the specified cluster
create_cluster_subnet_group	Creates a new Amazon Redshift subnet group
create_custom_domain_association	Used to create a custom domain name for a cluster
create_endpoint_access	Creates a Redshift-managed VPC endpoint
create_event_subscription	Creates an Amazon Redshift event notification subscription
create_hsm_client_certificate	Creates an HSM client certificate that an Amazon Redshift cluster will use to connect to an HSM
create_hsm_configuration	Creates an HSM configuration that contains the information required to connect to an HSM
create_redshift_idc_application	Creates an Amazon Redshift application for use with IAM Identity Center
create_scheduled_action	Creates a scheduled action
create_snapshot_copy_grant	Creates a snapshot copy grant that permits Amazon Redshift to use an Amazon S3 bucket to store snapshots
create_snapshot_schedule	Create a snapshot schedule that can be associated to a cluster and which can be used to create snapshots
create_tags	Adds tags to a cluster
create_usage_limit	Creates a usage limit for a specified Amazon Redshift feature on a cluster
deauthorize_data_share	From a datashare producer account, removes authorization from the specified datashare consumer account
delete_authentication_profile	Deletes an authentication profile
delete_cluster	Deletes a previously provisioned cluster without its final snapshot being created
delete_cluster_parameter_group	Deletes a specified Amazon Redshift parameter group
delete_cluster_security_group	Deletes an Amazon Redshift security group
delete_cluster_snapshot	Deletes the specified manual snapshot
delete_cluster_subnet_group	Deletes the specified cluster subnet group
delete_custom_domain_association	Contains information about deleting a custom domain association for a cluster
delete_endpoint_access	Deletes a Redshift-managed VPC endpoint
delete_event_subscription	Deletes an Amazon Redshift event notification subscription
delete_hsm_client_certificate	Deletes the specified HSM client certificate
delete_hsm_configuration	Deletes the specified Amazon Redshift HSM configuration
delete_partner	Deletes a partner integration from a cluster
delete_redshift_idc_application	Deletes an Amazon Redshift IAM Identity Center application
delete_resource_policy	Deletes the resource policy for a specified resource
delete_scheduled_action	Deletes a scheduled action
delete_snapshot_copy_grant	Deletes the specified snapshot copy grant
delete_snapshot_schedule	Deletes a snapshot schedule
delete_tags	Deletes tags from a resource
delete_usage_limit	Deletes a usage limit from a cluster
describe_account_attributes	Returns a list of attributes attached to an account
describe_authentication_profiles	Describes an authentication profile
describe_cluster_db_revisions	Returns an array of ClusterDbRevision objects
describe_cluster_parameter_groups	Returns a list of Amazon Redshift parameter groups, including parameter group names
describe_cluster_parameters	Returns a detailed list of parameters contained within the specified Amazon Redshift parameter group
describe_clusters	Returns properties of provisioned clusters including general cluster properties and snapshot information
describe_cluster_security_groups	Returns information about Amazon Redshift security groups
describe_cluster_snapshots	Returns one or more snapshot objects, which contain metadata about your snapshots

<code>describe_cluster_subnet_groups</code>	Returns one or more cluster subnet group objects, which contain meta
<code>describe_cluster_tracks</code>	Returns a list of all the available maintenance tracks
<code>describe_cluster_versions</code>	Returns descriptions of the available Amazon Redshift cluster versions
<code>describe_custom_domain_associations</code>	Contains information about custom domain associations for a cluster
<code>describe_data_shares</code>	Shows the status of any inbound or outbound datashares available in th
<code>describe_data_shares_for_consumer</code>	Returns a list of datashares where the account identifier being called is
<code>describe_data_shares_for_producer</code>	Returns a list of datashares when the account identifier being called is
<code>describe_default_cluster_parameters</code>	Returns a list of parameter settings for the specified parameter group fa
<code>describe_endpoint_access</code>	Describes a Redshift-managed VPC endpoint
<code>describe_endpoint_authorization</code>	Describes an endpoint authorization
<code>describe_event_categories</code>	Displays a list of event categories for all event source types, or for a sp
<code>describe_events</code>	Returns events related to clusters, security groups, snapshots, and paran
<code>describe_event_subscriptions</code>	Lists descriptions of all the Amazon Redshift event notification subscri
<code>describe_hsm_client_certificates</code>	Returns information about the specified HSM client certificate
<code>describe_hsm_configurations</code>	Returns information about the specified Amazon Redshift HSM config
<code>describe_inbound_integrations</code>	Returns a list of inbound integrations
<code>describe_logging_status</code>	Describes whether information, such as queries and connection attempt
<code>describe_node_configuration_options</code>	Returns properties of possible node configurations such as node type, n
<code>describe_orderable_cluster_options</code>	Returns a list of orderable cluster options
<code>describe_partners</code>	Returns information about the partner integrations defined for a cluster
<code>describe_redshift_idc_applications</code>	Lists the Amazon Redshift IAM Identity Center applications
<code>describe_reserved_node_exchange_status</code>	Returns exchange status details and associated metadata for a reserved
<code>describe_reserved_node_offerings</code>	Returns a list of the available reserved node offerings by Amazon Red
<code>describe_reserved_nodes</code>	Returns the descriptions of the reserved nodes
<code>describe_resize</code>	Returns information about the last resize operation for the specified clu
<code>describe_scheduled_actions</code>	Describes properties of scheduled actions
<code>describe_snapshot_copy_grants</code>	Returns a list of snapshot copy grants owned by the Amazon Web Serv
<code>describe_snapshot_schedules</code>	Returns a list of snapshot schedules
<code>describe_storage</code>	Returns account level backups storage size and provisional storage
<code>describe_table_restore_status</code>	Lists the status of one or more table restore requests made using the R
<code>describe_tags</code>	Returns a list of tags
<code>describe_usage_limits</code>	Shows usage limits on a cluster
<code>disable_logging</code>	Stops logging information, such as queries and connection attempts, fo
<code>disable_snapshot_copy</code>	Disables the automatic copying of snapshots from one region to anothe
<code>disassociate_data_share_consumer</code>	From a datashare consumer account, remove association for the specifi
<code>enable_logging</code>	Starts logging information, such as queries and connection attempts, fo
<code>enable_snapshot_copy</code>	Enables the automatic copy of snapshots from one region to another re
<code>failover_primary_compute</code>	Fails over the primary compute unit of the specified Multi-AZ cluster t
<code>get_cluster_credentials</code>	Returns a database user name and temporary password with temporary
<code>get_cluster_credentials_with_iam</code>	Returns a database user name and temporary password with temporary
<code>get_reserved_node_exchange_configuration_options</code>	Gets the configuration options for the reserved-node exchange
<code>get_reserved_node_exchange_offerings</code>	Returns an array of DC2 ReservedNodeOfferings that matches the pay
<code>get_resource_policy</code>	Get the resource policy for a specified resource
<code>modify_aqua_configuration</code>	This operation is retired
<code>modify_authentication_profile</code>	Modifies an authentication profile
<code>modify_cluster</code>	Modifies the settings for a cluster
<code>modify_cluster_db_revision</code>	Modifies the database revision of a cluster
<code>modify_cluster_iam_roles</code>	Modifies the list of Identity and Access Management (IAM) roles that

<code>modify_cluster_maintenance</code>	Modifies the maintenance settings of a cluster
<code>modify_cluster_parameter_group</code>	Modifies the parameters of a parameter group
<code>modify_cluster_snapshot</code>	Modifies the settings for a snapshot
<code>modify_cluster_snapshot_schedule</code>	Modifies a snapshot schedule for a cluster
<code>modify_cluster_subnet_group</code>	Modifies a cluster subnet group to include the specified list of VPC subnets
<code>modify_custom_domain_association</code>	Contains information for changing a custom domain association
<code>modify_endpoint_access</code>	Modifies a Redshift-managed VPC endpoint
<code>modify_event_subscription</code>	Modifies an existing Amazon Redshift event notification subscription
<code>modify_redshift_idc_application</code>	Changes an existing Amazon Redshift IAM Identity Center application
<code>modify_scheduled_action</code>	Modifies a scheduled action
<code>modify_snapshot_copy_retention_period</code>	Modifies the number of days to retain snapshots in the destination Amazon S3 bucket
<code>modify_snapshot_schedule</code>	Modifies a snapshot schedule
<code>modify_usage_limit</code>	Modifies a usage limit in a cluster
<code>pause_cluster</code>	Pauses a cluster
<code>purchase_reserved_node_offering</code>	Allows you to purchase reserved nodes
<code>put_resource_policy</code>	Updates the resource policy for a specified resource
<code>reboot_cluster</code>	Reboots a cluster
<code>reject_data_share</code>	From a datashare consumer account, rejects the specified datashare
<code>reset_cluster_parameter_group</code>	Sets one or more parameters of the specified parameter group to their default values
<code>resize_cluster</code>	Changes the size of the cluster
<code>restore_from_cluster_snapshot</code>	Creates a new cluster from a snapshot
<code>restore_table_from_cluster_snapshot</code>	Creates a new table from a table in an Amazon Redshift cluster snapshot
<code>resume_cluster</code>	Resumes a paused cluster
<code>revoke_cluster_security_group_ingress</code>	Revokes an ingress rule in an Amazon Redshift security group for a particular IP address
<code>revoke_endpoint_access</code>	Revokes access to a cluster
<code>revoke_snapshot_access</code>	Removes the ability of the specified Amazon Web Services account to restore from a snapshot
<code>rotate_encryption_key</code>	Rotates the encryption keys for a cluster
<code>update_partner_status</code>	Updates the status of a partner integration

Examples

```
## Not run:
svc <- redshift()
svc$accept_reserved_node_exchange(
  Foo = 123
)

## End(Not run)
```


Description

You can use the Amazon Redshift Data API to run queries on Amazon Redshift tables. You can run SQL statements, which are committed if the statement succeeds.

For more information about the Amazon Redshift Data API and CLI usage examples, see [Using the Amazon Redshift Data API](#) in the *Amazon Redshift Management Guide*.

Usage

```
redshiftdataapiservice(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- redshiftdataapiservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

batch_execute_statement	Runs one or more SQL statements, which can be data manipulation language (DML) or data definition language (DDL)
cancel_statement	Cancel a running query
describe_statement	Describes the details about a specific instance when a query was run by the Amazon Redshift Data API
describe_table	Describes the detailed information about a table from metadata in the cluster
execute_statement	Runs an SQL statement, which can be data manipulation language (DML) or data definition language (DDL)
get_statement_result	Fetches the temporarily cached result of an SQL statement
list_databases	List the databases in a cluster
list_schemas	Lists the schemas in a database

list_statements	List of SQL statements
list_tables	List the tables in a database

Examples

```
## Not run:
svc <- redshiftdataapiservice()
svc$batch_execute_statement(
  Foo = 123
)

## End(Not run)
```

redshiftserverless *Redshift Serverless*

Description

This is an interface reference for Amazon Redshift Serverless. It contains documentation for one of the programming or command line interfaces you can use to manage Amazon Redshift Serverless.

Amazon Redshift Serverless automatically provisions data warehouse capacity and intelligently scales the underlying resources based on workload demands. Amazon Redshift Serverless adjusts capacity in seconds to deliver consistently high performance and simplified operations for even the most demanding and volatile workloads. Amazon Redshift Serverless lets you focus on using your data to acquire new insights for your business and customers.

To learn more about Amazon Redshift Serverless, see [What is Amazon Redshift Serverless](#).

Usage

```
redshiftserverless(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key

	<ul style="list-style-type: none"> * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- redshiftserverless(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
```

```

        close_connection = "logical",
        timeout = "numeric",
        s3_force_path_style = "logical",
        sts_regional_endpoint = "string"
    ),
    credentials = list(
        creds = list(
            access_key_id = "string",
            secret_access_key = "string",
            session_token = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

convert_recovery_point_to_snapshot	Converts a recovery point to a snapshot
create_custom_domain_association	Creates a custom domain association for Amazon Redshift Serverless
create_endpoint_access	Creates an Amazon Redshift Serverless managed VPC endpoint
create_namespace	Creates a namespace in Amazon Redshift Serverless
create_scheduled_action	Creates a scheduled action
create_snapshot	Creates a snapshot of all databases in a namespace
create_snapshot_copy_configuration	Creates a snapshot copy configuration that lets you copy snapshots to another Amazon
create_usage_limit	Creates a usage limit for a specified Amazon Redshift Serverless usage type
create_workgroup	Creates an workgroup in Amazon Redshift Serverless
delete_custom_domain_association	Deletes a custom domain association for Amazon Redshift Serverless
delete_endpoint_access	Deletes an Amazon Redshift Serverless managed VPC endpoint
delete_namespace	Deletes a namespace from Amazon Redshift Serverless
delete_resource_policy	Deletes the specified resource policy
delete_scheduled_action	Deletes a scheduled action
delete_snapshot	Deletes a snapshot from Amazon Redshift Serverless
delete_snapshot_copy_configuration	Deletes a snapshot copy configuration
delete_usage_limit	Deletes a usage limit from Amazon Redshift Serverless
delete_workgroup	Deletes a workgroup
get_credentials	Returns a database user name and temporary password with temporary authorization t
get_custom_domain_association	Gets information about a specific custom domain association
get_endpoint_access	Returns information, such as the name, about a VPC endpoint
get_namespace	Returns information about a namespace in Amazon Redshift Serverless
get_recovery_point	Returns information about a recovery point
get_resource_policy	Returns a resource policy
get_scheduled_action	Returns information about a scheduled action
get_snapshot	Returns information about a specific snapshot
get_table_restore_status	Returns information about a TableRestoreStatus object
get_usage_limit	Returns information about a usage limit

<code>get_workgroup</code>	Returns information about a specific workgroup
<code>list_custom_domain_associations</code>	Lists custom domain associations for Amazon Redshift Serverless
<code>list_endpoint_access</code>	Returns an array of EndpointAccess objects and relevant information
<code>list_namespaces</code>	Returns information about a list of specified namespaces
<code>list_recovery_points</code>	Returns an array of recovery points
<code>list_scheduled_actions</code>	Returns a list of scheduled actions
<code>list_snapshot_copy_configurations</code>	Returns a list of snapshot copy configurations
<code>list_snapshots</code>	Returns a list of snapshots
<code>list_table_restore_status</code>	Returns information about an array of TableRestoreStatus objects
<code>list_tags_for_resource</code>	Lists the tags assigned to a resource
<code>list_usage_limits</code>	Lists all usage limits within Amazon Redshift Serverless
<code>list_workgroups</code>	Returns information about a list of specified workgroups
<code>put_resource_policy</code>	Creates or updates a resource policy
<code>restore_from_recovery_point</code>	Restore the data from a recovery point
<code>restore_from_snapshot</code>	Restores a namespace from a snapshot
<code>restore_table_from_recovery_point</code>	Restores a table from a recovery point to your Amazon Redshift Serverless instance
<code>restore_table_from_snapshot</code>	Restores a table from a snapshot to your Amazon Redshift Serverless instance
<code>tag_resource</code>	Assigns one or more tags to a resource
<code>untag_resource</code>	Removes a tag or set of tags from a resource
<code>update_custom_domain_association</code>	Updates an Amazon Redshift Serverless certificate associated with a custom domain
<code>update_endpoint_access</code>	Updates an Amazon Redshift Serverless managed endpoint
<code>update_namespace</code>	Updates a namespace with the specified settings
<code>update_scheduled_action</code>	Updates a scheduled action
<code>update_snapshot</code>	Updates a snapshot
<code>update_snapshot_copy_configuration</code>	Updates a snapshot copy configuration
<code>update_usage_limit</code>	Update a usage limit in Amazon Redshift Serverless
<code>update_workgroup</code>	Updates a workgroup with the specified configuration settings

Examples

```
## Not run:
svc <- redshiftserverless()
svc$convert_recovery_point_to_snapshot(
  Foo = 123
)

## End(Not run)
```

Description

Amazon SimpleDB is a web service providing the core database functions of data indexing and querying in the cloud. By offloading the time and effort associated with building and operating a web-scale database, SimpleDB provides developers the freedom to focus on application development.

A traditional, clustered relational database requires a sizable upfront capital outlay, is complex to design, and often requires extensive and repetitive database administration. Amazon SimpleDB is dramatically simpler, requiring no schema, automatically indexing your data and providing a simple API for storage and access. This approach eliminates the administrative burden of data modeling, index maintenance, and performance tuning. Developers gain access to this functionality within Amazon's proven computing environment, are able to scale instantly, and pay only for what they use.

Visit <http://aws.amazon.com/simpledb/> for more information.

Usage

```
simpledb(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the `config` parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile**: The name of a profile to use. If not given, then the default profile is used.
 - **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- simplifiedb(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[batch_delete_attributes](#) Performs multiple DeleteAttributes operations in a single call, which reduces round trips and latency

batch_put_attributes	The BatchPutAttributes operation creates or replaces attributes within one or more items
create_domain	The CreateDomain operation creates a new domain
delete_attributes	Deletes one or more attributes associated with an item
delete_domain	The DeleteDomain operation deletes a domain
domain_metadata	Returns information about the domain, including when the domain was created, the number of items
get_attributes	Returns all of the attributes associated with the specified item
list_domains	The ListDomains operation lists all domains associated with the Access Key ID
put_attributes	The PutAttributes operation creates or replaces attributes in an item
select	The Select operation returns a set of attributes for ItemNames that match the select expression

Examples

```
## Not run:
svc <- simpledb()
svc$batch_delete_attributes(
  Foo = 123
)

## End(Not run)
```

timestreamquery

Amazon Timestream Query

Description

Amazon Timestream Query

Usage

```
timestreamquery(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token

	<ul style="list-style-type: none"> – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- timestreamquery(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
```

```

    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

cancel_query	Cancel a query that has been issued
create_scheduled_query	Create a scheduled query that will be run on your behalf at the configured schedule
delete_scheduled_query	Delete a given scheduled query
describe_endpoints	DescribeEndpoints returns a list of available endpoints to make Timestream API calls against
describe_scheduled_query	Provides detailed information about a scheduled query
execute_scheduled_query	You can use this API to run a scheduled query manually
list_scheduled_queries	Gets a list of all scheduled queries in the caller's Amazon account and Region
list_tags_for_resource	List all tags on a Timestream query resource
prepare_query	A synchronous operation that allows you to submit a query with parameters to be stored by Time
query	Query is a synchronous operation that enables you to run a query against your Amazon Timestre
tag_resource	Associate a set of tags with a Timestream resource
untag_resource	Removes the association of tags from a Timestream query resource
update_scheduled_query	Update a scheduled query

Examples

```

## Not run:
svc <- timestreamquery()
svc$cancel_query(
  Foo = 123
)

## End(Not run)

```

timestreamwrite

Amazon Timestream Write

Description

Amazon Timestream is a fast, scalable, fully managed time-series database service that makes it easy to store and analyze trillions of time-series data points per day. With Timestream, you can easily store and analyze IoT sensor data to derive insights from your IoT applications. You can analyze industrial telemetry to streamline equipment management and maintenance. You can also store and analyze log data and metrics to improve the performance and availability of your applications.

Timestream is built from the ground up to effectively ingest, process, and store time-series data. It organizes data to optimize query processing. It automatically scales based on the volume of data ingested and on the query volume to ensure you receive optimal performance while inserting and querying data. As your data grows over time, Timestream's adaptive query processing engine spans across storage tiers to provide fast analysis while reducing costs.

Usage

```
timestreamwrite(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- config** Optional configuration of credentials, endpoint, and/or region.
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.
 - **region:** The AWS Region used in instantiating the client.
 - **close_connection:** Immediately close all HTTP connections.
 - **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
 - **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

	<ul style="list-style-type: none"> • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	<p>Optional credentials shorthand for the config parameter</p> <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- timestreamwrite(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
```

```

    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

create_batch_load_task	Creates a new Timestream batch load task
create_database	Creates a new Timestream database
create_table	Adds a new table to an existing database in your account
delete_database	Deletes a given Timestream database
delete_table	Deletes a given Timestream table
describe_batch_load_task	Returns information about the batch load task, including configurations, mappings, progress, and
describe_database	Returns information about the database, including the database name, time that the database was
describe_endpoints	Returns a list of available endpoints to make Timestream API calls against
describe_table	Returns information about the table, including the table name, database name, retention duration
list_batch_load_tasks	Provides a list of batch load tasks, along with the name, status, when the task is resumable until, a
list_databases	Returns a list of your Timestream databases
list_tables	Provides a list of tables, along with the name, status, and retention properties of each table
list_tags_for_resource	Lists all tags on a Timestream resource
resume_batch_load_task	Resume batch load task
tag_resource	Associates a set of tags with a Timestream resource
untag_resource	Removes the association of tags from a Timestream resource
update_database	Modifies the KMS key for an existing database
update_table	Modifies the retention duration of the memory store and magnetic store for your Timestream table
write_records	Enables you to write your time-series data into Timestream

Examples

```

## Not run:
svc <- timestreamwrite()
svc$create_batch_load_task(
  Foo = 123
)

## End(Not run)

```

Index

accept_reserved_node_exchange, [53](#)
add_lf_tags_to_resource, [26](#)
add_partner, [53](#)
add_role_to_db_cluster, [33](#), [45](#)
add_role_to_db_instance, [45](#)
add_source_identifier_to_subscription,
[7](#), [33](#), [45](#)
add_tags_to_resource, [7](#), [20](#), [33](#), [45](#)
apply_pending_maintenance_action, [7](#), [33](#),
[45](#)
associate_data_share_consumer, [53](#)
assume_decorated_role_with_saml, [26](#)
authorize_cache_security_group_ingress,
[20](#)
authorize_cluster_security_group_ingress,
[53](#)
authorize_data_share, [53](#)
authorize_db_security_group_ingress,
[45](#)
authorize_endpoint_access, [53](#)
authorize_snapshot_access, [53](#)

backtrack_db_cluster, [45](#)
batch_apply_update_action, [20](#)
batch_delete_attributes, [64](#)
batch_delete_cluster_snapshots, [53](#)
batch_execute_statement, [13](#), [51](#), [58](#)
batch_get_item, [13](#)
batch_grant_permissions, [26](#)
batch_modify_cluster_snapshots, [54](#)
batch_put_attributes, [65](#)
batch_revoke_permissions, [26](#)
batch_stop_update_action, [20](#)
batch_update_cluster, [30](#)
batch_write_item, [13](#)
begin_transaction, [51](#)
build_auth_token, [45](#)

cancel_export_task, [45](#)
cancel_gremlin_query, [37](#)

cancel_journal_kinesis_stream, [40](#)
cancel_loader_job, [37](#)
cancel_ml_data_processing_job, [37](#)
cancel_ml_model_training_job, [37](#)
cancel_ml_model_transform_job, [37](#)
cancel_open_cypher_query, [37](#)
cancel_query, [67](#)
cancel_resize, [54](#)
cancel_statement, [58](#)
cancel_transaction, [26](#)
commit_transaction, [26](#), [51](#)
complete_migration, [20](#)
convert_recovery_point_to_snapshot, [61](#)
copy_cluster_snapshot, [54](#)
copy_db_cluster_parameter_group, [7](#), [33](#),
[45](#)
copy_db_cluster_snapshot, [7](#), [33](#), [45](#)
copy_db_parameter_group, [33](#), [45](#)
copy_db_snapshot, [45](#)
copy_option_group, [45](#)
copy_serverless_cache_snapshot, [20](#)
copy_snapshot, [20](#), [30](#)
create_acl, [30](#)
create_authentication_profile, [54](#)
create_backup, [13](#)
create_batch_load_task, [70](#)
create_blue_green_deployment, [45](#)
create_cache_cluster, [20](#)
create_cache_parameter_group, [20](#)
create_cache_security_group, [20](#)
create_cache_subnet_group, [20](#)
create_cluster, [4](#), [10](#), [30](#), [54](#)
create_cluster_parameter_group, [54](#)
create_cluster_security_group, [54](#)
create_cluster_snapshot, [10](#), [54](#)
create_cluster_subnet_group, [54](#)
create_custom_db_engine_version, [45](#)
create_custom_domain_association, [54](#),
[61](#)

- create_data_cells_filter, 26
- create_database, 70
- create_db_cluster, 7, 33, 45
- create_db_cluster_endpoint, 33, 45
- create_db_cluster_parameter_group, 7, 33, 45
- create_db_cluster_snapshot, 7, 33, 45
- create_db_instance, 7, 33, 46
- create_db_instance_read_replica, 46
- create_db_parameter_group, 33, 46
- create_db_proxy, 46
- create_db_proxy_endpoint, 46
- create_db_security_group, 46
- create_db_snapshot, 46
- create_db_subnet_group, 7, 33, 46
- create_domain, 65
- create_endpoint_access, 54, 61
- create_event_subscription, 7, 33, 46, 54
- create_global_cluster, 7, 33, 46
- create_global_replication_group, 20
- create_global_table, 13
- create_hsm_client_certificate, 54
- create_hsm_configuration, 54
- create_integration, 46
- create_keyspace, 24
- create_lake_formation_identity_center_configuration, 26
- create_lake_formation_opt_in, 27
- create_ledger, 40
- create_lf_tag, 27
- create_ml_endpoint, 37
- create_namespace, 61
- create_option_group, 46
- create_parameter_group, 4, 30
- create_redshift_idc_application, 54
- create_replication_group, 20
- create_scheduled_action, 54, 61
- create_scheduled_query, 67
- create_serverless_cache, 20
- create_serverless_cache_snapshot, 20
- create_snapshot, 20, 30, 61
- create_snapshot_copy_configuration, 61
- create_snapshot_copy_grant, 54
- create_snapshot_schedule, 54
- create_subnet_group, 4, 30
- create_table, 13, 24, 70
- create_tags, 54
- create_tenant_database, 46
- create_usage_limit, 54, 61
- create_user, 20, 30
- create_user_group, 20
- create_workgroup, 61
- dax, 3
- deauthorize_data_share, 54
- decrease_node_groups_in_global_replication_group, 20
- decrease_replica_count, 20
- decrease_replication_factor, 5
- delete_acl, 30
- delete_attributes, 65
- delete_authentication_profile, 54
- delete_backup, 13
- delete_blue_green_deployment, 46
- delete_cache_cluster, 20
- delete_cache_parameter_group, 20
- delete_cache_security_group, 20
- delete_cache_subnet_group, 20
- delete_cluster, 5, 10, 30, 54
- delete_cluster_parameter_group, 54
- delete_cluster_security_group, 54
- delete_cluster_snapshot, 11, 54
- delete_cluster_subnet_group, 54
- delete_custom_db_engine_version, 46
- delete_custom_domain_association, 54, 61
- delete_data_cells_filter, 27
- delete_database, 70
- delete_db_cluster, 7, 33, 46
- delete_db_cluster_automated_backup, 46
- delete_db_cluster_endpoint, 33, 46
- delete_db_cluster_parameter_group, 7, 33, 46
- delete_db_cluster_snapshot, 7, 33, 46
- delete_db_instance, 7, 33, 46
- delete_db_instance_automated_backup, 46
- delete_db_parameter_group, 33, 46
- delete_db_proxy, 46
- delete_db_proxy_endpoint, 46
- delete_db_security_group, 46
- delete_db_snapshot, 46
- delete_db_subnet_group, 7, 33, 46
- delete_domain, 65
- delete_endpoint_access, 54, 61
- delete_event_subscription, 7, 33, 46, 54
- delete_global_cluster, 7, 33, 46

- delete_global_replication_group, 20
- delete_hsm_client_certificate, 54
- delete_hsm_configuration, 54
- delete_integration, 46
- delete_item, 13
- delete_keyspace, 24
- delete_lake_formation_identity_center_configuration, 27
- delete_lake_formation_opt_in, 27
- delete_ledger, 40
- delete_lf_tag, 27
- delete_ml_endpoint, 37
- delete_namespace, 61
- delete_objects_on_cancel, 27
- delete_option_group, 46
- delete_parameter_group, 5, 30
- delete_partner, 54
- delete_propertygraph_statistics, 37
- delete_redshift_idc_application, 54
- delete_replication_group, 20
- delete_resource_policy, 54, 61
- delete_scheduled_action, 54, 61
- delete_scheduled_query, 67
- delete_serverless_cache, 20
- delete_serverless_cache_snapshot, 20
- delete_snapshot, 20, 30, 61
- delete_snapshot_copy_configuration, 61
- delete_snapshot_copy_grant, 54
- delete_snapshot_schedule, 54
- delete_sparql_statistics, 37
- delete_subnet_group, 5, 30
- delete_table, 13, 24, 70
- delete_tags, 54
- delete_tenant_database, 46
- delete_usage_limit, 54, 61
- delete_user, 20, 30
- delete_user_group, 20
- delete_workgroup, 61
- deregister_db_proxy_targets, 46
- deregister_resource, 27
- describe_ac_ls, 30
- describe_account_attributes, 46, 54
- describe_authentication_profiles, 54
- describe_backup, 13
- describe_batch_load_task, 70
- describe_blue_green_deployments, 46
- describe_cache_clusters, 20
- describe_cache_engine_versions, 20
- describe_cache_parameter_groups, 20
- describe_cache_parameters, 20
- describe_cache_security_groups, 20
- describe_cache_subnet_groups, 20
- describe_certificates, 7, 46
- describe_cluster_db_revisions, 54
- describe_cluster_parameter_groups, 54
- describe_cluster_parameters, 54
- describe_cluster_security_groups, 54
- describe_cluster_snapshots, 54
- describe_cluster_subnet_groups, 55
- describe_cluster_tracks, 55
- describe_cluster_versions, 55
- describe_clusters, 5, 30, 54
- describe_continuous_backups, 13
- describe_contributor_insights, 13
- describe_custom_domain_associations, 55
- describe_data_shares, 55
- describe_data_shares_for_consumer, 55
- describe_data_shares_for_producer, 55
- describe_database, 70
- describe_db_cluster_automated_backups, 46
- describe_db_cluster_backtracks, 46
- describe_db_cluster_endpoints, 33, 46
- describe_db_cluster_parameter_groups, 8, 33, 46
- describe_db_cluster_parameters, 8, 33, 46
- describe_db_cluster_snapshot_attributes, 8, 33, 46
- describe_db_cluster_snapshots, 8, 33, 46
- describe_db_clusters, 8, 33, 46
- describe_db_engine_versions, 8, 33, 46
- describe_db_instance_automated_backups, 46
- describe_db_instances, 8, 34, 46
- describe_db_log_files, 47
- describe_db_parameter_groups, 34, 47
- describe_db_parameters, 34, 47
- describe_db_proxies, 47
- describe_db_proxy_endpoints, 47
- describe_db_proxy_target_groups, 47
- describe_db_proxy_targets, 47
- describe_db_recommendations, 47
- describe_db_security_groups, 47
- describe_db_snapshot_attributes, 47

- describe_db_snapshot_tenant_databases, [47](#)
- describe_db_snapshots, [47](#)
- describe_db_subnet_groups, [8, 34, 47](#)
- describe_default_cluster_parameters, [55](#)
- describe_default_parameters, [5](#)
- describe_endpoint_access, [55](#)
- describe_endpoint_authorization, [55](#)
- describe_endpoints, [13, 67, 70](#)
- describe_engine_default_cluster_parameters, [8, 34, 47](#)
- describe_engine_default_parameters, [20, 34, 47](#)
- describe_engine_versions, [30](#)
- describe_event_categories, [8, 34, 47, 55](#)
- describe_event_subscriptions, [8, 34, 47, 55](#)
- describe_events, [5, 8, 20, 30, 34, 47, 55](#)
- describe_export, [13](#)
- describe_export_tasks, [47](#)
- describe_global_clusters, [8, 34, 47](#)
- describe_global_replication_groups, [20](#)
- describe_global_table, [13](#)
- describe_global_table_settings, [13](#)
- describe_hsm_client_certificates, [55](#)
- describe_hsm_configurations, [55](#)
- describe_import, [13](#)
- describe_inbound_integrations, [55](#)
- describe_integrations, [47](#)
- describe_journal_kinesis_stream, [40](#)
- describe_journal_s3_export, [40](#)
- describe_kinesis_streaming_destination, [13](#)
- describe_lake_formation_identity_center_configuration, [4, 27](#)
- describe_ledger, [40](#)
- describe_limits, [13](#)
- describe_logging_status, [55](#)
- describe_node_configuration_options, [55](#)
- describe_option_group_options, [47](#)
- describe_option_groups, [47](#)
- describe_orderable_cluster_options, [55](#)
- describe_orderable_db_instance_options, [8, 34, 47](#)
- describe_parameter_groups, [5, 30](#)
- describe_parameters, [5, 30](#)
- describe_partners, [55](#)
- describe_pending_maintenance_actions, [8, 34, 47](#)
- describe_redshift_idc_applications, [55](#)
- describe_replication_groups, [20](#)
- describe_reserved_cache_nodes, [20](#)
- describe_reserved_cache_nodes_offerings, [20](#)
- describe_reserved_db_instances, [47](#)
- describe_reserved_db_instances_offerings, [47](#)
- describe_reserved_node_exchange_status, [55](#)
- describe_reserved_node_offerings, [55](#)
- describe_reserved_nodes, [30, 55](#)
- describe_reserved_nodes_offerings, [30](#)
- describe_resize, [55](#)
- describe_resource, [27](#)
- describe_scheduled_actions, [55](#)
- describe_scheduled_query, [67](#)
- describe_serverless_cache_snapshots, [21](#)
- describe_serverless_caches, [21](#)
- describe_service_updates, [21, 30](#)
- describe_snapshot_copy_grants, [55](#)
- describe_snapshot_schedules, [55](#)
- describe_snapshots, [21, 30](#)
- describe_source_regions, [47](#)
- describe_statement, [58](#)
- describe_storage, [55](#)
- describe_stream, [17](#)
- describe_subnet_groups, [5, 30](#)
- describe_table, [13, 58, 70](#)
- describe_table_replica_auto_scaling, [4](#)
- describe_table_restore_status, [55](#)
- describe_tags, [55](#)
- describe_tenant_databases, [47](#)
- describe_time_to_live, [14](#)
- describe_transaction, [27](#)
- describe_update_actions, [21](#)
- describe_usage_limits, [55](#)
- describe_user_groups, [21](#)
- describe_users, [21, 30](#)
- describe_valid_db_instance_modifications, [34, 47](#)
- disable_http_endpoint, [47](#)
- disable_kinesis_streaming_destination, [13](#)

- 14
- disable_logging, 55
- disable_snapshot_copy, 55
- disassociate_data_share_consumer, 55
- disassociate_global_replication_group, 21
- docdb, 5
- docdbelastic, 9
- domain_metadata, 65
- download_db_log_file_portion, 47
- dynamodb, 11
- dynamodbstreams, 15
- elasticache, 18
- enable_http_endpoint, 47
- enable_kinesis_streaming_destination, 14
- enable_logging, 55
- enable_snapshot_copy, 55
- execute_fast_reset, 37
- execute_gremlin_explain_query, 37
- execute_gremlin_profile_query, 37
- execute_gremlin_query, 37
- execute_open_cypher_explain_query, 37
- execute_open_cypher_query, 37
- execute_scheduled_query, 67
- execute_sql, 51
- execute_statement, 14, 51, 58
- execute_transaction, 14
- export_journal_to_s3, 40
- export_serverless_cache_snapshot, 21
- export_table_to_point_in_time, 14
- extend_transaction, 27
- failover_db_cluster, 8, 34, 47
- failover_global_cluster, 34, 47
- failover_global_replication_group, 21
- failover_primary_compute, 55
- failover_shard, 30
- get_attributes, 65
- get_block, 40
- get_cluster, 11
- get_cluster_credentials, 55
- get_cluster_credentials_with_iam, 55
- get_cluster_snapshot, 11
- get_credentials, 61
- get_custom_domain_association, 61
- get_data_cells_filter, 27
- get_data_lake_settings, 27
- get_digest, 40
- get_effective_permissions_for_path, 27
- get_endpoint_access, 61
- get_engine_status, 37
- get_gremlin_query_status, 37
- get_item, 14
- get_keyspace, 24
- get_lf_tag, 27
- get_loader_job_status, 37
- get_ml_data_processing_job, 37
- get_ml_endpoint, 37
- get_ml_model_training_job, 37
- get_ml_model_transform_job, 37
- get_namespace, 61
- get_open_cypher_query_status, 37
- get_propertygraph_statistics, 37
- get_propertygraph_stream, 37
- get_propertygraph_summary, 37
- get_query_state, 27
- get_query_statistics, 27
- get_rdf_graph_summary, 37
- get_records, 17
- get_recovery_point, 61
- get_reserved_node_exchange_configuration_options, 55
- get_reserved_node_exchange_offerings, 55
- get_resource_lf_tags, 27
- get_resource_policy, 55, 61
- get_revision, 40
- get_scheduled_action, 61
- get_shard_iterator, 17
- get_snapshot, 61
- get_sparql_statistics, 37
- get_sparql_stream, 37
- get_statement_result, 58
- get_table, 24
- get_table_objects, 27
- get_table_restore_status, 61
- get_temporary_glue_partition_credentials, 27
- get_temporary_glue_table_credentials, 27
- get_usage_limit, 61
- get_work_unit_results, 27
- get_work_units, 27
- get_workgroup, 62

- grant_permissions, 27
- import_table, 14
- increase_node_groups_in_global_replication_group, 21
- increase_replica_count, 21
- increase_replication_factor, 5
- keyspaces, 22
- lakeformation, 24
- list_allowed_node_type_modifications, 21
- list_allowed_node_type_updates, 30
- list_backups, 14
- list_batch_load_tasks, 70
- list_cluster_snapshots, 11
- list_clusters, 11
- list_contributor_insights, 14
- list_custom_domain_associations, 62
- list_data_cells_filter, 27
- list_databases, 58, 70
- list_domains, 65
- list_endpoint_access, 62
- list_exports, 14
- list_global_tables, 14
- list_gremlin_queries, 37
- list_imports, 14
- list_journal_kinesis_streams_for_ledger, 40
- list_journal_s3_exports, 40
- list_journal_s3_exports_for_ledger, 40
- list_keyspaces, 24
- list_lake_formation_opt_ins, 27
- list_ledgers, 40
- list_lf_tags, 27
- list_loader_jobs, 37
- list_ml_data_processing_jobs, 37
- list_ml_endpoints, 37
- list_ml_model_training_jobs, 37
- list_ml_model_transform_jobs, 37
- list_namespaces, 62
- list_open_cypher_queries, 37
- list_permissions, 27
- list_recovery_points, 62
- list_resources, 27
- list_scheduled_actions, 62
- list_scheduled_queries, 67
- list_schemas, 58
- list_snapshot_copy_configurations, 62
- list_snapshots, 62
- list_statements, 59
- list_streams, 17
- list_table_restore_status, 62
- list_table_storage_optimizers, 27
- list_tables, 14, 24, 59, 70
- list_tags, 5, 30
- list_tags_for_resource, 8, 11, 21, 24, 34, 40, 47, 62, 67, 70
- list_tags_of_resource, 14
- list_transactions, 27
- list_usage_limits, 62
- list_workgroups, 62
- manage_propertygraph_statistics, 37
- manage_sparql_statistics, 37
- memorydb, 28
- modify_activity_stream, 47
- modify_aqua_configuration, 55
- modify_authentication_profile, 55
- modify_cache_cluster, 21
- modify_cache_parameter_group, 21
- modify_cache_subnet_group, 21
- modify_certificates, 47
- modify_cluster, 55
- modify_cluster_db_revision, 55
- modify_cluster_iam_roles, 55
- modify_cluster_maintenance, 56
- modify_cluster_parameter_group, 56
- modify_cluster_snapshot, 56
- modify_cluster_snapshot_schedule, 56
- modify_cluster_subnet_group, 56
- modify_current_db_cluster_capacity, 47
- modify_custom_db_engine_version, 47
- modify_custom_domain_association, 56
- modify_db_cluster, 8, 34, 47
- modify_db_cluster_endpoint, 34, 47
- modify_db_cluster_parameter_group, 8, 34, 47
- modify_db_cluster_snapshot_attribute, 8, 34, 47
- modify_db_instance, 8, 34, 47
- modify_db_parameter_group, 34, 47
- modify_db_proxy, 47
- modify_db_proxy_endpoint, 47
- modify_db_proxy_target_group, 48
- modify_db_recommendation, 48
- modify_db_snapshot, 48

- modify_db_snapshot_attribute, 48
- modify_db_subnet_group, 8, 34, 48
- modify_endpoint_access, 56
- modify_event_subscription, 8, 34, 48, 56
- modify_global_cluster, 8, 34, 48
- modify_global_replication_group, 21
- modify_option_group, 48
- modify_redshift_idc_application, 56
- modify_replication_group, 21
- modify_replication_group_shard_configuration, 21
- modify_scheduled_action, 56
- modify_serverless_cache, 21
- modify_snapshot_copy_retention_period, 56
- modify_snapshot_schedule, 56
- modify_tenant_database, 48
- modify_usage_limit, 56
- modify_user, 21
- modify_user_group, 21

- neptune, 31
- neptunedata, 35

- pause_cluster, 56
- prepare_query, 67
- promote_read_replica, 48
- promote_read_replica_db_cluster, 34, 48
- purchase_reserved_cache_nodes_offering, 21
- purchase_reserved_db_instances_offering, 48
- purchase_reserved_node_offering, 56
- purchase_reserved_nodes_offering, 30
- put_attributes, 65
- put_data_lake_settings, 27
- put_item, 14
- put_resource_policy, 56, 62

- qldb, 38
- qldbsession, 40
- query, 14, 67

- rds, 43
- rdsdataservice, 49
- rebalance_slots_in_global_replication_group, 21
- reboot_cache_cluster, 21
- reboot_cluster, 56
- reboot_db_cluster, 48
- reboot_db_instance, 8, 34, 48
- reboot_node, 5
- redshift, 51
- redshiftdataapiservice, 56
- redshiftserverless, 59
- register_db_proxy_targets, 48
- register_resource, 27
- reject_data_share, 56
- remove_from_global_cluster, 8, 34, 48
- remove_iam_tags_from_resource, 27
- remove_role_from_db_cluster, 34, 48
- remove_role_from_db_instance, 48
- remove_source_identifier_from_subscription, 8, 34, 48
- remove_tags_from_resource, 8, 21, 34, 48
- reset_cache_parameter_group, 21
- reset_cluster_parameter_group, 56
- reset_db_cluster_parameter_group, 8, 34, 48
- reset_db_parameter_group, 34, 48
- reset_parameter_group, 30
- resize_cluster, 56
- restore_cluster_from_snapshot, 11
- restore_db_cluster_from_s3, 48
- restore_db_cluster_from_snapshot, 8, 34, 48
- restore_db_cluster_to_point_in_time, 8, 34, 48
- restore_db_instance_from_db_snapshot, 48
- restore_db_instance_from_s3, 48
- restore_db_instance_to_point_in_time, 48
- restore_from_cluster_snapshot, 56
- restore_from_recovery_point, 62
- restore_from_snapshot, 62
- restore_table, 24
- restore_table_from_backup, 14
- restore_table_from_cluster_snapshot, 56
- restore_table_from_recovery_point, 62
- restore_table_from_snapshot, 62
- restore_table_to_point_in_time, 14
- resume_batch_load_task, 70
- resume_cluster, 56
- revoke_cache_security_group_ingress, 21

- revoke_cluster_security_group_ingress, 56
- revoke_db_security_group_ingress, 48
- revoke_endpoint_access, 56
- revoke_permissions, 27
- revoke_snapshot_access, 56
- rollback_transaction, 51
- rotate_encryption_key, 56
- scan, 14
- search_databases_by_lf_tags, 27
- search_tables_by_lf_tags, 27
- select, 65
- send_command, 40, 42
- simplifiedb, 62
- start_activity_stream, 48
- start_db_cluster, 8, 34, 48
- start_db_instance, 48
- start_db_instance_automated_backups_replication, 48
- start_export_task, 48
- start_loader_job, 37
- start_migration, 21
- start_ml_data_processing_job, 37
- start_ml_model_training_job, 37
- start_ml_model_transform_job, 37
- start_query_planning, 27
- start_transaction, 27
- stop_activity_stream, 48
- stop_db_cluster, 8, 34, 48
- stop_db_instance, 48
- stop_db_instance_automated_backups_replication, 48
- stream_journal_to_kinesis, 40
- switchover_blue_green_deployment, 48
- switchover_global_cluster, 48
- switchover_read_replica, 48
- tag_resource, 5, 11, 14, 24, 30, 40, 62, 67, 70
- test_failover, 21
- test_migration, 21
- timestreamquery, 65
- timestreamwrite, 68
- transact_get_items, 14
- transact_write_items, 14
- untag_resource, 5, 11, 14, 24, 30, 40, 62, 67, 70
- update_acl, 30
- update_cluster, 5, 11, 30
- update_continuous_backups, 14
- update_contributor_insights, 14
- update_custom_domain_association, 62
- update_data_cells_filter, 27
- update_database, 70
- update_endpoint_access, 62
- update_global_table, 14
- update_global_table_settings, 14
- update_item, 14
- update_lake_formation_identity_center_configuration, 27
- update_ledger, 40
- update_ledger_permissions_mode, 40
- update_lf_tag, 27
- update_namespace, 62
- update_parameter_group, 5, 30
- update_partner_status, 56
- update_resource, 27
- update_scheduled_action, 62
- update_scheduled_query, 67
- update_snapshot, 62
- update_snapshot_copy_configuration, 62
- update_subnet_group, 5, 30
- update_table, 14, 24, 70
- update_table_objects, 27
- update_table_replica_auto_scaling, 14
- update_table_storage_optimizer, 27
- update_time_to_live, 14
- update_usage_limit, 62
- update_user, 30
- update_workgroup, 62
- write_records, 70