

Package ‘paws.security.identity’

September 11, 2023

Title 'Amazon Web Services' Security, Identity, & Compliance Services

Version 0.4.0

Description Interface to 'Amazon Web Services' security, identity, and compliance services, including the 'Identity & Access Management' (IAM) service for managing access to services and resources, and more <<https://aws.amazon.com/>>.

License Apache License (>= 2.0)

URL <https://github.com/paws-r/paws>

BugReports <https://github.com/paws-r/paws/issues>

Imports paws.common (>= 0.6.0)

Suggests testthat

Encoding UTF-8

RoxygenNote 7.2.3

Collate 'accessanalyzer_service.R' 'accessanalyzer_interfaces.R'
'accessanalyzer_operations.R' 'account_service.R'
'account_interfaces.R' 'account_operations.R' 'acm_service.R'
'acm_interfaces.R' 'acm_operations.R' 'acmpca_service.R'
'acmpca_interfaces.R' 'acmpca_operations.R'
'clouddirectory_service.R' 'clouddirectory_interfaces.R'
'clouddirectory_operations.R' 'cloudhsm_service.R'
'cloudhsm_interfaces.R' 'cloudhsm_operations.R'
'cloudhsmv2_service.R' 'cloudhsmv2_interfaces.R'
'cloudhsmv2_operations.R' 'cognitoidentity_service.R'
'cognitoidentity_interfaces.R' 'cognitoidentity_operations.R'
'cognitoidentityprovider_service.R'
'cognitoidentityprovider_interfaces.R'
'cognitoidentityprovider_operations.R' 'cognitosync_service.R'
'cognitosync_interfaces.R' 'cognitosync_operations.R'
'detective_service.R' 'detective_interfaces.R'
'detective_operations.R' 'directoryservice_service.R'
'directoryservice_interfaces.R' 'directoryservice_operations.R'
'fms_service.R' 'fms_interfaces.R' 'fms_operations.R'

'guardduty_service.R' 'guardduty_interfaces.R'
 'guardduty_operations.R' 'iam_service.R' 'iam_interfaces.R'
 'iam_operations.R' 'iamrolesanywhere_service.R'
 'iamrolesanywhere_interfaces.R' 'iamrolesanywhere_operations.R'
 'identitystore_service.R' 'identitystore_interfaces.R'
 'identitystore_operations.R' 'inspector2_service.R'
 'inspector2_interfaces.R' 'inspector2_operations.R'
 'inspector_service.R' 'inspector_interfaces.R'
 'inspector_operations.R' 'kms_service.R' 'kms_interfaces.R'
 'kms_operations.R' 'macie2_service.R' 'macie2_interfaces.R'
 'macie2_operations.R' 'macie_service.R' 'macie_interfaces.R'
 'macie_operations.R' 'ram_service.R' 'ram_interfaces.R'
 'ram_operations.R' 'reexports_paws.common.R'
 'secretsmanager_service.R' 'secretsmanager_interfaces.R'
 'secretsmanager_operations.R' 'securityhub_service.R'
 'securityhub_interfaces.R' 'securityhub_operations.R'
 'shield_service.R' 'shield_interfaces.R' 'shield_operations.R'
 'sso_service.R' 'sso_interfaces.R' 'sso_operations.R'
 'ssoadmin_service.R' 'ssoadmin_interfaces.R'
 'ssoadmin_operations.R' 'ssooidc_service.R'
 'ssooidc_interfaces.R' 'ssooidc_operations.R' 'sts_service.R'
 'sts_interfaces.R' 'sts_operations.R' 'waf_service.R'
 'waf_interfaces.R' 'waf_operations.R' 'wafregional_service.R'
 'wafregional_interfaces.R' 'wafregional_operations.R'
 'wafv2_service.R' 'wafv2_interfaces.R' 'wafv2_operations.R'

NeedsCompilation no

Author David Kretch [aut],
 Adam Banker [aut],
 Dyfan Jones [cre],
 Amazon.com, Inc. [cph]

Maintainer Dyfan Jones <dyfan.r.jones@gmail.com>

Repository CRAN

Date/Publication 2023-09-11 19:20:02 UTC

R topics documented:

accessanalyzer	3
account	6
acm	8
acmpca	11
clouddirectory	14
cloudhsm	18
cloudhsmv2	20
cognitoidentity	23
cognitoidentityprovider	26
cognitosync	31

<i>accessanalyzer</i>	3
detective	34
directoryservice	38
fms	42
guardduty	45
iam	49
iamrolesanywhere	54
identitystore	57
inspector	60
inspector2	63
kms	66
macie	71
macie2	74
ram	78
secretsmanager	81
securityhub	84
shield	88
sso	91
ssoadmin	94
ssooidc	97
sts	100
waf	102
wafregional	106
wafv2	111
Index	116

<code>accessanalyzer</code>	<i>Access Analyzer</i>
-----------------------------	------------------------

Description

Identity and Access Management Access Analyzer helps identify potential resource-access risks by enabling you to identify any policies that grant access to an external principal. It does this by using logic-based reasoning to analyze resource-based policies in your Amazon Web Services environment. An external principal can be another Amazon Web Services account, a root user, an IAM user or role, a federated user, an Amazon Web Services service, or an anonymous user. You can also use IAM Access Analyzer to preview and validate public and cross-account access to your resources before deploying permissions changes. This guide describes the Identity and Access Management Access Analyzer operations that you can call programmatically. For general information about IAM Access Analyzer, see [Identity and Access Management Access Analyzer](#) in the **IAM User Guide**.

To start using IAM Access Analyzer, you first need to create an analyzer.

Usage

```
accessanalyzer(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- accessanalyzer(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

apply_archive_rule	Retroactively applies the archive rule to existing findings that meet the archive rule criteria
cancel_policy_generation	Cancels the requested policy generation
create_access_preview	Creates an access preview that allows you to preview IAM Access Analyzer findings for your
create_analyzer	Creates an analyzer for your account
create_archive_rule	Creates an archive rule for the specified analyzer
delete_analyzer	Deletes the specified analyzer
delete_archive_rule	Deletes the specified archive rule
get_access_preview	Retrieves information about an access preview for the specified analyzer
get_analyzed_resource	Retrieves information about a resource that was analyzed
get_analyzer	Retrieves information about the specified analyzer
get_archive_rule	Retrieves information about an archive rule
get_finding	Retrieves information about the specified finding
get_generated_policy	Retrieves the policy that was generated using StartPolicyGeneration
list_access_preview_findings	Retrieves a list of access preview findings generated by the specified access preview

<code>list_access_previews</code>	Retrieves a list of access previews for the specified analyzer
<code>list_analyzed_resources</code>	Retrieves a list of resources of the specified type that have been analyzed by the specified analyzer
<code>list_analyzers</code>	Retrieves a list of analyzers
<code>list_archive_rules</code>	Retrieves a list of archive rules created for the specified analyzer
<code>list_findings</code>	Retrieves a list of findings generated by the specified analyzer
<code>list_policy_generations</code>	Lists all of the policy generations requested in the last seven days
<code>list_tags_for_resource</code>	Retrieves a list of tags applied to the specified resource
<code>start_policy_generation</code>	Starts the policy generation request
<code>start_resource_scan</code>	Immediately starts a scan of the policies applied to the specified resource
<code>tag_resource</code>	Adds a tag to the specified resource
<code>untag_resource</code>	Removes a tag from the specified resource
<code>update_archive_rule</code>	Updates the criteria and values for the specified archive rule
<code>update_findings</code>	Updates the status for the specified findings
<code>validate_policy</code>	Requests the validation of a policy and returns a list of findings

Examples

```
## Not run:
svc <- accessanalyzer()
svc$apply_archive_rule(
  Foo = 123
)

## End(Not run)
```

account

AWS Account

Description

Operations for Amazon Web Services Account Management

Usage

```
account(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

	<ul style="list-style-type: none"> – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. <ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- account(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
```

```

    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

delete_alternate_contact	Deletes the specified alternate contact from an Amazon Web Services account
disable_region	Disables (opts-out) a particular Region for an account
enable_region	Enables (opts-in) a particular Region for an account
get_alternate_contact	Retrieves the specified alternate contact attached to an Amazon Web Services account
get_contact_information	Retrieves the primary contact information of an Amazon Web Services account
get_region_opt_status	Retrieves the opt-in status of a particular Region
list_regions	Lists all the Regions for a given account and their respective opt-in statuses
put_alternate_contact	Modifies the specified alternate contact attached to an Amazon Web Services account
put_contact_information	Updates the primary contact information of an Amazon Web Services account

Examples

```

## Not run:
svc <- account()
svc$delete_alternate_contact(
  Foo = 123
)

## End(Not run)

```

Description

Certificate Manager

You can use Certificate Manager (ACM) to manage SSL/TLS certificates for your Amazon Web Services-based websites and applications. For more information about using ACM, see the [Certificate Manager User Guide](#).

Usage

```
acm(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- acm(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

add_tags_to_certificate	Adds one or more tags to an ACM certificate
delete_certificate	Deletes a certificate and its associated private key
describe_certificate	Returns detailed metadata about the specified ACM certificate
export_certificate	Exports a private certificate issued by a private certificate authority (CA) for use anywhere
get_account_configuration	Returns the account configuration options associated with an Amazon Web Services account
get_certificate	Retrieves an Amazon-issued certificate and its certificate chain
import_certificate	Imports a certificate into Certificate Manager (ACM) to use with services that are integrated with ACM
list_certificates	Retrieves a list of certificate ARNs and domain names

list_tags_for_certificate	Lists the tags that have been applied to the ACM certificate
put_account_configuration	Adds or modifies account-level configurations in ACM
remove_tags_from_certificate	Remove one or more tags from an ACM certificate
renew_certificate	Renews an eligible ACM certificate
request_certificate	Requests an ACM certificate for use with other Amazon Web Services services
resend_validation_email	Resends the email that requests domain ownership validation
update_certificate_options	Updates a certificate

Examples

```
## Not run:
svc <- acm()
svc$add_tags_to_certificate(
  Foo = 123
)

## End(Not run)
```

acmpca

AWS Certificate Manager Private Certificate Authority

Description

This is the *Amazon Web Services Private Certificate Authority API Reference*. It provides descriptions, syntax, and usage examples for each of the actions and data types involved in creating and managing a private certificate authority (CA) for your organization.

The documentation for each action shows the API request parameters and the JSON response. Alternatively, you can use one of the Amazon Web Services SDKs to access an API that is tailored to the programming language or platform that you prefer. For more information, see [Amazon Web Services SDKs](#).

Each Amazon Web Services Private CA API operation has a quota that determines the number of times the operation can be called per second. Amazon Web Services Private CA throttles API requests at different rates depending on the operation. Throttling means that Amazon Web Services Private CA rejects an otherwise valid request because the request exceeds the operation's quota for the number of requests per second. When a request is throttled, Amazon Web Services Private CA returns a **ThrottlingException** error. Amazon Web Services Private CA does not guarantee a minimum request rate for APIs.

To see an up-to-date list of your Amazon Web Services Private CA quotas, or to request a quota increase, log into your Amazon Web Services account and visit the Service Quotas console.

Usage

```
acmpca(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- acmpca(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_certificate_authority	Creates a root or subordinate private certificate authority (CA)
create_certificate_authority_audit_report	Creates an audit report that lists every time that your CA private key is used
create_permission	Grants one or more permissions on a private CA to the Certificate Manager (ACM)
delete_certificate_authority	Deletes a private certificate authority (CA)
delete_permission	Revokes permissions on a private CA granted to the Certificate Manager (ACM)
delete_policy	Deletes the resource-based policy attached to a private CA
describe_certificate_authority	Lists information about your private certificate authority (CA) or one that has been shared with you
describe_certificate_authority_audit_report	Lists information about a specific audit report created by calling the CreateCertificateAuthorityAuditReport operation
get_certificate	Retrieves a certificate from your private CA or one that has been shared with you
get_certificate_authority_certificate	Retrieves the certificate and certificate chain for your private certificate authority
get_certificate_authority_csr	Retrieves the certificate signing request (CSR) for your private certificate authority
get_policy	Retrieves the resource-based policy attached to a private CA
import_certificate_authority_certificate	Imports a signed private CA certificate into Amazon Web Services Private CA
issue_certificate	Uses your private certificate authority (CA), or one that has been shared with you, to issue a certificate
list_certificate_authorities	Lists the private certificate authorities that you created by using the CreateCertificateAuthority operation
list_permissions	List all permissions on a private CA, if any, granted to the Certificate Manager (ACM)
list_tags	Lists the tags, if any, that are associated with your private CA or one that has been shared with you
put_policy	Attaches a resource-based policy to a private CA
restore_certificate_authority	Restores a certificate authority (CA) that is in the DELETED state
revoke_certificate	Revokes a certificate that was issued inside Amazon Web Services Private CA

[tag_certificate_authority](#)
[untag_certificate_authority](#)
[update_certificate_authority](#)

Adds one or more tags to your private CA
 Remove one or more tags from your private CA
 Updates the status or configuration of a private certificate authority (CA)

Examples

```

## Not run:
svc <- acmpca()
svc$create_certificate_authority(
  Foo = 123
)

## End(Not run)

```

clouddirectory	<i>Amazon CloudDirectory</i>
----------------	------------------------------

Description

Amazon Cloud Directory

Amazon Cloud Directory is a component of the AWS Directory Service that simplifies the development and management of cloud-scale web, mobile, and IoT applications. This guide describes the Cloud Directory operations that you can call programmatically and includes detailed information on data types and errors. For information about Cloud Directory features, see [AWS Directory Service](#) and the [Amazon Cloud Directory Developer Guide](#).

Usage

```

clouddirectory(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)

```

Arguments

config Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token

	<ul style="list-style-type: none"> – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. <ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- clouddirectory(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
```

```

        timeout = "numeric",
        s3_force_path_style = "logical",
        sts_regional_endpoint = "string"
    ),
    credentials = list(
        creds = list(
            access_key_id = "string",
            secret_access_key = "string",
            session_token = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

add_facet_to_object	Adds a new Facet to an object
apply_schema	Copies the input published schema, at the specified version, into the Directory with the sa
attach_object	Attaches an existing object to another object
attach_policy	Attaches a policy object to a regular object
attach_to_index	Attaches the specified object to the specified index
attach_typed_link	Attaches a typed link to a specified source and target object
batch_read	Performs all the read operations in a batch
batch_write	Performs all the write operations in a batch
create_directory	Creates a Directory by copying the published schema into the directory
create_facet	Creates a new Facet in a schema
create_index	Creates an index object
create_object	Creates an object in a Directory
create_schema	Creates a new schema in a development state
create_typed_link_facet	Creates a TypedLinkFacet
delete_directory	Deletes a directory
delete_facet	Deletes a given Facet
delete_object	Deletes an object and its associated attributes
delete_schema	Deletes a given schema
delete_typed_link_facet	Deletes a TypedLinkFacet
detach_from_index	Detaches the specified object from the specified index
detach_object	Detaches a given object from the parent object
detach_policy	Detaches a policy from an object
detach_typed_link	Detaches a typed link from a specified source and target object
disable_directory	Disables the specified directory
enable_directory	Enables the specified directory
get_applied_schema_version	Returns current applied schema version ARN, including the minor version in use
get_directory	Retrieves metadata about a directory
get_facet	Gets details of the Facet, such as facet name, attributes, Rules, or ObjectType
get_link_attributes	Retrieves attributes that are associated with a typed link

get_object_attributes	Retrieves attributes within a facet that are associated with an object
get_object_information	Retrieves metadata about an object
get_schema_as_json	Retrieves a JSON representation of the schema
get_typed_link_facet_information	Returns the identity attribute order for a specific TypedLinkFacet
list_applied_schema_arns	Lists schema major versions applied to a directory
list_attached_indices	Lists indices attached to the specified object
list_development_schema_arns	Retrieves each Amazon Resource Name (ARN) of schemas in the development state
list_directories	Lists directories created within an account
list_facet_attributes	Retrieves attributes attached to the facet
list_facet_names	Retrieves the names of facets that exist in a schema
list_incoming_typed_links	Returns a paginated list of all the incoming TypedLinkSpecifier information for an object
list_index	Lists objects attached to the specified index
list_managed_schema_arns	Lists the major version families of each managed schema
list_object_attributes	Lists all attributes that are associated with an object
list_object_children	Returns a paginated list of child objects that are associated with a given object
list_object_parent_paths	Retrieves all available parent paths for any object type such as node, leaf node, policy node
list_object_parents	Lists parent objects that are associated with a given object in pagination fashion
list_object_policies	Returns policies attached to an object in pagination fashion
list_outgoing_typed_links	Returns a paginated list of all the outgoing TypedLinkSpecifier information for an object
list_policy_attachments	Returns all of the ObjectIdentifiers to which a given policy is attached
list_published_schema_arns	Lists the major version families of each published schema
list_tags_for_resource	Returns tags for a resource
list_typed_link_facet_attributes	Returns a paginated list of all attribute definitions for a particular TypedLinkFacet
list_typed_link_facet_names	Returns a paginated list of TypedLink facet names for a particular schema
lookup_policy	Lists all policies from the root of the Directory to the object specified
publish_schema	Publishes a development schema with a major version and a recommended minor version
put_schema_from_json	Allows a schema to be updated using JSON upload
remove_facet_from_object	Removes the specified facet from the specified object
tag_resource	An API operation for adding tags to a resource
untag_resource	An API operation for removing tags from a resource
update_facet	Does the following:
update_link_attributes	Updates a given typed link's attributes
update_object_attributes	Updates a given object's attributes
update_schema	Updates the schema name with a new name
update_typed_link_facet	Updates a TypedLinkFacet
upgrade_applied_schema	Upgrades a single directory in-place using the PublishedSchemaArn with schema updates
upgrade_published_schema	Upgrades a published schema under a new minor version revision using the current content

Examples

```
## Not run:
svc <- clouddirectory()
svc$add_facet_to_object(
  Foo = 123
)

## End(Not run)
```

cloudhsm

*Amazon CloudHSM***Description**

AWS CloudHSM Service

This is documentation for **AWS CloudHSM Classic**. For more information, see [AWS CloudHSM Classic FAQs](#), the [AWS CloudHSM Classic User Guide](#), and the [AWS CloudHSM Classic API Reference](#).

For information about the current version of AWS CloudHSM, see [AWS CloudHSM](#), the [AWS CloudHSM User Guide](#), and the [AWS CloudHSM API Reference](#).

Usage

```
cloudhsm(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config

Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.
- **endpoint:** The complete URL to use for the constructed client.
- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. <http://s3.amazonaws.com/BUCKET/KEY>.
- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials

Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key

- **session_token**: AWS temporary session token
 - **profile**: The name of a profile to use. If not given, then the default profile is used.
 - **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- cloudhsm(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>add_tags_to_resource</code>	This is documentation for AWS CloudHSM Classic
<code>create_hapg</code>	This is documentation for AWS CloudHSM Classic
<code>create_hsm</code>	This is documentation for AWS CloudHSM Classic
<code>create_luna_client</code>	This is documentation for AWS CloudHSM Classic
<code>delete_hapg</code>	This is documentation for AWS CloudHSM Classic
<code>delete_hsm</code>	This is documentation for AWS CloudHSM Classic
<code>delete_luna_client</code>	This is documentation for AWS CloudHSM Classic
<code>describe_hapg</code>	This is documentation for AWS CloudHSM Classic
<code>describe_hsm</code>	This is documentation for AWS CloudHSM Classic
<code>describe_luna_client</code>	This is documentation for AWS CloudHSM Classic
<code>get_config</code>	This is documentation for AWS CloudHSM Classic
<code>list_available_zones</code>	This is documentation for AWS CloudHSM Classic
<code>list_hapgs</code>	This is documentation for AWS CloudHSM Classic
<code>list_hsms</code>	This is documentation for AWS CloudHSM Classic
<code>list_luna_clients</code>	This is documentation for AWS CloudHSM Classic
<code>list_tags_for_resource</code>	This is documentation for AWS CloudHSM Classic
<code>modify_hapg</code>	This is documentation for AWS CloudHSM Classic
<code>modify_hsm</code>	This is documentation for AWS CloudHSM Classic
<code>modify_luna_client</code>	This is documentation for AWS CloudHSM Classic
<code>remove_tags_from_resource</code>	This is documentation for AWS CloudHSM Classic

Examples

```
## Not run:
svc <- cloudhsm()
svc$add_tags_to_resource(
  Foo = 123
)

## End(Not run)
```

cloudhsmv2

AWS CloudHSM V2

Description

For more information about AWS CloudHSM, see [AWS CloudHSM](#) and the [AWS CloudHSM User Guide](#).

Usage

```
cloudhsmv2(
  config = list(),
  credentials = list(),
  endpoint = NULL,
```

```
    region = NULL
  )
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- cloudhsmv2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

copy_backup_to_region	Copy an AWS CloudHSM cluster backup to a different region
create_cluster	Creates a new AWS CloudHSM cluster
create_hsm	Creates a new hardware security module (HSM) in the specified AWS CloudHSM cluster
delete_backup	Deletes a specified AWS CloudHSM backup
delete_cluster	Deletes the specified AWS CloudHSM cluster
delete_hsm	Deletes the specified HSM
describe_backups	Gets information about backups of AWS CloudHSM clusters
describe_clusters	Gets information about AWS CloudHSM clusters
initialize_cluster	Claims an AWS CloudHSM cluster by submitting the cluster certificate issued by your issuing ce
list_tags	Gets a list of tags for the specified AWS CloudHSM cluster
modify_backup_attributes	Modifies attributes for AWS CloudHSM backup
modify_cluster	Modifies AWS CloudHSM cluster
restore_backup	Restores a specified AWS CloudHSM backup that is in the PENDING_DELETION state
tag_resource	Adds or overwrites one or more tags for the specified AWS CloudHSM cluster

`untag_resource` Removes the specified tag or tags from the specified AWS CloudHSM cluster

Examples

```
## Not run:
svc <- cloudhsmv2()
svc$copy_backup_to_region(
  Foo = 123
)

## End(Not run)
```

cognitoidentity	<i>Amazon Cognito Identity</i>
-----------------	--------------------------------

Description

Amazon Cognito Federated Identities

Amazon Cognito Federated Identities is a web service that delivers scoped temporary credentials to mobile devices and other untrusted environments. It uniquely identifies a device and supplies the user with a consistent identity over the lifetime of an application.

Using Amazon Cognito Federated Identities, you can enable authentication with one or more third-party identity providers (Facebook, Google, or Login with Amazon) or an Amazon Cognito user pool, and you can also choose to support unauthenticated access from your app. Cognito delivers a unique identifier for each user and acts as an OpenID token provider trusted by AWS Security Token Service (STS) to access temporary, limited-privilege AWS credentials.

For a description of the authentication flow from the Amazon Cognito Developer Guide see [Authentication Flow](#).

For more information see [Amazon Cognito Federated Identities](#).

Usage

```
cognitoidentity(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- cognitoidentity(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_identity_pool	Creates a new identity pool
delete_identities	Deletes identities from an identity pool
delete_identity_pool	Deletes an identity pool
describe_identity	Returns metadata related to the given identity, including when the identity was created
describe_identity_pool	Gets details about a particular identity pool, including the pool name, ID description, and roles
get_credentials_for_identity	Returns credentials for the provided identity ID
get_id	Generates (or retrieves) a Cognito ID
get_identity_pool_roles	Gets the roles for an identity pool
get_open_id_token	Gets an OpenID token, using a known Cognito ID
get_open_id_token_for_developer_identity	Registers (or retrieves) a Cognito IdentityId and an OpenID Connect token for a DeveloperUserIdentifier
get_principal_tag_attribute_map	Use GetPrincipalTagAttributeMap to list all mappings between PrincipalTags and IdentityIDs
list_identities	Lists the identities in an identity pool
list_identity_pools	Lists all of the Cognito identity pools registered for your account
list_tags_for_resource	Lists the tags that are assigned to an Amazon Cognito identity pool
lookup_developer_identity	Retrieves the IdentityID associated with a DeveloperUserIdentifier or the list of DeveloperUserIdentifiers associated with an IdentityID
merge_developer_identities	Merges two users having different IdentityIDs, existing in the same identity pool
set_identity_pool_roles	Sets the roles for an identity pool
set_principal_tag_attribute_map	You can use this operation to use default (username and clientID) attribute or custom attributes
tag_resource	Assigns a set of tags to the specified Amazon Cognito identity pool
unlink_developer_identity	Unlinks a DeveloperUserIdentifier from an existing identity

unlink_identity	Unlinks a federated identity from an existing account
untag_resource	Removes the specified tags from the specified Amazon Cognito identity pool
update_identity_pool	Updates an identity pool

Examples

```
## Not run:
svc <- cognitoidentity()
svc$create_identity_pool(
  Foo = 123
)

## End(Not run)
```

cognitoidentityprovider

Amazon Cognito Identity Provider

Description

With the Amazon Cognito user pools API, you can set up user pools and app clients, and authenticate users. To authenticate users from third-party identity providers (IdPs) in this API, you can [link IdP users to native user profiles](#). Learn more about the authentication and authorization of federated users in the [Using the Amazon Cognito user pools API and user pool endpoints](#).

This API reference provides detailed information about API operations and object types in Amazon Cognito. At the bottom of the page for each API operation and object, under *See Also*, you can learn how to use it in an Amazon Web Services SDK in the language of your choice.

Along with resource management operations, the Amazon Cognito user pools API includes classes of operations and authorization models for client-side and server-side user operations. For more information, see [Using the Amazon Cognito native and OIDC APIs](#) in the *Amazon Cognito Developer Guide*.

You can also start reading about the CognitoIdentityProvider client in the following SDK guides.

- [Amazon Web Services Command Line Interface](#)
- [Amazon Web Services SDK for .NET](#)
- [Amazon Web Services SDK for C++](#)
- [Amazon Web Services SDK for Go](#)
- [Amazon Web Services SDK for Java V2](#)
- [Amazon Web Services SDK for JavaScript](#)
- [Amazon Web Services SDK for PHP V3](#)

- [Amazon Web Services SDK for Python](#)
- [Amazon Web Services SDK for Ruby V3](#)

To get started with an Amazon Web Services SDK, see [Tools to Build on Amazon Web Services](#). For example actions and scenarios, see [Code examples for Amazon Cognito Identity Provider using Amazon Web Services SDKs](#).

Usage

```
cognitoidentityprovider(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- cognitoidentityprovider(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

add_custom_attributes	Adds additional user attributes to the user pool schema
admin_add_user_to_group	Adds the specified user to the specified group
admin_confirm_sign_up	Confirms user registration as an admin without using a confirmation code
admin_create_user	Creates a new user in the specified user pool
admin_delete_user	Deletes a user as an administrator
admin_delete_user_attributes	Deletes the user attributes in a user pool as an administrator
admin_disable_provider_for_user	Prevents the user from signing in with the specified external (SAML or social) identity
admin_disable_user	Deactivates a user and revokes all access tokens for the user

admin_enable_user	Enables the specified user as an administrator
admin_forget_device	Forgets the device, as an administrator
admin_get_device	Gets the device, as an administrator
admin_get_user	Gets the specified user by user name in a user pool as an administrator
admin_initiate_auth	Initiates the authentication flow, as an administrator
admin_link_provider_for_user	Links an existing user account in a user pool (DestinationUser) to an identity from an external provider
admin_list_devices	Lists devices, as an administrator
admin_list_groups_for_user	Lists the groups that the user belongs to
admin_list_user_auth_events	A history of user activity and any risks detected as part of Amazon Cognito advanced security
admin_remove_user_from_group	Removes the specified user from the specified group
admin_reset_user_password	Resets the specified user's password in a user pool as an administrator
admin_respond_to_auth_challenge	Responds to an authentication challenge, as an administrator
admin_set_user_mfa_preference	The user's multi-factor authentication (MFA) preference, including which MFA option is preferred
admin_set_user_password	Sets the specified user's password in a user pool as an administrator
admin_set_user_settings	This action is no longer supported
admin_update_auth_event_feedback	Provides feedback for an authentication event indicating if it was from a valid user
admin_update_device_status	Updates the device status as an administrator
admin_update_user_attributes	This action might generate an SMS text message
admin_user_global_sign_out	Signs out a user from all devices
associate_software_token	Begins setup of time-based one-time password (TOTP) multi-factor authentication (MFA)
change_password	Changes the password for a specified user in a user pool
confirm_device	Confirms tracking of the device
confirm_forgot_password	Allows a user to enter a confirmation code to reset a forgotten password
confirm_sign_up	Confirms registration of a new user
create_group	Creates a new group in the specified user pool
create_identity_provider	Creates an IdP for a user pool
create_resource_server	Creates a new OAuth2
create_user_import_job	Creates a user import job
create_user_pool	This action might generate an SMS text message
create_user_pool_client	Creates the user pool client
create_user_pool_domain	Creates a new domain for a user pool
delete_group	Deletes a group
delete_identity_provider	Deletes an IdP for a user pool
delete_resource_server	Deletes a resource server
delete_user	Allows a user to delete their own user profile
delete_user_attributes	Deletes the attributes for a user
delete_user_pool	Deletes the specified Amazon Cognito user pool
delete_user_pool_client	Allows the developer to delete the user pool client
delete_user_pool_domain	Deletes a domain for a user pool
describe_identity_provider	Gets information about a specific IdP
describe_resource_server	Describes a resource server
describe_risk_configuration	Describes the risk configuration
describe_user_import_job	Describes the user import job
describe_user_pool	Returns the configuration information and metadata of the specified user pool
describe_user_pool_client	Client method for returning the configuration information and metadata of the specified user pool
describe_user_pool_domain	Gets information about a domain
forget_device	Forgets the specified device
forgot_password	Calling this API causes a message to be sent to the end user with a confirmation code to reset their password

<code>get_csv_header</code>	Gets the header information for the comma-separated value (CSV) file to be used as input
<code>get_device</code>	Gets the device
<code>get_group</code>	Gets a group
<code>get_identity_provider_by_identifier</code>	Gets the specified IdP
<code>get_log_delivery_configuration</code>	Gets the detailed activity logging configuration for a user pool
<code>get_signing_certificate</code>	This method takes a user pool ID, and returns the signing certificate
<code>get_ui_customization</code>	Gets the user interface (UI) Customization information for a particular app client's app
<code>get_user</code>	Gets the user attributes and metadata for a user
<code>get_user_attribute_verification_code</code>	Generates a user attribute verification code for the specified attribute name
<code>get_user_pool_mfa_config</code>	Gets the user pool multi-factor authentication (MFA) configuration
<code>global_sign_out</code>	Signs out a user from all devices
<code>initiate_auth</code>	Initiates sign-in for a user in the Amazon Cognito user directory
<code>list_devices</code>	Lists the sign-in devices that Amazon Cognito has registered to the current user
<code>list_groups</code>	Lists the groups associated with a user pool
<code>list_identity_providers</code>	Lists information about all IdPs for a user pool
<code>list_resource_servers</code>	Lists the resource servers for a user pool
<code>list_tags_for_resource</code>	Lists the tags that are assigned to an Amazon Cognito user pool
<code>list_user_import_jobs</code>	Lists user import jobs for a user pool
<code>list_user_pool_clients</code>	Lists the clients that have been created for the specified user pool
<code>list_user_pools</code>	Lists the user pools associated with an Amazon Web Services account
<code>list_users</code>	Lists users and their basic details in a user pool
<code>list_users_in_group</code>	Lists the users in the specified group
<code>resend_confirmation_code</code>	Resends the confirmation (for confirmation of registration) to a specific user in the user pool
<code>respond_to_auth_challenge</code>	Responds to the authentication challenge
<code>revoke_token</code>	Revokes all of the access tokens generated by, and at the same time as, the specified refresh token
<code>set_log_delivery_configuration</code>	Sets up or modifies the detailed activity logging configuration of a user pool
<code>set_risk_configuration</code>	Configures actions on detected risks
<code>set_ui_customization</code>	Sets the user interface (UI) customization information for a user pool's built-in app UI
<code>set_user_mfa_preference</code>	Set the user's multi-factor authentication (MFA) method preference, including which MFA methods to use
<code>set_user_pool_mfa_config</code>	Sets the user pool multi-factor authentication (MFA) configuration
<code>set_user_settings</code>	This action is no longer supported
<code>sign_up</code>	Registers the user in the specified user pool and creates a user name, password, and user attributes
<code>start_user_import_job</code>	Starts the user import
<code>stop_user_import_job</code>	Stops the user import job
<code>tag_resource</code>	Assigns a set of tags to an Amazon Cognito user pool
<code>untag_resource</code>	Removes the specified tags from an Amazon Cognito user pool
<code>update_auth_event_feedback</code>	Provides the feedback for an authentication event, whether it was from a valid user or not
<code>update_device_status</code>	Updates the device status
<code>update_group</code>	Updates the specified group with the specified attributes
<code>update_identity_provider</code>	Updates IdP information for a user pool
<code>update_resource_server</code>	Updates the name and scopes of resource server
<code>update_user_attributes</code>	Allows a user to update a specific attribute (one at a time)
<code>update_user_pool</code>	This action might generate an SMS text message
<code>update_user_pool_client</code>	Updates the specified user pool app client with the specified attributes
<code>update_user_pool_domain</code>	Updates the Secure Sockets Layer (SSL) certificate for the custom domain for your user pool
<code>verify_software_token</code>	Use this API to register a user's entered time-based one-time password (TOTP) code and its associated secret
<code>verify_user_attribute</code>	Verifies the specified user attributes in the user pool

Examples

```
## Not run:
svc <- cognitoidentityprovider()
# This request submits a value for all possible parameters for
# AdminCreateUser.
svc$admin_create_user(
  DesiredDeliveryMediums = list(
    "SMS"
  ),
  MessageAction = "SUPPRESS",
  TemporaryPassword = "This-is-my-test-99!",
  UserAttributes = list(
    list(
      Name = "name",
      Value = "John"
    ),
    list(
      Name = "phone_number",
      Value = "+12065551212"
    ),
    list(
      Name = "email",
      Value = "testuser@example.com"
    )
  ),
  UserPoolId = "us-east-1_EXAMPLE",
  Username = "testuser"
)

## End(Not run)
```

Description

Amazon Cognito Sync provides an AWS service and client library that enable cross-device syncing of application-related user data. High-level client libraries are available for both iOS and Android. You can use these libraries to persist data locally so that it's available even if the device is offline. Developer credentials don't need to be stored on the mobile device to access the service. You can use Amazon Cognito to obtain a normalized user ID and credentials. User data is persisted in a dataset that can store up to 1 MB of key-value pairs, and you can have up to 20 datasets per user identity.

With Amazon Cognito Sync, the data stored for each identity is accessible only to credentials assigned to that identity. In order to use the Cognito Sync service, you need to make API calls using credentials retrieved with [Amazon Cognito Identity service](#).

If you want to use Cognito Sync in an Android or iOS application, you will probably want to make API calls via the AWS Mobile SDK. To learn more, see the [Developer Guide for Android](#) and the [Developer Guide for iOS](#).

Usage

```
cognitosync(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- cognitosync(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

bulk_publish	Initiates a bulk publish of all existing datasets for an Identity Pool to the configured stream
delete_dataset	Deletes the specific dataset
describe_dataset	Gets meta data about a dataset by identity and dataset name
describe_identity_pool_usage	Gets usage details (for example, data storage) about a particular identity pool
describe_identity_usage	Gets usage information for an identity, including number of datasets and data usage
get_bulk_publish_details	Get the status of the last BulkPublish operation for an identity pool
get_cognito_events	Gets the events and the corresponding Lambda functions associated with an identity pool
get_identity_pool_configuration	Gets the configuration settings of an identity pool

list_datasets	Lists datasets for an identity
list_identity_pool_usage	Gets a list of identity pools registered with Cognito
list_records	Gets paginated records, optionally changed after a particular sync count for a dataset and id
register_device	Registers a device to receive push sync notifications
set_cognito_events	Sets the AWS Lambda function for a given event type for an identity pool
set_identity_pool_configuration	Sets the necessary configuration for push sync
subscribe_to_dataset	Subscribes to receive notifications when a dataset is modified by another device
unsubscribe_from_dataset	Unsubscribes from receiving notifications when a dataset is modified by another device
update_records	Posts updates to records and adds and deletes records for a dataset and user

Examples

```
## Not run:
svc <- cognitosync()
svc$bulk_publish(
  Foo = 123
)

## End(Not run)
```

detective

Amazon Detective

Description

Detective uses machine learning and purpose-built visualizations to help you to analyze and investigate security issues across your Amazon Web Services (Amazon Web Services) workloads. Detective automatically extracts time-based events such as login attempts, API calls, and network traffic from CloudTrail and Amazon Virtual Private Cloud (Amazon VPC) flow logs. It also extracts findings detected by Amazon GuardDuty.

The Detective API primarily supports the creation and management of behavior graphs. A behavior graph contains the extracted data from a set of member accounts, and is created and managed by an administrator account.

To add a member account to the behavior graph, the administrator account sends an invitation to the account. When the account accepts the invitation, it becomes a member account in the behavior graph.

Detective is also integrated with Organizations. The organization management account designates the Detective administrator account for the organization. That account becomes the administrator account for the organization behavior graph. The Detective administrator account is also the delegated administrator account for Detective in Organizations.

The Detective administrator account can enable any organization account as a member account in the organization behavior graph. The organization accounts do not receive invitations. The Detective administrator account can also invite other accounts to the organization behavior graph.

Every behavior graph is specific to a Region. You can only use the API to manage behavior graphs that belong to the Region that is associated with the currently selected endpoint.

The administrator account for a behavior graph can use the Detective API to do the following:

- Enable and disable Detective. Enabling Detective creates a new behavior graph.
- View the list of member accounts in a behavior graph.
- Add member accounts to a behavior graph.
- Remove member accounts from a behavior graph.
- Apply tags to a behavior graph.

The organization management account can use the Detective API to select the delegated administrator for Detective.

The Detective administrator account for an organization can use the Detective API to do the following:

- Perform all of the functions of an administrator account.
- Determine whether to automatically enable new organization accounts as member accounts in the organization behavior graph.

An invited member account can use the Detective API to do the following:

- View the list of behavior graphs that they are invited to.
- Accept an invitation to contribute to a behavior graph.
- Decline an invitation to contribute to a behavior graph.
- Remove their account from a behavior graph.

All API actions are logged as CloudTrail events. See [Logging Detective API Calls with CloudTrail](#).

We replaced the term "master account" with the term "administrator account." An administrator account is used to centrally manage multiple accounts. In the case of Detective, the administrator account manages the accounts in their behavior graph.

Usage

```
detective(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key

	<ul style="list-style-type: none"> * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- detective(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
```

```

        close_connection = "logical",
        timeout = "numeric",
        s3_force_path_style = "logical",
        sts_regional_endpoint = "string"
    ),
    credentials = list(
        creds = list(
            access_key_id = "string",
            secret_access_key = "string",
            session_token = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

accept_invitation	Accepts an invitation for the member account to contribute data to a behavior graph
batch_get_graph_member_datasources	Gets data source package information for the behavior graph
batch_get_membership_datasources	Gets information on the data source package history for an account
create_graph	Creates a new behavior graph for the calling account, and sets that account as the administrator account. CreateMembers is used to send invitations to accounts
create_members	CreateMembers is used to send invitations to accounts
delete_graph	Disables the specified behavior graph and queues it to be deleted
delete_members	Removes the specified member accounts from the behavior graph
describe_organization_configuration	Returns information about the configuration for the organization behavior graph
disable_organization_admin_account	Removes the Detective administrator account in the current Region
disassociate_membership	Removes the member account from the specified behavior graph
enable_organization_admin_account	Designates the Detective administrator account for the organization in the current Region
get_members	Returns the membership details for specified member accounts for a behavior graph
list_datasource_packages	Lists data source packages in the behavior graph
list_graphs	Returns the list of behavior graphs that the calling account is an administrator account for
list_invitations	Retrieves the list of open and accepted behavior graph invitations for the member account
list_members	Retrieves the list of member accounts for a behavior graph
list_organization_admin_accounts	Returns information about the Detective administrator account for an organization
list_tags_for_resource	Returns the tag values that are assigned to a behavior graph
reject_invitation	Rejects an invitation to contribute the account data to a behavior graph
start_monitoring_member	Sends a request to enable data ingest for a member account that has a status of ACCREDITED
tag_resource	Applies tag values to a behavior graph
untag_resource	Removes tags from a behavior graph
update_datasource_packages	Starts a data source packages for the behavior graph
update_organization_configuration	Updates the configuration for the Organizations integration in the current Region

Examples

```
## Not run:
svc <- detective()
svc$accept_invitation(
  Foo = 123
)

## End(Not run)
```

directoryservice

AWS Directory Service

Description

Directory Service

Directory Service is a web service that makes it easy for you to setup and run directories in the Amazon Web Services cloud, or connect your Amazon Web Services resources with an existing self-managed Microsoft Active Directory. This guide provides detailed information about Directory Service operations, data types, parameters, and errors. For information about Directory Services features, see [Directory Service](#) and the [Directory Service Administration Guide](#).

Amazon Web Services provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, etc.). The SDKs provide a convenient way to create programmatic access to Directory Service and other Amazon Web Services services. For more information about the Amazon Web Services SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Usage

```
directoryservice(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- config Optional configuration of credentials, endpoint, and/or region.
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.

	<ul style="list-style-type: none"> – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client.
	<ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- directoryservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
```

```

    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

accept_shared_directory	Accepts a directory sharing request that was sent from the directory owner account
add_ip_routes	If the DNS server for your self-managed domain uses a publicly addressable IP address
add_region	Adds two domain controllers in the specified Region for the specified directory
add_tags_to_resource	Adds or overwrites one or more tags for the specified directory
cancel_schema_extension	Cancels an in-progress schema extension to a Microsoft AD directory
connect_directory	Creates an AD Connector to connect to a self-managed directory
create_alias	Creates an alias for a directory and assigns the alias to the directory
create_computer	Creates an Active Directory computer object in the specified directory
create_conditional_forwarder	Creates a conditional forwarder associated with your Amazon Web Services directory
create_directory	Creates a Simple AD directory
create_log_subscription	Creates a subscription to forward real-time Directory Service domain controller security logs
create_microsoft_ad	Creates a Microsoft AD directory in the Amazon Web Services Cloud
create_snapshot	Creates a snapshot of a Simple AD or Microsoft AD directory in the Amazon Web Services Cloud
create_trust	Directory Service for Microsoft Active Directory allows you to configure trust relationships between your Managed Microsoft AD directory and other Active Directory forests
delete_conditional_forwarder	Deletes a conditional forwarder that has been set up for your Amazon Web Services directory
delete_directory	Deletes an Directory Service directory
delete_log_subscription	Deletes the specified log subscription
delete_snapshot	Deletes a directory snapshot
delete_trust	Deletes an existing trust relationship between your Managed Microsoft AD directory and other Active Directory forests
deregister_certificate	Deletes from the system the certificate that was registered for secure LDAP or client authentication
deregister_event_topic	Removes the specified directory as a publisher to the specified Amazon SNS topic
describe_certificate	Displays information about the certificate registered for secure LDAP or client authentication
describe_client_authentication_settings	Retrieves information about the type of client authentication for the specified directory
describe_conditional_forwarders	Obtains information about the conditional forwarders for this account
describe_directories	Obtains information about the directories that belong to this account
describe_domain_controllers	Provides information about any domain controllers in your directory
describe_event_topics	Obtains information about which Amazon SNS topics receive status messages from your directory
describe_ldaps_settings	Describes the status of LDAP security for the specified directory
describe_regions	Provides information about the Regions that are configured for multi-Region replication
describe_settings	Retrieves information about the configurable settings for the specified directory
describe_shared_directories	Returns the shared directories in your account

<code>describe_snapshots</code>	Obtains information about the directory snapshots that belong to this account
<code>describe_trusts</code>	Obtains information about the trust relationships for this account
<code>describe_update_directory</code>	Describes the updates of a directory for a particular update type
<code>disable_client_authentication</code>	Disables alternative client authentication methods for the specified directory
<code>disable_ldaps</code>	Deactivates LDAP secure calls for the specified directory
<code>disable_radius</code>	Disables multi-factor authentication (MFA) with the Remote Authentication Dial In
<code>disable_sso</code>	Disables single-sign on for a directory
<code>enable_client_authentication</code>	Enables alternative client authentication methods for the specified directory
<code>enable_ldaps</code>	Activates the switch for the specific directory to always use LDAP secure calls
<code>enable_radius</code>	Enables multi-factor authentication (MFA) with the Remote Authentication Dial In
<code>enable_sso</code>	Enables single sign-on for a directory
<code>get_directory_limits</code>	Obtains directory limit information for the current Region
<code>get_snapshot_limits</code>	Obtains the manual snapshot limits for a directory
<code>list_certificates</code>	For the specified directory, lists all the certificates registered for a secure LDAP or c
<code>list_ip_routes</code>	Lists the address blocks that you have added to a directory
<code>list_log_subscriptions</code>	Lists the active log subscriptions for the Amazon Web Services account
<code>list_schema_extensions</code>	Lists all schema extensions applied to a Microsoft AD Directory
<code>list_tags_for_resource</code>	Lists all tags on a directory
<code>register_certificate</code>	Registers a certificate for a secure LDAP or client certificate authentication
<code>register_event_topic</code>	Associates a directory with an Amazon SNS topic
<code>reject_shared_directory</code>	Rejects a directory sharing request that was sent from the directory owner account
<code>remove_ip_routes</code>	Removes IP address blocks from a directory
<code>remove_region</code>	Stops all replication and removes the domain controllers from the specified Region
<code>remove_tags_from_resource</code>	Removes tags from a directory
<code>reset_user_password</code>	Resets the password for any user in your Managed Microsoft AD or Simple AD dire
<code>restore_from_snapshot</code>	Restores a directory using an existing directory snapshot
<code>share_directory</code>	Shares a specified directory (DirectoryId) in your Amazon Web Services account (d
<code>start_schema_extension</code>	Applies a schema extension to a Microsoft AD directory
<code>unshare_directory</code>	Stops the directory sharing between the directory owner and consumer accounts
<code>update_conditional_forwarder</code>	Updates a conditional forwarder that has been set up for your Amazon Web Service
<code>update_directory_setup</code>	Updates the directory for a particular update type
<code>update_number_of_domain_controllers</code>	Adds or removes domain controllers to or from the directory
<code>update_radius</code>	Updates the Remote Authentication Dial In User Service (RADIUS) server informa
<code>update_settings</code>	Updates the configurable settings for the specified directory
<code>update_trust</code>	Updates the trust that has been set up between your Managed Microsoft AD directo
<code>verify_trust</code>	Directory Service for Microsoft Active Directory allows you to configure and verify

Examples

```
## Not run:
svc <- directoryservice()
svc$accept_shared_directory(
  Foo = 123
)

## End(Not run)
```

fms

*Firewall Management Service***Description**

This is the *Firewall Manager API Reference*. This guide is for developers who need detailed information about the Firewall Manager API actions, data types, and errors. For detailed information about Firewall Manager features, see the [Firewall Manager Developer Guide](#).

Some API actions require explicit resource permissions. For information, see the developer guide topic [Service roles for Firewall Manager](#).

Usage

```
fms(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.
- **endpoint:** The complete URL to use for the constructed client.
- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the `config` parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- fms(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[associate_admin_account](#)
[associate_third_party_firewall](#)
[batch_associate_resource](#)

Sets a Firewall Manager default administrator account
 Sets the Firewall Manager policy administrator as a tenant administrator of a thi
 Associate resources to a Firewall Manager resource set

batch_disassociate_resource	Disassociates resources from a Firewall Manager resource set
delete_apps_list	Permanently deletes an Firewall Manager applications list
delete_notification_channel	Deletes an Firewall Manager association with the IAM role and the Amazon Simple Notification Service (SNS) topic
delete_policy	Permanently deletes an Firewall Manager policy
delete_protocols_list	Permanently deletes an Firewall Manager protocols list
delete_resource_set	Deletes the specified ResourceSet
disassociate_admin_account	Disassociates an Firewall Manager administrator account
disassociate_third_party_firewall	Disassociates a Firewall Manager policy administrator from a third-party firewall
get_admin_account	Returns the Organizations account that is associated with Firewall Manager as the administrator
get_admin_scope	Returns information about the specified account's administrative scope
get_apps_list	Returns information about the specified Firewall Manager applications list
get_compliance_detail	Returns detailed compliance information about the specified member account
get_notification_channel	Information about the Amazon Simple Notification Service (SNS) topic that is used for notifications
get_policy	Returns information about the specified Firewall Manager policy
get_protection_status	If you created a Shield Advanced policy, returns policy-level attack summary information
get_protocols_list	Returns information about the specified Firewall Manager protocols list
get_resource_set	Gets information about a specific resource set
get_third_party_firewall_association_status	The onboarding status of a Firewall Manager admin account to third-party firewall
get_violation_details	Retrieves violations for a resource based on the specified Firewall Manager policy
list_admin_accounts_for_organization	Returns a AdminAccounts object that lists the Firewall Manager administrators
list_admins_managing_account	Lists the accounts that are managing the specified Organizations member account
list_apps_lists	Returns an array of AppsListDataSummary objects
list_compliance_status	Returns an array of PolicyComplianceStatus objects
list_discovered_resources	Returns an array of resources in the organization's accounts that are available to Firewall Manager
list_member_accounts	Returns a MemberAccounts object that lists the member accounts in the administrative account
list_policies	Returns an array of PolicySummary objects
list_protocols_lists	Returns an array of ProtocolsListDataSummary objects
list_resource_set_resources	Returns an array of resources that are currently associated to a resource set
list_resource_sets	Returns an array of ResourceSetSummary objects
list_tags_for_resource	Retrieves the list of tags for the specified Amazon Web Services resource
list_third_party_firewall_firewall_policies	Retrieves a list of all of the third-party firewall policies that are associated with the specified Firewall Manager policy
put_admin_account	Creates or updates an Firewall Manager administrator account
put_apps_list	Creates an Firewall Manager applications list
put_notification_channel	Designates the IAM role and Amazon Simple Notification Service (SNS) topic for notifications
put_policy	Creates an Firewall Manager policy
put_protocols_list	Creates an Firewall Manager protocols list
put_resource_set	Creates the resource set
tag_resource	Adds one or more tags to an Amazon Web Services resource
untag_resource	Removes one or more tags from an Amazon Web Services resource

Examples

```
## Not run:
svc <- fms()
svc$associate_admin_account(
  Foo = 123
)
```

```
## End(Not run)
```

guardduty

Amazon GuardDuty

Description

Amazon GuardDuty is a continuous security monitoring service that analyzes and processes the following data sources: VPC flow logs, Amazon Web Services CloudTrail management event logs, CloudTrail S3 data event logs, EKS audit logs, DNS logs, and Amazon EBS volume data. It uses threat intelligence feeds, such as lists of malicious IPs and domains, and machine learning to identify unexpected, potentially unauthorized, and malicious activity within your Amazon Web Services environment. This can include issues like escalations of privileges, uses of exposed credentials, or communication with malicious IPs, domains, or presence of malware on your Amazon EC2 instances and container workloads. For example, GuardDuty can detect compromised EC2 instances and container workloads serving malware, or mining bitcoin.

GuardDuty also monitors Amazon Web Services account access behavior for signs of compromise, such as unauthorized infrastructure deployments like EC2 instances deployed in a Region that has never been used, or unusual API calls like a password policy change to reduce password strength.

GuardDuty informs you about the status of your Amazon Web Services environment by producing security findings that you can view in the GuardDuty console or through Amazon EventBridge. For more information, see the [AmazonGuardDuty User Guide](#).

Usage

```
guardduty(  
  config = list(),  
  credentials = list(),  
  endpoint = NULL,  
  region = NULL  
)
```

Arguments

- `config` Optional configuration of credentials, endpoint, and/or region.
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.

- **endpoint**: The complete URL to use for the constructed client.
- **region**: The AWS Region used in instantiating the client.
- **close_connection**: Immediately close all HTTP connections.
- **timeout**: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style**: Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint**: Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials Optional credentials shorthand for the config parameter

- **creds**:
 - **access_key_id**: AWS access key ID
 - **secret_access_key**: AWS secret access key
 - **session_token**: AWS temporary session token
- **profile**: The name of a profile to use. If not given, then the default profile is used.
- **anonymous**: Set anonymous credentials.

endpoint Optional shorthand for complete URL to use for the constructed client.

region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- guardduty(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
```

```

    ),
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
  )
)

```

Operations

accept_administrator_invitation	Accepts the invitation to be a member account and get monitored by a GuardDuty administrator account
accept_invitation	Accepts the invitation to be monitored by a GuardDuty administrator account
archive_findings	Archives GuardDuty findings that are specified by the list of finding IDs
create_detector	Creates a single Amazon GuardDuty detector
create_filter	Creates a filter using the specified finding criteria
create_ip_set	Creates a new IPSet, which is called a trusted IP list in the console user interface
create_members	Creates member accounts of the current Amazon Web Services account by specifying the list of member account IDs
create_publishing_destination	Creates a publishing destination to export findings to
create_sample_findings	Generates sample findings of types specified by the list of finding types
create_threat_intel_set	Creates a new ThreatIntelSet
decline_invitations	Declines invitations sent to the current member account by Amazon Web Services
delete_detector	Deletes an Amazon GuardDuty detector that is specified by the detector ID
delete_filter	Deletes the filter specified by the filter name
delete_invitations	Deletes invitations sent to the current member account by Amazon Web Services
delete_ip_set	Deletes the IPSet specified by the ipSetId
delete_members	Deletes GuardDuty member accounts (to the current GuardDuty administrator account)
delete_publishing_destination	Deletes the publishing definition with the specified destinationId
delete_threat_intel_set	Deletes the ThreatIntelSet specified by the ThreatIntelSet ID
describe_malware_scans	Returns a list of malware scans
describe_organization_configuration	Returns information about the account selected as the delegated administrator for the organization
describe_publishing_destination	Returns information about the publishing destination specified by the provided destinationId
disable_organization_admin_account	Disables an Amazon Web Services account within the Organization as the GuardDuty administrator account
disassociate_from_administrator_account	Disassociates the current GuardDuty member account from its administrator account
disassociate_from_master_account	Disassociates the current GuardDuty member account from its administrator account
disassociate_members	Disassociates GuardDuty member accounts (from the current administrator account)
enable_organization_admin_account	Enables an Amazon Web Services account within the organization as the GuardDuty administrator account
get_administrator_account	Provides the details for the GuardDuty administrator account associated with the organization
get_coverage_statistics	Retrieves aggregated statistics for your account
get_detector	Retrieves an Amazon GuardDuty detector specified by the detectorId
get_filter	Returns the details of the filter specified by the filter name
get_findings	Describes Amazon GuardDuty findings specified by finding IDs
get_findings_statistics	Lists Amazon GuardDuty findings statistics for the specified detector ID

get_invitations_count	Returns the count of all GuardDuty membership invitations that were sent to the c
get_ip_set	Retrieves the IPSet specified by the ipSetId
get_malware_scan_settings	Returns the details of the malware scan settings
get_master_account	Provides the details for the GuardDuty administrator account associated with the c
get_member_detectors	Describes which data sources are enabled for the member account's detector
get_members	Retrieves GuardDuty member accounts (of the current GuardDuty administrator a
get_remaining_free_trial_days	Provides the number of days left for each data source used in the free trial period
get_threat_intel_set	Retrieves the ThreatIntelSet that is specified by the ThreatIntelSet ID
get_usage_statistics	Lists Amazon GuardDuty usage statistics over the last 30 days for the specified d
invite_members	Invites Amazon Web Services accounts to become members of an organization ad
list_coverage	Lists coverage details for your GuardDuty account
list_detectors	Lists detectorIds of all the existing Amazon GuardDuty detector resources
list_filters	Returns a paginated list of the current filters
list_findings	Lists Amazon GuardDuty findings for the specified detector ID
list_invitations	Lists all GuardDuty membership invitations that were sent to the current Amazon
list_ip_sets	Lists the IPSets of the GuardDuty service specified by the detector ID
list_members	Lists details about all member accounts for the current GuardDuty administrator a
list_organization_admin_accounts	Lists the accounts configured as GuardDuty delegated administrators
list_publishing_destinations	Returns a list of publishing destinations associated with the specified detectorId
list_tags_for_resource	Lists tags for a resource
list_threat_intel_sets	Lists the ThreatIntelSets of the GuardDuty service specified by the detector ID
start_malware_scan	Initiates the malware scan
start_monitoring_members	Turns on GuardDuty monitoring of the specified member accounts
stop_monitoring_members	Stops GuardDuty monitoring for the specified member accounts
tag_resource	Adds tags to a resource
unarchive_findings	Unarchives GuardDuty findings specified by the findingIds
untag_resource	Removes tags from a resource
update_detector	Updates the Amazon GuardDuty detector specified by the detectorId
update_filter	Updates the filter specified by the filter name
update_findings_feedback	Marks the specified GuardDuty findings as useful or not useful
update_ip_set	Updates the IPSet specified by the IPSet ID
update_malware_scan_settings	Updates the malware scan settings
update_member_detectors	Contains information on member accounts to be updated
update_organization_configuration	Configures the delegated administrator account with the provided values
update_publishing_destination	Updates information about the publishing destination specified by the destination
update_threat_intel_set	Updates the ThreatIntelSet specified by the ThreatIntelSet ID

Examples

```
## Not run:
svc <- guardduty()
svc$accept_administrator_invitation(
  Foo = 123
)

## End(Not run)
```

iam

AWS Identity and Access Management

Description

Identity and Access Management

Identity and Access Management (IAM) is a web service for securely controlling access to Amazon Web Services services. With IAM, you can centrally manage users, security credentials such as access keys, and permissions that control which Amazon Web Services resources users and applications can access. For more information about IAM, see [Identity and Access Management \(IAM\)](#) and the [Identity and Access Management User Guide](#).

Usage

```
iam(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config

Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials

Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- iam(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[add_client_id_to_open_id_connect_provider](#)
[add_role_to_instance_profile](#)
[add_user_to_group](#)

Adds a new client ID (also known as audience) to the list of client IDs a
 Adds the specified IAM role to the specified instance profile
 Adds the specified user to the specified group

attach_group_policy	Attaches the specified managed policy to the specified IAM group
attach_role_policy	Attaches the specified managed policy to the specified IAM role
attach_user_policy	Attaches the specified managed policy to the specified user
change_password	Changes the password of the IAM user who is calling this operation
create_access_key	Creates a new Amazon Web Services secret access key and corresponding access key ID
create_account_alias	Creates an alias for your Amazon Web Services account
create_group	Creates a new group
create_instance_profile	Creates a new instance profile
create_login_profile	Creates a password for the specified IAM user
create_open_id_connect_provider	Creates an IAM entity to describe an identity provider (IdP) that supports OpenID Connect
create_policy	Creates a new managed policy for your Amazon Web Services account
create_policy_version	Creates a new version of the specified managed policy
create_role	Creates a new role for your Amazon Web Services account
create_saml_provider	Creates an IAM resource that describes an identity provider (IdP) that supports SAML
create_service_linked_role	Creates an IAM role that is linked to a specific Amazon Web Services service
create_service_specific_credential	Generates a set of credentials consisting of a user name and password that can be used to access a service
create_user	Creates a new IAM user for your Amazon Web Services account
create_virtual_mfa_device	Creates a new virtual MFA device for the Amazon Web Services account
deactivate_mfa_device	Deactivates the specified MFA device and removes it from association with the specified IAM user
delete_access_key	Deletes the access key pair associated with the specified IAM user
delete_account_alias	Deletes the specified Amazon Web Services account alias
delete_account_password_policy	Deletes the password policy for the Amazon Web Services account
delete_group	Deletes the specified IAM group
delete_group_policy	Deletes the specified inline policy that is embedded in the specified IAM group
delete_instance_profile	Deletes the specified instance profile
delete_login_profile	Deletes the password for the specified IAM user, For more information, see IAM User Passwords
delete_open_id_connect_provider	Deletes an OpenID Connect identity provider (IdP) resource object in IAM
delete_policy	Deletes the specified managed policy
delete_policy_version	Deletes the specified version from the specified managed policy
delete_role	Deletes the specified role
delete_role_permissions_boundary	Deletes the permissions boundary for the specified IAM role
delete_role_policy	Deletes the specified inline policy that is embedded in the specified IAM role
delete_saml_provider	Deletes a SAML provider resource in IAM
delete_server_certificate	Deletes the specified server certificate
delete_service_linked_role	Submits a service-linked role deletion request and returns a DeletionTask object
delete_service_specific_credential	Deletes the specified service-specific credential
delete_signing_certificate	Deletes a signing certificate associated with the specified IAM user
delete_ssh_public_key	Deletes the specified SSH public key
delete_user	Deletes the specified IAM user
delete_user_permissions_boundary	Deletes the permissions boundary for the specified IAM user
delete_user_policy	Deletes the specified inline policy that is embedded in the specified IAM user
delete_virtual_mfa_device	Deletes a virtual MFA device
detach_group_policy	Removes the specified managed policy from the specified IAM group
detach_role_policy	Removes the specified managed policy from the specified role
detach_user_policy	Removes the specified managed policy from the specified user
enable_mfa_device	Enables the specified MFA device and associates it with the specified IAM user
generate_credential_report	Generates a credential report for the Amazon Web Services account
generate_organizations_access_report	Generates a report for service last accessed data for Organizations

<code>generate_service_last_accessed_details</code>	Generates a report that includes details about when an IAM resource (user, group, or role) was last accessed.
<code>get_access_key_last_used</code>	Retrieves information about when the specified access key was last used.
<code>get_account_authorization_details</code>	Retrieves information about all IAM users, groups, roles, and policies in the account.
<code>get_account_password_policy</code>	Retrieves the password policy for the Amazon Web Services account.
<code>get_account_summary</code>	Retrieves information about IAM entity usage and IAM quotas in the Amazon Web Services account.
<code>get_context_keys_for_custom_policy</code>	Gets a list of all of the context keys referenced in the input policies.
<code>get_context_keys_for_principal_policy</code>	Gets a list of all of the context keys referenced in all the IAM policies that are attached to the specified principal.
<code>get_credential_report</code>	Retrieves a credential report for the Amazon Web Services account.
<code>get_group</code>	Returns a list of IAM users that are in the specified IAM group.
<code>get_group_policy</code>	Retrieves the specified inline policy document that is embedded in the specified IAM group.
<code>get_instance_profile</code>	Retrieves information about the specified instance profile, including the associated IAM role.
<code>get_login_profile</code>	Retrieves the user name for the specified IAM user.
<code>get_mfa_device</code>	Retrieves information about an MFA device for a specified user.
<code>get_open_id_connect_provider</code>	Returns information about the specified OpenID Connect (OIDC) provider.
<code>get_organizations_access_report</code>	Retrieves the service last accessed data report for Organizations that was generated for the specified account.
<code>get_policy</code>	Retrieves information about the specified managed policy, including the policy document.
<code>get_policy_version</code>	Retrieves information about the specified version of the specified managed policy.
<code>get_role</code>	Retrieves information about the specified role, including the role's path, permissions, and associated policies.
<code>get_role_policy</code>	Retrieves the specified inline policy document that is embedded with the specified IAM role.
<code>get_saml_provider</code>	Returns the SAML provider metadocument that was uploaded when the provider was created.
<code>get_server_certificate</code>	Retrieves information about the specified server certificate stored in IAM.
<code>get_service_last_accessed_details</code>	Retrieves a service last accessed report that was created using the GenerateServiceLastAccessedDetails API.
<code>get_service_last_accessed_details_with_entities</code>	After you generate a group or policy report using the GenerateServiceLastAccessedDetails API, this API returns the details of the entities that were accessed.
<code>get_service_linked_role_deletion_status</code>	Retrieves the status of your service-linked role deletion.
<code>get_ssh_public_key</code>	Retrieves the specified SSH public key, including metadata about the key.
<code>get_user</code>	Retrieves information about the specified IAM user, including the user's name, email address, and associated policies.
<code>get_user_policy</code>	Retrieves the specified inline policy document that is embedded in the specified IAM user.
<code>list_access_keys</code>	Returns information about the access key IDs associated with the specified IAM user.
<code>list_account_aliases</code>	Lists the account alias associated with the Amazon Web Services account.
<code>list_attached_group_policies</code>	Lists all managed policies that are attached to the specified IAM group.
<code>list_attached_role_policies</code>	Lists all managed policies that are attached to the specified IAM role.
<code>list_attached_user_policies</code>	Lists all managed policies that are attached to the specified IAM user.
<code>list_entities_for_policy</code>	Lists all IAM users, groups, and roles that the specified managed policy is attached to.
<code>list_group_policies</code>	Lists the names of the inline policies that are embedded in the specified IAM group.
<code>list_groups</code>	Lists the IAM groups that have the specified path prefix.
<code>list_groups_for_user</code>	Lists the IAM groups that the specified IAM user belongs to.
<code>list_instance_profiles</code>	Lists the instance profiles that have the specified path prefix.
<code>list_instance_profiles_for_role</code>	Lists the instance profiles that have the specified associated IAM role.
<code>list_instance_profile_tags</code>	Lists the tags that are attached to the specified IAM instance profile.
<code>list_mfa_devices</code>	Lists the MFA devices for an IAM user.
<code>list_mfa_device_tags</code>	Lists the tags that are attached to the specified IAM virtual multi-factor authentication device.
<code>list_open_id_connect_providers</code>	Lists information about the IAM OpenID Connect (OIDC) provider resources.
<code>list_open_id_connect_provider_tags</code>	Lists the tags that are attached to the specified OpenID Connect (OIDC) provider.
<code>list_policies</code>	Lists all the managed policies that are available in your Amazon Web Services account.
<code>list_policies_granting_service_access</code>	Retrieves a list of policies that the IAM identity (user, group, or role) can use to grant service access to other IAM identities.
<code>list_policy_tags</code>	Lists the tags that are attached to the specified IAM customer managed policy.
<code>list_policy_versions</code>	Lists information about the versions of the specified managed policy, including the policy document.
<code>list_role_policies</code>	Lists the names of the inline policies that are embedded in the specified IAM role.

<code>list_roles</code>	Lists the IAM roles that have the specified path prefix
<code>list_role_tags</code>	Lists the tags that are attached to the specified role
<code>list_saml_providers</code>	Lists the SAML provider resource objects defined in IAM in the account
<code>list_saml_provider_tags</code>	Lists the tags that are attached to the specified Security Assertion Markup Language (SAML) provider
<code>list_server_certificates</code>	Lists the server certificates stored in IAM that have the specified path prefix
<code>list_server_certificate_tags</code>	Lists the tags that are attached to the specified IAM server certificate
<code>list_service_specific_credentials</code>	Returns information about the service-specific credentials associated with the specified IAM user
<code>list_signing_certificates</code>	Returns information about the signing certificates associated with the specified IAM user
<code>list_ssh_public_keys</code>	Returns information about the SSH public keys associated with the specified IAM user
<code>list_user_policies</code>	Lists the names of the inline policies embedded in the specified IAM user
<code>list_users</code>	Lists the IAM users that have the specified path prefix
<code>list_user_tags</code>	Lists the tags that are attached to the specified IAM user
<code>list_virtual_mfa_devices</code>	Lists the virtual MFA devices defined in the Amazon Web Services account
<code>put_group_policy</code>	Adds or updates an inline policy document that is embedded in the specified IAM group
<code>put_role_permissions_boundary</code>	Adds or updates the policy that is specified as the IAM role's permissions boundary
<code>put_role_policy</code>	Adds or updates an inline policy document that is embedded in the specified IAM role
<code>put_user_permissions_boundary</code>	Adds or updates the policy that is specified as the IAM user's permissions boundary
<code>put_user_policy</code>	Adds or updates an inline policy document that is embedded in the specified IAM user
<code>remove_client_id_from_open_id_connect_provider</code>	Removes the specified client ID (also known as audience) from the list of client IDs for the specified OpenID Connect (OIDC)-compatible identity provider
<code>remove_role_from_instance_profile</code>	Removes the specified IAM role from the specified EC2 instance profile
<code>remove_user_from_group</code>	Removes the specified user from the specified group
<code>reset_service_specific_credential</code>	Resets the password for a service-specific credential
<code>resync_mfa_device</code>	Synchronizes the specified MFA device with its IAM resource object
<code>set_default_policy_version</code>	Sets the specified version of the specified policy as the policy's default version
<code>set_security_token_service_preferences</code>	Sets the specified version of the global endpoint token as the token version
<code>simulate_custom_policy</code>	Simulate how a set of IAM policies and optionally a resource-based policy works with a specified IAM entity
<code>simulate_principal_policy</code>	Simulate how a set of IAM policies attached to an IAM entity works with a specified resource
<code>tag_instance_profile</code>	Adds one or more tags to an IAM instance profile
<code>tag_mfa_device</code>	Adds one or more tags to an IAM virtual multi-factor authentication (MFA) device
<code>tag_open_id_connect_provider</code>	Adds one or more tags to an OpenID Connect (OIDC)-compatible identity provider
<code>tag_policy</code>	Adds one or more tags to an IAM customer managed policy
<code>tag_role</code>	Adds one or more tags to an IAM role
<code>tag_saml_provider</code>	Adds one or more tags to a Security Assertion Markup Language (SAML) provider
<code>tag_server_certificate</code>	Adds one or more tags to an IAM server certificate
<code>tag_user</code>	Adds one or more tags to an IAM user
<code>untag_instance_profile</code>	Removes the specified tags from the IAM instance profile
<code>untag_mfa_device</code>	Removes the specified tags from the IAM virtual multi-factor authentication (MFA) device
<code>untag_open_id_connect_provider</code>	Removes the specified tags from the specified OpenID Connect (OIDC)-compatible identity provider
<code>untag_policy</code>	Removes the specified tags from the customer managed policy
<code>untag_role</code>	Removes the specified tags from the role
<code>untag_saml_provider</code>	Removes the specified tags from the specified Security Assertion Markup Language (SAML) provider
<code>untag_server_certificate</code>	Removes the specified tags from the IAM server certificate
<code>untag_user</code>	Removes the specified tags from the user
<code>update_access_key</code>	Changes the status of the specified access key from Active to Inactive, or vice versa
<code>update_account_password_policy</code>	Updates the password policy settings for the Amazon Web Services account
<code>update_assume_role_policy</code>	Updates the policy that grants an IAM entity permission to assume a role
<code>update_group</code>	Updates the name and/or the path of the specified IAM group
<code>update_login_profile</code>	Changes the password for the specified IAM user

<code>update_open_id_connect_provider_thumbprint</code>	Replaces the existing list of server certificate thumbprints associated with a role
<code>update_role</code>	Updates the description or maximum session duration setting of a role Use <code>UpdateRole</code> instead
<code>update_role_description</code>	Use <code>UpdateRole</code> instead
<code>update_saml_provider</code>	Updates the metadata document for an existing SAML provider resource
<code>update_server_certificate</code>	Updates the name and/or the path of the specified server certificate store
<code>update_service_specific_credential</code>	Sets the status of a service-specific credential to Active or Inactive
<code>update_signing_certificate</code>	Changes the status of the specified user signing certificate from active to inactive
<code>update_ssh_public_key</code>	Sets the status of an IAM user's SSH public key to active or inactive
<code>update_user</code>	Updates the name and/or the path of the specified IAM user
<code>upload_server_certificate</code>	Uploads a server certificate entity for the Amazon Web Services account
<code>upload_signing_certificate</code>	Uploads an X
<code>upload_ssh_public_key</code>	Uploads an SSH public key and associates it with the specified IAM user

Examples

```
## Not run:
svc <- iam()
# The following add-client-id-to-open-id-connect-provider command adds the
# client ID my-application-ID to the OIDC provider named
# server.example.com:
svc$add_client_id_to_open_id_connect_provider(
  ClientID = "my-application-ID",
  OpenIDConnectProviderArn = "arn:aws:iam::123456789012:oidc-provider/server.example.com"
)

## End(Not run)
```

iamrolesanywhere

IAM Roles Anywhere

Description

Identity and Access Management Roles Anywhere provides a secure way for your workloads such as servers, containers, and applications that run outside of Amazon Web Services to obtain temporary Amazon Web Services credentials. Your workloads can use the same IAM policies and roles you have for native Amazon Web Services applications to access Amazon Web Services resources. Using IAM Roles Anywhere eliminates the need to manage long-term credentials for workloads running outside of Amazon Web Services.

To use IAM Roles Anywhere, your workloads must use X.509 certificates issued by their certificate authority (CA). You register the CA with IAM Roles Anywhere as a trust anchor to establish trust between your public key infrastructure (PKI) and IAM Roles Anywhere. If you don't manage your own PKI system, you can use Private Certificate Authority to create a CA and then use that to establish trust with IAM Roles Anywhere.

This guide describes the IAM Roles Anywhere operations that you can call programmatically. For more information about IAM Roles Anywhere, see the [IAM Roles Anywhere User Guide](#).

Usage

```
iamrolesanywhere(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- iamrolesanywhere(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

create_profile	Creates a profile, a list of the roles that Roles Anywhere service is trusted to assume
create_trust_anchor	Creates a trust anchor to establish trust between IAM Roles Anywhere and your certificate authority
delete_crl	Deletes a certificate revocation list (CRL)
delete_profile	Deletes a profile
delete_trust_anchor	Deletes a trust anchor
disable_crl	Disables a certificate revocation list (CRL)
disable_profile	Disables a profile
disable_trust_anchor	Disables a trust anchor
enable_crl	Enables a certificate revocation list (CRL)
enable_profile	Enables temporary credential requests for a profile
enable_trust_anchor	Enables a trust anchor
get_crl	Gets a certificate revocation list (CRL)
get_profile	Gets a profile
get_subject	Gets a subject, which associates a certificate identity with authentication attempts

get_trust_anchor	Gets a trust anchor
import_crl	Imports the certificate revocation list (CRL)
list_crls	Lists all certificate revocation lists (CRL) in the authenticated account and Amazon Web Services Region
list_profiles	Lists all profiles in the authenticated account and Amazon Web Services Region
list_subjects	Lists the subjects in the authenticated account and Amazon Web Services Region
list_tags_for_resource	Lists the tags attached to the resource
list_trust_anchors	Lists the trust anchors in the authenticated account and Amazon Web Services Region
put_notification_settings	Attaches a list of notification settings to a trust anchor
reset_notification_settings	Resets the custom notification setting to IAM Roles Anywhere default setting
tag_resource	Attaches tags to a resource
untag_resource	Removes tags from the resource
update_crl	Updates the certificate revocation list (CRL)
update_profile	Updates a profile, a list of the roles that IAM Roles Anywhere service is trusted to assume
update_trust_anchor	Updates a trust anchor

Examples

```
## Not run:
svc <- iamrolesanywhere()
svc$create_profile(
  Foo = 123
)

## End(Not run)
```

identitystore

AWS SSO Identity Store

Description

The Identity Store service used by AWS IAM Identity Center (successor to AWS Single Sign-On) provides a single place to retrieve all of your identities (users and groups). For more information, see the [IAM Identity Center User Guide](#).

<note> <p>Although AWS Single Sign-On was renamed, the `sso` and `identitystore`

Usage

```
identitystore(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- identitystore(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_group	Creates a group within the specified identity store
create_group_membership	Creates a relationship between a member and a group
create_user	Creates a user within the specified identity store
delete_group	Delete a group within an identity store given GroupId
delete_group_membership	Delete a membership within a group given MembershipId
delete_user	Deletes a user within an identity store given UserId
describe_group	Retrieves the group metadata and attributes from GroupId in an identity store
describe_group_membership	Retrieves membership metadata and attributes from MembershipId in an identity store
describe_user	Retrieves the user metadata and attributes from the UserId in an identity store
get_group_id	Retrieves GroupId in an identity store
get_group_membership_id	Retrieves the MembershipId in an identity store
get_user_id	Retrieves the UserId in an identity store
is_member_in_groups	Checks the user's membership in all requested groups and returns if the member exists
list_group_memberships	For the specified group in the specified identity store, returns the list of all GroupMemberships
list_group_memberships_for_member	For the specified member in the specified identity store, returns the list of all GroupMemberships
list_groups	Lists all groups in the identity store
list_users	Lists all users in the identity store
update_group	For the specified group in the specified identity store, updates the group metadata and attributes
update_user	For the specified user in the specified identity store, updates the user metadata and attributes

Examples

```
## Not run:
svc <- identitystore()
svc$create_group(
  Foo = 123
)

## End(Not run)
```

inspector

Amazon Inspector

Description

Amazon Inspector enables you to analyze the behavior of your AWS resources and to identify potential security issues. For more information, see [Amazon Inspector User Guide](#).

Usage

```
inspector(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.
 - **region:** The AWS Region used in instantiating the client.
- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style**: Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint**: Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service’s operations using syntax like `svc$operation(...)`, where `svc` is the name you’ve assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- inspector(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    )
  )
)

```

```

    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

add_attributes_to_findings	Assigns attributes (key and value pairs) to the findings that are specified by the ARNs of the findings
create_assessment_target	Creates a new assessment target using the ARN of the resource group that is generated by the assessment template
create_assessment_template	Creates an assessment template for the assessment target that is specified by the ARN of the assessment target
create_exclusions_preview	Starts the generation of an exclusions preview for the specified assessment template
create_resource_group	Creates a resource group using the specified set of tags (key and value pairs) that are used to identify the resource group
delete_assessment_run	Deletes the assessment run that is specified by the ARN of the assessment run
delete_assessment_target	Deletes the assessment target that is specified by the ARN of the assessment target
delete_assessment_template	Deletes the assessment template that is specified by the ARN of the assessment template
describe_assessment_runs	Describes the assessment runs that are specified by the ARNs of the assessment runs
describe_assessment_targets	Describes the assessment targets that are specified by the ARNs of the assessment targets
describe_assessment_templates	Describes the assessment templates that are specified by the ARNs of the assessment templates
describe_cross_account_access_role	Describes the IAM role that enables Amazon Inspector to access your AWS account
describe_exclusions	Describes the exclusions that are specified by the exclusions' ARNs
describe_findings	Describes the findings that are specified by the ARNs of the findings
describe_resource_groups	Describes the resource groups that are specified by the ARNs of the resource groups
describe_rules_packages	Describes the rules packages that are specified by the ARNs of the rules packages
get_assessment_report	Produces an assessment report that includes detailed and comprehensive results of a scan
get_exclusions_preview	Retrieves the exclusions preview (a list of ExclusionPreview objects) specified by the ARN of the assessment template
get_telemetry_metadata	Information about the data that is collected for the specified assessment run
list_assessment_run_agents	Lists the agents of the assessment runs that are specified by the ARNs of the assessment runs
list_assessment_runs	Lists the assessment runs that correspond to the assessment templates that are specified by the ARNs of the assessment templates
list_assessment_targets	Lists the ARNs of the assessment targets within this AWS account
list_assessment_templates	Lists the assessment templates that correspond to the assessment targets that are specified by the ARNs of the assessment targets
list_event_subscriptions	Lists all the event subscriptions for the assessment template that is specified by the ARN of the assessment template
list_exclusions	List exclusions that are generated by the assessment run
list_findings	Lists findings that are generated by the assessment runs that are specified by the ARNs of the assessment runs
list_rules_packages	Lists all available Amazon Inspector rules packages
list_tags_for_resource	Lists all tags associated with an assessment template
preview_agents	Previews the agents installed on the EC2 instances that are part of the specified assessment run
register_cross_account_access_role	Registers the IAM role that grants Amazon Inspector access to AWS Services needed to perform the assessment
remove_attributes_from_findings	Removes entire attributes (key and value pairs) from the findings that are specified by the ARNs of the findings
set_tags_for_resource	Sets tags (key and value pairs) to the assessment template that is specified by the ARN of the assessment template
start_assessment_run	Starts the assessment run specified by the ARN of the assessment template
stop_assessment_run	Stops the assessment run that is specified by the ARN of the assessment run
subscribe_to_event	Enables the process of sending Amazon Simple Notification Service (SNS) notifications for the specified assessment run
unsubscribe_from_event	Disables the process of sending Amazon Simple Notification Service (SNS) notifications for the specified assessment run
update_assessment_target	Updates the assessment target that is specified by the ARN of the assessment target

Examples

```
## Not run:
svc <- inspector()
# Assigns attributes (key and value pairs) to the findings that are
# specified by the ARNs of the findings.
svc$add_attributes_to_findings(
  attributes = list(
    list(
      key = "Example",
      value = "example"
    )
  ),
  findingArns = list(
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-..."
  )
)

## End(Not run)
```

inspector2

Inspector2

Description

Amazon Inspector is a vulnerability discovery service that automates continuous scanning for security vulnerabilities within your Amazon EC2 and Amazon ECR environments.

Usage

```
inspector2(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- config Optional configuration of credentials, endpoint, and/or region.
 - **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token

	<ul style="list-style-type: none"> – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. <ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- inspector2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
```

```

        timeout = "numeric",
        s3_force_path_style = "logical",
        sts_regional_endpoint = "string"
    ),
    credentials = list(
        creds = list(
            access_key_id = "string",
            secret_access_key = "string",
            session_token = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

associate_member	Associates an Amazon Web Services account with an Amazon Inspector
batch_get_account_status	Retrieves the Amazon Inspector status of multiple Amazon Web Servi
batch_get_code_snippet	Retrieves code snippets from findings that Amazon Inspector detected
batch_get_finding_details	Gets vulnerability details for findings
batch_get_free_trial_info	Gets free trial status for multiple Amazon Web Services accounts
batch_get_member_ec_2_deep_inspection_status	Retrieves Amazon Inspector deep inspection activation status of multi
batch_update_member_ec_2_deep_inspection_status	Activates or deactivates Amazon Inspector deep inspection for the pro
cancel_findings_report	Cancels the given findings report
cancel_sbom_export	Cancels a software bill of materials (SBOM) report
create_filter	Creates a filter resource using specified filter criteria
create_findings_report	Creates a finding report
create_sbom_export	Creates a software bill of materials (SBOM) report
delete_filter	Deletes a filter resource
describe_organization_configuration	Describe Amazon Inspector configuration settings for an Amazon Wel
disable	Disables Amazon Inspector scans for one or more Amazon Web Servi
disable_delegated_admin_account	Disables the Amazon Inspector delegated administrator for your organ
disassociate_member	Disassociates a member account from an Amazon Inspector delegated
enable	Enables Amazon Inspector scans for one or more Amazon Web Servi
enable_delegated_admin_account	Enables the Amazon Inspector delegated administrator for your Organ
get_configuration	Retrieves setting configurations for Inspector scans
get_delegated_admin_account	Retrieves information about the Amazon Inspector delegated administ
get_ec_2_deep_inspection_configuration	Retrieves the activation status of Amazon Inspector deep inspection an
get_encryption_key	Gets an encryption key
get_findings_report_status	Gets the status of a findings report
get_member	Gets member information for your organization
get_sbom_export	Gets details of a software bill of materials (SBOM) report
list_account_permissions	Lists the permissions an account has to configure Amazon Inspector
list_coverage	Lists coverage details for you environment
list_coverage_statistics	Lists Amazon Inspector coverage statistics for your environment

<code>list_delegated_admin_accounts</code>	Lists information about the Amazon Inspector delegated administrators
<code>list_filters</code>	Lists the filters associated with your account
<code>list_finding_aggregations</code>	Lists aggregated finding data for your environment based on specific criteria
<code>list_findings</code>	Lists findings for your environment
<code>list_members</code>	List members associated with the Amazon Inspector delegated administrator
<code>list_tags_for_resource</code>	Lists all tags attached to a given resource
<code>list_usage_totals</code>	Lists the Amazon Inspector usage totals over the last 30 days
<code>reset_encryption_key</code>	Resets an encryption key
<code>search_vulnerabilities</code>	Lists Amazon Inspector coverage details for a specific vulnerability
<code>tag_resource</code>	Adds tags to a resource
<code>untag_resource</code>	Removes tags from a resource
<code>update_configuration</code>	Updates setting configurations for your Amazon Inspector account
<code>update_ec_2_deep_inspection_configuration</code>	Activates, deactivates Amazon Inspector deep inspection, or updates custom paths
<code>update_encryption_key</code>	Updates an encryption key
<code>update_filter</code>	Specifies the action that is to be applied to the findings that match the filter
<code>update_organization_configuration</code>	Updates the configurations for your Amazon Inspector organization
<code>update_org_ec_2_deep_inspection_configuration</code>	Updates the Amazon Inspector deep inspection custom paths for your organization

Examples

```
## Not run:
svc <- inspector2()
svc$associate_member(
  Foo = 123
)

## End(Not run)
```

kms

AWS Key Management Service

Description

Key Management Service

Key Management Service (KMS) is an encryption and key management web service. This guide describes the KMS operations that you can call programmatically. For general information about KMS, see the *Key Management Service Developer Guide*.

KMS has replaced the term *customer master key (CMK)* with *KMS key* and *KMS key*. The concept has not changed. To prevent breaking changes, KMS is keeping some variations of this term.

Amazon Web Services provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, macOS, Android, etc.). The SDKs provide a convenient way to create programmatic access to KMS and other Amazon Web Services services. For example, the SDKs take care of tasks such as signing requests (see below), managing errors,

and retrying requests automatically. For more information about the Amazon Web Services SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

We recommend that you use the Amazon Web Services SDKs to make programmatic API calls to KMS.

If you need to use FIPS 140-2 validated cryptographic modules when communicating with Amazon Web Services, use the FIPS endpoint in your preferred Amazon Web Services Region. For more information about the available FIPS endpoints, see [Service endpoints](#) in the Key Management Service topic of the *Amazon Web Services General Reference*.

All KMS API calls must be signed and be transmitted using Transport Layer Security (TLS). KMS recommends you always use the latest supported TLS version. Clients must also support cipher suites with Perfect Forward Secrecy (PFS) such as Ephemeral Diffie-Hellman (DHE) or Elliptic Curve Ephemeral Diffie-Hellman (ECDHE). Most modern systems such as Java 7 and later support these modes.

Signing Requests

Requests must be signed using an access key ID and a secret access key. We strongly recommend that you do not use your Amazon Web Services account root access key ID and secret access key for everyday work. You can use the access key ID and secret access key for an IAM user or you can use the Security Token Service (STS) to generate temporary security credentials and use those to sign requests.

All KMS requests must be signed with [Signature Version 4](#).

Logging API Requests

KMS supports CloudTrail, a service that logs Amazon Web Services API calls and related events for your Amazon Web Services account and delivers them to an Amazon S3 bucket that you specify. By using the information collected by CloudTrail, you can determine what requests were made to KMS, who made the request, when it was made, and so on. To learn more about CloudTrail, including how to turn it on and find your log files, see the [CloudTrail User Guide](#).

Additional Resources

For more information about credentials and request signing, see the following:

- [Amazon Web Services Security Credentials](#) - This topic provides general information about the types of credentials used to access Amazon Web Services.
- [Temporary Security Credentials](#) - This section of the *IAM User Guide* describes how to create and use temporary security credentials.
- [Signature Version 4 Signing Process](#) - This set of topics walks you through the process of signing a request using an access key ID and a secret access key.

Commonly Used API Operations

Of the API operations discussed in this guide, the following will prove the most useful for most applications. You will likely perform operations other than these, such as creating keys and assigning policies, by using the console.

- [encrypt](#)
- [decrypt](#)
- [generate_data_key](#)
- [generate_data_key_without_plaintext](#)

Usage

```
kms(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

`endpoint` Optional shorthand for complete URL to use for the constructed client.

`region` Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- kms(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

cancel_key_deletion	Cancels the deletion of a KMS key
connect_custom_key_store	Connects or reconnects a custom key store to its backing key store
create_alias	Creates a friendly name for a KMS key
create_custom_key_store	Creates a custom key store backed by a key store that you own and manage
create_grant	Adds a grant to a KMS key
create_key	Creates a unique customer managed KMS key in your Amazon Web Services account
decrypt	Decrypts ciphertext that was encrypted by a KMS key using any of the following operations
delete_alias	Deletes the specified alias
delete_custom_key_store	Deletes a custom key store
delete_imported_key_material	Deletes key material that was previously imported
describe_custom_key_stores	Gets information about custom key stores in the account and Region
describe_key	Provides detailed information about a KMS key
disable_key	Sets the state of a KMS key to disabled
disable_key_rotation	Disables automatic rotation of the key material of the specified symmetric encryption key

<code>disconnect_custom_key_store</code>	Disconnects the custom key store from its backing key store
<code>enable_key</code>	Sets the key state of a KMS key to enabled
<code>enable_key_rotation</code>	Enables automatic rotation of the key material of the specified symmetric encryption key
<code>encrypt</code>	Encrypts plaintext of up to 4,096 bytes using a KMS key
<code>generate_data_key</code>	Returns a unique symmetric data key for use outside of KMS
<code>generate_data_key_pair</code>	Returns a unique asymmetric data key pair for use outside of KMS
<code>generate_data_key_pair_without_plaintext</code>	Returns a unique asymmetric data key pair for use outside of KMS
<code>generate_data_key_without_plaintext</code>	Returns a unique symmetric data key for use outside of KMS
<code>generate_mac</code>	Generates a hash-based message authentication code (HMAC) for a message using a KMS key
<code>generate_random</code>	Returns a random byte string that is cryptographically secure
<code>get_key_policy</code>	Gets a key policy attached to the specified KMS key
<code>get_key_rotation_status</code>	Gets a Boolean value that indicates whether automatic rotation of the key material is enabled
<code>get_parameters_for_import</code>	Returns the public key and an import token you need to import or reimport key material
<code>get_public_key</code>	Returns the public key of an asymmetric KMS key
<code>import_key_material</code>	Imports or reimports key material into an existing KMS key that was created with the <code>GenerateDataKeyPairWithoutPlaintext</code> operation
<code>list_aliases</code>	Gets a list of aliases in the caller's Amazon Web Services account and region
<code>list_grants</code>	Gets a list of all grants for the specified KMS key
<code>list_key_policies</code>	Gets the names of the key policies that are attached to a KMS key
<code>list_keys</code>	Gets a list of all KMS keys in the caller's Amazon Web Services account and Region
<code>list_resource_tags</code>	Returns all tags on the specified KMS key
<code>list_retirable_grants</code>	Returns information about all grants in the Amazon Web Services account and Region that are eligible for retirement
<code>put_key_policy</code>	Attaches a key policy to the specified KMS key
<code>re_encrypt</code>	Decrypts ciphertext and then reencrypts it entirely within KMS
<code>replicate_key</code>	Replicates a multi-Region key into the specified Region
<code>retire_grant</code>	Deletes a grant
<code>revoke_grant</code>	Deletes the specified grant
<code>schedule_key_deletion</code>	Schedules the deletion of a KMS key
<code>sign</code>	Creates a digital signature for a message or message digest by using the private key of a KMS key
<code>tag_resource</code>	Adds or edits tags on a customer managed key
<code>untag_resource</code>	Deletes tags from a customer managed key
<code>update_alias</code>	Associates an existing KMS alias with a different KMS key
<code>update_custom_key_store</code>	Changes the properties of a custom key store
<code>update_key_description</code>	Updates the description of a KMS key
<code>update_primary_region</code>	Changes the primary key of a multi-Region key
<code>verify</code>	Verifies a digital signature that was generated by the Sign operation
<code>verify_mac</code>	Verifies the hash-based message authentication code (HMAC) for a specified message

Examples

```
## Not run:
svc <- kms()
# The following example cancels deletion of the specified KMS key.
svc$cancel_key_deletion(
  KeyId = "1234abcd-12ab-34cd-56ef-1234567890ab"
)

## End(Not run)
```

macie

*Amazon Macie***Description**

Amazon Macie Classic

Amazon Macie Classic has been discontinued and is no longer available.

A new Amazon Macie is now available with significant design improvements and additional features, at a lower price and in most Amazon Web Services Regions. We encourage you to take advantage of the new and improved features, and benefit from the reduced cost. To learn about features and pricing for the new Macie, see [Amazon Macie](#). To learn how to use the new Macie, see the [Amazon Macie User Guide](#).

Usage

```
macie(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config

Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.
- **endpoint:** The complete URL to use for the constructed client.
- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials

Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID

- **secret_access_key**: AWS secret access key
 - **session_token**: AWS temporary session token
 - **profile**: The name of a profile to use. If not given, then the default profile is used.
 - **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- macie(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

associate_member_account	(Discontinued) Associates a specified Amazon Web Services account with Amazon Macie Classic
associate_s3_resources	(Discontinued) Associates specified S3 resources with Amazon Macie Classic for monitoring
disassociate_member_account	(Discontinued) Removes the specified member account from Amazon Macie Classic
disassociate_s3_resources	(Discontinued) Removes specified S3 resources from being monitored by Amazon Macie Classic
list_member_accounts	(Discontinued) Lists all Amazon Macie Classic member accounts for the current Macie Classic
list_s3_resources	(Discontinued) Lists all the S3 resources associated with Amazon Macie Classic
update_s3_resources	(Discontinued) Updates the classification types for the specified S3 resources

Examples

```
## Not run:
svc <- macie2()
svc$associate_member_account(
  Foo = 123
)

## End(Not run)
```

macie2

Amazon Macie 2

Description

Amazon Macie

Usage

```
macie2(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.
 - **region:** The AWS Region used in instantiating the client.
- **close_connection:** Immediately close all HTTP connections.

	<ul style="list-style-type: none"> • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- macie2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

accept_invitation	Accepts an Amazon Macie membership invitation that was received from a spe
batch_get_custom_data_identifiers	Retrieves information about one or more custom data identifiers
create_allow_list	Creates and defines the settings for an allow list
create_classification_job	Creates and defines the settings for a classification job
create_custom_data_identifier	Creates and defines the criteria and other settings for a custom data identifier
create_findings_filter	Creates and defines the criteria and other settings for a findings filter
create_invitations	Sends an Amazon Macie membership invitation to one or more accounts
create_member	Associates an account with an Amazon Macie administrator account
create_sample_findings	Creates sample findings
decline_invitations	Declines Amazon Macie membership invitations that were received from specif
delete_allow_list	Deletes an allow list
delete_custom_data_identifier	Soft deletes a custom data identifier
delete_findings_filter	Deletes a findings filter
delete_invitations	Deletes Amazon Macie membership invitations that were received from specif
delete_member	Deletes the association between an Amazon Macie administrator account and a
describe_buckets	Retrieves (queries) statistical data and other information about one or more S3 b
describe_classification_job	Retrieves the status and settings for a classification job
describe_organization_configuration	Retrieves the Amazon Macie configuration settings for an organization in Organ
disable_macie	Disables Amazon Macie and deletes all settings and resources for a Macie acco
disable_organization_admin_account	Disables an account as the delegated Amazon Macie administrator account for a
disassociate_from_administrator_account	Disassociates a member account from its Amazon Macie administrator account
disassociate_from_master_account	(Deprecated) Disassociates a member account from its Amazon Macie adminis
disassociate_member	Disassociates an Amazon Macie administrator account from a member account
enable_macie	Enables Amazon Macie and specifies the configuration settings for a Macie acc
enable_organization_admin_account	Designates an account as the delegated Amazon Macie administrator account fo
get_administrator_account	Retrieves information about the Amazon Macie administrator account for an ac
get_allow_list	Retrieves the settings and status of an allow list
get_automated_discovery_configuration	Retrieves the configuration settings and status of automated sensitive data disco
get_bucket_statistics	Retrieves (queries) aggregated statistical data about all the S3 buckets that Ama
get_classification_export_configuration	Retrieves the configuration settings for storing data classification results
get_classification_scope	Retrieves the classification scope settings for an account
get_custom_data_identifier	Retrieves the criteria and other settings for a custom data identifier
get_findings	Retrieves the details of one or more findings
get_findings_filter	Retrieves the criteria and other settings for a findings filter
get_findings_publication_configuration	Retrieves the configuration settings for publishing findings to Security Hub
get_finding_statistics	Retrieves (queries) aggregated statistical data about findings

get_invitations_count	Retrieves the count of Amazon Macie membership invitations that were received
get_macie_session	Retrieves the status and configuration settings for an Amazon Macie account
get_master_account	(Deprecated) Retrieves information about the Amazon Macie administrator account
get_member	Retrieves information about an account that's associated with an Amazon Macie account
get_resource_profile	Retrieves (queries) sensitive data discovery statistics and the sensitivity score for an S3 bucket
get_reveal_configuration	Retrieves the status and configuration settings for retrieving occurrences of sensitive data
get_sensitive_data_occurrences	Retrieves occurrences of sensitive data reported by a finding
get_sensitive_data_occurrences_availability	Checks whether occurrences of sensitive data can be retrieved for a finding
get_sensitivity_inspection_template	Retrieves the settings for the sensitivity inspection template for an account
get_usage_statistics	Retrieves (queries) quotas and aggregated usage data for one or more accounts
get_usage_totals	Retrieves (queries) aggregated usage data for an account
list_allow_lists	Retrieves a subset of information about all the allow lists for an account
list_classification_jobs	Retrieves a subset of information about one or more classification jobs
list_classification_scopes	Retrieves a subset of information about the classification scope for an account
list_custom_data_identifiers	Retrieves a subset of information about all the custom data identifiers for an account
list_findings	Retrieves a subset of information about one or more findings
list_findings_filters	Retrieves a subset of information about all the findings filters for an account
list_invitations	Retrieves information about the Amazon Macie membership invitations that were received
list_managed_data_identifiers	Retrieves information about all the managed data identifiers that Amazon Macie has discovered
list_members	Retrieves information about the accounts that are associated with an Amazon Macie account
list_organization_admin_accounts	Retrieves information about the delegated Amazon Macie administrator accounts
list_resource_profile_artifacts	Retrieves information about objects that were selected from an S3 bucket for analysis
list_resource_profile_detections	Retrieves information about the types and amount of sensitive data that Amazon Macie discovered
list_sensitivity_inspection_templates	Retrieves a subset of information about the sensitivity inspection template for an account
list_tags_for_resource	Retrieves the tags (keys and values) that are associated with an Amazon Macie resource
put_classification_export_configuration	Creates or updates the configuration settings for storing data classification results in Amazon S3
put_findings_publication_configuration	Updates the configuration settings for publishing findings to Security Hub
search_resources	Retrieves (queries) statistical data and other information about Amazon Web Services resources
tag_resource	Adds or updates one or more tags (keys and values) that are associated with an Amazon Macie resource
test_custom_data_identifier	Tests a custom data identifier
untag_resource	Removes one or more tags (keys and values) from an Amazon Macie resource
update_allow_list	Updates the settings for an allow list
update_automated_discovery_configuration	Enables or disables automated sensitive data discovery for an account
update_classification_job	Changes the status of a classification job
update_classification_scope	Updates the classification scope settings for an account
update_findings_filter	Updates the criteria and other settings for a findings filter
update_macie_session	Suspends or re-enables Amazon Macie, or updates the configuration settings for an Amazon Macie account
update_member_session	Enables an Amazon Macie administrator to suspend or re-enable Macie for a member account
update_organization_configuration	Updates the Amazon Macie configuration settings for an organization in Organizations
update_resource_profile	Updates the sensitivity score for an S3 bucket
update_resource_profile_detections	Updates the sensitivity scoring settings for an S3 bucket
update_reveal_configuration	Updates the status and configuration settings for retrieving occurrences of sensitive data
update_sensitivity_inspection_template	Updates the settings for the sensitivity inspection template for an account

Examples

```
## Not run:
```

```

svc <- macie2()
svc$accept_invitation(
  Foo = 123
)

## End(Not run)

```

ram

AWS Resource Access Manager

Description

This is the *Resource Access Manager API Reference*. This documentation provides descriptions and syntax for each of the actions and data types in RAM. RAM is a service that helps you securely share your Amazon Web Services resources to other Amazon Web Services accounts. If you use Organizations to manage your accounts, then you can share your resources with your entire organization or to organizational units (OUs). For supported resource types, you can also share resources with individual Identity and Access Management (IAM) roles and users.

To learn more about RAM, see the following resources:

- [Resource Access Manager product page](#)
- [Resource Access Manager User Guide](#)

Usage

```
ram(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.
 - **region:** The AWS Region used in instantiating the client.
- **close_connection:** Immediately close all HTTP connections.
- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

	<ul style="list-style-type: none"> • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	<p>Optional credentials shorthand for the config parameter</p> <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- ram(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
```

```

        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

accept_resource_share_invitation	Accepts an invitation to a resource share from another Amazon Web Services
associate_resource_share	Adds the specified list of principals and list of resources to a resource share
associate_resource_share_permission	Adds or replaces the RAM permission for a resource type included in a resource share
create_permission	Creates a customer managed permission for a specified resource type that you own
create_permission_version	Creates a new version of the specified customer managed permission
create_resource_share	Creates a resource share
delete_permission	Deletes the specified customer managed permission in the Amazon Web Services console
delete_permission_version	Deletes one version of a customer managed permission
delete_resource_share	Deletes the specified resource share
disassociate_resource_share	Removes the specified principals or resources from participating in the specified resource share
disassociate_resource_share_permission	Removes a managed permission from a resource share
enable_sharing_with_aws_organization	Enables resource sharing within your organization in Organizations
get_permission	Retrieves the contents of a managed permission in JSON format
get_resource_policies	Retrieves the resource policies for the specified resources that you own and have shared with others
get_resource_share_associations	Retrieves the lists of resources and principals that associated for resource share
get_resource_share_invitations	Retrieves details about invitations that you have received for resource shares
get_resource_shares	Retrieves details about the resource shares that you own or that are shared with you
list_pending_invitation_resources	Lists the resources in a resource share that is shared with you but for which there are pending invitations
list_permission_associations	Lists information about the managed permission and its associations to any resource types
list_permissions	Retrieves a list of available RAM permissions that you can use for the specified resource type
list_permission_versions	Lists the available versions of the specified RAM permission
list_principals	Lists the principals that you are sharing resources with or that are sharing resources with you
list_replace_permission_associations_work_items	Retrieves the current status of the asynchronous tasks performed by RAM when you replace a managed permission
list_resources	Lists the resources that you added to a resource share or the resources that are shared with you
list_resource_share_permissions	Lists the RAM permissions that are associated with a resource share
list_resource_types	Lists the resource types that can be shared by RAM
promote_permission_created_from_policy	When you attach a resource-based policy to a resource, RAM automatically creates a managed permission
promote_resource_share_created_from_policy	When you attach a resource-based policy to a resource, RAM automatically creates a resource share
reject_resource_share_invitation	Rejects an invitation to a resource share from another Amazon Web Services account
replace_permission_associations	Updates all resource shares that use a managed permission to a different managed permission
set_default_permission_version	Designates the specified version number as the default version for the specified managed permission
tag_resource	Adds the specified tag keys and values to a resource share or managed permission
untag_resource	Removes the specified tag key and value pairs from the specified resource share or managed permission
update_resource_share	Modifies some of the properties of the specified resource share

Examples

```
## Not run:
```

```
svc <- ram()
svc$accept_resource_share_invitation(
  Foo = 123
)

## End(Not run)
```

secretsmanager	<i>AWS Secrets Manager</i>
----------------	----------------------------

Description

Amazon Web Services Secrets Manager

Amazon Web Services Secrets Manager provides a service to enable you to store, manage, and retrieve, secrets.

This guide provides descriptions of the Secrets Manager API. For more information about using this service, see the [Amazon Web Services Secrets Manager User Guide](#).

API Version

This version of the Secrets Manager API Reference documents the Secrets Manager API version 2017-10-17.

For a list of endpoints, see [Amazon Web Services Secrets Manager endpoints](#).

Support and Feedback for Amazon Web Services Secrets Manager

We welcome your feedback. Send your comments to awssecretsmanager-feedback@amazon.com, or post your feedback and questions in the Amazon Web Services Secrets Manager Discussion Forum. For more information about the Amazon Web Services Discussion Forums, see Forums Help.

Logging API Requests

Amazon Web Services Secrets Manager supports Amazon Web Services CloudTrail, a service that records Amazon Web Services API calls for your Amazon Web Services account and delivers log files to an Amazon S3 bucket. By using information that's collected by Amazon Web Services CloudTrail, you can determine the requests successfully made to Secrets Manager, who made the request, when it was made, and so on. For more about Amazon Web Services Secrets Manager and support for Amazon Web Services CloudTrail, see [Logging Amazon Web Services Secrets Manager Events with Amazon Web Services CloudTrail](#) in the *Amazon Web Services Secrets Manager User Guide*. To learn more about CloudTrail, including enabling it and find your log files, see the [Amazon Web Services CloudTrail User Guide](#).

Usage

```
secretsmanager(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- secretsmanager(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

cancel_rotate_secret	Turns off automatic rotation, and if a rotation is currently in progress, cancels the rotation
create_secret	Creates a new secret
delete_resource_policy	Deletes the resource-based permission policy attached to the secret
delete_secret	Deletes a secret and all of its versions
describe_secret	Retrieves the details of a secret
get_random_password	Generates a random password
get_resource_policy	Retrieves the JSON text of the resource-based policy document attached to the secret
get_secret_value	Retrieves the contents of the encrypted fields SecretString or SecretBinary from the secret
list_secrets	Lists the secrets that are stored by Secrets Manager in the Amazon Web Services account
list_secret_version_ids	Lists the versions of a secret
put_resource_policy	Attaches a resource-based permission policy to a secret
put_secret_value	Creates a new version with a new encrypted secret value and attaches it to the secret
remove_regions_from_replication	For a secret that is replicated to other Regions, deletes the secret replicas from the Region
replicate_secret_to_regions	Replicates the secret to a new Regions
restore_secret	Cancels the scheduled deletion of a secret by removing the DeletedDate time stamp
rotate_secret	Configures and starts the asynchronous process of rotating the secret
stop_replication_to_replica	Removes the link between the replica secret and the primary secret and promotes the replica
tag_resource	Attaches tags to a secret
untag_resource	Removes specific tags from a secret
update_secret	Modifies the details of a secret, including metadata and the secret value

[update_secret_version_stage](#)
[validate_resource_policy](#)

Modifies the staging labels attached to a version of a secret
 Validates that a resource policy does not grant a wide range of principals access to your s

Examples

```
## Not run:
svc <- secretsmanager()
# The following example shows how to cancel rotation for a secret. The
# operation sets the RotationEnabled field to false and cancels all
# scheduled rotations. To resume scheduled rotations, you must re-enable
# rotation by calling the rotate-secret operation.
svc$cancel_rotate_secret(
  SecretId = "MyTestDatabaseSecret"
)

## End(Not run)
```

securityhub

AWS SecurityHub

Description

Security Hub provides you with a comprehensive view of the security state of your Amazon Web Services environment and resources. It also provides you with the readiness status of your environment based on controls from supported security standards. Security Hub collects security data from Amazon Web Services accounts, services, and integrated third-party products and helps you analyze security trends in your environment to identify the highest priority security issues. For more information about Security Hub, see the *Security Hub User Guide*.

When you use operations in the Security Hub API, the requests are executed only in the Amazon Web Services Region that is currently active or in the specific Amazon Web Services Region that you specify in your request. Any configuration or settings change that results from the operation is applied only to that Region. To make the same change in other Regions, run the same command for each Region in which you want to apply the change.

For example, if your Region is set to us-west-2, when you use [create_members](#) to add a member account to Security Hub, the association of the member account with the administrator account is created only in the us-west-2 Region. Security Hub must be enabled for the member account in the same Region that the invitation was sent from.

The following throttling limits apply to using Security Hub API operations.

- [batch_enable_standards](#) - RateLimit of 1 request per second. BurstLimit of 1 request per second.
- [get_findings](#) - RateLimit of 3 requests per second. BurstLimit of 6 requests per second.
- [batch_import_findings](#) - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.

- [batch_update_findings](#) - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.
- [update_standards_control](#) - RateLimit of 1 request per second. BurstLimit of 5 requests per second.
- All other operations - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.

Usage

```
securityhub(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- securityhub(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[accept_administrator_invitation](#)
[accept_invitation](#)
[batch_delete_automation_rules](#)
[batch_disable_standards](#)

Accepts the invitation to be a member account and be monitored by the SecurityHub service.
 This method is deprecated
 Deletes one or more automation rules
 Disables the standards specified by the provided StandardsSubscriptionArns

<code>batch_enable_standards</code>	Enables the standards specified by the provided StandardsArn
<code>batch_get_automation_rules</code>	Retrieves a list of details for automation rules based on rule Amazon Resource Name
<code>batch_get_security_controls</code>	Provides details about a batch of security controls for the current Amazon Web Services account
<code>batch_get_standards_control_associations</code>	For a batch of security controls and standards, identifies whether each control is associated with a standard
<code>batch_import_findings</code>	Imports security findings generated by a finding provider into Security Hub
<code>batch_update_automation_rules</code>	Updates one or more automation rules based on rule Amazon Resource Name
<code>batch_update_findings</code>	Used by Security Hub customers to update information about their investigations
<code>batch_update_standards_control_associations</code>	For a batch of security controls and standards, this operation updates the enabled status of the association
<code>create_action_target</code>	Creates a custom action target in Security Hub
<code>create_automation_rule</code>	Creates an automation rule based on input parameters
<code>create_finding_aggregator</code>	Used to enable finding aggregation
<code>create_insight</code>	Creates a custom insight in Security Hub
<code>create_members</code>	Creates a member association in Security Hub between the specified accounts
<code>decline_invitations</code>	Declines invitations to become a member account
<code>delete_action_target</code>	Deletes a custom action target from Security Hub
<code>delete_finding_aggregator</code>	Deletes a finding aggregator
<code>delete_insight</code>	Deletes the insight specified by the InsightArn
<code>delete_invitations</code>	Deletes invitations received by the Amazon Web Services account to become a member account
<code>delete_members</code>	Deletes the specified member accounts from Security Hub
<code>describe_action_targets</code>	Returns a list of the custom action targets in Security Hub in your account
<code>describe_hub</code>	Returns details about the Hub resource in your account, including the HubArn
<code>describe_organization_configuration</code>	Returns information about the Organizations configuration for Security Hub
<code>describe_products</code>	Returns information about product integrations in Security Hub
<code>describe_standards</code>	Returns a list of the available standards in Security Hub
<code>describe_standards_controls</code>	Returns a list of security standards controls
<code>disable_import_findings_for_product</code>	Disables the integration of the specified product with Security Hub
<code>disable_organization_admin_account</code>	Disables a Security Hub administrator account
<code>disable_security_hub</code>	Disables Security Hub in your account only in the current Amazon Web Services Region
<code>disassociate_from_administrator_account</code>	Disassociates the current Security Hub member account from the associated administrator account
<code>disassociate_from_master_account</code>	This method is deprecated
<code>disassociate_members</code>	Disassociates the specified member accounts from the associated administrator account
<code>enable_import_findings_for_product</code>	Enables the integration of a partner product with Security Hub
<code>enable_organization_admin_account</code>	Designates the Security Hub administrator account for an organization
<code>enable_security_hub</code>	Enables Security Hub for your account in the current Region or the Region you specify
<code>get_administrator_account</code>	Provides the details for the Security Hub administrator account for the current Amazon Web Services Region
<code>get_enabled_standards</code>	Returns a list of the standards that are currently enabled
<code>get_finding_aggregator</code>	Returns the current finding aggregation configuration
<code>get_finding_history</code>	Returns history for a Security Hub finding in the last 90 days
<code>get_findings</code>	Returns a list of findings that match the specified criteria
<code>get_insight_results</code>	Lists the results of the Security Hub insight specified by the insight ARN
<code>get_insights</code>	Lists and describes insights for the specified insight ARNs
<code>get_invitations_count</code>	Returns the count of all Security Hub membership invitations that were sent to the specified account
<code>get_master_account</code>	This method is deprecated
<code>get_members</code>	Returns the details for the Security Hub member accounts for the specified account
<code>invite_members</code>	Invites other Amazon Web Services accounts to become member accounts for the specified account
<code>list_automation_rules</code>	A list of automation rules and their metadata for the calling account
<code>list_enabled_products_for_import</code>	Lists all findings-generating solutions (products) that you are subscribed to receive findings from
<code>list_finding_aggregators</code>	If finding aggregation is enabled, then ListFindingAggregators returns the ARNs of the enabled finding aggregators

list_invitations	Lists all Security Hub membership invitations that were sent to the current AdministratorAccount.
list_members	Lists details about all member accounts for the current Security Hub administrator account.
list_organization_admin_accounts	Lists the Security Hub administrator accounts.
list_security_control_definitions	Lists all of the security controls that apply to a specified standard.
list_standards_control_associations	Specifies whether a control is currently enabled or disabled in each enabled standard.
list_tags_for_resource	Returns a list of tags associated with a resource.
tag_resource	Adds one or more tags to a resource.
untag_resource	Removes one or more tags from a resource.
update_action_target	Updates the name and description of a custom action target in Security Hub.
update_finding_aggregator	Updates the finding aggregation configuration.
update_findings	UpdateFindings is deprecated.
update_insight	Updates the Security Hub insight identified by the specified insight ARN.
update_organization_configuration	Used to update the configuration related to Organizations.
update_security_hub_configuration	Updates configuration options for Security Hub.
update_standards_control	Used to control whether an individual security standard control is enabled or disabled.

Examples

```
## Not run:
svc <- securityhub()
# The following example demonstrates how an account can accept an
# invitation from the Security Hub administrator account to be a member
# account. This operation is applicable only to member accounts that are
# not added through AWS Organizations.
svc$accept_administrator_invitation(
  AdministratorId = "123456789012",
  InvitationId = "7ab938c5d52d7904ad09f9e7c20cc4eb"
)

## End(Not run)
```

shield

AWS Shield

Description

Shield Advanced

This is the *Shield Advanced API Reference*. This guide is for developers who need detailed information about the Shield Advanced API actions, data types, and errors. For detailed information about WAF and Shield Advanced features and an overview of how to use the WAF and Shield Advanced APIs, see the [WAF and Shield Developer Guide](#).

Usage

```
shield(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- shield(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
sts_regional_endpoint = "string"
),
credentials = list(
    creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

associate_drt_log_bucket	Authorizes the Shield Response Team (SRT) to access the specified Amazon
associate_drt_role	Authorizes the Shield Response Team (SRT) using the specified role, to acce
associate_health_check	Adds health-based detection to the Shield Advanced protection for a resourc
associate_proactive_engagement_details	Initializes proactive engagement and sets the list of contacts for the Shield R
create_protection	Enables Shield Advanced for a specific Amazon Web Services resource
create_protection_group	Creates a grouping of protected resources so they can be handled as a collect
create_subscription	Activates Shield Advanced for an account
delete_protection	Deletes an Shield Advanced Protection
delete_protection_group	Removes the specified protection group
delete_subscription	Removes Shield Advanced from an account
describe_attack	Describes the details of a DDoS attack
describe_attack_statistics	Provides information about the number and type of attacks Shield has detect
describe_drt_access	Returns the current role and list of Amazon S3 log buckets used by the Shiel
describe_emergency_contact_settings	A list of email addresses and phone numbers that the Shield Response Team
describe_protection	Lists the details of a Protection object
describe_protection_group	Returns the specification for the specified protection group
describe_subscription	Provides details about the Shield Advanced subscription for an account
disable_application_layer_automatic_response	Disable the Shield Advanced automatic application layer DDoS mitigation fo
disable_proactive_engagement	Removes authorization from the Shield Response Team (SRT) to notify cont
disassociate_drt_log_bucket	Removes the Shield Response Team's (SRT) access to the specified Amazon

disassociate_drt_role	Removes the Shield Response Team's (SRT) access to your Amazon Web Services account
disassociate_health_check	Removes health-based detection from the Shield Advanced protection for a resource
enable_application_layer_automatic_response	Enable the Shield Advanced automatic application layer DDoS mitigation for a resource
enable_proactive_engagement	Authorizes the Shield Response Team (SRT) to use email and phone to notify you about attacks
get_subscription_state	Returns the SubscriptionState, either Active or Inactive
list_attacks	Returns all ongoing DDoS attacks or all DDoS attacks during a specified time period
list_protection_groups	Retrieves ProtectionGroup objects for the account
list_protections	Retrieves Protection objects for the account
list_resources_in_protection_group	Retrieves the resources that are included in the protection group
list_tags_for_resource	Gets information about Amazon Web Services tags for a specified Amazon Resource Name (ARN)
tag_resource	Adds or updates tags for a resource in Shield
untag_resource	Removes tags from a resource in Shield
update_application_layer_automatic_response	Updates an existing Shield Advanced automatic application layer DDoS mitigation for a resource
update_emergency_contact_settings	Updates the details of the list of email addresses and phone numbers that the SRT can use to contact you
update_protection_group	Updates an existing protection group
update_subscription	Updates the details of an existing subscription

Examples

```
## Not run:
svc <- shield()
svc$associate_drt_log_bucket(
  Foo = 123
)

## End(Not run)
```

sso

AWS Single Sign-On

Description

AWS IAM Identity Center (successor to AWS Single Sign-On) Portal is a web service that makes it easy for you to assign user access to IAM Identity Center resources such as the AWS access portal. Users can get AWS account applications and roles assigned to them and get federated into the application.

Although AWS Single Sign-On was renamed, the `sso` and `identitystore` API namespaces will continue to retain their original name for backward compatibility purposes. For more information, see [IAM Identity Center rename](#).

This reference guide describes the IAM Identity Center Portal operations that you can call programmatically and includes detailed information on data types and errors.

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms, such as Java, Ruby, .Net, iOS, or Android. The SDKs provide a convenient way to

create programmatic access to IAM Identity Center and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Usage

```
sso(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the [Operations](#) section.

Service syntax

```

svc <- sso(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

get_role_credentials	Returns the STS short-term credentials for a given role name that is assigned to the user
list_account_roles	Lists all roles that are assigned to the user for a given AWS account
list_accounts	Lists all AWS accounts assigned to the user
logout	Removes the locally stored SSO tokens from the client-side cache and sends an API call to the IAM Id

Examples

```

## Not run:
svc <- sso()
svc$get_role_credentials(
  Foo = 123
)

```

```
## End(Not run)
```

```
ssoadmin
```

```
    AWS Single Sign-On Admin
```

Description

AWS IAM Identity Center (successor to AWS Single Sign-On) helps you securely create, or connect, your workforce identities and manage their access centrally across AWS accounts and applications. IAM Identity Center is the recommended approach for workforce authentication and authorization in AWS, for organizations of any size and type.

Although AWS Single Sign-On was renamed, the `sso` and `identitystore` API namespaces will continue to retain their original name for backward compatibility purposes. For more information, see [IAM Identity Center rename](#).

This reference guide provides information on single sign-on operations which could be used for access management of AWS accounts. For information about IAM Identity Center features, see the [IAM Identity Center User Guide](#).

Many operations in the IAM Identity Center APIs rely on identifiers for users and groups, known as principals. For more information about how to work with principals and principal IDs in IAM Identity Center, see the [Identity Store API Reference](#).

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, and more). The SDKs provide a convenient way to create programmatic access to IAM Identity Center and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Usage

```
ssoadmin(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.

- **region**: The AWS Region used in instantiating the client.
- **close_connection**: Immediately close all HTTP connections.
- **timeout**: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style**: Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **sts_regional_endpoint**: Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

credentials Optional credentials shorthand for the config parameter

- **creds**:
 - **access_key_id**: AWS access key ID
 - **secret_access_key**: AWS secret access key
 - **session_token**: AWS temporary session token
- **profile**: The name of a profile to use. If not given, then the default profile is used.
- **anonymous**: Set anonymous credentials.

endpoint Optional shorthand for complete URL to use for the constructed client.

region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- ssoadmin(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
```

```

credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

attach_customer_managed_policy_reference_to_permission_set	Attaches the specified customer managed policy to the s
attach_managed_policy_to_permission_set	Attaches an AWS managed policy ARN to a permission
create_account_assignment	Assigns access to a principal for a specified AWS accou
create_instance_access_control_attribute_configuration	Enables the attributes-based access control (ABAC) fea
create_permission_set	Creates a permission set within a specified IAM Identity
delete_account_assignment	Deletes a principal's access from a specified AWS accou
delete_inline_policy_from_permission_set	Deletes the inline policy from a specified permission set
delete_instance_access_control_attribute_configuration	Disables the attributes-based access control (ABAC) fea
delete_permissions_boundary_from_permission_set	Deletes the permissions boundary from a specified Permi
delete_permission_set	Deletes the specified permission set
describe_account_assignment_creation_status	Describes the status of the assignment creation request
describe_account_assignment_deletion_status	Describes the status of the assignment deletion request
describe_instance_access_control_attribute_configuration	Returns the list of IAM Identity Center identity store att
describe_permission_set	Gets the details of the permission set
describe_permission_set_provisioning_status	Describes the status for the given permission set provisi
detach_customer_managed_policy_reference_from_permission_set	Detaches the specified customer managed policy from th
detach_managed_policy_from_permission_set	Detaches the attached AWS managed policy ARN from
get_inline_policy_for_permission_set	Obtains the inline policy assigned to the permission set
get_permissions_boundary_for_permission_set	Obtains the permissions boundary for a specified Permi
list_account_assignment_creation_status	Lists the status of the AWS account assignment creation
list_account_assignment_deletion_status	Lists the status of the AWS account assignment deletion
list_account_assignments	Lists the assignee of the specified AWS account with th
list_accounts_for_provisioned_permission_set	Lists all the AWS accounts where the specified permissi
list_customer_managed_policy_references_in_permission_set	Lists all customer managed policies attached to a specif
list_instances	Lists the IAM Identity Center instances that the caller h
list_managed_policies_in_permission_set	Lists the AWS managed policy that is attached to a spec
list_permission_set_provisioning_status	Lists the status of the permission set provisioning requ
list_permission_sets	Lists the PermissionSets in an IAM Identity Center insta
list_permission_sets_provisioned_to_account	Lists all the permission sets that are provisioned to a sp
list_tags_for_resource	Lists the tags that are attached to a specified resource
provision_permission_set	The process by which a specified permission set is prov
put_inline_policy_to_permission_set	Attaches an inline policy to a permission set
put_permissions_boundary_to_permission_set	Attaches an AWS managed or customer managed policy

tag_resource	Associates a set of tags with a specified resource
untag_resource	Disassociates a set of tags from a specified resource
update_instance_access_control_attribute_configuration	Updates the IAM Identity Center identity store attribute
update_permission_set	Updates an existing permission set

Examples

```
## Not run:
svc <- ssoadmin()
svc$attach_customer_managed_policy_reference_to_permission_set(
  Foo = 123
)

## End(Not run)
```

ssooidc

AWS SSO OIDC

Description

AWS IAM Identity Center (successor to AWS Single Sign-On) OpenID Connect (OIDC) is a web service that enables a client (such as AWS CLI or a native application) to register with IAM Identity Center. The service also enables the client to fetch the user's access token upon successful authentication and authorization with IAM Identity Center.

Although AWS Single Sign-On was renamed, the `sso` and `identitystore` API namespaces will continue to retain their original name for backward compatibility purposes. For more information, see [IAM Identity Center rename](#).

Considerations for Using This Guide

Before you begin using this guide, we recommend that you first review the following important information about how the IAM Identity Center OIDC service works.

- The IAM Identity Center OIDC service currently implements only the portions of the OAuth 2.0 Device Authorization Grant standard (<https://tools.ietf.org/html/rfc8628>) that are necessary to enable single sign-on authentication with the AWS CLI. Support for other OIDC flows frequently needed for native applications, such as Authorization Code Flow (+ PKCE), will be addressed in future releases.
- The service emits only OIDC access tokens, such that obtaining a new token (For example, token refresh) requires explicit user re-authentication.
- The access tokens provided by this service grant access to all AWS account entitlements assigned to an IAM Identity Center user, not just a particular application.
- The documentation in this guide does not describe the mechanism to convert the access token into AWS Auth (“sigv4”) credentials for use with IAM-protected AWS service endpoints. For more information, see [GetRoleCredentials](#) in the *IAM Identity Center Portal API Reference Guide*.

For general information about IAM Identity Center, see [What is IAM Identity Center?](#) in the *IAM Identity Center User Guide*.

Usage

```
ssooidc(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the *Operations* section.

Service syntax

```

svc <- ssooidc(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

create_token	Creates and returns an access token for the authorized client
register_client	Registers a client with IAM Identity Center
start_device_authorization	Initiates device authorization by requesting a pair of verification codes from the authorization server

Examples

```

## Not run:
svc <- ssooidc()
svc$create_token(
  Foo = 123
)

```

```
## End(Not run)
```

 sts

AWS Security Token Service

Description

Security Token Service

Security Token Service (STS) enables you to request temporary, limited-privilege credentials for users. This guide provides descriptions of the STS API. For more information about using this service, see [Temporary Security Credentials](#).

Usage

```
sts(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sts(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[assume_role](#)

Returns a set of temporary security credentials that you can use to access Amazon Web Ser

assume_role_with_saml	Returns a set of temporary security credentials for users who have been authenticated via a
assume_role_with_web_identity	Returns a set of temporary security credentials for users who have been authenticated in a
decode_authorization_message	Decodes additional information about the authorization status of a request from an encoded
get_access_key_info	Returns the account identifier for the specified access key ID
get_caller_identity	Returns details about the IAM user or role whose credentials are used to call the operation
get_federation_token	Returns a set of temporary security credentials (consisting of an access key ID, a secret acc
get_session_token	Returns a set of temporary credentials for an Amazon Web Services account or IAM user

Examples

```
## Not run:
svc <- sts()
#
svc$assume_role(
  ExternalId = "123ABC",
  Policy = "{\Version\": \"2012-10-17\", \"Statement\": [{\Sid\": \"Stmt1\", \"Effect\": \"A...\",
  RoleArn = \"arn:aws:iam::123456789012:role/demo\",
  RoleSessionName = \"testAssumeRoleSession\",
  Tags = list(
    list(
      Key = \"Project\",
      Value = \"Unicorn\"
    ),
    list(
      Key = \"Team\",
      Value = \"Automation\"
    ),
    list(
      Key = \"Cost-Center\",
      Value = \"12345\"
    )
  ),
  TransitiveTagKeys = list(
    \"Project\",
    \"Cost-Center\"
  )
)
## End(Not run)
```

Description

This is **AWS WAF Classic** documentation. For more information, see **AWS WAF Classic** in the developer guide.

For the latest version of AWS WAF, use the AWS WAFV2 API and see the **AWS WAF Developer Guide**. With the latest version, AWS WAF has a single set of endpoints for regional and global use.

This is the *AWS WAF Classic API Reference* for using AWS WAF Classic with Amazon CloudFront. The AWS WAF Classic actions and data types listed in the reference are available for protecting Amazon CloudFront distributions. You can use these actions and data types via the endpoint *waf.amazonaws.com*. This guide is for developers who need detailed information about the AWS WAF Classic API actions, data types, and errors. For detailed information about AWS WAF Classic features and an overview of how to use the AWS WAF Classic API, see the **AWS WAF Classic** in the developer guide.

Usage

```
waf(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to `true` to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**

- **access_key_id:** AWS access key ID
- **secret_access_key:** AWS secret access key
- **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous**: Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- waf(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[create_byte_match_set](#)
[create_geo_match_set](#)
[create_ip_set](#)

This is AWS WAF Classic documentation
This is AWS WAF Classic documentation
This is AWS WAF Classic documentation

create_rate_based_rule	This is AWS WAF Classic documentation
create_regex_match_set	This is AWS WAF Classic documentation
create_regex_pattern_set	This is AWS WAF Classic documentation
create_rule	This is AWS WAF Classic documentation
create_rule_group	This is AWS WAF Classic documentation
create_size_constraint_set	This is AWS WAF Classic documentation
create_sql_injection_match_set	This is AWS WAF Classic documentation
create_web_acl	This is AWS WAF Classic documentation
create_web_acl_migration_stack	Creates an AWS CloudFormation WAFV2 template for the specified web ACL in the sp
create_xss_match_set	This is AWS WAF Classic documentation
delete_byte_match_set	This is AWS WAF Classic documentation
delete_geo_match_set	This is AWS WAF Classic documentation
delete_ip_set	This is AWS WAF Classic documentation
delete_logging_configuration	This is AWS WAF Classic documentation
delete_permission_policy	This is AWS WAF Classic documentation
delete_rate_based_rule	This is AWS WAF Classic documentation
delete_regex_match_set	This is AWS WAF Classic documentation
delete_regex_pattern_set	This is AWS WAF Classic documentation
delete_rule	This is AWS WAF Classic documentation
delete_rule_group	This is AWS WAF Classic documentation
delete_size_constraint_set	This is AWS WAF Classic documentation
delete_sql_injection_match_set	This is AWS WAF Classic documentation
delete_web_acl	This is AWS WAF Classic documentation
delete_xss_match_set	This is AWS WAF Classic documentation
get_byte_match_set	This is AWS WAF Classic documentation
get_change_token	This is AWS WAF Classic documentation
get_change_token_status	This is AWS WAF Classic documentation
get_geo_match_set	This is AWS WAF Classic documentation
get_ip_set	This is AWS WAF Classic documentation
get_logging_configuration	This is AWS WAF Classic documentation
get_permission_policy	This is AWS WAF Classic documentation
get_rate_based_rule	This is AWS WAF Classic documentation
get_rate_based_rule_managed_keys	This is AWS WAF Classic documentation
get_regex_match_set	This is AWS WAF Classic documentation
get_regex_pattern_set	This is AWS WAF Classic documentation
get_rule	This is AWS WAF Classic documentation
get_rule_group	This is AWS WAF Classic documentation
get_sampled_requests	This is AWS WAF Classic documentation
get_size_constraint_set	This is AWS WAF Classic documentation
get_sql_injection_match_set	This is AWS WAF Classic documentation
get_web_acl	This is AWS WAF Classic documentation
get_xss_match_set	This is AWS WAF Classic documentation
list_activated_rules_in_rule_group	This is AWS WAF Classic documentation
list_byte_match_sets	This is AWS WAF Classic documentation
list_geo_match_sets	This is AWS WAF Classic documentation
list_ip_sets	This is AWS WAF Classic documentation
list_logging_configurations	This is AWS WAF Classic documentation
list_rate_based_rules	This is AWS WAF Classic documentation

list_regex_match_sets	This is AWS WAF Classic documentation
list_regex_pattern_sets	This is AWS WAF Classic documentation
list_rule_groups	This is AWS WAF Classic documentation
list_rules	This is AWS WAF Classic documentation
list_size_constraint_sets	This is AWS WAF Classic documentation
list_sql_injection_match_sets	This is AWS WAF Classic documentation
list_subscribed_rule_groups	This is AWS WAF Classic documentation
list_tags_for_resource	This is AWS WAF Classic documentation
list_web_acl_ls	This is AWS WAF Classic documentation
list_xss_match_sets	This is AWS WAF Classic documentation
put_logging_configuration	This is AWS WAF Classic documentation
put_permission_policy	This is AWS WAF Classic documentation
tag_resource	This is AWS WAF Classic documentation
untag_resource	This is AWS WAF Classic documentation
update_byte_match_set	This is AWS WAF Classic documentation
update_geo_match_set	This is AWS WAF Classic documentation
update_ip_set	This is AWS WAF Classic documentation
update_rate_based_rule	This is AWS WAF Classic documentation
update_regex_match_set	This is AWS WAF Classic documentation
update_regex_pattern_set	This is AWS WAF Classic documentation
update_rule	This is AWS WAF Classic documentation
update_rule_group	This is AWS WAF Classic documentation
update_size_constraint_set	This is AWS WAF Classic documentation
update_sql_injection_match_set	This is AWS WAF Classic documentation
update_web_acl	This is AWS WAF Classic documentation
update_xss_match_set	This is AWS WAF Classic documentation

Examples

```
## Not run:
svc <- waf()
# The following example creates an IP match set named MyIPSetFriendlyName.
svc$create_ip_set(
  ChangeToken = "abcd12f2-46da-4fdb-b8d5-fbd4c466928f",
  Name = "MyIPSetFriendlyName"
)

## End(Not run)
```

Description

This is **AWS WAF Classic Regional** documentation. For more information, see [AWS WAF Classic](#) in the developer guide.

For the latest version of AWS WAF, use the AWS WAFV2 API and see the [AWS WAF Developer Guide](#). With the latest version, AWS WAF has a single set of endpoints for regional and global use.

This is the *AWS WAF Regional Classic API Reference* for using AWS WAF Classic with the AWS resources, Elastic Load Balancing (ELB) Application Load Balancers and API Gateway APIs. The AWS WAF Classic actions and data types listed in the reference are available for protecting Elastic Load Balancing (ELB) Application Load Balancers and API Gateway APIs. You can use these actions and data types by means of the endpoints listed in [AWS Regions and Endpoints](#). This guide is for developers who need detailed information about the AWS WAF Classic API actions, data types, and errors. For detailed information about AWS WAF Classic features and an overview of how to use the AWS WAF Classic API, see the [AWS WAF Classic](#) in the developer guide.

Usage

```
wafregional(
    config = list(),
    credentials = list(),
    endpoint = NULL,
    region = NULL
)
```

Arguments

`config` Optional configuration of credentials, endpoint, and/or region.

- **credentials:**

- **creds:**

- * **access_key_id:** AWS access key ID
- * **secret_access_key:** AWS secret access key
- * **session_token:** AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

- **endpoint:** The complete URL to use for the constructed client.

- **region:** The AWS Region used in instantiating the client.

- **close_connection:** Immediately close all HTTP connections.

- **timeout:** The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.

- **s3_force_path_style:** Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.

- **sts_regional_endpoint:** Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html>

`credentials` Optional credentials shorthand for the config parameter

- **creds:**
 - **access_key_id:** AWS access key ID
 - **secret_access_key:** AWS secret access key
 - **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
- endpoint Optional shorthand for complete URL to use for the constructed client.
- region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- wafregional(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

associate_web_acl	This is AWS WAF Classic Regional documentation
create_byte_match_set	This is AWS WAF Classic documentation
create_geo_match_set	This is AWS WAF Classic documentation
create_ip_set	This is AWS WAF Classic documentation
create_rate_based_rule	This is AWS WAF Classic documentation
create_regex_match_set	This is AWS WAF Classic documentation
create_regex_pattern_set	This is AWS WAF Classic documentation
create_rule	This is AWS WAF Classic documentation
create_rule_group	This is AWS WAF Classic documentation
create_size_constraint_set	This is AWS WAF Classic documentation
create_sql_injection_match_set	This is AWS WAF Classic documentation
create_web_acl	This is AWS WAF Classic documentation
create_web_acl_migration_stack	Creates an AWS CloudFormation WAFV2 template for the specified web ACL in the sp
create_xss_match_set	This is AWS WAF Classic documentation
delete_byte_match_set	This is AWS WAF Classic documentation
delete_geo_match_set	This is AWS WAF Classic documentation
delete_ip_set	This is AWS WAF Classic documentation
delete_logging_configuration	This is AWS WAF Classic documentation
delete_permission_policy	This is AWS WAF Classic documentation
delete_rate_based_rule	This is AWS WAF Classic documentation
delete_regex_match_set	This is AWS WAF Classic documentation
delete_regex_pattern_set	This is AWS WAF Classic documentation
delete_rule	This is AWS WAF Classic documentation
delete_rule_group	This is AWS WAF Classic documentation
delete_size_constraint_set	This is AWS WAF Classic documentation
delete_sql_injection_match_set	This is AWS WAF Classic documentation
delete_web_acl	This is AWS WAF Classic documentation
delete_xss_match_set	This is AWS WAF Classic documentation
disassociate_web_acl	This is AWS WAF Classic Regional documentation
get_byte_match_set	This is AWS WAF Classic documentation
get_change_token	This is AWS WAF Classic documentation
get_change_token_status	This is AWS WAF Classic documentation
get_geo_match_set	This is AWS WAF Classic documentation
get_ip_set	This is AWS WAF Classic documentation
get_logging_configuration	This is AWS WAF Classic documentation
get_permission_policy	This is AWS WAF Classic documentation
get_rate_based_rule	This is AWS WAF Classic documentation
get_rate_based_rule_managed_keys	This is AWS WAF Classic documentation
get_regex_match_set	This is AWS WAF Classic documentation
get_regex_pattern_set	This is AWS WAF Classic documentation
get_rule	This is AWS WAF Classic documentation
get_rule_group	This is AWS WAF Classic documentation
get_sampled_requests	This is AWS WAF Classic documentation
get_size_constraint_set	This is AWS WAF Classic documentation
get_sql_injection_match_set	This is AWS WAF Classic documentation
get_web_acl	This is AWS WAF Classic documentation

get_web_acl_for_resource	This is AWS WAF Classic Regional documentation
get_xss_match_set	This is AWS WAF Classic documentation
list_activated_rules_in_rule_group	This is AWS WAF Classic documentation
list_byte_match_sets	This is AWS WAF Classic documentation
list_geo_match_sets	This is AWS WAF Classic documentation
list_ip_sets	This is AWS WAF Classic documentation
list_logging_configurations	This is AWS WAF Classic documentation
list_rate_based_rules	This is AWS WAF Classic documentation
list_regex_match_sets	This is AWS WAF Classic documentation
list_regex_pattern_sets	This is AWS WAF Classic documentation
list_resources_for_web_acl	This is AWS WAF Classic Regional documentation
list_rule_groups	This is AWS WAF Classic documentation
list_rules	This is AWS WAF Classic documentation
list_size_constraint_sets	This is AWS WAF Classic documentation
list_sql_injection_match_sets	This is AWS WAF Classic documentation
list_subscribed_rule_groups	This is AWS WAF Classic documentation
list_tags_for_resource	This is AWS WAF Classic documentation
list_web_acl_s	This is AWS WAF Classic documentation
list_xss_match_sets	This is AWS WAF Classic documentation
put_logging_configuration	This is AWS WAF Classic documentation
put_permission_policy	This is AWS WAF Classic documentation
tag_resource	This is AWS WAF Classic documentation
untag_resource	This is AWS WAF Classic documentation
update_byte_match_set	This is AWS WAF Classic documentation
update_geo_match_set	This is AWS WAF Classic documentation
update_ip_set	This is AWS WAF Classic documentation
update_rate_based_rule	This is AWS WAF Classic documentation
update_regex_match_set	This is AWS WAF Classic documentation
update_regex_pattern_set	This is AWS WAF Classic documentation
update_rule	This is AWS WAF Classic documentation
update_rule_group	This is AWS WAF Classic documentation
update_size_constraint_set	This is AWS WAF Classic documentation
update_sql_injection_match_set	This is AWS WAF Classic documentation
update_web_acl	This is AWS WAF Classic documentation
update_xss_match_set	This is AWS WAF Classic documentation

Examples

```
## Not run:
svc <- wafregional()
# The following example creates an IP match set named MyIPSetFriendlyName.
svc$create_ip_set(
  ChangeToken = "abcd12f2-46da-4fdb-b8d5-fbd4c466928f",
  Name = "MyIPSetFriendlyName"
)

## End(Not run)
```

Description

WAF

This is the latest version of the **WAF** API, released in November, 2019. The names of the entities that you use to access this API, like endpoints and namespaces, all have the versioning information added, like "V2" or "v2", to distinguish from the prior version. We recommend migrating your resources to this version, because it has a number of significant improvements.

If you used WAF prior to this release, you can't use this WAFV2 API to access any WAF resources that you created before. You can access your old rules, web ACLs, and other WAF resources only through the WAF Classic APIs. The WAF Classic APIs have retained the prior names, endpoints, and namespaces.

For information, including how to migrate your WAF resources to this version, see the [WAF Developer Guide](#).

WAF is a web application firewall that lets you monitor the HTTP and HTTPS requests that are forwarded to an Amazon CloudFront distribution, Amazon API Gateway REST API, Application Load Balancer, AppSync GraphQL API, Amazon Cognito user pool, App Runner service, or Amazon Web Services Verified Access instance. WAF also lets you control access to your content, to protect the Amazon Web Services resource that WAF is monitoring. Based on conditions that you specify, such as the IP addresses that requests originate from or the values of query strings, the protected resource responds to requests with either the requested content, an HTTP 403 status code (Forbidden), or with a custom response.

This API guide is for developers who need detailed information about WAF API actions, data types, and errors. For detailed information about WAF features and guidance for configuring and using WAF, see the [WAF Developer Guide](#).

You can make calls using the endpoints listed in [WAF endpoints and quotas](#).

- For regional applications, you can use any of the endpoints in the list. A regional application can be an Application Load Balancer (ALB), an Amazon API Gateway REST API, an AppSync GraphQL API, an Amazon Cognito user pool, an App Runner service, or an Amazon Web Services Verified Access instance.
- For Amazon CloudFront applications, you must use the API endpoint listed for US East (N. Virginia): us-east-1.

Alternatively, you can use one of the Amazon Web Services SDKs to access an API that's tailored to the programming language or platform that you're using. For more information, see [Amazon Web Services SDKs](#).

We currently provide two versions of the WAF API: this API and the prior versions, the classic WAF APIs. This new API provides the same functionality as the older versions, with the following major improvements:

- You use one API for both global and regional applications. Where you need to distinguish the scope, you specify a Scope parameter and set it to CLOUDFRONT or REGIONAL.
- You can define a web ACL or rule group with a single call, and update it with a single call. You define all rule specifications in JSON format, and pass them to your rule group or web ACL calls.
- The limits WAF places on the use of rules more closely reflects the cost of running each type of rule. Rule groups include capacity settings, so you know the maximum cost of a rule group when you use it.

Usage

```
wafv2(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. – endpoint: The complete URL to use for the constructed client. – region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • sts_regional_endpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- wafv2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    sts_regional_endpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

[associate_web_acl](#)

[check_capacity](#)

[create_api_key](#)

[create_ip_set](#)

[create_regex_pattern_set](#)

[create_rule_group](#)

[create_web_acl](#)

[delete_firewall_manager_rule_groups](#)

Associates a web ACL with a regional application resource, to protect the re

Returns the web ACL capacity unit (WCU) requirements for a specified sco

Creates an API key that contains a set of token domains

Creates an IPSet, which you use to identify web requests that originate from

Creates a RegexPatternSet, which you reference in a RegexPatternSetRefer

Creates a RuleGroup per the specifications provided

Creates a WebACL per the specifications provided

Deletes all rule groups that are managed by Firewall Manager for the specif

<code>delete_ip_set</code>	Deletes the specified IPSet
<code>delete_logging_configuration</code>	Deletes the LoggingConfiguration from the specified web ACL
<code>delete_permission_policy</code>	Permanently deletes an IAM policy from the specified rule group
<code>delete_regex_pattern_set</code>	Deletes the specified RegexPatternSet
<code>delete_rule_group</code>	Deletes the specified RuleGroup
<code>delete_web_acl</code>	Deletes the specified WebACL
<code>describe_all_managed_products</code>	Provides high-level information for the Amazon Web Services Managed Rule Groups
<code>describe_managed_products_by_vendor</code>	Provides high-level information for the managed rule groups owned by a specific vendor
<code>describe_managed_rule_group</code>	Provides high-level information for a managed rule group, including description and status
<code>disassociate_web_acl</code>	Disassociates the specified regional application resource from any existing web ACLs
<code>generate_mobile_sdk_release_url</code>	Generates a presigned download URL for the specified release of the mobile SDK
<code>get_decrypted_api_key</code>	Returns your API key in decrypted form
<code>get_ip_set</code>	Retrieves the specified IPSet
<code>get_logging_configuration</code>	Returns the LoggingConfiguration for the specified web ACL
<code>get_managed_rule_set</code>	Retrieves the specified managed rule set
<code>get_mobile_sdk_release</code>	Retrieves information for the specified mobile SDK release, including release name and version
<code>get_permission_policy</code>	Returns the IAM policy that is attached to the specified rule group
<code>get_rate_based_statement_managed_keys</code>	Retrieves the IP addresses that are currently blocked by a rate-based rule in the specified web ACL
<code>get_regex_pattern_set</code>	Retrieves the specified RegexPatternSet
<code>get_rule_group</code>	Retrieves the specified RuleGroup
<code>get_sampled_requests</code>	Gets detailed information about a specified number of requests—a sample—through the specified web ACL
<code>get_web_acl</code>	Retrieves the specified WebACL
<code>get_web_acl_for_resource</code>	Retrieves the WebACL for the specified resource
<code>list_api_keys</code>	Retrieves a list of the API keys that you've defined for the specified scope
<code>list_available_managed_rule_groups</code>	Retrieves an array of managed rule groups that are available for you to use
<code>list_available_managed_rule_group_versions</code>	Returns a list of the available versions for the specified managed rule group
<code>list_ip_sets</code>	Retrieves an array of IPSetSummary objects for the IP sets that you manage
<code>list_logging_configurations</code>	Retrieves an array of your LoggingConfiguration objects
<code>list_managed_rule_sets</code>	Retrieves the managed rule sets that you own
<code>list_mobile_sdk_releases</code>	Retrieves a list of the available releases for the mobile SDK and the specified vendor
<code>list_regex_pattern_sets</code>	Retrieves an array of RegexPatternSetSummary objects for the regex pattern sets
<code>list_resources_for_web_acl</code>	Retrieves an array of the Amazon Resource Names (ARNs) for the regional application resources associated with the specified web ACL
<code>list_rule_groups</code>	Retrieves an array of RuleGroupSummary objects for the rule groups that you manage
<code>list_tags_for_resource</code>	Retrieves the TagInfoForResource for the specified resource
<code>list_web_acl_s</code>	Retrieves an array of WebACLSummary objects for the web ACLs that you manage
<code>put_logging_configuration</code>	Enables the specified LoggingConfiguration, to start logging from a web ACL
<code>put_managed_rule_set_versions</code>	Defines the versions of your managed rule set that you are offering to the customer
<code>put_permission_policy</code>	Attaches an IAM policy to the specified resource
<code>tag_resource</code>	Associates tags with the specified Amazon Web Services resource
<code>untag_resource</code>	Disassociates tags from an Amazon Web Services resource
<code>update_ip_set</code>	Updates the specified IPSet
<code>update_managed_rule_set_version_expiry_date</code>	Updates the expiration information for your managed rule set
<code>update_regex_pattern_set</code>	Updates the specified RegexPatternSet
<code>update_rule_group</code>	Updates the specified RuleGroup
<code>update_web_acl</code>	Updates the specified WebACL

Examples

```
## Not run:  
svc <- wafv2()  
svc$associate_web_acl(  
  Foo = 123  
)  
  
## End(Not run)
```

Index

accept_administrator_invitation, [47](#), [86](#)
accept_invitation, [37](#), [47](#), [76](#), [86](#)
accept_resource_share_invitation, [80](#)
accept_shared_directory, [40](#)
accessanalyzer, [3](#)
account, [6](#)
acm, [8](#)
acmpca, [11](#)
add_attributes_to_findings, [62](#)
add_client_id_to_open_id_connect_provider, [50](#)
add_custom_attributes, [28](#)
add_facet_to_object, [16](#)
add_ip_routes, [40](#)
add_region, [40](#)
add_role_to_instance_profile, [50](#)
add_tags_to_certificate, [10](#)
add_tags_to_resource, [20](#), [40](#)
add_user_to_group, [50](#)
admin_add_user_to_group, [28](#)
admin_confirm_sign_up, [28](#)
admin_create_user, [28](#)
admin_delete_user, [28](#)
admin_delete_user_attributes, [28](#)
admin_disable_provider_for_user, [28](#)
admin_disable_user, [28](#)
admin_enable_user, [29](#)
admin_forget_device, [29](#)
admin_get_device, [29](#)
admin_get_user, [29](#)
admin_initiate_auth, [29](#)
admin_link_provider_for_user, [29](#)
admin_list_devices, [29](#)
admin_list_groups_for_user, [29](#)
admin_list_user_auth_events, [29](#)
admin_remove_user_from_group, [29](#)
admin_reset_user_password, [29](#)
admin_respond_to_auth_challenge, [29](#)
admin_set_user_mfa_preference, [29](#)
admin_set_user_password, [29](#)
admin_set_user_settings, [29](#)
admin_update_auth_event_feedback, [29](#)
admin_update_device_status, [29](#)
admin_update_user_attributes, [29](#)
admin_user_global_sign_out, [29](#)
apply_archive_rule, [5](#)
apply_schema, [16](#)
archive_findings, [47](#)
associate_admin_account, [43](#)
associate_drt_log_bucket, [90](#)
associate_drt_role, [90](#)
associate_health_check, [90](#)
associate_member, [65](#)
associate_member_account, [74](#)
associate_proactive_engagement_details, [90](#)
associate_resource_share, [80](#)
associate_resource_share_permission, [80](#)
associate_s3_resources, [74](#)
associate_software_token, [29](#)
associate_third_party_firewall, [43](#)
associate_web_acl, [109](#), [113](#)
assume_role, [101](#)
assume_role_with_saml, [102](#)
assume_role_with_web_identity, [102](#)
attach_customer_managed_policy_reference_to_permission_set, [96](#)
attach_group_policy, [51](#)
attach_managed_policy_to_permission_set, [96](#)
attach_object, [16](#)
attach_policy, [16](#)
attach_role_policy, [51](#)
attach_to_index, [16](#)
attach_typed_link, [16](#)
attach_user_policy, [51](#)
batch_associate_resource, [43](#)

- batch_delete_automation_rules, 86
- batch_disable_standards, 86
- batch_disassociate_resource, 44
- batch_enable_standards, 84, 87
- batch_get_account_status, 65
- batch_get_automation_rules, 87
- batch_get_code_snippet, 65
- batch_get_custom_data_identifiers, 76
- batch_get_finding_details, 65
- batch_get_free_trial_info, 65
- batch_get_graph_member_datasources, 37
- batch_get_member_ec_2_deep_inspection_status, 65
- batch_get_membership_datasources, 37
- batch_get_security_controls, 87
- batch_get_standards_control_associations, 87
- batch_import_findings, 84, 87
- batch_read, 16
- batch_update_automation_rules, 87
- batch_update_findings, 85, 87
- batch_update_member_ec_2_deep_inspection_status, 65
- batch_update_standards_control_associations, 87
- batch_write, 16
- bulk_publish, 33

- cancel_findings_report, 65
- cancel_key_deletion, 69
- cancel_policy_generation, 5
- cancel_rotate_secret, 83
- cancel_sbom_export, 65
- cancel_schema_extension, 40
- change_password, 29, 51
- check_capacity, 113
- clouddirectory, 14
- cloudhsm, 18
- cloudhsmv2, 20
- cognitoidentity, 23
- cognitoidentityprovider, 26
- cognitosync, 31
- confirm_device, 29
- confirm_forgot_password, 29
- confirm_sign_up, 29
- connect_custom_key_store, 69
- connect_directory, 40
- copy_backup_to_region, 22
- create_access_key, 51
- create_access_preview, 5
- create_account_alias, 51
- create_account_assignment, 96
- create_action_target, 87
- create_alias, 40, 69
- create_allow_list, 76
- create_analyzer, 5
- create_api_key, 113
- create_archive_rule, 5
- create_assessment_target, 62
- create_assessment_template, 62
- create_automation_rule, 87
- create_byte_match_set, 104, 109
- create_certificate_authority, 13
- create_certificate_authority_audit_report, 13
- create_classification_job, 76
- create_cluster, 22
- create_computer, 40
- create_conditional_forwarder, 40
- create_custom_data_identifier, 76
- create_custom_key_store, 69
- create_detector, 47
- create_directory, 16, 40
- create_exclusions_preview, 62
- create_facet, 16
- create_filter, 47, 65
- create_finding_aggregator, 87
- create_findings_filter, 76
- create_findings_report, 65
- create_geo_match_set, 104, 109
- create_grant, 69
- create_graph, 37
- create_group, 29, 51, 59
- create_group_membership, 59
- create_hapg, 20
- create_hsm, 20, 22
- create_identity_pool, 25
- create_identity_provider, 29
- create_index, 16
- create_insight, 87
- create_instance_access_control_attribute_configuration, 96
- create_instance_profile, 51
- create_invitations, 76
- create_ip_set, 47, 104, 109, 113
- create_key, 69
- create_log_subscription, 40

- create_login_profile, [51](#)
- create_luna_client, [20](#)
- create_member, [76](#)
- create_members, [37](#), [47](#), [84](#), [87](#)
- create_microsoft_ad, [40](#)
- create_object, [16](#)
- create_open_id_connect_provider, [51](#)
- create_permission, [13](#), [80](#)
- create_permission_set, [96](#)
- create_permission_version, [80](#)
- create_policy, [51](#)
- create_policy_version, [51](#)
- create_profile, [56](#)
- create_protection, [90](#)
- create_protection_group, [90](#)
- create_publishing_destination, [47](#)
- create_rate_based_rule, [105](#), [109](#)
- create_regex_match_set, [105](#), [109](#)
- create_regex_pattern_set, [105](#), [109](#), [113](#)
- create_resource_group, [62](#)
- create_resource_server, [29](#)
- create_resource_share, [80](#)
- create_role, [51](#)
- create_rule, [105](#), [109](#)
- create_rule_group, [105](#), [109](#), [113](#)
- create_saml_provider, [51](#)
- create_sample_findings, [47](#), [76](#)
- create_sbom_export, [65](#)
- create_schema, [16](#)
- create_secret, [83](#)
- create_service_linked_role, [51](#)
- create_service_specific_credential, [51](#)
- create_size_constraint_set, [105](#), [109](#)
- create_snapshot, [40](#)
- create_sql_injection_match_set, [105](#),
[109](#)
- create_subscription, [90](#)
- create_threat_intel_set, [47](#)
- create_token, [99](#)
- create_trust, [40](#)
- create_trust_anchor, [56](#)
- create_typed_link_facet, [16](#)
- create_user, [51](#), [59](#)
- create_user_import_job, [29](#)
- create_user_pool, [29](#)
- create_user_pool_client, [29](#)
- create_user_pool_domain, [29](#)
- create_virtual_mfa_device, [51](#)
- create_web_acl, [105](#), [109](#), [113](#)
- create_web_acl_migration_stack, [105](#),
[109](#)
- create_xss_match_set, [105](#), [109](#)
- deactivate_mfa_device, [51](#)
- decline_invitations, [47](#), [76](#), [87](#)
- decode_authorization_message, [102](#)
- decrypt, [67](#), [69](#)
- delete_access_key, [51](#)
- delete_account_alias, [51](#)
- delete_account_assignment, [96](#)
- delete_account_password_policy, [51](#)
- delete_action_target, [87](#)
- delete_alias, [69](#)
- delete_allow_list, [76](#)
- delete_alternate_contact, [8](#)
- delete_analyzer, [5](#)
- delete_apps_list, [44](#)
- delete_archive_rule, [5](#)
- delete_assessment_run, [62](#)
- delete_assessment_target, [62](#)
- delete_assessment_template, [62](#)
- delete_backup, [22](#)
- delete_byte_match_set, [105](#), [109](#)
- delete_certificate, [10](#)
- delete_certificate_authority, [13](#)
- delete_cluster, [22](#)
- delete_conditional_forwarder, [40](#)
- delete_crl, [56](#)
- delete_custom_data_identifier, [76](#)
- delete_custom_key_store, [69](#)
- delete_dataset, [33](#)
- delete_detector, [47](#)
- delete_directory, [16](#), [40](#)
- delete_facet, [16](#)
- delete_filter, [47](#), [65](#)
- delete_finding_aggregator, [87](#)
- delete_findings_filter, [76](#)
- delete_firewall_manager_rule_groups,
[113](#)
- delete_geo_match_set, [105](#), [109](#)
- delete_graph, [37](#)
- delete_group, [29](#), [51](#), [59](#)
- delete_group_membership, [59](#)
- delete_group_policy, [51](#)
- delete_hapg, [20](#)
- delete_hsm, [20](#), [22](#)
- delete_identities, [25](#)

- delete_identity_pool, [25](#)
- delete_identity_provider, [29](#)
- delete_imported_key_material, [69](#)
- delete_inline_policy_from_permission_set, [96](#)
- delete_insight, [87](#)
- delete_instance_access_control_attribute_configuration, [96](#)
- delete_instance_profile, [51](#)
- delete_invitations, [47, 76, 87](#)
- delete_ip_set, [47, 105, 109, 114](#)
- delete_log_subscription, [40](#)
- delete_logging_configuration, [105, 109, 114](#)
- delete_login_profile, [51](#)
- delete_luna_client, [20](#)
- delete_member, [76](#)
- delete_members, [37, 47, 87](#)
- delete_notification_channel, [44](#)
- delete_object, [16](#)
- delete_open_id_connect_provider, [51](#)
- delete_permission, [13, 80](#)
- delete_permission_policy, [105, 109, 114](#)
- delete_permission_set, [96](#)
- delete_permission_version, [80](#)
- delete_permissions_boundary_from_permission_set, [96](#)
- delete_policy, [13, 44, 51](#)
- delete_policy_version, [51](#)
- delete_profile, [56](#)
- delete_protection, [90](#)
- delete_protection_group, [90](#)
- delete_protocols_list, [44](#)
- delete_publishing_destination, [47](#)
- delete_rate_based_rule, [105, 109](#)
- delete_regex_match_set, [105, 109](#)
- delete_regex_pattern_set, [105, 109, 114](#)
- delete_resource_policy, [83](#)
- delete_resource_server, [29](#)
- delete_resource_set, [44](#)
- delete_resource_share, [80](#)
- delete_role, [51](#)
- delete_role_permissions_boundary, [51](#)
- delete_role_policy, [51](#)
- delete_rule, [105, 109](#)
- delete_rule_group, [105, 109, 114](#)
- delete_saml_provider, [51](#)
- delete_schema, [16](#)
- delete_secret, [83](#)
- delete_server_certificate, [51](#)
- delete_service_linked_role, [51](#)
- delete_service_specific_credential, [51](#)
- delete_signing_certificate, [51](#)
- delete_size_constraint_set, [105, 109](#)
- delete_snapshot, [40](#)
- delete_sql_injection_match_set, [105, 109](#)
- delete_ssh_public_key, [51](#)
- delete_subscription, [90](#)
- delete_threat_intel_set, [47](#)
- delete_trust, [40](#)
- delete_trust_anchor, [56](#)
- delete_typed_link_facet, [16](#)
- delete_user, [29, 51, 59](#)
- delete_user_attributes, [29](#)
- delete_user_permissions_boundary, [51](#)
- delete_user_policy, [51](#)
- delete_user_pool, [29](#)
- delete_user_pool_client, [29](#)
- delete_user_pool_domain, [29](#)
- delete_virtual_mfa_device, [51](#)
- delete_web_acl, [105, 109, 114](#)
- delete_xss_match_set, [105, 109](#)
- deregister_certificate, [40](#)
- deregister_event_topic, [40](#)
- describe_account_assignment_creation_status, [96](#)
- describe_account_assignment_deletion_status, [96](#)
- describe_action_targets, [87](#)
- describe_all_managed_products, [114](#)
- describe_assessment_runs, [62](#)
- describe_assessment_targets, [62](#)
- describe_assessment_templates, [62](#)
- describe_attack, [90](#)
- describe_attack_statistics, [90](#)
- describe_backups, [22](#)
- describe_buckets, [76](#)
- describe_certificate, [10, 40](#)
- describe_certificate_authority, [13](#)
- describe_certificate_authority_audit_report, [13](#)
- describe_classification_job, [76](#)
- describe_client_authentication_settings, [40](#)
- describe_clusters, [22](#)

- describe_conditional_forwarders, [40](#)
- describe_cross_account_access_role, [62](#)
- describe_custom_key_stores, [69](#)
- describe_dataset, [33](#)
- describe_directories, [40](#)
- describe_domain_controllers, [40](#)
- describe_drt_access, [90](#)
- describe_emergency_contact_settings, [90](#)
- describe_event_topics, [40](#)
- describe_exclusions, [62](#)
- describe_findings, [62](#)
- describe_group, [59](#)
- describe_group_membership, [59](#)
- describe_hapg, [20](#)
- describe_hsm, [20](#)
- describe_hub, [87](#)
- describe_identity, [25](#)
- describe_identity_pool, [25](#)
- describe_identity_pool_usage, [33](#)
- describe_identity_provider, [29](#)
- describe_identity_usage, [33](#)
- describe_instance_access_control_attribute_configuration, [96](#)
- describe_key, [69](#)
- describe_ldaps_settings, [40](#)
- describe_luna_client, [20](#)
- describe_malware_scans, [47](#)
- describe_managed_products_by_vendor, [114](#)
- describe_managed_rule_group, [114](#)
- describe_organization_configuration, [37](#), [47](#), [65](#), [76](#), [87](#)
- describe_permission_set, [96](#)
- describe_permission_set_provisioning_status, [96](#)
- describe_products, [87](#)
- describe_protection, [90](#)
- describe_protection_group, [90](#)
- describe_publishing_destination, [47](#)
- describe_regions, [40](#)
- describe_resource_groups, [62](#)
- describe_resource_server, [29](#)
- describe_risk_configuration, [29](#)
- describe_rules_packages, [62](#)
- describe_secret, [83](#)
- describe_settings, [40](#)
- describe_shared_directories, [40](#)
- describe_snapshots, [41](#)
- describe_standards, [87](#)
- describe_standards_controls, [87](#)
- describe_subscription, [90](#)
- describe_trusts, [41](#)
- describe_update_directory, [41](#)
- describe_user, [59](#)
- describe_user_import_job, [29](#)
- describe_user_pool, [29](#)
- describe_user_pool_client, [29](#)
- describe_user_pool_domain, [29](#)
- detach_customer_managed_policy_reference_from_permission_set, [96](#)
- detach_from_index, [16](#)
- detach_group_policy, [51](#)
- detach_managed_policy_from_permission_set, [96](#)
- detach_object, [16](#)
- detach_policy, [16](#)
- detach_role_policy, [51](#)
- detach_typed_link, [16](#)
- detach_user_policy, [51](#)
- delegated_admin_account, [34](#)
- directoryservice, [38](#)
- disable, [65](#)
- disable_application_layer_automatic_response, [90](#)
- disable_client_authentication, [41](#)
- disable_crl, [56](#)
- disable_delegated_admin_account, [65](#)
- disable_directory, [16](#)
- disable_import_findings_for_product, [87](#)
- disable_key, [69](#)
- disable_key_rotation, [69](#)
- disable_ldaps, [41](#)
- disable_macie, [76](#)
- disable_organization_admin_account, [37](#), [47](#), [76](#), [87](#)
- disable_proactive_engagement, [90](#)
- disable_profile, [56](#)
- disable_radius, [41](#)
- disable_region, [8](#)
- disable_security_hub, [87](#)
- disable_sso, [41](#)
- disable_trust_anchor, [56](#)
- disassociate_admin_account, [44](#)
- disassociate_drt_log_bucket, [90](#)

- disassociate_drt_role, [91](#)
- disassociate_from_administrator_account, [47, 76, 87](#)
- disassociate_from_master_account, [47, 76, 87](#)
- disassociate_health_check, [91](#)
- disassociate_member, [65, 76](#)
- disassociate_member_account, [74](#)
- disassociate_members, [47, 87](#)
- disassociate_membership, [37](#)
- disassociate_resource_share, [80](#)
- disassociate_resource_share_permission, [80](#)
- disassociate_s3_resources, [74](#)
- disassociate_third_party_firewall, [44](#)
- disassociate_web_acl, [109, 114](#)
- disconnect_custom_key_store, [70](#)

- enable, [65](#)
- enable_application_layer_automatic_response, [91](#)
- enable_client_authentication, [41](#)
- enable_crl, [56](#)
- enable_delegated_admin_account, [65](#)
- enable_directory, [16](#)
- enable_import_findings_for_product, [87](#)
- enable_key, [70](#)
- enable_key_rotation, [70](#)
- enable_ldaps, [41](#)
- enable_macie, [76](#)
- enable_mfa_device, [51](#)
- enable_organization_admin_account, [37, 47, 76, 87](#)
- enable_proactive_engagement, [91](#)
- enable_profile, [56](#)
- enable_radius, [41](#)
- enable_region, [8](#)
- enable_security_hub, [87](#)
- enable_sharing_with_aws_organization, [80](#)
- enable_sso, [41](#)
- enable_trust_anchor, [56](#)
- encrypt, [67, 70](#)
- export_certificate, [10](#)

- fms, [42](#)
- forget_device, [29](#)
- forgot_password, [29](#)

- generate_credential_report, [51](#)
- generate_data_key, [67, 70](#)
- generate_data_key_pair, [70](#)
- generate_data_key_pair_without_plaintext, [70](#)
- generate_data_key_without_plaintext, [67, 70](#)
- generate_mac, [70](#)
- generate_mobile_sdk_release_url, [114](#)
- generate_organizations_access_report, [51](#)
- generate_random, [70](#)
- generate_service_last_accessed_details, [52](#)

- get_access_key_info, [102](#)
- get_access_key_last_used, [52](#)
- get_access_preview, [5](#)
- get_account_authorization_details, [52](#)
- get_account_configuration, [10](#)
- get_account_password_policy, [52](#)
- get_account_summary, [52](#)
- get_admin_account, [44](#)
- get_admin_scope, [44](#)
- get_administrator_account, [47, 76, 87](#)
- get_allow_list, [76](#)
- get_alternate_contact, [8](#)
- get_analyzed_resource, [5](#)
- get_analyzer, [5](#)
- get_applied_schema_version, [16](#)
- get_apps_list, [44](#)
- get_archive_rule, [5](#)
- get_assessment_report, [62](#)
- get_automated_discovery_configuration, [76](#)
- get_bucket_statistics, [76](#)
- get_bulk_publish_details, [33](#)
- get_byte_match_set, [105, 109](#)
- get_caller_identity, [102](#)
- get_certificate, [10, 13](#)
- get_certificate_authority_certificate, [13](#)
- get_certificate_authority_csr, [13](#)
- get_change_token, [105, 109](#)
- get_change_token_status, [105, 109](#)
- get_classification_export_configuration, [76](#)
- get_classification_scope, [76](#)
- get_cognito_events, [33](#)

- get_compliance_detail, [44](#)
- get_config, [20](#)
- get_configuration, [65](#)
- get_contact_information, [8](#)
- get_context_keys_for_custom_policy, [52](#)
- get_context_keys_for_principal_policy, [52](#)
- get_coverage_statistics, [47](#)
- get_credentials_report, [52](#)
- get_credentials_for_identity, [25](#)
- get_crl, [56](#)
- get_csv_header, [30](#)
- get_custom_data_identifier, [76](#)
- get_decrypted_api_key, [114](#)
- get_delegated_admin_account, [65](#)
- get_detector, [47](#)
- get_device, [30](#)
- get_directory, [16](#)
- get_directory_limits, [41](#)
- get_ec_2_deep_inspection_configuration, [65](#)
- get_enabled_standards, [87](#)
- get_encryption_key, [65](#)
- get_exclusions_preview, [62](#)
- get_facet, [16](#)
- get_federation_token, [102](#)
- get_filter, [47](#)
- get_finding, [5](#)
- get_finding_aggregator, [87](#)
- get_finding_history, [87](#)
- get_finding_statistics, [76](#)
- get_findings, [47](#), [76](#), [84](#), [87](#)
- get_findings_filter, [76](#)
- get_findings_publication_configuration, [76](#)
- get_findings_report_status, [65](#)
- get_findings_statistics, [47](#)
- get_generated_policy, [5](#)
- get_geo_match_set, [105](#), [109](#)
- get_group, [30](#), [52](#)
- get_group_id, [59](#)
- get_group_membership_id, [59](#)
- get_group_policy, [52](#)
- get_id, [25](#)
- get_identity_pool_configuration, [33](#)
- get_identity_pool_roles, [25](#)
- get_identity_provider_by_identifier, [30](#)
- get_inline_policy_for_permission_set, [96](#)
- get_insight_results, [87](#)
- get_insights, [87](#)
- get_instance_profile, [52](#)
- get_invitations_count, [48](#), [77](#), [87](#)
- get_ip_set, [48](#), [105](#), [109](#), [114](#)
- get_key_policy, [70](#)
- get_key_rotation_status, [70](#)
- get_link_attributes, [16](#)
- get_log_delivery_configuration, [30](#)
- get_logging_configuration, [105](#), [109](#), [114](#)
- get_login_profile, [52](#)
- get_macie_session, [77](#)
- get_malware_scan_settings, [48](#)
- get_managed_rule_set, [114](#)
- get_master_account, [48](#), [77](#), [87](#)
- get_member, [65](#), [77](#)
- get_member_detectors, [48](#)
- get_members, [37](#), [48](#), [87](#)
- get_mfa_device, [52](#)
- get_mobile_sdk_release, [114](#)
- get_notification_channel, [44](#)
- get_object_attributes, [17](#)
- get_object_information, [17](#)
- get_open_id_connect_provider, [52](#)
- get_open_id_token, [25](#)
- get_open_id_token_for_developer_identity, [25](#)
- get_organizations_access_report, [52](#)
- get_parameters_for_import, [70](#)
- get_permission, [80](#)
- get_permission_policy, [105](#), [109](#), [114](#)
- get_permissions_boundary_for_permission_set, [96](#)
- get_policy, [13](#), [44](#), [52](#)
- get_policy_version, [52](#)
- get_principal_tag_attribute_map, [25](#)
- get_profile, [56](#)
- get_protection_status, [44](#)
- get_protocols_list, [44](#)
- get_public_key, [70](#)
- get_random_password, [83](#)
- get_rate_based_rule, [105](#), [109](#)
- get_rate_based_rule_managed_keys, [105](#), [109](#)
- get_rate_based_statement_managed_keys, [114](#)

- get_regex_match_set, [105](#), [109](#)
- get_regex_pattern_set, [105](#), [109](#), [114](#)
- get_region_opt_status, [8](#)
- get_remaining_free_trial_days, [48](#)
- get_resource_policies, [80](#)
- get_resource_policy, [83](#)
- get_resource_profile, [77](#)
- get_resource_set, [44](#)
- get_resource_share_associations, [80](#)
- get_resource_share_invitations, [80](#)
- get_resource_shares, [80](#)
- get_reveal_configuration, [77](#)
- get_role, [52](#)
- get_role_credentials, [93](#)
- get_role_policy, [52](#)
- get_rule, [105](#), [109](#)
- get_rule_group, [105](#), [109](#), [114](#)
- get_saml_provider, [52](#)
- get_sampled_requests, [105](#), [109](#), [114](#)
- get_sbom_export, [65](#)
- get_schema_as_json, [17](#)
- get_secret_value, [83](#)
- get_sensitive_data_occurrences, [77](#)
- get_sensitive_data_occurrences_availability, [77](#)
- get_sensitivity_inspection_template, [77](#)
- get_server_certificate, [52](#)
- get_service_last_accessed_details, [52](#)
- get_service_last_accessed_details_with_entities, [52](#)
- get_service_linked_role_deletion_status, [52](#)
- get_session_token, [102](#)
- get_signing_certificate, [30](#)
- get_size_constraint_set, [105](#), [109](#)
- get_snapshot_limits, [41](#)
- get_sql_injection_match_set, [105](#), [109](#)
- get_ssh_public_key, [52](#)
- get_subject, [56](#)
- get_subscription_state, [91](#)
- get_telemetry_metadata, [62](#)
- get_third_party_firewall_association_status, [44](#)
- get_threat_intel_set, [48](#)
- get_trust_anchor, [57](#)
- get_typed_link_facet_information, [17](#)
- get_ui_customization, [30](#)
- get_usage_statistics, [48](#), [77](#)
- get_usage_totals, [77](#)
- get_user, [30](#), [52](#)
- get_user_attribute_verification_code, [30](#)
- get_user_id, [59](#)
- get_user_policy, [52](#)
- get_user_pool_mfa_config, [30](#)
- get_violation_details, [44](#)
- get_web_acl, [105](#), [109](#), [114](#)
- get_web_acl_for_resource, [110](#), [114](#)
- get_xss_match_set, [105](#), [110](#)
- global_sign_out, [30](#)
- guardduty, [45](#)
- iam, [49](#)
- iamrolesanywhere, [54](#)
- identitystore, [57](#)
- import_certificate, [10](#)
- import_certificate_authority_certificate, [13](#)
- import_crl, [57](#)
- import_key_material, [70](#)
- initialize_cluster, [22](#)
- initiate_auth, [30](#)
- inspector, [60](#)
- inspector2, [63](#)
- invite_members, [48](#), [87](#)
- is_member_in_groups, [59](#)
- issue_certificate, [13](#)
- kms, [66](#)
- list_access_keys, [52](#)
- list_access_preview_findings, [5](#)
- list_access_previews, [6](#)
- list_account_aliases, [52](#)
- list_account_assignment_creation_status, [96](#)
- list_account_assignment_deletion_status, [96](#)
- list_account_assignments, [96](#)
- list_account_permissions, [65](#)
- list_account_roles, [93](#)
- list_accounts, [93](#)
- list_accounts_for_provisioned_permission_set, [96](#)
- list_activated_rules_in_rule_group, [105](#), [110](#)

- `list_admin_accounts_for_organization`,
44
- `list_admins_managing_account`, 44
- `list_aliases`, 70
- `list_allow_lists`, 77
- `list_analyzed_resources`, 6
- `list_analyzers`, 6
- `list_api_keys`, 114
- `list_applied_schema_arns`, 17
- `list_apps_lists`, 44
- `list_archive_rules`, 6
- `list_assessment_run_agents`, 62
- `list_assessment_runs`, 62
- `list_assessment_targets`, 62
- `list_assessment_templates`, 62
- `list_attached_group_policies`, 52
- `list_attached_indices`, 17
- `list_attached_role_policies`, 52
- `list_attached_user_policies`, 52
- `list_attacks`, 91
- `list_automation_rules`, 87
- `list_available_managed_rule_group_versions`,
114
- `list_available_managed_rule_groups`,
114
- `list_available_zones`, 20
- `list_byte_match_sets`, 105, 110
- `list_certificate_authorities`, 13
- `list_certificates`, 10, 41
- `list_classification_jobs`, 77
- `list_classification_scopes`, 77
- `list_compliance_status`, 44
- `list_coverage`, 48, 65
- `list_coverage_statistics`, 65
- `list_crls`, 57
- `list_custom_data_identifiers`, 77
- `list_customer_managed_policy_references_in_permission_set`,
96
- `list_datasets`, 34
- `list_datasource_packages`, 37
- `list_delegated_admin_accounts`, 66
- `list_detectors`, 48
- `list_development_schema_arns`, 17
- `list_devices`, 30
- `list_directories`, 17
- `list_discovered_resources`, 44
- `list_enabled_products_for_import`, 87
- `list_entities_for_policy`, 52
- `list_event_subscriptions`, 62
- `list_exclusions`, 62
- `list_facet_attributes`, 17
- `list_facet_names`, 17
- `list_filters`, 48, 66
- `list_finding_aggregations`, 66
- `list_finding_aggregators`, 87
- `list_findings`, 6, 48, 62, 66, 77
- `list_findings_filters`, 77
- `list_geo_match_sets`, 105, 110
- `list_grants`, 70
- `list_graphs`, 37
- `list_group_memberships`, 59
- `list_group_memberships_for_member`, 59
- `list_group_policies`, 52
- `list_groups`, 30, 52, 59
- `list_groups_for_user`, 52
- `list_hapgs`, 20
- `list_hsms`, 20
- `list_identities`, 25
- `list_identity_pool_usage`, 34
- `list_identity_pools`, 25
- `list_identity_providers`, 30
- `list_incoming_typed_links`, 17
- `list_index`, 17
- `list_instance_profile_tags`, 52
- `list_instance_profiles`, 52
- `list_instance_profiles_for_role`, 52
- `list_instances`, 96
- `list_invitations`, 37, 48, 77, 88
- `list_ip_routes`, 41
- `list_ip_sets`, 48, 105, 110, 114
- `list_key_policies`, 70
- `list_keys`, 70
- `list_log_subscriptions`, 41
- `list_logging_configurations`, 105, 110,
- `list_managed_data_identifiers`, 77
- `list_managed_policies_in_permission_set`,
96
- `list_managed_rule_sets`, 114
- `list_managed_schema_arns`, 17
- `list_member_accounts`, 44, 74
- `list_members`, 37, 48, 66, 77, 88
- `list_mfa_device_tags`, 52
- `list_mfa_devices`, 52
- `list_mobile_sdk_releases`, 114

- [list_object_attributes](#), [17](#)
- [list_object_children](#), [17](#)
- [list_object_parent_paths](#), [17](#)
- [list_object_parents](#), [17](#)
- [list_object_policies](#), [17](#)
- [list_open_id_connect_provider_tags](#), [52](#)
- [list_open_id_connect_providers](#), [52](#)
- [list_organization_admin_accounts](#), [37](#), [48](#), [77](#), [88](#)
- [list_outgoing_typed_links](#), [17](#)
- [list_pending_invitation_resources](#), [80](#)
- [list_permission_associations](#), [80](#)
- [list_permission_set_provisioning_status](#), [96](#)
- [list_permission_sets](#), [96](#)
- [list_permission_sets_provisioned_to_account](#), [96](#)
- [list_permission_versions](#), [80](#)
- [list_permissions](#), [13](#), [80](#)
- [list_policies](#), [44](#), [52](#)
- [list_policies_granting_service_access](#), [52](#)
- [list_policy_attachments](#), [17](#)
- [list_policy_generations](#), [6](#)
- [list_policy_tags](#), [52](#)
- [list_policy_versions](#), [52](#)
- [list_principals](#), [80](#)
- [list_profiles](#), [57](#)
- [list_protection_groups](#), [91](#)
- [list_protections](#), [91](#)
- [list_protocols_lists](#), [44](#)
- [list_published_schema_arns](#), [17](#)
- [list_publishing_destinations](#), [48](#)
- [list_rate_based_rules](#), [105](#), [110](#)
- [list_records](#), [34](#)
- [list_regex_match_sets](#), [106](#), [110](#)
- [list_regex_pattern_sets](#), [106](#), [110](#), [114](#)
- [list_regions](#), [8](#)
- [list_replace_permission_associations_work](#), [80](#)
- [list_resource_profile_artifacts](#), [77](#)
- [list_resource_profile_detections](#), [77](#)
- [list_resource_servers](#), [30](#)
- [list_resource_set_resources](#), [44](#)
- [list_resource_sets](#), [44](#)
- [list_resource_share_permissions](#), [80](#)
- [list_resource_tags](#), [70](#)
- [list_resource_types](#), [80](#)
- [list_resources](#), [80](#)
- [list_resources_for_web_acl](#), [110](#), [114](#)
- [list_resources_in_protection_group](#), [91](#)
- [list_retirable_grants](#), [70](#)
- [list_role_policies](#), [52](#)
- [list_role_tags](#), [53](#)
- [list_roles](#), [53](#)
- [list_rule_groups](#), [106](#), [110](#), [114](#)
- [list_rules](#), [106](#), [110](#)
- [list_rules_packages](#), [62](#)
- [list_s3_resources](#), [74](#)
- [list_saml_provider_tags](#), [53](#)
- [list_saml_providers](#), [53](#)
- [list_schema_extensions](#), [41](#)
- [list_secret_version_ids](#), [73](#)
- [list_secrets](#), [83](#)
- [list_security_control_definitions](#), [88](#)
- [list_sensitivity_inspection_templates](#), [77](#)
- [list_server_certificate_tags](#), [53](#)
- [list_server_certificates](#), [53](#)
- [list_service_specific_credentials](#), [53](#)
- [list_signing_certificates](#), [53](#)
- [list_size_constraint_sets](#), [106](#), [110](#)
- [list_sql_injection_match_sets](#), [106](#), [110](#)
- [list_ssh_public_keys](#), [53](#)
- [list_standards_control_associations](#), [88](#)
- [list_subjects](#), [57](#)
- [list_subscribed_rule_groups](#), [106](#), [110](#)
- [list_tags](#), [13](#), [22](#)
- [list_tags_for_certificate](#), [11](#)
- [list_tags_for_resource](#), [6](#), [17](#), [20](#), [25](#), [30](#), [37](#), [41](#), [44](#), [48](#), [57](#), [62](#), [66](#), [77](#), [88](#), [91](#), [96](#), [106](#), [110](#), [114](#)
- [list_third_party_firewall_firewall_policies](#), [44](#)
- [list_threat_intel_sets](#), [48](#)
- [list_trust_anchors](#), [57](#)
- [list_typed_link_facet_attributes](#), [17](#)
- [list_typed_link_facet_names](#), [17](#)
- [list_usage_totals](#), [66](#)
- [list_user_import_jobs](#), [30](#)
- [list_user_policies](#), [53](#)
- [list_user_pool_clients](#), [30](#)
- [list_user_pools](#), [30](#)
- [list_user_tags](#), [53](#)
- [list_users](#), [30](#), [53](#), [59](#)

list_users_in_group, [30](#)
list_virtual_mfa_devices, [53](#)
list_web_ac_ls, [106](#), [110](#), [114](#)
list_xss_match_sets, [106](#), [110](#)
logout, [93](#)
lookup_developer_identity, [25](#)
lookup_policy, [17](#)

macie, [71](#)
macie2, [74](#)
merge_developer_identities, [25](#)
modify_backup_attributes, [22](#)
modify_cluster, [22](#)
modify_hapg, [20](#)
modify_hsm, [20](#)
modify_luna_client, [20](#)

preview_agents, [62](#)
promote_permission_created_from_policy, [80](#)
promote_resource_share_created_from_policy, [80](#)
provision_permission_set, [96](#)
publish_schema, [17](#)
put_account_configuration, [11](#)
put_admin_account, [44](#)
put_alternate_contact, [8](#)
put_apps_list, [44](#)
put_classification_export_configuration, [77](#)
put_contact_information, [8](#)
put_findings_publication_configuration, [77](#)
put_group_policy, [53](#)
put_inline_policy_to_permission_set, [96](#)
put_key_policy, [70](#)
put_logging_configuration, [106](#), [110](#), [114](#)
put_managed_rule_set_versions, [114](#)
put_notification_channel, [44](#)
put_notification_settings, [57](#)
put_permission_policy, [106](#), [110](#), [114](#)
put_permissions_boundary_to_permission_set, [96](#)
put_policy, [13](#), [44](#)
put_protocols_list, [44](#)
put_resource_policy, [83](#)
put_resource_set, [44](#)
put_role_permissions_boundary, [53](#)
put_role_policy, [53](#)
put_schema_from_json, [17](#)
put_secret_value, [83](#)
put_user_permissions_boundary, [53](#)
put_user_policy, [53](#)

ram, [78](#)
re_encrypt, [70](#)
register_certificate, [41](#)
register_client, [99](#)
register_cross_account_access_role, [62](#)
register_device, [34](#)
register_event_topic, [41](#)
reject_invitation, [37](#)
reject_resource_share_invitation, [80](#)
reject_shared_directory, [41](#)
remove_attributes_from_findings, [62](#)
remove_client_id_from_open_id_connect_provider, [53](#)
remove_facet_from_object, [17](#)
remove_ip_routes, [41](#)
remove_region, [41](#)
remove_regions_from_replication, [83](#)
remove_role_from_instance_profile, [53](#)
remove_tags_from_certificate, [11](#)
remove_tags_from_resource, [20](#), [41](#)
remove_user_from_group, [53](#)
renew_certificate, [11](#)
replace_permission_associations, [80](#)
replicate_key, [70](#)
replicate_secret_to_regions, [83](#)
request_certificate, [11](#)
resend_confirmation_code, [30](#)
resend_validation_email, [11](#)
reset_encryption_key, [66](#)
reset_notification_settings, [57](#)
reset_service_specific_credential, [53](#)
reset_user_password, [41](#)
respond_to_auth_challenge, [30](#)
restore_backup, [22](#)
restore_certificate_authority, [13](#)
restore_from_snapshot, [41](#)
restore_secret, [83](#)
resync_mfa_device, [53](#)
retire_grant, [70](#)
revoke_certificate, [13](#)
revoke_grant, [70](#)
revoke_token, [30](#)
rotate_secret, [83](#)

- schedule_key_deletion, 70
- search_resources, 77
- search_vulnerabilities, 66
- secretsmanager, 81
- securityhub, 84
- set_cognito_events, 34
- set_default_permission_version, 80
- set_default_policy_version, 53
- set_identity_pool_configuration, 34
- set_identity_pool_roles, 25
- set_log_delivery_configuration, 30
- set_principal_tag_attribute_map, 25
- set_risk_configuration, 30
- set_security_token_service_preferences, 53
- set_tags_for_resource, 62
- set_ui_customization, 30
- set_user_mfa_preference, 30
- set_user_pool_mfa_config, 30
- set_user_settings, 30
- share_directory, 41
- shield, 88
- sign, 70
- sign_up, 30
- simulate_custom_policy, 53
- simulate_principal_policy, 53
- sso, 91
- ssoadmin, 94
- ssooidc, 97
- start_assessment_run, 62
- start_device_authorization, 99
- start_malware_scan, 48
- start_monitoring_member, 37
- start_monitoring_members, 48
- start_policy_generation, 6
- start_resource_scan, 6
- start_schema_extension, 41
- start_user_import_job, 30
- stop_assessment_run, 62
- stop_monitoring_members, 48
- stop_replication_to_replica, 83
- stop_user_import_job, 30
- sts, 100
- subscribe_to_dataset, 34
- subscribe_to_event, 62
- tag_certificate_authority, 14
- tag_instance_profile, 53
- tag_mfa_device, 53
- tag_open_id_connect_provider, 53
- tag_policy, 53
- tag_resource, 6, 17, 22, 25, 30, 37, 44, 48, 57, 66, 70, 77, 80, 83, 88, 91, 97, 106, 110, 114
- tag_role, 53
- tag_saml_provider, 53
- tag_server_certificate, 53
- tag_user, 53
- test_custom_data_identifier, 77
- unarchive_findings, 48
- unlink_developer_identity, 25
- unlink_identity, 26
- unshare_directory, 41
- unsubscribe_from_dataset, 34
- unsubscribe_from_event, 62
- untag_certificate_authority, 14
- untag_instance_profile, 53
- untag_mfa_device, 53
- untag_open_id_connect_provider, 53
- untag_policy, 53
- untag_resource, 6, 17, 23, 26, 30, 37, 44, 48, 57, 66, 70, 77, 80, 83, 88, 91, 97, 106, 110, 114
- untag_role, 53
- untag_saml_provider, 53
- untag_server_certificate, 53
- untag_user, 53
- update_access_key, 53
- update_account_password_policy, 53
- update_action_target, 88
- update_alias, 70
- update_allow_list, 77
- update_application_layer_automatic_response, 91
- update_archive_rule, 6
- update_assessment_target, 62
- update_assume_role_policy, 53
- update_auth_event_feedback, 30
- update_automated_discovery_configuration, 77
- update_byte_match_set, 106, 110
- update_certificate_authority, 14
- update_certificate_options, 11
- update_classification_job, 77
- update_classification_scope, 77
- update_conditional_forwarder, 41
- update_configuration, 66

- update_crl, [57](#)
- update_custom_key_store, [70](#)
- update_datasource_packages, [37](#)
- update_detector, [48](#)
- update_device_status, [30](#)
- update_directory_setup, [41](#)
- update_ec_2_deep_inspection_configuration, [66](#)
- update_emergency_contact_settings, [91](#)
- update_encryption_key, [66](#)
- update_facet, [17](#)
- update_filter, [48, 66](#)
- update_finding_aggregator, [88](#)
- update_findings, [6, 88](#)
- update_findings_feedback, [48](#)
- update_findings_filter, [77](#)
- update_geo_match_set, [106, 110](#)
- update_group, [30, 53, 59](#)
- update_identity_pool, [26](#)
- update_identity_provider, [30](#)
- update_insight, [88](#)
- update_instance_access_control_attribute_configuration, [97](#)
- update_ip_set, [48, 106, 110, 114](#)
- update_key_description, [70](#)
- update_link_attributes, [17](#)
- update_login_profile, [53](#)
- update_macie_session, [77](#)
- update_malware_scan_settings, [48](#)
- update_managed_rule_set_version_expiry_date, [114](#)
- update_member_detectors, [48](#)
- update_member_session, [77](#)
- update_number_of_domain_controllers, [41](#)
- update_object_attributes, [17](#)
- update_open_id_connect_provider_thumbprint, [54](#)
- update_org_ec_2_deep_inspection_configuration, [66](#)
- update_organization_configuration, [37, 48, 66, 77, 88](#)
- update_permission_set, [97](#)
- update_primary_region, [70](#)
- update_profile, [57](#)
- update_protection_group, [91](#)
- update_publishing_destination, [48](#)
- update_radius, [41](#)
- update_rate_based_rule, [106, 110](#)
- update_records, [34](#)
- update_regex_match_set, [106, 110](#)
- update_regex_pattern_set, [106, 110, 114](#)
- update_resource_profile, [77](#)
- update_resource_profile_detections, [77](#)
- update_resource_server, [30](#)
- update_resource_share, [80](#)
- update_reveal_configuration, [77](#)
- update_role, [54](#)
- update_role_description, [54](#)
- update_rule, [106, 110](#)
- update_rule_group, [106, 110, 114](#)
- update_s3_resources, [74](#)
- update_saml_provider, [54](#)
- update_schema, [17](#)
- update_secret, [83](#)
- update_secret_version_stage, [84](#)
- update_security_hub_configuration, [88](#)
- update_sensitivity_inspection_template, [77](#)
- update_server_certificate, [54](#)
- update_service_specific_credential, [54](#)
- update_settings, [41](#)
- update_signing_certificate, [54](#)
- update_size_constraint_set, [106, 110](#)
- update_sql_injection_match_set, [106, 110](#)
- update_ssh_public_key, [54](#)
- update_standards_control, [85, 88](#)
- update_subscription, [91](#)
- update_threat_intel_set, [48](#)
- update_trust, [41](#)
- update_trust_anchor, [57](#)
- update_typed_link_facet, [17](#)
- update_user, [54, 59](#)
- update_user_attributes, [30](#)
- update_user_pool, [30](#)
- update_user_pool_client, [30](#)
- update_user_pool_domain, [30](#)
- update_web_acl, [106, 110, 114](#)
- update_xss_match_set, [106, 110](#)
- upgrade_applied_schema, [17](#)
- upgrade_published_schema, [17](#)
- upload_server_certificate, [54](#)
- upload_signing_certificate, [54](#)
- upload_ssh_public_key, [54](#)
- validate_policy, [6](#)

validate_resource_policy, [84](#)
verify, [70](#)
verify_mac, [70](#)
verify_software_token, [30](#)
verify_trust, [41](#)
verify_user_attribute, [30](#)

waf, [102](#)
wafregional, [106](#)
wafv2, [111](#)