

Package ‘wakefield’

September 13, 2020

Title Generate Random Data Sets

Version 0.3.6

Maintainer Tyler Rinker <tyler.rinker@gmail.com>

Description Generates random data sets including: data.frames, lists, and vectors.

Depends R (>= 3.2.0)

Imports chron, ggplot2, dplyr, stringi

Suggests testthat

License GPL-2

LazyData TRUE

URL <https://github.com/trinker/wakefield>

BugReports <https://github.com/trinker/wakefield/issues>

Collate 'utils.R' 'r_sample.R' 'age.R' 'r_sample_factor.R' 'animal.R' 'r_sample_binary.R' 'answer.R' 'area.R' 'as_integer.R' 'car.R' 'children.R' 'coin.R' 'color.R' 'date_stamp.R' 'r_sample_logical.R' 'death.R' 'dice.R' 'dna.R' 'dob.R' 'dummy.R' 'education.R' 'employment.R' 'eye.R' 'grade.R' 'grade_level.R' 'group.R' 'hair.R' 'normal.R' 'height.R' 'hour.R' 'id.R' 'income.R' 'internet_browser.R' 'interval.R' 'iq.R' 'language.R' 'level.R' 'r_sample_ordered.R' 'likert.R' 'lorem_ipsum.R' 'marital.R' 'military.R' 'minute.R' 'month.R' 'r_sample_replace.R' 'wakefield-package.R' 'name.R' 'peek.R' 'political.R' 'probs.R' 'r_data.R' 'r_data_frame.R' 'r_dummy.R' 'seriesname.R' 'r_insert.R' 'r_list.R' 'r_na.R' 'r_sample_integer.R' 'r_series.R' 'race.R' 'relate.R' 'religion.R' 'sat.R' 'second.R' 'sentence.R' 'sex.R' 'sex_inclusive.R' 'smokes.R' 'speed.R' 'state.R' 'string.R' 'table_heat.R' 'time_stamp.R' 'upper.R' 'valid.R' 'variables.R' 'varname.R' 'year.R' 'zip_code.R'

RoxygenNote 7.1.1

NeedsCompilation no

Author Tyler Rinker [aut, cre],
 Josh O'Brien [ctb],
 Ananda Mahto [ctb],
 Matthew Sigal [ctb],
 Jonathan Carroll [ctb],
 Scott Westenberger [ctb]

Repository CRAN

Date/Publication 2020-09-13 17:30:02 UTC

R topics documented:

| | |
|----------------------------|----|
| age | 4 |
| animal | 5 |
| animal_list | 6 |
| answer | 6 |
| area | 7 |
| as_integer | 8 |
| car | 9 |
| children | 10 |
| coin | 11 |
| color | 12 |
| date_stamp | 13 |
| death | 14 |
| dice | 15 |
| dna | 16 |
| dob | 17 |
| dummy | 18 |
| education | 19 |
| employment | 20 |
| eye | 22 |
| grade | 23 |
| grade_level | 24 |
| grady_augmented | 25 |
| group | 26 |
| hair | 27 |
| height | 28 |
| hour | 30 |
| id | 31 |
| income | 32 |
| internet_browser | 33 |
| interval | 34 |
| iq | 35 |
| language | 36 |
| languages | 37 |
| level | 38 |
| likert | 39 |
| lorem_ipsum | 40 |

| | |
|-------------------------------------|----|
| marital | 41 |
| military | 42 |
| minute | 43 |
| month | 44 |
| name | 45 |
| name_neutral | 46 |
| normal | 47 |
| peek | 48 |
| plot.tbl_df | 49 |
| political | 50 |
| presidential_debates_2012 | 51 |
| print.available | 51 |
| print.variable | 52 |
| probs | 52 |
| race | 53 |
| relate | 54 |
| religion | 55 |
| r_data | 57 |
| r_data_frame | 58 |
| r_dummy | 60 |
| r_insert | 61 |
| r_list | 62 |
| r_na | 63 |
| r_sample | 64 |
| r_sample_binary | 65 |
| r_sample_factor | 66 |
| r_sample_integer | 67 |
| r_sample_logical | 68 |
| r_sample_ordered | 68 |
| r_sample_replace | 69 |
| r_series | 70 |
| sat | 72 |
| second | 73 |
| sentence | 74 |
| seriesname | 75 |
| sex | 75 |
| sex_inclusive | 76 |
| smokes | 78 |
| speed | 79 |
| state | 80 |
| state_populations | 83 |
| string | 83 |
| table_heat | 84 |
| time_stamp | 85 |
| upper | 86 |
| valid | 88 |
| variables | 89 |
| varname | 90 |

| | |
|---------------------|----|
| wakefield | 90 |
| year | 91 |
| zip_code | 92 |

| | |
|--------------|-----------|
| Index | 93 |
|--------------|-----------|

| | |
|-----|---------------------------------------|
| age | <i>Generate Random Vector of Ages</i> |
|-----|---------------------------------------|

Description

Generate a random vector of ages within the provided range. The default age range is set between 18 and 89, to match the age ranges which appear (see e.g., <https://gssdataexplorer.norc.org/variables/53/vshow>).

Usage

```
age(n, x = 18:89, prob = NULL, name = "Age")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random integer vector of ages within the provided range (defaults to 18:89).

See Also

Other variable functions: `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `internet_browser()`, `iq()`, `language`, `level()`, `likert()`, `lorem_ipsum()`, `marital()`, `military()`, `month()`, `name`, `normal()`, `political()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
age(10) # draw 10 ages with default values
hist(age(n=10000))
interval(age, 3, n = 1000)
```

| | |
|--------|--|
| animal | <i>Generate Random Vector of animals</i> |
|--------|--|

Description

animal - Generate a random vector of animals.

pet - Generate a random vector of pets.

Usage

```
animal(n, k = 10, x = wakefield::animal_list, prob = NULL, name = "Animal")
```

```
pet(  
  n,  
  x = c("Dog", "Cat", "None", "Bird", "Horse"),  
  prob = c(0.365, 0.304, 0.258, 0.031, 0.015),  
  name = "Pet"  
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| k | The number of the elements of <code>x</code> to sample from (uses <code>sample(x,k)</code>). |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The household pets and probabilities:

| | |
|-------|--------|
| Dog | 36.5 % |
| Cat | 30.4 % |
| None | 25.8 % |
| Bird | 3.1 % |
| Horse | 1.5 % |

Value

Returns a random factor vector of animal elements.

See Also

Other variable functions: [age\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
animal(10)
pie(table(animal(10000)))

pet(10)
pie(table(pet(10000)))
```

animal_list

Animal List

Description

A dataset containing a character vector animals

Usage

```
data(animal_list)
```

Format

A character vector with 591 elements

References

<https://a-z-animals.com/animals>

answer

Generate Random Vector of Answers (Yes/No)

Description

Generate a random vector of answers (yes/no).

Usage

```
answer(n, x = c("No", "Yes"), prob = NULL, name = "Answer")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of answers to sample from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of answers (yes/no) outcome elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
answer(10)
100*table(answer(n <- 10000))/n
```

| | |
|------|--|
| area | <i>Generate Random Vector of Areas</i> |
|------|--|

Description

Generate a random vector of areas ("Suburban", "Urban", "Rural").

Usage

```
area(n, x = c("Suburban", "Urban", "Rural"), prob = NULL, name = "Area")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of area status elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
area(10)
barplot(table(area(10000)))
```

as_integer

Convert a Factor Data Frame to Integer

Description

Converts a [data.frame](#) of [factors](#) to integers.

Usage

```
as_integer(x, cols = NULL, fun = as.integer)
```

Arguments

| | |
|------|---|
| x | A data.frame of factors . |
| cols | Numeric indices of the columns to include (use - to exclude as well). Default is to assign random NAs to all columns except the first column. |
| fun | An as. coercion function to apply to each column. Default is as.integer . |

Value

Returns a [data.frame](#) equal to the [class](#) of x with integer columns rather than factor.

See Also

[r_series](#)

Examples

```

as_integer(r_series(likert_7, 5, 10))
as_integer(r_series(likert_7, 5, 10), cols = c(2, 4))

library(dplyr)
r_data_frame(n=100,
  age,
  political,
  sex,
  grade
) %>%
  as_integer(2:3)

```

| | |
|-----|---------------------------------------|
| car | <i>Generate Random Vector of Cars</i> |
|-----|---------------------------------------|

Description

Generate a random vector of cars (see [?mtcars](#)).

Usage

```
car(n, x = rownames(datasets::mtcars), prob = NULL, name = "Car")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of car elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
car(10)
table(car(10000))
```

children

Generate Random Vector of Number of Children

Description

Generate a random vector of number of children.

Usage

```
children(
  n,
  x = 0:10,
  prob = c(0.25, 0.25, 0.15, 0.15, 0.1, 0.02, 0.02, 0.02, 0.02, 0.01, 0.01),
  name = "Children"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of number of children elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
children(10)
pie(table(children(100)))
```

| | |
|------|---|
| coin | <i>Generate Random Vector of Coin Flips</i> |
|------|---|

Description

Generate a random vector of coin flips (heads/tails).

Usage

```
coin(n, x = c("Tails", "Heads"), prob = NULL, name = "Coin")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of coin outcomes to sample from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of coin flip outcome elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
coin(10)
100*table(coin(n <- 10000))/n
```

color *Generate Random Vector of Colors*

Description

color - Generate a random vector of colors (sampled from colors()).

color - Generate a random vector of *psychological primary* colors (sampled from colors()).

Usage

```
color(n, k = 10, x = grDevices::colors(), prob = NULL, name = "Color")
```

```
primary(
  n,
  x = c("Red", "Green", "Blue", "Yellow", "Black", "White"),
  prob = NULL,
  name = "Color"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| k | The number of the elements of <code>x</code> to sample from (uses <code>sample(x,k)</code>). |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of color elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language_level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name_normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```

color(10)
pie(tab <- table(color(10000)), col = names(tab))

primary(10)
pie(tab <- table(primary(10000)), col = names(tab))
barplot(tab <- table(primary(10000, prob = probs(6))), col = names(tab))

```

date_stamp

Generate Random Vector of Dates

Description

Generate a random vector of dates.

Usage

```

date_stamp(
  n,
  random = FALSE,
  x = NULL,
  start = Sys.Date(),
  k = 12,
  by = "-1 months",
  prob = NULL,
  name = "Date"
)

```

Arguments

| | |
|--------|---|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| random | logical. If TRUE the dates are randomized, otherwise the dates are sequential. |
| x | A vector of elements to chose from. This may be NULL if arguments are supplied to start, k, and by. The x argument takes precedence over the other three if !is.null. Note that start, k, and by work together to make a vector of dates to sample from. See seq.Date for additional information. |
| start | A date to start the sequence at. |
| k | The length of the sequence (number of the elements) so build out from start. |
| by | The interval to use in building the sequence. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's varname attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of date elements.

See Also

[seq.Date](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
date_stamp(10)
pie(table(date_stamp(2000, prob = probs(12))))

## Supply dates to `x` to sample from
date_stamp(10, x = seq(as.Date("1980-11-16"), length = 30, by = "1 years"))
```

death

Generate Random Vector of Deaths Outcomes

Description

Generate a random logical vector of deaths (TRUE/FALSE).

Usage

```
death(n, prob = NULL, name = "Death")

died(n, prob = NULL, name = "Died")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random logical vector of death outcome elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
death(10)
died(10)
100*table(death(n <- 10000))/n
100*table(death(n <- 10000, prob = c(.3, .7)))/n
r_data_frame(10, died)
```

dice

*Generate Random Vector of Dice Throws***Description**

Generate a random vector of dice throws.

Usage

```
dice(n, x = 1:6, prob = NULL, name = "Dice")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of dice throw elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```

dice(10)
barplot(table(dice(10000)))

```

dna

*Generate Random Vector of DNA Nucleobases***Description**

Generate a random vector of DNA nucleobases ("Guanine", "Adenine", "Thymine", "Cytosine").

Usage

```

dna(
  n,
  x = c("Guanine", "Adenine", "Thymine", "Cytosine"),
  prob = NULL,
  name = "DNA"
)

```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of DNA nucleobase elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```

dna(10)
barplot(table(dna(10000)))

```

`dob`*Generate Random Vector of Birth Dates*

Description

Generate a random vector of birth dates.

Usage

```
dob(  
  n,  
  random = TRUE,  
  x = NULL,  
  start = Sys.Date() - 365 * 15,  
  k = 365 * 2,  
  by = "1 days",  
  prob = NULL,  
  name = "DOB"  
)  
  
birth(  
  n,  
  random = TRUE,  
  x = NULL,  
  start = Sys.Date() - 365 * 15,  
  k = 365 * 2,  
  by = "1 days",  
  prob = NULL,  
  name = "Birth"  
)
```

Arguments

| | |
|---------------------|---|
| <code>n</code> | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| <code>random</code> | logical. If TRUE the dates are randomized, otherwise the dates are sequential. |
| <code>x</code> | A vector of elements to chose from. This may be NULL if arguments are supplied to <code>start</code> , <code>k</code> , and <code>by</code> . The <code>x</code> argument takes precedence over the other three if <code>!is.null</code> . Note that <code>start</code> , <code>k</code> , and <code>by</code> work together to make a vector of dates to sample from. See seq.Date for additional information. |
| <code>start</code> | A date to start the sequence at. |
| <code>k</code> | The length of the sequence (number of the elements) so build out from <code>start</code> . |
| <code>by</code> | The interval to use in building the sequence. |
| <code>prob</code> | A vector of probabilities to chose from. |

name The name to assign to the output vector's varname attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Value

Returns a random vector of birth date elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
dob(10)
barplot(table(birth(15)))
barplot(table(birth(30)))
```

dummy

Generate Random Dummy Coded Vector

Description

Generate a random dummy coded (0/1) vector.

Usage

```
dummy(n, prob = NULL, name = "Dummy")
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's varname attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Value

Returns a random dummy vector of (0/1) elements.

See Also

[sample.int](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
dummy(100, name = "Var")
table(dummy(1000))
```

education

Generate Random Vector of Educational Attainment Level

Description

Generate a random vector of educational attainment level.

Usage

```
education(
  n,
  x = c("No Schooling Completed", "Nursery School to 8th Grade",
        "9th Grade to 12th Grade, No Diploma", "Regular High School Diploma",
        "GED or Alternative Credential", "Some College, Less than 1 Year",
        "Some College, 1 or More Years, No Degree", "Associate's Degree",
        "Bachelor's Degree", "Master's Degree", "Professional School Degree",
        "Doctorate Degree"),
  prob = c(0.013, 0.05, 0.085, 0.246, 0.039, 0.064, 0.15, 0.075, 0.176, 0.072, 0.019,
           0.012),
  name = "Education"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The educational attainments and probabilities used match approximate U.S. educational attainment make-up (<http://www.census.gov>):

| Highest Attainment | Percent |
|--|----------------|
| No Schooling Completed | 1.3 % |
| Nursery School to 8th Grade | 5 % |
| 9th Grade to 12th Grade, No Diploma | 8.5 % |
| Regular High School Diploma | 24.6 % |
| GED or Alternative Credential | 3.9 % |
| Some College, Less than 1 Year | 6.4 % |
| Some College, 1 or More Years, No Degree | 15 % |
| Associate's Degree | 7.5 % |
| Bachelor's Degree | 17.6 % |
| Master's Degree | 7.2 % |
| Professional School Degree | 1.9 % |
| Doctorate Degree | 1.2 % |

Value

Returns a random vector of educational attainment level elements.

References

<http://www.census.gov>

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
education(10)
pie(table(education(10000)))
```

employment

Generate Random Vector of Employment Statuses

Description

Generate a random vector of employment statuses.

Usage

```
employment(
  n,
  x = c("Full Time", "Part Time", "Unemployed", "Retired", "Student"),
  prob = c(0.6, 0.1, 0.1, 0.1, 0.1),
  name = "Employment"
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of elements to chose from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The following arbitrary probabilities are used:

| Employment Status | Percent |
|--------------------------|----------------|
| Full Time | 60% |
| Part Time | 10% |
| Unemployed | 10% |
| Retired | 10% |
| Student | 10% |

Value

Returns a random vector of employment status elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
employment(10)
pie(table(employment(10000)))
barplot(table(employment(10000)))
```

eye

Generate Random Vector of Eye Colors

Description

Generate a random vector of eye colors.

Usage

```
eye(  
  n,  
  x = c("Brown", "Blue", "Green", "Hazel", "Gray"),  
  prob = c(0.44, 0.3, 0.13, 0.09, 0.04),  
  name = "Eye"  
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The eye colors and probabilities:

| Color | Percent |
|-------|---------|
| Brown | 44 % |
| Blue | 30 % |
| Green | 13 % |
| Hazel | 9 % |
| Gray | 4 % |

Value

Returns a random vector of eye color elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#),

```
grade_level(), grade(), group(), hair(), height(), income(), internet_browser(), iq(),
language, level(), likert(), lorem_ipsum(), marital(), military(), month(), name, normal(),
political(), race(), religion(), sat(), sentence(), sex_inclusive(), sex(), smokes(),
speed(), state(), string(), upper(), valid(), year(), zip_code()
```

Examples

```
eye(10)
barplot(v <- table(eye(10000)), col = replace(names(v), 4, "yellowgreen"))
```

| | |
|-------|---|
| grade | <i>Generate Random Vector of Grades</i> |
|-------|---|

Description

grade - Generate a random normal vector of percent grades.
 grade - Generate a random normal vector of letter grades.
 grade - Generate a random normal vector of grade point averages (GPA; 0.0 - 4.0 scale).

Usage

```
grade(n, mean = 88, sd = 4, name = "Grade", digits = 1)
grade_letter(n, mean = 88, sd = 4, name = "Grade_Letter")
gpa(n, mean = 88, sd = 4, name = "GPA")
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| mean | The mean value for the normal distribution to be drawn from. |
| sd | The standard deviation of the normal distribution to draw from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |
| digits | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |

Details

The conversion between percent range, letter grade, and GPA is:

| Percent | Letter | GPA |
|---------|--------|------|
| 97-100 | A+ | 4.00 |
| 93-96 | A | 4.00 |

| | | |
|-------|----|------|
| 90-92 | A- | 3.67 |
| 87-89 | B+ | 3.33 |
| 83-86 | B | 3.00 |
| 80-82 | B- | 2.67 |
| 77-79 | C+ | 2.33 |
| 73-76 | C | 2.00 |
| 70-72 | C- | 1.67 |
| 67-69 | D+ | 1.33 |
| 63-66 | D | 1.00 |
| 60-62 | D- | 0.67 |
| < 60 | F | 0.00 |

Value

Returns a random normal vector of grade elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
grade(10)
hist(grade(10000))
interval(grade, 5, n = 1000)

grade_letter(10)
barplot(table(grade_letter(10000)))

gpa(10)
hist(gpa(10000))
```

grade_level

Generate Random Vector of Grade Levels

Description

Generate a random vector of grade levels.

Usage

```
grade_level(
  n,
  x = c("K", "1", "2", "3", "4", "5", "6", "7", "8", "9", "10", "11", "12"),
  prob = NULL,
  name = "Grade_Level"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of grade level elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
grade_level(10)
barplot(table(grade_level(10000)))
```

| | |
|-----------------|--|
| grady_augmented | <i>Augmented List of Grady Ward's English Words and Mark Kantrowitz's Names List</i> |
|-----------------|--|

Description

A dataset containing a vector of Grady Ward's English words augmented with **qdapDictionaries**'s DICTIONARY, Mark Kantrowitz's names list, other proper nouns, and contractions.

Usage

```
data(grady_augmented)
```

Format

A character vector with 122806 elements

Details

A dataset containing a vector of Grady Ward's English words augmented with proper nouns (U.S. States, Countries, Mark Kantrowitz's Names List, and months) and contractions. That dataset is augmented to increase the data set size.

References

Moby Thesaurus List by Grady Ward <https://www.gutenberg.org>

List of names from Mark Kantrowitz <http://www.cs.cmu.edu/afs/cs/project/ai-repository/ai/areas/nlp/corpora/names/>.
A copy of the <http://www.cs.cmu.edu/afs/cs/project/ai-repository/ai/areas/nlp/corpora/names/readme.txt>
per the author's request.

group

Generate Random Vector of Control/Treatment Groups

Description

Generate a random vector of binary groups (e.g., control/treatment).

Usage

```
group(n, x = c("Control", "Treatment"), prob = NULL, name = "Group")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of groups to sample from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of group (control/treatment) elements.

Note

If you want > 2 groups see 'r_sample_factor'.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
group(10)
100*table(group(n <- 10000))/n
100*table(group(n <- 10000, prob = c(.3, .7)))/n
```

| | |
|------|--|
| hair | <i>Generate Random Vector of Hair Colors</i> |
|------|--|

Description

Generate a random vector of hair colors.

Usage

```
hair(
  n,
  x = c("Brown", "Black", "Blonde", "Red"),
  prob = c(0.35, 0.28, 0.26, 0.11),
  name = "Hair"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The hair colors and probabilities:

| Color | Percent |
|--------|---------|
| Brown | 35 % |
| Black | 28 % |
| Blonde | 26 % |
| Red | 11 % |

Value

Returns a random vector of hair color elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
hair(10)
v <- table(hair(10000))
lbs <- paste0(names(v), "\n", round(100*v/sum(v), 1), "%")
pie(v, col = replace(names(v), 3, "yellow"), labels = lbs)
```

height

Generate Random Vector of Heights

Description

height and height_in - Generate a random normal vector of heights in inches.

height_cm - Generate a random normal vector of heights in centimeters.

Usage

```
height(
  n,
  mean = 69,
  sd = 3.75,
  min = 1,
  max = NULL,
  digits = 0,
  name = "Height"
)
```

```
height_in(  
  n,  
  mean = 69,  
  sd = 3.75,  
  min = 1,  
  max = NULL,  
  digits = 1,  
  name = "Height(in)"  
)  
  
height_cm(  
  n,  
  mean = 175.26,  
  sd = 9.525,  
  min = 1,  
  max = NULL,  
  digits = 1,  
  name = "Height(cm)"  
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| mean | The mean value for the normal distribution to be drawn from. |
| sd | The standard deviation of the normal distribution to draw from. |
| min | A numeric lower boundary cutoff. Results less than this value will be replaced with min. |
| max | A numeric upper boundary cutoff. Results greater than this value will be replaced with max. |
| digits | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random normal vector of height elements.

Note

`height` rounds to nearest whole number. `height_in` & `height_cm` round to the nearest tenths.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#),

[eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language_level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
height(10)
hist(height(10000))
interval(height, 5, n = 1000)
```

hour

Generate a Random Sequence of H:M:S Times

Description

Generate a random vector of H:M:S times.

Usage

```
hour(n, x = seq(0, 23.5, by = 0.5), prob = NULL, random = FALSE, name = "Hour")
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| random | logical. If TRUE the times are randomized, otherwise the times are sequential. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of H:M:S time elements.

See Also

[times](#)

Examples

```
hour(20)
hour(20, random=TRUE)
```

| | |
|----|-------------------------------|
| id | <i>Identification Numbers</i> |
|----|-------------------------------|

Description

id - Generate a sequential [character](#) vector of zero-padded identification numbers (IDs).

id_factor - Generate a sequential [factor](#) vector of zero-padded identification numbers (IDs).

Usage

```
id(n, random = FALSE, name = "ID")
```

```
id_factor(n, random = FALSE, name = "ID")
```

Arguments

| | |
|--------|---|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| random | logical. If TRUE the IDs are randomized, otherwise the IDs are sequential. |
| name | The name to assign to the output vector's varname attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a (optionally random) vector of [character/factor](#) observations ID numbers.

Warning

id uses [sprintf](#) to generate the padded ID. Per [sprintf](#)'s documentation: "The format string is passed down the OS's sprintf function...The behaviour on inputs not documented here is 'undefined', which means it is allowed to differ by platform." See [sprintf](#) for details.

Note

id is faster than id_factor, as the later coerces the vector to a [factor](#).

See Also

[sprintf](#)

Examples

```
id(1000)
r_data_frame(n=21, id)
```

`income`*Generate Random Gamma Vector of Incomes*

Description

Generate a random gamma vector of incomes.

Usage

```
income(n, digits = 2, name = "Income")
```

Arguments

| | |
|---------------------|--|
| <code>n</code> | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| <code>digits</code> | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |
| <code>name</code> | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

Incomes are generated using: `rgamma(n, 2) * 2000`.

Value

Returns a random gamma vector of income elements.

See Also

[gamma](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
income(10)
hist(income(10000))
pie(table(cut(income(10000), 10)))
```

internet_browser *Generate Random Vector of Internet Browsers*

Description

Generate a random vector of Internet browser.

Usage

```
internet_browser(  
  n,  
  x = c("Chrome", "IE", "Firefox", "Safari", "Opera", "Android"),  
  prob = c(0.5027, 0.175, 0.1689, 0.0994, 0.017, 0.0132),  
  name = "Browser"  
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of elements to chose from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The browser use and probabilities (from <https://gs.statcounter.com/>):

| Browser | Percent |
|----------------|----------------|
| Chrome | 50.27 % |
| IE | 17.50 % |
| Firefox | 16.89 % |
| Safari | 9.94 % |
| Opera | 1.70 % |
| Android | 1.32 % |

Value

Returns a random factor vector of Internet browser elements.

References

<https://gs.statcounter.com/>

See Also

Other variable functions: `age()`, `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `iq()`, `language`, `level()`, `likert()`, `lorem_ipsum()`, `marital()`, `military()`, `month()`, `name`, `normal()`, `political()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
internet_browser(20)
barplot(table(internet_browser(10000)))
pie(table(internet_browser(10000)))
```

interval

Cut Numeric Into Factor

Description

A wrapper for `cut` that cuts the vector and then adds the varname produced by the original function.

Usage

```
interval(
  fun,
  breaks,
  ...,
  labels = NULL,
  include.lowest = FALSE,
  right = TRUE,
  dig.lab = 3,
  ordered_result = FALSE,
  n
)
```

Arguments

| | |
|-----------------------------|--|
| <code>fun</code> | A vector producing function. |
| <code>breaks</code> | Either a numeric vector of two or more unique cut points or a single number (greater than or equal to 2) giving the number of intervals into which the vector produced from <code>fun</code> is to be cut. |
| <code>labels</code> | Labels for the levels of the resulting category. By default, labels are constructed using "(a,b)" interval notation. If <code>labels = FALSE</code> , simple integer codes are returned instead of a factor. |
| <code>include.lowest</code> | logical. If TRUE an 'x[i]' equal to the lowest (or highest, for <code>right = FALSE</code>) 'breaks' value should be included. |

| | |
|-----------------------------|--|
| <code>right</code> | logical. If TRUE the intervals will be closed on the right (and open on the left). |
| <code>dig.lab</code> | An integer which is used when labels are not given. It determines the number of digits used in formatting the break numbers. |
| <code>ordered_result</code> | logical. If TRUE the result be an ordered factor. |
| <code>n</code> | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| <code>...</code> | Other arguments passed to <code>fun</code> . |

Value

Returns a `cut` factor vector.

See Also

[cut](#)

Examples

```
interval(normal, 4, n=100)
attributes(interval(normal, 4, n=100))
interval(age, 3, n = 1000)
```

| | |
|----|---|
| iq | <i>Generate Random Vector of Intelligence Quotients (IQs)</i> |
|----|---|

Description

Generate a random normal vector of intelligence quotients (IQs).

Usage

```
iq(n, mean = 100, sd = 10, min = 0, max = NULL, digits = 0, name = "IQ")
```

Arguments

| | |
|---------------------|--|
| <code>n</code> | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| <code>mean</code> | The mean value for the normal distribution to be drawn from. |
| <code>sd</code> | The standard deviation of the normal distribution to draw from. |
| <code>min</code> | A numeric lower boundary cutoff. Results less than this value will be replaced with <code>min</code> . |
| <code>max</code> | A numeric upper boundary cutoff. Results greater than this value will be replaced with <code>max</code> . |
| <code>digits</code> | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |
| <code>name</code> | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random normal vector of IQ elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
iq(10)
hist(iq(10000))
interval(iq, 5, n = 1000)
```

language

Generate Random Vector of Languages

Description

Generate a random vector of languages from the [presidential_debates_2012](#).

Usage

```
language(
  n,
  x = wakefield::languages[["Language"]],
  prob = wakefield::languages[["Proportion"]],
  name = "Language"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random character vector of language elements.

See Also

Other variable functions: `age()`, `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `internet_browser()`, `iq()`, `level()`, `likert()`, `lorem_ipsum()`, `marital()`, `military()`, `month()`, `name`, `normal()`, `political()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
language(10)
pie(table(language(10000)))

lang <- wakefield::languages[sample(1:99, 6), ]
lang["prop"] <- lang[["N"]]/sum(lang[["N"]])
labs <- round(100 * lang[["prop"]], 1)
pie(lang[["prop"]], paste0(lang[["Language"]], "\n", labs, "%"))
```

languages

Languages of the World

Description

A dataset containing native language use statistics taken from: https://en.wikipedia.org/wiki/List_of_languages_by_number_of_native_speakers

Usage

```
data(languages)
```

Format

A data frame with 99 rows and 4 variables

Details

- Language. The language spoken.
- N. The number of speakers world-wide.
- Proportion. The proportion of speakers.
- Percent. The percentage of speakers.

References

https://en.wikipedia.org/wiki/List_of_languages_by_number_of_native_speakers

| | |
|-------|---|
| level | <i>Generate Random Vector of Levels</i> |
|-------|---|

Description

level - Generate a random vector of integer levels (1-4).

math - Generate a random vector of integer mathematics levels (1-4) similar to New York State grades 3-8 assessment results.

ela - Generate a random vector of integer English language arts (ELA) levels (1-4) similar to New York State grades 3-8 assessment results.

Usage

```
level(n, x = 1:4, prob = NULL, name = "Level")
```

```
math(n, x = 1:4, prob = c(0.29829, 0.33332, 0.22797, 0.14042), name = "Math")
```

```
ela(n, x = 1:4, prob = c(0.3161, 0.37257, 0.2233, 0.08803), name = "ELA")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

Distribution of levels (used in `prob`) were taken from New York State' s 2014 assessment report: <http://www.p12.nysed.gov/irs/>

| Level | ELA | Math |
|-------|-------|-------|
| 1 | 31.6% | 29.8% |
| 2 | 37.3% | 33.3% |
| 3 | 22.3% | 22.8% |
| 4 | 8.8% | 14.0% |

Value

Returns a random vector of integer levels (1-4) elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
level(10)
barplot(table(level(10000, prob = probs(4))))
```

```
math(10)
barplot(table(math(10000)))
```

```
ela(10)
barplot(table(ela(10000)))
```

likert

Generate Random Vector of Likert-Type Responses

Description

Generate a random vector of Likert-type responses.

Usage

```
likert(
  n,
  x = c("Strongly Agree", "Agree", "Neutral", "Disagree", "Strongly Disagree"),
  prob = NULL,
  name = "Likert"
)

likert_5(
  n,
  x = c("Strongly Agree", "Agree", "Neutral", "Disagree", "Strongly Disagree"),
  prob = NULL,
  name = "Likert"
)

likert_7(
  n,
  x = c("Strongly Agree", "Agree", "Somewhat Agree", "Neutral", "Somewhat Disagree",
        "Disagree", "Strongly Disagree"),
  prob = NULL,
  name = "Likert"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of Likert-type response elements.

Note

`likert` & `likert_5` are identical outputs, sampling from a 5-point response scale. `likert_7` samples from a 7-point response scale.

See Also

Other variable functions: `age()`, `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `internet_browser()`, `iq()`, `language`, `level()`, `lorem_ipsum()`, `marital()`, `military()`, `month()`, `name`, `normal()`, `political()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
dice(10)
barplot(table(dice(10000)))
```

lorem_ipsum

Generate Random Lorem Ipsum Strings

Description

Generates (pseudo)random lorem ipsum text.

Usage

```
lorem_ipsum(n, ..., name = "Lorem_Ipsum")

paragraph(n, ..., name = "Paragraph")
```


Arguments

`n` The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

`...` Other arguments passed to `stri_rand_lipsum`.

`name` The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Value

Returns a random character vector of string elements.

Note

`lorem_ipsum` and `paragraph` produce identical strings but will produce different vector/column names when used inside of `r_data_frame` or `r_list`.

See Also

[stri_rand_lipsum](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
lorem_ipsum(10)
paragraph(10)

lorem_ipsum(10, start_lipsum = FALSE)
```

```
marital
```

Generate Random Vector of Marital Statuses

Description

Generate a random vector of marital statuses.

Usage

```
marital(
  n,
  x = c("Married", "Divorced", "Widowed", "Separated", "Never Married"),
  prob = NULL,
  name = "Marital"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of marital status elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
marital(10)
barplot(table(marital(10000)))
```

military

Generate Random Vector of Military Branches

Description

Generate a random vector of military branches.

Usage

```
military(
  n,
  x = c("Army", "Air Force", "Navy", "Marine Corps", "Coast Guard"),
  prob = c(0.3785, 0.2334, 0.2218, 0.1366, 0.0296),
  name = "Military"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The military branches and probabilities used match approximate U.S. military make-up:

| Branch | N | Percent |
|--------------|---------|---------|
| Army | 541,291 | 37.9% |
| Air Force | 333,772 | 23.3% |
| Navy | 317,237 | 22.2% |
| Marine Corps | 195,338 | 13.7% |
| Coast Guard | 42,357 | 3.0% |

Value

Returns a random factor vector of military branch elements.

See Also

Other variable functions: `age()`, `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `internet_browser()`, `iq()`, `language`, `level()`, `likert()`, `lorem_ipsum()`, `marital()`, `month()`, `name`, `normal()`, `political()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
military(10)
barplot(table(military(10000)))
pie(table(military(10000)))
```

 minute

Generate a Random Sequence of Minutes in H:M:S Format

Description

Generate a random vector of minutes in H:M:S format.

Usage

```
minute(
  n,
  x = seq(0, 59, by = 1)/60,
  prob = NULL,
  random = FALSE,
  name = "Minute"
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| random | logical. If TRUE the times are randomized, otherwise the times are sequential. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of minute time elements in H:M:S format.

See Also

[times](#)

Examples

```
minute(20)
minute(20, random=TRUE)
pie(table(minute(2000, x = seq(0, 59, by = 10)/60, prob = probs(6))))
```

month

Generate Random Vector of Months

Description

Generate a random factor vector of months.

Usage

```
month(n, x = month.name, prob = NULL, name = "Month")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random character vector of month elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
month(10)
pie(table(month(10000, prob = probs(12))))
```

| | |
|------|--|
| name | <i>Generate Random Vector of Names</i> |
|------|--|

Description

Generate a random vector of first names. This dataset includes all unique entries from the `babynames` package.

Usage

```
name(  
  n,  
  x = wakefield::name_neutral,  
  prob = NULL,  
  replace = FALSE,  
  name = "Name"  
)
```

Arguments

| | |
|---------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| replace | logical. If TRUE sampling is done with replacement. Default is without replacement. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of name elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
name(10)
name(100)
name(1000, replace = TRUE)
```

name_neutral

Gender Neutral Names

Description

A dataset containing a character vector gender neutral names according to the U.S. Census.

Usage

```
data(name_neutral)
```

Format

A character vector with 662 elements

References

<http://www.census.gov>

| | |
|--------|--------------------------------------|
| normal | <i>Generate Random Normal Vector</i> |
|--------|--------------------------------------|

Description

normal - A wrapper for [rnorm](#) that generate a random normal vector.

normal_round - A wrapper for [rnorm](#) that generate a rounded random normal vector.

Usage

```
normal(n, mean = 0, sd = 1, min = NULL, max = NULL, name = "Normal")
```

```
normal_round(  
  n,  
  mean = 0,  
  sd = 1,  
  min = NULL,  
  max = NULL,  
  digits = 2,  
  name = "Normal"  
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| mean | The mean value for the normal distribution to be drawn from. |
| sd | The standard deviation of the normal distribution to draw from. |
| min | A numeric lower boundary cutoff. Results less than this value will be replaced with <code>min</code> . |
| max | A numeric upper boundary cutoff. Results greater than this value will be replaced with <code>max</code> . |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |
| digits | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |

Value

Returns a random vector of elements.

See Also[rnorm](#)[round](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
normal(100, name = "Var")
hist(normal(10000, 100, 10))
interval(normal, 9, n = 1000)
```

peek

Data Frame Viewing

Description

Convenience function to view all the columns of the head of a truncated [data.frame](#). peek invisibly returns x. This makes its use ideal in a **dplyr/magrittr** pipeline.

Usage

```
peek(x, n = 10, width = 10, ...)
```

Arguments

| | |
|-------|---|
| x | A data.frame object. |
| n | Number of rows to display. |
| width | The width of the columns to be displayed. |
| ... | For internal use. |

Details

By default **dplyr** does not print all columns of a data frame (`tbl_df`). This makes inspection of data difficult at times, particularly with text string data. peek allows the user to see a truncated head for inspection purposes.

Value

Prints a truncated head but invisibly returns x.

See Also[head](#)**Examples**

```
(dat1 <- r_data_frame(100, id, sentence, paragraph))
peek(dat1)
peek(dat1, n = 20)
peek(dat1, width = 40)

library(dplyr)

## Use in a dplyr/magrittr pipeline to view the data (silly example)
par(mfrow = c(2, 2))

r_data_frame(1000, id, sex, pet, employment, eye, sentence, paragraph) %>%
  peek %>%
  (function(x, ind = 2:5){ invisible(lapply(ind, function(i) pie(table(x[[i]]))))})

## A wider data set example
dat2 <- r_data_theme()

dat2
peek(dat2)
```

plot.tbl_df

Plots a tbl_df Object

Description

Plots a `tbl_df` object.

Usage

```
## S3 method for class 'tbl_df'
plot(x, ...)
```

Arguments

`x` The `tbl_df` object.

`...` Arguments passed to [table_heat](#).

 political

Generate Random Vector of Political Parties

Description

Generate a random vector of political parties.

Usage

```
political(
  n,
  x = c("Democrat", "Republican", "Constitution", "Libertarian", "Green"),
  prob = c(0.577269133302094, 0.410800432748879, 0.00491084954793489,
    0.00372590303330866, 0.0032936813677832),
  name = "Political"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The political parties and probabilities used match approximate U.S. political make-up of registered voters (2014). The default make up is:

| Party | N | Percent |
|--------------|------------|---------|
| Democrat | 43,140,758 | 57.73% |
| Republican | 30,700,138 | 41.08% |
| Constitution | 367,000 | .49% |
| Libertarian | 278,446 | .37% |
| Green | 246,145 | .33% |

Value

Returns a random factor vector of political party elements.

See Also

Other variable functions: `age()`, `animal()`, `answer()`, `area()`, `car()`, `children()`, `coin()`, `color`, `date_stamp()`, `death()`, `dice()`, `dna()`, `dob()`, `dummy()`, `education()`, `employment()`, `eye()`, `grade_level()`, `grade()`, `group()`, `hair()`, `height()`, `income()`, `internet_browser()`, `iq()`, `language`, `level()`, `likert()`, `lorem_ipsum()`, `marital()`, `military()`, `month()`, `name`, `normal()`, `race()`, `religion()`, `sat()`, `sentence()`, `sex_inclusive()`, `sex()`, `smokes()`, `speed()`, `state()`, `string()`, `upper()`, `valid()`, `year()`, `zip_code()`

Examples

```
political(10)
barplot(table(political(10000)))
```

```
presidential_debates_2012
```

2012 U.S. Presidential Debate Dialogue

Description

A dataset containing 2911 ordered sentences used by speakers during the three 2012 presidential debates.

Usage

```
data(presidential_debates_2012)
```

Format

A character vector with 2911 elements

```
print.available      Prints an available Object.
```

Description

Prints an available object.

Usage

```
## S3 method for class 'available'
print(x, ...)
```

Arguments

| | |
|------------------|----------------------|
| <code>x</code> | The available object |
| <code>...</code> | ignored |

| | |
|-----------------------------|---------------------------------|
| <code>print.variable</code> | <i>Prints a variable Object</i> |
|-----------------------------|---------------------------------|

Description

Prints a variable object

Usage

```
## S3 method for class 'variable'  
print(x, ...)
```

Arguments

| | |
|------------------|----------------------|
| <code>x</code> | The variable object. |
| <code>...</code> | Ignored. |

| | |
|--------------------|---|
| <code>probs</code> | <i>Generate a Random Vector of Probabilities.</i> |
|--------------------|---|

Description

Generate a random vector of probabilities that sum to 1.

Usage

```
probs(j, upper = 1e+06)
```

Arguments

| | |
|--------------------|--|
| <code>j</code> | An integer of number of probability elements (typically performs best at $j < 4000$). |
| <code>upper</code> | <code>probs</code> works by sampling from <code>1 : upper</code> <code>j</code> times and then dividing each sample by the sum of all samples. |

Value

Returns a vector of probabilities summing to 1.

Examples

```
probs(10)  
sum(probs(100))  
pie(table(month(10000, prob = probs(12))))
```

race *Generate Random Vector of Races*

Description

Generate a random vector of races.

Usage

```
race(
  n,
  x = c("White", "Hispanic", "Black", "Asian", "Bi-Racial", "Native", "Other",
        "Hawaiian"),
  prob = c(0.637, 0.163, 0.122, 0.047, 0.019, 0.007, 0.002, 0.0015),
  name = "Race"
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of elements to chose from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The races and probabilities used match approximate U.S. racial make-up. The default make up is:

| Race | Percent |
|-------------|----------------|
| White | 63.70 % |
| Hispanic | 16.30 % |
| Black | 12.20 % |
| Asian | 4.70 % |
| Bi-Racial | 1.90 % |
| Native | .70 % |
| Other | .20 % |
| Hawaiian | .15 % |

Value

Returns a random factor vector of elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
race(10)
100*table(race(n <- 10000))/n
```

relate

Create Related Numeric Columns

Description

Generate columns that are related.

Usage

```
relate(
  x,
  j,
  name = NULL,
  operation = "+",
  mean = 5,
  sd = 1,
  rep.sep = "_",
  digits = max(nchar(sub("^[^.]*. ", "", x)))
)
```

Arguments

| | |
|-----------|--|
| x | A starting column. |
| j | The number of columns to produce. |
| name | An optional prefix name to give to the columns. If NULL attempts to take from the varname attribute of x. If not found, "Variable" is used. |
| operation | A operation character vector of length 1; either <code>c("+", "-", "*", "/")</code> . This is the relationship between columns. |
| mean | Mean is the average value to add, subtract, multiple, or divide by. |
| sd | The amount of variability to allow in mean. Setting to 0 will constrain the operation between <code>x_(n - 1)</code> column and <code>x_n</code> to be exactly the mean value (see Examples for a demonstration). |

| | |
|---------|---|
| rep.sep | A separator to use for repeated variable names. For example if the <code>age</code> is used three times (<code>r_data_frame(age, age, age)</code>), the name "Age" will be assigned to all three columns. The results in column names <code>c("Age_1", "Age_2", "Age_3")</code> . |
| digits | The number of digits to round to. Defaults to the max number of significant digits in <code>x</code> . |

Value

Returns a `tbl_df`.

See Also

[r_series](#)

Examples

```
relate(1:10, 10)

(x <- r_data_frame(10, id, relate(1:10, 10, "Time", mean = 2)))
library(ggplot2)

dat <- with(x, data.frame(ID = rep(ID, ncol(x[, -1])), stack(x[, -1])))
dat[["Time"]] <- factor(sub("Time_", "", dat[["ind"]]), levels = 1:10)
ggplot(dat, aes(x = Time, y = values, color = ID, group = ID)) +
  geom_line(size=.8)

relate(1:10, 10, name = "X", operation = "-")
relate(1:10, 10, "X", mean = 1, sd = 0)
relate(1:10, 10, "Var", "x")
relate(1:10, 10, "Var", "/" )

relate(gpa(30), 5, mean = .1)
relate(likert(10), 5, mean = .1, sd = .2)
relate(date_stamp(10), 6)
relate(time_stamp(10), 6)
relate(rep(100, 10), 6, "Reaction", "-")
```

religion

Generate Random Vector of Religions

Description

Generate a random vector of religion.

Usage

```
religion(
  n,
  x = c("Christian", "Muslim", "None", "Hindu", "Buddhist", "Folk", "Other", "Jewish"),
  prob = c(0.31477, 0.23163, 0.16323, 0.14985, 0.07083, 0.05882, 0.00859, 0.00227),
  name = "Religion"
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of elements to chose from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The religion and probabilities used match approximate world religion make-up (from [Pew Research Center](#)). The default make up is:

| Religion | N | Percent |
|-----------|---------------|---------|
| Christian | 2,173,260,000 | 31.48 % |
| Muslim | 1,599,280,000 | 23.16 % |
| None | 1,127,000,000 | 16.32 % |
| Hindu | 1,034,620,000 | 14.99 % |
| Buddhist | 489,030,000 | 7.08 % |
| Folk | 406,140,000 | 5.88 % |
| Other | 59,330,000 | .86 % |
| Jewish | 15,670,000 | .23 % |

Value

Returns a random factor vector of religion elements.

References

<https://www.pewforum.org/2012/12/18/table-religious-composition-by-country-in-numbers/>

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#),

[normal\(\)](#), [political\(\)](#), [race\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
religion(10)
barplot(table(religion(10000)))
pie(table(religion(10000)))
```

| | |
|--------|-------------------------------------|
| r_data | <i>Pre-Selected Column Data Set</i> |
|--------|-------------------------------------|

Description

r_data - Generate a data set with pre-set columns selected.

r_data_theme - Generate a themed data set with pre-set columns.

Usage

```
r_data(n = 500, ...)
```

```
r_data_theme(n = 100, data_theme = "the_works")
```

Arguments

| | |
|------------|---|
| n | The length to pass to the randomly generated vectors (number of rows). |
| data_theme | A data theme. Currently selections include: the_works all available variable functions survey ID column plus 10 numeric 5-point Likert type response columns survey2 ID column plus 10 5-point Likert type response columns |
| ... | A set of optionally named arguments. Using wakefield variable functions require no name or call parenthesis. |

Details

The pre-selected columns include:

- ID
- Race
- Age
- Sex
- Hour
- IQ
- Height
- Died

The user may use ... to add additional columns. r_data is a convenience function to quickly produce a data set. For more specific usage use the more flexible [r_data_frame](#) function.

Value

Returns a `tbl_df`.

See Also

`r_data_frame`

Examples

```
r_data()
r_data(10)
r_data(10, paragraph, Attending = valid)

peek(r_data_theme())
plot(r_data_theme(), flip=TRUE)

r_data_theme("survey")
r_data_theme("survey2")
```

r_data_frame

Data Frame Production (From Variable Functions)

Description

Produce a `tbl_df` data frame that allows the user to lazily pass unnamed **wakefield** variable functions (optionally, without call parenthesis).

Usage

```
r_data_frame(n, ..., rep.sep = "_")
```

Arguments

| | |
|---------|--|
| n | The length to pass to the randomly generated vectors. |
| rep.sep | A separator to use for repeated variable names. For example if the <code>age</code> is used three times (<code>r_data_frame(age, age, age)</code>), the name "Age" will be assigned to all three columns. The results in column names <code>c("Age_1", "Age_2", "Age_3")</code> . To turn of this behavior use <code>rep.sep = NULL</code> . This results in <code>c("Age", "Age.1", "Age.2")</code> column names in the <code>data.frame</code> . |
| ... | A set of optionally named arguments. Using wakefield variable functions require no name or call parenthesis. |

Value

Returns a `tbl_df`.

Author(s)

Josh O'Brien and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/29617983/1000343>

See Also

[r_list](#), [r_series](#) [r_dummy](#)

Examples

```
r_data_frame(n = 30,
  id,
  race,
  age,
  sex,
  hour,
  iq,
  height,
  died,
  Scoring = rnorm,
  Smoker = valid
)

r_data_frame(n = 30,
  id,
  race,
  age(x = 8:14),
  Gender = sex,
  Time = hour,
  iq,
  grade, grade, grade, #repeated measures
  height(mean=50, sd = 10),
  died,
  Scoring = rnorm,
  Smoker = valid
)

r_data_frame(n = 500,
  id,
  age, age, age,
  grade, grade, grade
)

## Repeated Measures/Time Series
r_data_frame(n=100,
  id,
  age,
  sex,
  r_series(likert, 3),
```

```

    r_series(likert, 4, name = "Item", integer = TRUE)
  )

  ## Expanded Dummy Coded Variables
  r_data_frame(n=100,
    id,
    age,
    r_dummy(sex, prefix=TRUE),
    r_dummy(political)
  )

  ## `peek` to view all columns
  ## `plot` (`table_heat`) for a graphic representation
  library(dplyr)
  r_data_frame(n=100,
    id,
    dob,
    animal,
    grade, grade,
    death,
    dummy,
    grade_letter,
    gender,
    paragraph,
    sentence
  ) %>%
    r_na() %>%
    peek %>%
    plot(palette = "Set1")

```

r_dummy

Generate Random Dummy Values

Description

Generate random values from a **wakefield** variable function.

Usage

```
r_dummy(fun, n, ..., prefix = FALSE, rep.sep = "_")
```

Arguments

| | |
|--------|---|
| fun | A wakefield variable function. |
| n | The number of rows to produce. |
| prefix | logical. If TRUE the original factor name (supplied to fun as name argument) will prefix the column names that were generated from the factor's categories. |

rep.sep A separator to use for the variable and category part of names when prefix = TRUE. For example if the `age` is used (`r_dummy(sex)`), this results in column names `c("Sex_Male", "Sex_Female")`.

... Additional arguments passed to fun.

Value

Returns a `tbl_df`.

See Also

[r_list](#), [r_data_frame](#), [r_series](#)

Examples

```
r_dummy(sex, 10)
r_dummy(race, 1000)
r_dummy(race, 1000, name = "Ethnicity")
```

r_insert

Insert Data Frames Into r_data_frame

Description

Safely insert `data.frame` objects into a `r_data_frame` or `r_list`.

Usage

```
r_insert(x, name = "Inserted")
```

Arguments

x A `data.frame` to add a `seriesname` attribute (i.e., `attributes(x)[["seriesname"]]`)

name A name to assign to `attributes(x)[["seriesname"]]`.

Value

Returns a `data.frame` with a `attributes(x)[["seriesname"]]` assigned.

See Also

[seriesname](#)

Examples

```

dat <- dplyr::data_frame(
  Age_1 = age(100), Age_2 = age(100), Age_3 = age(100),
  Smokes = smokes(n=100),
  Sick = ifelse(Smokes, sample(5:10, 100, TRUE), sample(0:4, 100, TRUE)),
  Death = ifelse(Smokes, sample(0:1, 100, TRUE, prob = c(.2, .8)),
    sample(0:1, 100, TRUE, prob = c(.7, .3)))
)

r_data_frame(100,
  id,
  r_insert(dat)
)

r_list(10,
  id,
  r_insert(dat)
)

```

r_list*List Production (From Variable Functions)*

Description

Produce a named [list](#) that allows the user to lazily pass unnamed **wakefield** variable functions (optionally, without call parenthesis).

Usage

```
r_list(n, ..., rep.sep = "_")
```

Arguments

| | |
|---------|---|
| n | The length to pass to the randomly generated vectors. |
| rep.sep | A separator to use for repeated variable names. For example if the age is used three times (<code>r_list(age, age, age)</code>), the name "Age" will be assigned to all three vectors in the list. The results in column names <code>c("Age_1", "Age_2", "Age_3")</code> . To turn of this behavior use <code>rep.sep = NULL</code> . This results in <code>c("Age", "Age", "Age")</code> for vector names, leading to <code>c("Age", "Age.1", "Age.2")</code> if coerced to a data.frame . |
| ... | A set of optionally named arguments. Using wakefield variable functions require no name or call parenthesis. |

Value

Returns a named list of equal length vectors.

Author(s)

Josh O'Brien and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/29617983/1000343>

See Also

[r_data_frame](#), [r_series](#) [r_dummy](#)

Examples

```
r_list(  
  n = 30,  
  id,  
  race,  
  age,  
  sex,  
  hour,  
  iq,  
  height,  
  died,  
  Scoring = rnorm  
)
```

```
r_list(  
  n = 30,  
  id,  
  race,  
  age(x = 8:14),  
  Gender = sex,  
  Time = hour,  
  iq,  
  height(mean=50, sd = 10),  
  died,  
  Scoring = rnorm  
)
```

r_na

Replace a Proportion of Values With NA

Description

Replaces a proportion of values with NA. Useful for simulating missing data.

Usage

```
r_na(x, cols = -1, prob = 0.05)
```

Arguments

| | |
|------|---|
| x | A <code>data.frame</code> or <code>list</code> to randomly replace elements with NAs. |
| cols | Numeric indices of the columns to include (use - to exclude as well). Default is to assign random NAs to all columns except the first column. |
| prob | The proportion of each column/vector elements to assign to NA. |

Value

Returns a `data.frame` or `list` with random missing values.

Examples

```
r_na(mtcars)
r_na(mtcars, NULL)

library(dplyr)

r_data_frame(
  n = 30,
  id,
  race,
  age,
  sex,
  hour,
  iq,
  height,
  died,
  Scoring = rnorm,
  Smoker = valid
) %>%
  r_na(prob=.4)
```

`r_sample`*Generate Random Vector*

Description

Generate a random vector.

Usage

```
r_sample(n, x = 1:100, prob = NULL, name = "Sample")
```


Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of elements.

See Also

[sample](#)

Examples

```
r_sample(100, name = "Var")
table(r_sample(x = c("Dog", "Cat", "Fish", "Bird"), n=1000))
r_sample(x = c("B", "W"), prob = c(.7, .3), n = 25, name = "Race")
r_sample(25, x = c(TRUE, FALSE))
```

| | |
|-----------------|--------------------------------------|
| r_sample_binary | <i>Generate Random Binary Vector</i> |
|-----------------|--------------------------------------|

Description

`r_sample_binary` - Generate a random binary vector.

`r_sample_binary_factor` - Generate a random binary vector and coerces to a factor.

Usage

```
r_sample_binary(n, x = 1:2, prob = NULL, name = "Binary")
```

```
r_sample_binary_factor(n, x = 1:2, prob = NULL, name = "Binary")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of length 2 to sample from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random binary vector of elements.

See Also

[sample.int](#)

Examples

```
r_sample_binary(100, name = "Var")
table(r_sample_binary(1000))
c("B", "W")[r_sample_binary(10)]
```

| | |
|-----------------|--------------------------------------|
| r_sample_factor | <i>Generate Random Factor Vector</i> |
|-----------------|--------------------------------------|

Description

Generate a random vector and coerces to a factor.

Usage

```
r_sample_factor(n, x = LETTERS, prob = NULL, name = "Factor")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random actor vector of elements.

See Also

[sample](#)

Examples

```
r_sample_factor(100, name = "Var")
table(r_sample_factor(x = c("Dog", "Cat", "Fish", "Bird"), n=1000))
r_sample_factor(x = c("B", "W"), prob = c(.7, .3), n = 25)
```

| | |
|------------------|---------------------------------------|
| r_sample_integer | <i>Generate Random Integer Vector</i> |
|------------------|---------------------------------------|

Description

Generate a random integer vector.

Usage

```
r_sample_integer(n, x = 1:100, prob = NULL, name = "Integer")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random integer vector of elements.

See Also

[sample](#)

Examples

```
r_sample_integer(100, name = "Var")  
table(r_sample_integer(x = c("Dog", "Cat", "Fish", "Bird"), n=1000))  
r_sample_integer(x = c("B", "W"), prob = c(.7, .3), n = 25, name = "Race")  
r_sample_integer(25, x = c(TRUE, FALSE))
```

r_sample_logical *Generate Random Logical Vector*

Description

Generate a random logical (TRUE/FALSE) vector.

Usage

```
r_sample_logical(n, prob = NULL, name = "Logical")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random logical (TRUE/FALSE) vector of elements.

See Also

[sample](#)

Examples

```
r_sample_logical(100, name = "Var")
table(r_sample_logical(1000))
c("B", "W")[r_sample_logical(10)]
```

r_sample_ordered *Generate Random Ordered Factor Vector*

Description

Generate a random vector and coerces to an ordered factor.

Usage

```
r_sample_ordered(n, x = LETTERS[1:5], prob = NULL, name = "Ordered")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random factor vector of elements.

See Also

[sample](#), [ordered](#)

Examples

```
r_sample_ordered(100, name = "Var")

lvls <- c("Strongly Agree", "Agree", "Neutral", "Disagree", "Strongly Disagree")
table(r_sample_ordered(x = lvls, n=1000))

(out <- r_sample_ordered(x = c("Black", "Grey", "White"),
  prob = c(.5, .2, .3), n = 100))
slices <- c(table(out))
pie(slices, main="Pie Chart of Colors", col = tolower(names(slices)))
```

| | |
|------------------|---|
| r_sample_replace | <i>Generate Random Vector (Without Replacement)</i> |
|------------------|---|

Description

Generate a random vector without replacement.

Usage

```
r_sample_replace(n, x = 1:100, prob = NULL, replace = FALSE, name = "Sample")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |

| | |
|---------|---|
| replace | logical. If TRUE sampling is done with replacement. Default is without replacement. |
| name | The name to assign to the output vector's varname attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of elements.

See Also

[sample](#)

Examples

```
r_sample(100, name = "Var")
table(r_sample(x = c("Dog", "Cat", "Fish", "Bird"), n=1000))
r_sample(x = c("B", "W"), prob = c(.7, .3), n = 25, name = "Race")
r_sample(25, x = c(TRUE, FALSE))
```

r_series

Data Frame Series (Repeated Measures)

Description

Produce a [tbl_df](#) data frame of repeated measures from a wakefield variable function.

Usage

```
r_series(fun, j, n, ..., integer = FALSE, relate = NULL, rep.sep = "_")
```

Arguments

| | |
|---------|--|
| fun | A wakefield variable function. |
| j | The number of columns to produce. |
| n | The number of rows to produce. |
| integer | logical. If TRUE factor columns will be coerced to integer. |
| relate | Allows the user to specify the relationship between columns. May be a named list of <code>c("operation", "mean", "sd")</code> or a string of the form of "fM_sd" where 'f' is one of (+, -, *, /), 'M' is a mean value, and 'sd' is a standard deviation of the mean value (e.g., "*4_1"). See relate for details. |
| rep.sep | A separator to use for repeated variable names. For example if the age is used three times (<code>r_data_frame(age, age, age)</code>), the name "Age" will be assigned to all three columns. The results in column names <code>c("Age_1", "Age_2", "Age_3")</code> . |
| ... | Additional arguments passed to fun. |

Value

Returns a `tbl_df`.

References

<https://github.com/trinker/wakefield/issues/1/#issuecomment-96166910>

See Also

`r_list`, `r_data_frame` `r_dummy`

Examples

```
r_series(grade, 5, 10)

## Custom name prefix
r_series(likert, 5, 10, name = "Question")

## Convert factors to integers
r_series(likert_7, 5, 10, integer = TRUE)

## Related variables
r_series(likert, 10, 200, relate = list(operation = "*", mean = 2, sd = 1))
r_series(likert, 10, 200, relate = "--3_1")
r_series(age, 10, 200, relate = "+5_0")

## Change sd to reduce/increase correlation
round(cor(r_series(grade, 10, 10, relate = "+1_2")), 2)
round(cor(r_series(grade, 10, 10, relate = "+1_0")), 2)
round(cor(r_series(grade, 10, 10, relate = "+1_.5")), 2)
round(cor(r_series(grade, 10, 10, relate = "+1_20")), 2)

## Plot Example 1
library(dplyr); library(ggplot2)

dat <- r_data_frame(12,
  name,
  r_series(likert, 10, relate = "+1_.5")
)

# Suggested use of tidyr or reshape2 package here instead
dat <- data.frame(
  ID = rep(dat[[1]], ncol(dat[-1])),
  stack(dat[-1])
)

dat[["Time"]] <- factor(sub("Variable_", "", dat[["ind"]]), levels = 1:10)
ggplot(dat, aes(x = Time, y = values, color = ID, group = ID)) +
  geom_line(size=.8)

## Plot Example 2
dat <- r_data_frame(12,
```

```

    name,
    r_series(grade, 100, relate = "+1_2")
  )

# Suggested use of tidyr or reshape2 package here instead
dat <- data.frame(
  ID = rep(dat[[1]], ncol(dat[-1])),
  ind = rep(colnames(dat[-1]), each = nrow(dat)),
  values = unlist(dat[-1])
)

dat[["Time"]] <- as.numeric(sub("Grade_", "", dat[["ind"]]))
ggplot(dat, aes(x = Time, y = values, color = ID, group = ID)) +
  geom_line(size=.8) + theme_bw()

```

 sat

Generate Random Vector of Scholastic Aptitude Test (SATs)

Description

grade - Generate a random normal vector of scholastic aptitude test (SATs).

Usage

```
sat(n, mean = 1500, sd = 100, min = 0, max = 2400, digits = 0, name = "SAT")
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| mean | The mean value for the normal distribution to be drawn from. |
| sd | The standard deviation of the normal distribution to draw from. |
| min | A numeric lower boundary cutoff. Results less than this value will be replaced with min. |
| max | A numeric upper boundary cutoff. Results greater than this value will be replaced with max. |
| digits | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random normal vector of SAT elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
sat(10)
hist(sat(10000))
interval(sat, 5, n = 1000)
```

second

Generate a Random Sequence of Seconds in H:M:S Format

Description

Generate a random vector of seconds in H:M:S format.

Usage

```
second(
  n,
  x = seq(0, 59, by = 1)/3600,
  prob = NULL,
  random = FALSE,
  name = "Second"
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| random | logical. If TRUE the times are randomized, otherwise the times are sequential. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of second time elements in H:M:S format.

See Also[times](#)**Examples**

```
second(20)
second(20, random=TRUE)
pie(table(second(2000, x = seq(0, 59, by = 10)/3600, prob = probs(6))))
```

sentence

*Generate Random Vector of Sentences***Description**

Generate a random vector of sentences from the [presidential_debates_2012](#).

Usage

```
sentence(
  n,
  x = wakefield::presidential_debates_2012,
  prob = NULL,
  name = "Sentence"
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random character vector of sentence elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
sentence(10)
```

| | |
|------------|--|
| seriesname | <i>Add Internal Name to Data Frame</i> |
|------------|--|

Description

Adds `attributes(x)[["seriesname"]]` attribute to a `data.frame`.

Usage

```
seriesname(x, name)
```

Arguments

`x` A `data.frame` to add a `seriesname` attribute (i.e., `attributes(x)[["seriesname"]]`)
`name` A name to assign to `attributes(x)[["seriesname"]]`.

Value

Returns a `data.frame` with a `attributes(x)[["seriesname"]]` assigned.

Examples

```
seriesname(mtcars, "Cars")  
attributes(seriesname(mtcars, "Cars"))
```

| | |
|-----|--|
| sex | <i>Generate Random Vector of Genders</i> |
|-----|--|

Description

Generate a random vector of genders.

Usage

```
sex(  
  n,  
  x = c("Male", "Female"),  
  prob = c(0.51219512195122, 0.48780487804878),  
  name = "Sex"  
)  
  
gender(  
  n,
```

```
x = c("Male", "Female"),
prob = c(0.51219512195122, 0.48780487804878),
name = "Gender"
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of length 2 to sample from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The genders and probabilities used match approximate gender make-up:

| Gender | Percent |
|--------|---------|
| Male | 51.22 % |
| Female | 48.78 % |

Value

Returns a random factor vector of gender elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
sex(10)
100*table(sex(n <- 10000))/n
```

Description

Generate a random vector of non-binary genders. Proportion of trans* category was taken from the [Williams Institute Report \(2011\)](#), and subtracted equally from the male and female categories.

Usage

```
sex_inclusive(  
  n,  
  x = c("Male", "Female", "Intersex"),  
  prob = NULL,  
  name = "Sex"  
)  
  
gender_inclusive(  
  n,  
  x = c("Male", "Female", "Trans*"),  
  prob = NULL,  
  name = "Gender"  
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The genders and probabilities used match approximate gender make-up:

| Gender | Percent |
|--------|---------|
| Male | 51.07 % |
| Female | 48.63 % |
| Trans* | 0.30 % |

Value

Returns a random factor vector of sex or gender elements.

Author(s)

Matthew Sigal <msigal@yorku.ca>

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
sex_inclusive(10)
barplot(table(sex_inclusive(10000)))

gender_inclusive(10)
barplot(table(gender_inclusive(10000)))
```

smokes

Generate Random Logical Smokes Vector

Description

Generate a random logical (TRUE/FALSE) smokes vector.

Usage

```
smokes(n, prob = c(0.822, 0.178), name = "Smokes")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Details

The probabilities are non-smoker: 82.2% vs. smoker: 17.8%.

Value

Returns a random logical vector of smokes elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
smokes(10)
100*table(smokes(n <- 1000))/n
```

speed

Generate Random Vector of Speeds

Description

speed and speed_in - Generate a random normal vector of speeds in inches.

speed_cm - Generate a random normal vector of speeds in centimeters.

Usage

```
speed(n, mean = 55, sd = 10, min = 0, max = NULL, digits = 0, name = "Speed")
```

```
speed_mph(
  n,
  mean = 55,
  sd = 10,
  min = 0,
  max = NULL,
  digits = 1,
  name = "Speed(mph)"
)
```

```
speed_kph(
  n,
  mean = 88.5,
  sd = 16,
  min = 0,
  max = NULL,
  digits = 1,
  name = "Speed(kph)"
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| mean | The mean value for the normal distribution to be drawn from. |
| sd | The standard deviation of the normal distribution to draw from. |
| min | A numeric lower boundary cutoff. Results less than this value will be replaced with <code>min</code> . |
| max | A numeric upper boundary cutoff. Results greater than this value will be replaced with <code>max</code> . |
| digits | Integer indicating the number of decimal places to be used. Negative values are allowed (see round). |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random normal vector of speed elements.

Note

`speed` rounds to nearest whole number. `speed_in` & `speed_in` round to the nearest tenths.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
speed(10)
hist(speed(10000))
interval(speed, 5, n = 1000)
```

state

Generate Random Vector of states

Description

Generate a random factor vector of states.

Usage

```
state(
  n,
  x = datasets::state.name,
  prob = wakefield::state_populations[["Proportion"]],
  name = "State"
)
```

Arguments

n The number elements to generate. This can be globally set within the environment of `r_data_frame` or `r_list`.

x A vector of elements to chose from.

prob A vector of probabilities to chose from.

name The name to assign to the output vector's `varname` attribute. This is used to auto assign names to the column/vector name when used inside of `r_data_frame` or `r_list`.

Details

The state populations and probabilities:

| State | Population | Percent |
|----------------|-------------------|----------------|
| California | 37,253,956 | 12.09 % |
| Texas | 25,145,561 | 8.16 % |
| New York | 19,378,102 | 6.29 % |
| Florida | 18,801,310 | 6.10 % |
| Illinois | 12,830,632 | 4.16 % |
| Pennsylvania | 12,702,379 | 4.12 % |
| Ohio | 11,536,504 | 3.74 % |
| Michigan | 9,883,640 | 3.21 % |
| Georgia | 9,687,653 | 3.14 % |
| North Carolina | 9,535,483 | 3.09 % |
| New Jersey | 8,791,894 | 2.85 % |
| Virginia | 8,001,024 | 2.60 % |
| Washington | 6,724,540 | 2.18 % |
| Massachusetts | 6,547,629 | 2.12 % |
| Indiana | 6,483,802 | 2.10 % |
| Arizona | 6,392,017 | 2.07 % |
| Tennessee | 6,346,105 | 2.06 % |
| Missouri | 5,988,927 | 1.94 % |
| Maryland | 5,773,552 | 1.87 % |
| Wisconsin | 5,686,986 | 1.85 % |
| Minnesota | 5,303,925 | 1.72 % |
| Colorado | 5,029,196 | 1.63 % |
| Alabama | 4,779,736 | 1.55 % |
| South Carolina | 4,625,364 | 1.50 % |
| Louisiana | 4,533,372 | 1.47 % |

| | | |
|---------------|-----------|--------|
| Kentucky | 4,339,367 | 1.41 % |
| Oregon | 3,831,074 | 1.24 % |
| Oklahoma | 3,751,351 | 1.22 % |
| Connecticut | 3,574,097 | 1.16 % |
| Iowa | 3,046,355 | .99 % |
| Mississippi | 2,967,297 | .96 % |
| Arkansas | 2,915,918 | .95 % |
| Kansas | 2,853,118 | .93 % |
| Utah | 2,763,885 | .90 % |
| Nevada | 2,700,551 | .88 % |
| New Mexico | 2,059,179 | .67 % |
| West Virginia | 1,852,994 | .60 % |
| Nebraska | 1,826,341 | .59 % |
| Idaho | 1,567,582 | .51 % |
| Hawaii | 1,360,301 | .44 % |
| Maine | 1,328,361 | .43 % |
| New Hampshire | 1,316,470 | .43 % |
| Rhode Island | 1,052,567 | .34 % |
| Montana | 989,415 | .32 % |
| Delaware | 897,934 | .29 % |
| South Dakota | 814,180 | .26 % |
| Alaska | 710,231 | .23 % |
| North Dakota | 672,591 | .22 % |
| Vermont | 625,741 | .20 % |
| Wyoming | 563,626 | .18 % |

Value

Returns a random character vector of state elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
state(10)
pie(table(state(10000)))
sort(100*table(state(n <- 10000))/n)
```

| | |
|-------------------|---------------------------------|
| state_populations | <i>State Populations (2010)</i> |
|-------------------|---------------------------------|

Description

A dataset containing U.S. state populations.

Usage

```
data(state_populations)
```

Format

A data frame with 50 rows and 3 variables

Details

- State. The 50 U.S. states.
- Population. Population of state.
- Proportion. Proportion of total U.S. population.

References

https://en.wikipedia.org/wiki/List_of_U.S._states_and_territories_by_population

| | |
|--------|--|
| string | <i>Generate Random Vector of Strings</i> |
|--------|--|

Description

Generate a random vector of strings.

Usage

```
string(n, x = "[A-Za-z0-9]", length = 10, name = "String")
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A character vector specifying character classes to draw elements from. |
| length | Integer vector, desired string lengths. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random character vector of string elements.

See Also

[stri_rand_strings](#)

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```
string(10)
```

| | |
|------------|---|
| table_heat | <i>View Data Table Column Types as Heat Map</i> |
|------------|---|

Description

Generate a heat map of column types from a [data.frame](#).

Usage

```
table_heat(
  x,
  flip = FALSE,
  palette = "Set3",
  print = interactive(),
  sep = "\n"
)
```

Arguments

| | |
|---------|---|
| x | A data.frame . |
| flip | logical. If TRUE the data.frame is flipped so that the columns are on the y axis and observations on the x axis. This is useful when there are many columns or the column names are longer. |
| palette | A palette to chose from. See scale_fill_brewer for more. These choices should exceed the number of unique column types. Use NULL to use ggplot2 's default color scheme. |
| print | logical. If TRUE the pot is printed. Option for use in document construction such as knitr or rmarkdown . |
| sep | A separator to use between column types. Column types are determined via <code>sapply(x, class)</code> . When multiple types are present these are collapsed. By default the \n is used. |

Details

By default column names retain their order. Column types are ordered alphabetically in the legend, with NA appearing last.

Value

Returns a **ggplot2** object.

Examples

```
table_heat(mtcars) #boring
table_heat(CO2)
table_heat(iris)
table_heat(state_populations)

dat <- r_data_frame(100,
  lorem_ipsum,
  birth,
  animal,
  age,
  grade, grade,
  death,
  dummy,
  grade_letter
)

table_heat(dat)
table_heat(dat, flip=TRUE)

table_heat(r_data_theme(), flip=TRUE)

## NA values
table_heat(r_na(dat, NULL))

## Colors
table_heat(r_na(dat, NULL), palette = NULL)
table_heat(r_na(dat, NULL), palette = "Set1")
table_heat(r_na(dat, NULL), palette = "Set2")
table_heat(r_na(dat, NULL), palette = "Set1")
table_heat(r_na(dat, NULL), palette = "Dark2")
table_heat(r_na(dat, NULL), palette = "Spectral")
table_heat(r_na(dat, NULL), palette = "Reds")
```

time_stamp

Generate a Random Sequence of Times in H:M:S Format

Description

Generate a random vector of times in H:M:S format.

Usage

```
time_stamp(
  n,
  x = seq(0, 23, by = 1),
  prob = NULL,
  random = FALSE,
  name = "Time"
)
```

Arguments

| | |
|--------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| random | logical. If TRUE the times are randomized, otherwise the times are sequential. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of time elements in H:M:S format.

See Also

[times](#)

Examples

```
time_stamp(20)
time_stamp(20, random=TRUE)
pie(table(time_stamp(2000, x = seq(0, 23, by = 2), prob = probs(12))))
```

upper

Generate Random Letter Vector

Description

upper - Generates a random character vector of upper case letters.

lower - Generates a random character vector of lower case letters.

upper_factor - Generates a random factor vector of upper case letters.

lower_factor - Generates a random factor vector of lower case letters.

Usage

```

upper(n, k = 5, x = LETTERS, prob = NULL, name = "Upper")

lower(
  n,
  k = 5,
  x = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p",
        "q", "r", "s", "t", "u", "v", "w", "x", "y", "z"),
  prob = NULL,
  name = "Lower"
)

upper_factor(n, k = 5, x = LETTERS, prob = NULL, name = "Upper")

lower_factor(
  n,
  k = 5,
  x = c("a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p",
        "q", "r", "s", "t", "u", "v", "w", "x", "y", "z"),
  prob = NULL,
  name = "Lower"
)

```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| k | The number of the elements of <code>x</code> to sample from (uses 1:k). |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random character/factor vector of letter elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [valid\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```

upper(10)
lower(10)
upper_factor(10)
lower_factor(10)
barplot(table(upper(10000)))
barplot(table(upper(10000, prob = probs(5))))

```

valid

Generate Random Logical Vector

Description

Generate a random logical (TRUE/FALSE) vector.

Usage

```
valid(n, prob = NULL, name = "Valid")
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random logical vector of elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [year\(\)](#), [zip_code\(\)](#)

Examples

```

valid(10)
100*table(valid(n <- 1000))/n

```

variables

Available Variable Functions

Description

See a listing of all available variable functions for use in `r_data_frame` or `r_list`.

Usage

```
variables(type = NULL, ncols = 5, ...)
```

Arguments

| | |
|--------------------|---|
| <code>type</code> | The output type. Must be either <code>NULL</code> (returns a character vector), <code>"matrix"</code> , or <code>"list"</code> ; or the user may extract a specific type from a list using: <code>"character"</code> , <code>"date"</code> , <code>"factor"</code> , <code>"integer"</code> , <code>"logical"</code> , <code>"numeric"</code> , <code>"ordered factor"</code> . Setting <code>type = TRUE</code> will also return a <code>list</code> . The <code>list</code> version breaks the variable functions into classes. Specifying a specific class (e.g., <code>type = "numeric"</code>) will list only variable functions that yield a numeric output. |
| <code>ncols</code> | The number of columns to use if <code>type = "matrix"</code> . |
| <code>...</code> | Other arguments passed to <code>matrix</code> . |

Value

Returns a `character` vector, `matrix` of all variable functions, or a `list` of variable functions by type.

Examples

```
variables()

variables("list")
variables(TRUE)
names(variables("list"))
variables("ordered factor")
variables("numeric")

variables("matrix")
variables("matrix", ncols=3)
variables("matrix", 1)
variables("matrix", byrow = TRUE)
```

| | |
|---------|------------------------------------|
| varname | <i>Add Internal Name to Vector</i> |
|---------|------------------------------------|

Description

Adds the class variable and an internal `attributes(x)[["varname"]]` attribute to a vector.

Usage

```
varname(x, name)
```

Arguments

| | |
|------|--|
| x | A vector to add a varname attribute (i.e., <code>attributes(x)[["varname"]]</code>) |
| name | A name to assign to <code>attributes(x)[["varname"]]</code> . |

Value

Returns a vector of the class variable with a `attributes(x)[["varname"]]` assigned.

Examples

```
varname(1:10, "A")
attributes(varname(1:10, "A"))
sum(varname(1:10, "A"))

varname(LETTERS, "Caps")
attributes(varname(LETTERS, "Caps"))
paste(varname(LETTERS, "Caps"), collapse="")
```

| | |
|-----------|----------------------------------|
| wakefield | <i>Generate Random Data Sets</i> |
|-----------|----------------------------------|

Description

Generates random data sets including: `data.frames`, lists, and vectors.

year *Generate Random Vector of Years*

Description

Generate a random vector of years.

Usage

```
year(  
  n,  
  x = 1996:as.numeric(format(Sys.Date(), "%Y")),  
  prob = NULL,  
  name = "Year"  
)
```

Arguments

| | |
|------|--|
| n | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| x | A vector of elements to chose from. |
| prob | A vector of probabilities to chose from. |
| name | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of year elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [zip_code\(\)](#)

Examples

```
year(10)  
pr <- probs(length(1996:2016))  
pie(table(year(10000, x= 1996:2016, prob = pr)))
```

`zip_code`*Generate Random Vector of Zip Codes*

Description

Generate a random vector of zip codes.

Usage

```
zip_code(n, k = 10, x = 10000:99999, prob = NULL, name = "Zip")
```

Arguments

| | |
|-------------------|--|
| <code>n</code> | The number elements to generate. This can be globally set within the environment of <code>r_data_frame</code> or <code>r_list</code> . |
| <code>k</code> | The number of the elements of <code>x</code> to sample from (uses <code>sample(x,k)</code>). |
| <code>x</code> | A vector of elements to chose from. |
| <code>prob</code> | A vector of probabilities to chose from. |
| <code>name</code> | The name to assign to the output vector's <code>varname</code> attribute. This is used to auto assign names to the column/vector name when used inside of <code>r_data_frame</code> or <code>r_list</code> . |

Value

Returns a random vector of zip code elements.

See Also

Other variable functions: [age\(\)](#), [animal\(\)](#), [answer\(\)](#), [area\(\)](#), [car\(\)](#), [children\(\)](#), [coin\(\)](#), [color](#), [date_stamp\(\)](#), [death\(\)](#), [dice\(\)](#), [dna\(\)](#), [dob\(\)](#), [dummy\(\)](#), [education\(\)](#), [employment\(\)](#), [eye\(\)](#), [grade_level\(\)](#), [grade\(\)](#), [group\(\)](#), [hair\(\)](#), [height\(\)](#), [income\(\)](#), [internet_browser\(\)](#), [iq\(\)](#), [language](#), [level\(\)](#), [likert\(\)](#), [lorem_ipsum\(\)](#), [marital\(\)](#), [military\(\)](#), [month\(\)](#), [name](#), [normal\(\)](#), [political\(\)](#), [race\(\)](#), [religion\(\)](#), [sat\(\)](#), [sentence\(\)](#), [sex_inclusive\(\)](#), [sex\(\)](#), [smokes\(\)](#), [speed\(\)](#), [state\(\)](#), [string\(\)](#), [upper\(\)](#), [valid\(\)](#), [year\(\)](#)

Examples

```
zip_code(10)
pie(table(zip_code(10000, prob = probs(10))))
```

Index

- * **age**
 - age, [4](#)
- * **animal**
 - animal, [5](#)
- * **answer**
 - answer, [6](#)
- * **area**
 - area, [7](#)
- * **army**
 - military, [42](#)
- * **birth**
 - dob, [17](#)
- * **branch**
 - military, [42](#)
- * **browser**
 - internet_browser, [33](#)
- * **capitals**
 - upper, [86](#)
- * **car**
 - car, [9](#)
- * **character**
 - lorem_ipsum, [40](#)
 - string, [83](#)
- * **children**
 - children, [10](#)
- * **class**
 - table_heat, [84](#)
- * **coin**
 - coin, [11](#)
- * **color**
 - color, [12](#)
- * **correlate**
 - relate, [54](#)
- * **cut**
 - interval, [34](#)
- * **datasets**
 - animal_list, [6](#)
 - grady_augmented, [25](#)
 - languages, [37](#)
 - name_neutral, [46](#)
 - presidential_debates_2012, [51](#)
 - state_populations, [83](#)
- * **date**
 - date_stamp, [13](#)
- * **death**
 - death, [14](#)
- * **democrat**
 - political, [50](#)
- * **dice**
 - dice, [15](#)
- * **died**
 - death, [14](#)
- * **divorce**
 - marital, [41](#)
- * **dna**
 - dna, [16](#)
- * **dob**
 - dob, [17](#)
- * **dummy**
 - r_dummy, [60](#)
- * **education**
 - education, [19](#)
- * **employment**
 - employment, [20](#)
- * **eye**
 - eye, [22](#)
- * **factor**
 - r_sample_ordered, [68](#)
- * **false**
 - valid, [88](#)
- * **gender**
 - sex, [75](#)
 - sex_inclusive, [76](#)
- * **gpa**
 - grade, [23](#)
- * **grade**
 - grade, [23](#)
 - grade_level, [24](#)

- * **group**
 - group, 26
- * **hair**
 - hair, 27
- * **head**
 - coin, 11
- * **height**
 - height, 28
- * **hour**
 - hour, 30
- * **identification**
 - id, 31
- * **id**
 - id, 31
- * **income**
 - income, 32
- * **insert**
 - r_insert, 61
- * **integer**
 - as_integer, 8
- * **intelligence**
 - iq, 35
- * **interval**
 - interval, 34
- * **iq**
 - iq, 35
- * **iris**
 - eye, 22
- * **language**
 - language, 36
- * **letters**
 - upper, 86
- * **level**
 - level, 38
- * **likert**
 - likert, 39
- * **list**
 - r_list, 62
- * **logical**
 - valid, 88
- * **lower**
 - upper, 86
- * **marines**
 - military, 42
- * **marital**
 - marital, 41
- * **married**
 - marital, 41
- * **military**
 - military, 42
- * **minute**
 - minute, 43
- * **missing**
 - r_na, 63
- * **month**
 - month, 44
- * **name**
 - name, 45
- * **navy**
 - military, 42
- * **na**
 - r_na, 63
- * **normal**
 - normal, 47
- * **no**
 - answer, 6
- * **numeric**
 - as_integer, 8
- * **ordered**
 - r_sample_ordered, 68
- * **percent**
 - probs, 52
- * **pet**
 - animal, 5
- * **political**
 - political, 50
- * **politics**
 - political, 50
- * **probability**
 - probs, 52
- * **race**
 - race, 53
- * **related**
 - relate, 54
- * **religion**
 - religion, 55
- * **republican**
 - political, 50
- * **responses**
 - likert, 39
- * **sat**
 - sat, 72
- * **second**
 - second, 73
- * **sentence**
 - sentence, 74

- * **sex**
 - sex, 75
 - sex_inclusive, 76
 - * **smoking**
 - smokes, 78
 - * **speed**
 - speed, 79
 - * **state**
 - state, 80
 - * **string**
 - lorem_ipsum, 40
 - string, 83
 - * **tail**
 - coin, 11
 - * **time**
 - hour, 30
 - minute, 43
 - second, 73
 - time_stamp, 85
 - * **true**
 - valid, 88
 - * **type**
 - variables, 89
 - * **upper**
 - upper, 86
 - * **valid**
 - valid, 88
 - * **variable functions**
 - age, 4
 - animal, 5
 - answer, 6
 - area, 7
 - car, 9
 - children, 10
 - coin, 11
 - color, 12
 - date_stamp, 13
 - death, 14
 - dice, 15
 - dna, 16
 - dob, 17
 - dummy, 18
 - education, 19
 - employment, 20
 - eye, 22
 - grade, 23
 - grade_level, 24
 - group, 26
 - hair, 27
 - height, 28
 - income, 32
 - internet_browser, 33
 - iq, 35
 - language, 36
 - level, 38
 - likert, 39
 - lorem_ipsum, 40
 - marital, 41
 - military, 42
 - month, 44
 - name, 45
 - normal, 47
 - political, 50
 - race, 53
 - religion, 55
 - sat, 72
 - sentence, 74
 - sex, 75
 - sex_inclusive, 76
 - smokes, 78
 - speed, 79
 - state, 80
 - string, 83
 - upper, 86
 - valid, 88
 - year, 91
 - zip_code, 92
 - * **widow**
 - marital, 41
 - * **year**
 - year, 91
 - * **yes**
 - answer, 6
 - * **zip_code**
 - zip_code, 92
- age, 4, 6–12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54–56, 58, 61, 62, 70, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- animal, 4, 5, 7–12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- animal_list, 6
- answer, 4, 6, 6, 8–12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46,

- 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- area, 4, 6, 7, 7, 9–12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- as.integer, 8
- as_integer, 8
- birth (dob), 17
- car, 4, 6–8, 9, 10–12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- character, 31, 89
- children, 4, 6–9, 10, 11, 12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- class, 8
- coin, 4, 6–10, 11, 12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- color, 4, 6–11, 12, 14–16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- cut, 34, 35
- data.frame, 8, 48, 58, 61, 62, 64, 75, 84
- date_stamp, 4, 6–12, 13, 15, 16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- death, 4, 6–12, 14, 14, 15, 16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- dice, 4, 6–12, 14, 15, 15, 16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- died (death), 14
- dna, 4, 6–12, 14, 15, 16, 18–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- dob, 4, 6–12, 14–16, 17, 19–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- dummy, 4, 6–12, 14–16, 18, 18, 20–22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- education, 4, 6–12, 14–16, 18, 19, 19, 21, 22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- ela (level), 38
- employment, 4, 6–12, 14–16, 18–20, 20, 22, 24, 25, 27–29, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- eye, 4, 6–12, 14–16, 18–21, 22, 24, 25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- factor, 8, 31
- gamma, 32
- gender (sex), 75
- gender_inclusive (sex_inclusive), 76
- gpa (grade), 23
- grade, 4, 6–12, 14–16, 18–21, 23, 23, 25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- grade_letter (grade), 23
- grade_level, 4, 6–12, 14–16, 18–21, 23, 24, 24, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- grady_augmented, 25
- group, 4, 6–12, 14–16, 18–21, 23–25, 26, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- hair, 4, 6–12, 14–16, 18–21, 23–25, 27, 27, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- head, 49

- height, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 28, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- height_cm (height), 28
- height_in (height), 28
- hour, 30
- id, 31
- id_factor (id), 31
- income, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- internet_browser, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 33, 36, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- interval, 34
- iq, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 35, 37, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- language, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 36, 39–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- languages, 37
- level, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 38, 40–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- likert, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39, 39, 41–43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- likert_5 (likert), 39
- likert_7 (likert), 39
- list, 62, 64, 89
- lorem_ipsum, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39, 40, 40, 42, 43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- lower (upper), 86
- lower_factor (upper), 86
- marital, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–41, 41, 43, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- math (level), 38
- matrix, 89
- military, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–42, 42, 45, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- minute, 43
- month, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–43, 44, 46, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- mtcars, 9
- name, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 45, 48, 51, 54, 56, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- name_neutral, 46
- normal, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 47, 51, 54, 57, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- normal_round (normal), 47
- ordered, 69
- package-wakefield (wakefield), 90
- paragraph (lorem_ipsum), 40
- peek, 48
- pet (animal), 5
- plot.tbl_df, 49
- political, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30, 32, 34, 36, 37, 39–43, 45, 46, 48, 50, 54, 57, 73, 74, 76, 78–80, 82, 84, 87, 88, 91, 92
- presidential_debates_2012, 36, 51, 74
- primary (color), 12
- print.available, 51
- print.variable, 52
- probs, 52
- r_data, 57
- r_data_frame, 57, 58, 58, 61, 63, 71, 89
- r_data_theme (r_data), 57
- r_dummy, 59, 60, 63, 71
- r_insert, 61
- r_list, 59, 61, 62, 71, 89

- r_na, 63
- r_sample, 64
- r_sample_binary, 65
- r_sample_binary_factor
(r_sample_binary), 65
- r_sample_factor, 66
- r_sample_integer, 67
- r_sample_logical, 68
- r_sample_ordered, 68
- r_sample_replace, 69
- r_series, 8, 55, 59, 61, 63, 70
- race, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 53, 57, 73, 74, 76, 78–80, 82, 84,
87, 88, 91, 92
- relate, 54, 70
- religion, 4, 6–12, 14–16, 18–21, 23–25, 27,
28, 30, 32, 34, 36, 37, 39–43, 45, 46,
48, 51, 54, 55, 73, 74, 76, 78–80, 82,
84, 87, 88, 91, 92
- rnorm, 47, 48
- round, 23, 29, 32, 35, 47, 48, 72, 80
- sample, 65–70
- sample.int, 19, 66
- sat, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30,
32, 34, 36, 37, 39–43, 45, 46, 48, 51,
54, 57, 72, 74, 76, 78–80, 82, 84, 87,
88, 91, 92
- scale_fill_brewer, 84
- second, 73
- sentence, 4, 6–12, 14–16, 18–21, 23–25, 27,
28, 30, 32, 34, 36, 37, 39–43, 45, 46,
48, 51, 54, 57, 73, 74, 76, 78–80, 82,
84, 87, 88, 91, 92
- seq.Date, 13, 14, 17
- seriesname, 61, 75
- sex, 4, 6–12, 14–16, 18–21, 23–25, 27, 28, 30,
32, 34, 36, 37, 39–43, 45, 46, 48, 51,
54, 57, 73, 74, 75, 78–80, 82, 84, 87,
88, 91, 92
- sex_inclusive, 4, 6–12, 14–16, 18–21,
23–25, 27, 28, 30, 32, 34, 36, 37,
39–43, 45, 46, 48, 51, 54, 57, 73, 74,
76, 76, 79, 80, 82, 84, 87, 88, 91, 92
- smokes, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78, 78, 80, 82,
84, 87, 88, 91, 92
- speed, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78, 79, 79, 82,
84, 87, 88, 91, 92
- speed_kph (speed), 79
- speed_mph (speed), 79
- sprintf, 31
- state, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78–80, 80, 84,
87, 88, 91, 92
- state_populations, 83
- stri_rand_lipsum, 41
- stri_rand_strings, 84
- string, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78–80, 82, 83,
87, 88, 91, 92
- table_heat, 49, 84
- tbl_df, 55, 58, 61, 70, 71
- time_stamp, 85
- times, 30, 44, 74, 86
- upper, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78–80, 82, 84,
86, 88, 91, 92
- upper_factor (upper), 86
- valid, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78–80, 82, 84,
87, 88, 91, 92
- variables, 89
- varname, 90
- wakefield, 90
- year, 4, 6–12, 14–16, 18–21, 23–25, 27, 28,
30, 32, 34, 36, 37, 39–43, 45, 46, 48,
51, 54, 57, 73, 74, 76, 78–80, 82, 84,
87, 88, 91, 92
- zip_code, 4, 6–12, 14–16, 18–21, 23–25, 27,
28, 30, 32, 34, 36, 37, 39–43, 45, 46,
48, 51, 54, 57, 73, 74, 76, 78–80, 82,
84, 87, 88, 91, 92